Network security

1

- Most slides are taken from
  - Cryptography and Network Security, by William Stallings, Lecture slides by Lawrie Brown

2

Modern Block Ciphers

- now look at modern block ciphers
- one of the most widely used types of cryptographic algorithms
- provide secrecy /authentication services
- focus on DES (Data Encryption Standard)
- to illustrate block cipher design principles

3

Block vs Stream Ciphers

- block ciphers process messages in blocks, each of which is then en/decrypted
- like a substitution on very big characters
  - 64-bits or more
- stream ciphers process messages a bit or byte at a time when en/decrypting
- many current ciphers are block ciphers
- broader range of applications


4

Block Cipher Principles

- most symmetric block ciphers are based on a **Feistel Cipher Structure**
- needed since must be able to **decrypt** ciphertext to recover messages efficiently
- block ciphers look like an extremely large substitution
- would need table of 2^{64} entries for a 64-bit block
- instead create from smaller building blocks
- using idea of a product cipher

5

Ideal Block Cipher



6

Claude Shannon and Substitution-Permutation Ciphers

- Claude Shannon introduced idea of substitution-permutation (S-P) networks in 1949 paper
- form basis of modern block ciphers
- S-P nets are based on the two primitive cryptographic operations seen before:
  - *substitution* (S-box)
  - *permutation* (P-box)
- provide *confusion* & *diffusion* of message & key

7

Confusion and Diffusion

- cipher needs to completely obscure statistical properties of original message
- a one-time pad does this
- more practically Shannon suggested combining S & P elements to obtain:
  - **confusion** – makes relationship between ciphertext and key as complex as possible
  - **diffusion** – dissipates statistical structure of plaintext over bulk of ciphertext


8

Feistel Cipher Structure

- Horst Feistel devised the **feistel cipher**
  - based on concept of invertible product cipher
- partitions input block into two halves
  - process through multiple rounds
  - perform a substitution on left data half
  - based on round function of right half & subkey
  - then have permutation swapping halves
- implements Shannon's S-P net concept

9

Feistel Cipher Structure




10

Feistel Cipher Design Elements

- block size
- key size
- number of rounds
- subkey generation algorithm
- round function
- fast software en/decryption
- ease of analysis

11

Feistel Cipher Decryption



12

Data Encryption Standard (DES)

- most widely used block cipher in world
- adopted in 1977 by NBS (now NIST)
  - as FIPS PUB 46
- encrypts 64-bit data using 56-bit key
- has widespread use
- has been considerable controversy over its security
  - Length of the key
  - Design criteria of S-box

13

DES History

- IBM developed Lucifer cipher
  - by team led by Feistel in late 60's
  - used 64-bit data blocks with 128-bit key
- then redeveloped as a commercial cipher with input from NSA and others
- in 1973 NBS issued request for proposals for a national cipher standard
- IBM submitted their revised Lucifer which was eventually accepted as the DES with key size of 56 bits to fit on a single chip


14

DES Design Controversy

- DES standard is public
- There was considerable controversy over design
  - in choice of 56-bit key (vs Lucifer 128-bit)
  - and because design criteria were classified
- subsequent events and public analysis show in fact design was appropriate
- use of DES has flourished
  - especially in financial applications
  - still standardised for legacy application use

15

DES Encryption



16

Initial Permutation IP

- first step of the data computation
- IP reorders the input data bits
- even bits to LH half, odd bits to RH half
- quite regular in structure (easy in h/w)
- example:

```
IP(675a6967 5e5a6b5a) -> (ffb2194d 004df6fb)
```

17

Initial Permutation IP

(a) Initial Permutation (IP)


58	50	42	34	26	18	10	2
60	52	44	36	28	20	12	4
62	54	46	38	30	22	14	6
64	56	48	40	32	24	16	8
57	49	41	33	25	17	9	1
59	51	43	35	27	19	11	3
61	53	45	37	29	21	13	5
63	55	47	39	31	23	15	7

(b) Inverse Initial Permutation (IP^{-1})

40	8	48	16	56	24	64	32
39	7	47	15	55	23	63	31
38	6	46	14	54	22	62	30
37	5	45	13	53	21	61	29
36	4	44	12	52	20	60	28
35	3	43	11	51	19	59	27
34	2	42	10	50	18	58	26
33	1	41	9	49	17	57	25

18

Single round



19

DES Round Structure

- uses two 32-bit L & R halves
- as for any Feistel cipher can describe as:
  $L_i = R_{i-1}$
  $R_i = L_{i-1} \oplus \mathrm{F}(R_{i-1}, K_i)$
- F takes 32-bit R half and 48-bit subkey:
  - expands R to 48-bits using perm E
  - adds to subkey using XOR
  - passes through 8 S-boxes to get 32-bit result
  - finally permutes using 32-bit perm P

20


Expansion

(c) Expansion Permutation (E)

32	1	2	3	4	5
4	5	6	7	8	9
8	9	10	11	12	13
12	13	14	15	16	17
16	17	18	19	20	21
20	21	22	23	24	25
24	25	26	27	28	29
28	29	30	31	32	1

21

DES Round Structure



22

Substitution Boxes S

- have eight S-boxes which map 6 to 4 bits
- each S-box is actually 4 little 4 bit boxes
  - outer bits 1 & 6 (**row** bits) select one row of 4
  - inner bits 2-5 (**col** bits) are substituted
  - result is 8 lots of 4 bits, or 32 bits
- row selection depends on both data & key
  - feature known as autoclaving (autokeying)
- example:
  - `S(18 09 12 3d 11 17 38 39) = 5fd25e03`

23

Substitution Boxes S

S_5		Middle 4 bits of input															
		0000	**0001**	**0010**	**0011**	**0100**	**0101**	**0110**	**0111**	**1000**	**1001**	**1010**	**1011**	**1100**	**1101**	**1110**	**1111**
Outer bits	**00**	0010	1100	0100	0001	0111	1010	1011	0110	1000	0101	0011	1111	1101	0000	1110	1001
	01	1110	1011	0010	1100	0100	0111	1101	0001	0101	0000	1111	1010	0011	1001	1000	0110
	10	0100	0010	0001	1011	1010	1101	0111	1000	1111	1001	1100	0101	0110	0011	0000	1110
	11	1011	1000	1100	0111	0001	1110	0010	1101	0110	1111	0000	1001	1010	0100	0101	0011

24

Substitution Boxes S

4	13	1	2	15	11	8	3	10	6	12	5	9	0	7
15	7	4	14	2	13	1	10	6	12	11	9	5	3	8
1	14	8	13	6	2	11	15	12	9	7	3	10	5	0
12	8	2	4	9	1	7	5	11	3	14	10	0	6	13

1	8	14	6	11	3	4	9	7	2	13	12	0	5	10
13	4	7	15	2	8	14	12	0	1	10	6	9	11	5
14	7	11	10	4	13	1	5	8	12	6	9	3	2	15
8	10	1	3	15	4	2	11	6	7	12	0	5	14	9

25

Permutation

(d) Permutation Function (P)

16	7	20	21	29	12	28	17
1	15	23	26	5	18	31	10
2	8	24	14	32	27	3	9
19	13	30	6	22	11	4	25

26

DES Key Schedule

- forms subkeys used in each round
  - initial permutation of the key (PC1) which divides 56-bits in two 28-bit halves
  - 16 stages consisting of:
    - rotating **each half** separately either 1 or 2 places depending on the **key rotation schedule** K
    - selecting 24-bits from each half & permuting them by PC2 for use in round function F
- note practical use issues in h/w vs s/w

27

DES Key Schedule

(a) Input Key

1	2	3	4	5	6	7	8
9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32
33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48
49	50	51	52	53	54	55	56
57	58	59	60	61	62	63	64

28

DES Key Schedule

(b) Permuted Choice One (PC-1)

57	49	41	33	25	17	9
1	58	50	42	34	26	18
10	2	59	51	43	35	27
19	11	3	60	52	44	36
63	55	47	39	31	23	15
7	62	54	46	38	30	22
14	6	61	53	45	37	29
21	13	5	28	20	12	4

(c) Permuted Choice Two (PC-2)

14	17	11	24	1	5	3	28
15	6	21	10	23	19	12	4
26	8	16	7	27	20	13	2
41	52	31	37	47	55	30	40
51	45	33	48	44	49	39	56
34	53	46	42	50	36	29	32

(d) Schedule of Left Shifts

Round number	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Bits rotated	1	1	2	2	2	2	2	2	1	2	2	2	2	2	2	1

29

DES Decryption

- decrypt must unwind steps of data computation
- with Feistel design, do encryption steps again using subkeys in reverse order (SK16 … SK1)
  - IP undoes final FP step of encryption
  - 1st round with SK16 undoes 16th encrypt round
  - ….
  - 16th round with SK1 undoes 1st encrypt round
  - then final FP undoes initial encryption IP
  - thus recovering original data value

30

Avalanche Effect

- key desirable property of encryption alg
- where a change of **one** input or key bit results in changing approx **half** output bits
- making attempts to "home-in" by guessing keys impossible
- DES exhibits strong avalanche

31

Strength of DES – Key Size

- 56-bit keys have $2^{56} = 7.2 \times 10^{16}$ values
- brute force search looks hard
- recent advances have shown is possible
  - in 1997 on Internet in a few months
  - in 1998 on dedicated h/w (EFF) in a few days
  - in 1999 above combined in 22hrs!
- still must be able to recognize plaintext
- must now consider alternatives to DES

32

Strength of DES – Analytic Attacks

- now have several analytic attacks on DES
- these utilise some deep structure of the cipher
  - by gathering information about encryptions
  - can eventually recover some/all of the sub-key bits
  - if necessary then exhaustively search for the rest
- generally these are statistical attacks, include
  - differential cryptanalysis
  - linear cryptanalysis
  - related key attacks

33

Strength of DES – Timing Attacks

- attacks actual implementation of cipher
- use knowledge of consequences of implementation to derive information about some/all subkey bits
- specifically use fact that calculations can take varying times depending on the value of the inputs to it
- particularly problematic on smartcards

34

Differential Cryptanalysis

- one of the most significant recent (public) advances in cryptanalysis
- known by NSA in 70's cf DES design
- Murphy, Biham & Shamir published in 90's
- powerful method to analyse block ciphers
- used to analyse most current block ciphers with varying degrees of success
- DES reasonably resistant to it, cf Lucifer

35

Differential Cryptanalysis

- a statistical attack against Feistel ciphers
- uses cipher structure not previously used
- design of S-P networks has output of function *f* influenced by both input & key
- hence cannot trace values back through cipher without knowing value of the key
- differential cryptanalysis compares two related pairs of encryptions

36

Differential Cryptanalysis Compares Pairs of Encryptions

- with a known difference in the input
- searching for a known difference in output
- when same subkeys are used

$$\begin{aligned}\Delta m_{i+1} &= m_{i+1} \oplus m'_{i+1} \\ &= [m_{i-1} \oplus \mathrm{f}(m_i, K_i)] \oplus [m'_{i-1} \oplus \mathrm{f}(m'_i, K_i)] \\ &= \Delta m_{i-1} \oplus [\mathrm{f}(m_i, K_i) \oplus \mathrm{f}(m'_i, K_i)]\end{aligned}$$


37

Differential Cryptanalysis

- have some input difference giving some output difference with probability p
- if find instances of some higher probability input / output difference pairs occurring
- can infer subkey that was used in round
- then must iterate process over many rounds (with decreasing probabilities)

38

Differen



39

Differential Cryptanalysis

- perform attack by repeatedly encrypting plaintext pairs with known input XOR until obtain desired output XOR
- when found
  - if intermediate rounds match required XOR have a **right pair**
  - if not then have a **wrong pair**, relative ratio is S/N for attack
- can then deduce keys values for the rounds
  - right pairs suggest same key bits
  - wrong pairs give random values
- for large numbers of rounds, probability is so low that more pairs are required than exist with 64-bit inputs
- Biham and Shamir have shown how a 13-round iterated characteristic can break the full 16-round DES

40

Linear Cryptanalysis

- another recent development
- also a statistical method
- must be iterated over rounds, with decreasing probabilities
- developed by Matsui et al in early 90's
- based on finding linear approximations
- can attack DES with 2^{43} known plaintexts, easier but still in practise infeasible

41

Linear Cryptanalysis

- find linear approximations with prob p != ½

$$P[i_1,i_2,\ldots,i_a] \oplus C[j_1,j_2,\ldots,j_b] = K[k_1,k_2,\ldots,k_c]$$

where i_a, j_b, k_c are bit locations in P,C,K

- gives linear equation for key bits
- get one key bit using max likelihood alg
- using a large number of trial encryptions
- effectiveness given by: $|p - 1/2|$

42

Weak key

- DES *weak keys* produce sixteen identical subkeys
  - With parity bits
    - Alternating ones + zeros (0x0101010101010101)
    - Alternating 'F' + 'E' (0xFEFEFEFEFEFEFEFE)
    - '0xE0E0E0E0F1F1F1F1'
    - '0x1F1F1F1F0E0E0E0E'
  - Without parity bits
    - all zeros (0x0000000000000000)
    - all ones (0xFFFFFFFFFFFFFFFF)
    - '0xE1E1E1E1F0F0F0F0'
    - '0x1E1E1E1E0F0F0F0F'

43

Semi-weak key

- Produce 2 different keys instead of 16
  - 0x011F011F010E010E and 0x1F011F010E010E01
  - 0x01E001E001F101F1 and 0xE001E001F101F101
  - 0x01FE01FE01FE01FE and 0xFE01FE01FE01FE01
  - 0x1FE01FE00EF10EF1 and 0xE01FE01FF10EF10E
  - 0x1FFE1FFE0EFE0EFE and 0xFE1FFE1FFE0EFE0E
  - 0xE0FEE0FEF1FEF1FE and 0xFEE0FEE0FEF1FEF1

44

DES Design Criteria

- as reported by Coppersmith in [COPP94]
- 7 criteria for S-boxes provide for
  - non-linearity
  - resistance to differential cryptanalysis
  - good confusion
- 3 criteria for permutation P provide for
  - increased diffusion

45

Block Cipher Design

- basic principles still like Feistel's in 1970's
- number of rounds
  - more is better, exhaustive search best attack
- function f:
  - provides "confusion", is nonlinear, avalanche
  - have issues of how S-boxes are selected
- key schedule
  - complex subkey creation, key avalanche

46

Summary

- have considered:
  - block vs stream ciphers
  - Feistel cipher design & structure
  - DES
    - details
    - strength
  - Differential & Linear Cryptanalysis
  - block cipher design principles

47