

Document ID: a-public

Corpus ID: tenant-a-support

Tenant: Tenant A

Classification: public

Title: Tenant A Customer Retrieval Overview

Fixture status: Synthetic tutorial content

Contains real customer data: No

Tenant A Customer Retrieval Overview

Audience

This guide is for Tenant A employees and approved partner reviewers. Every organization, workflow, review activity, and example described here is fictional and exists only to support a security tutorial about retrieval authorization.

Knowledge organization

Tenant A organizes fictional support material by service topic, publication state, and intended audience. Each original document retains its tenant, corpus, and classification labels so later processing can preserve the source security boundary.

Short, topic-focused paragraphs are converted into searchable chunks. A result keeps a citation to its original document and metadata, allowing a reader to distinguish an extracted passage from the complete fictional source used in this tutorial.

Search, citation, and review

Retrieval boundary

Customer retrieval data must be isolated by tenant at query time and again before protected content is loaded. The first check narrows discovery, while the second authorizes the original document before any selected passage reaches the model.

Search relevance never grants access. A high-scoring chunk is only a candidate, and the service uses its original document metadata when asking whether the current principal may perform the requested action on that protected resource.

Sharing and maintenance

Public documentation may be shared with approved partner reviewers after its publication state is confirmed. Confidential material remains outside that public review path, even when similar vocabulary causes a vector index to rank it near a public passage.

Reviewers examine citations, flag stale explanations, and record whether a public answer remains supported by its source. These fictional checks improve clarity without allowing document text or search scores to alter the server's authorization result.