

# Glympse Intents Reference



## [Glympse Intents Reference](#)

### [Introduction](#)

### [Reference](#)

### [Sending](#)

### [Overview](#)

### [com.glympse.android.intent.CREATE](#)

### [CALLBACK\\_ACTION](#)

### [Viewing](#)

### [com.glympse.android.intent.VIEW](#)


## Introduction

Glympse application provides a way to send and view Glympses using Android intents.

## Reference

### Sending

#### Overview



*com.glympse.android.intent.CREATE*

### Action

com.glympse.android.intent.CREATE

## Extras

Property	Description	Type
source	Package name of caller process.	String
duration	Ticket duration in milliseconds.	long
recipients	<p>The recipients to be added to the ticket.</p> <pre>{   "type": TYPE,                                (required)   "subtype": SUBTYPE,                          (varies by type)   "brand": BRAND,                              (optional)   "name": NAME,                                (optional)   "address": ADDRESS,                          (varies by type)   "create_only": true false                    (opt., default: false) }</pre> <p>The following types are supported:</p> <ul style="list-style-type: none"> <li>• app</li> <li>• link</li> <li>• sms</li> <li>• email</li> </ul> <p><code>create_only</code> flag tells Glympse application whether it should deliver invite (using mechanism associated with particular invite <code>type</code>) or just create invite URL and use <code>callback_action</code> (if specified) to notify caller application on the result.</p>	Array of String (JSON)
message	Message to be set.	String
destination	<p>Destination to be set.</p> <pre>{   "name": NAME,                                (optional)   "latitude": LATITUDE,                        (required)   "longitude": LONGITUDE                       (required) }</pre>	String (JSON)
flags	<p>A combination of the following flags to customize appearance of Send a Glympse wizard:</p> <ul style="list-style-type: none"> <li>• FLAG_RECIPIENTS_EDITABLE 0x0000000000000000L</li> <li>• FLAG_RECIPIENTS_READ_ONLY 0x0000000000000001L</li> <li>• FLAG_RECIPIENTS_DELETE_ONLY 0x0000000000000002L</li> <li>• FLAG_MESSAGE_EDITABLE 0x0000000000000000L</li> <li>• FLAG_MESSAGE_READ_ONLY 0x0000000000000010L</li> <li>• FLAG_MESSAGE_DELETE_ONLY 0x0000000000000020L</li> <li>• FLAG_MESSAGE_HIDDEN 0x0000000000000040L</li> <li>• FLAG_DESTINATION_EDITABLE 0x0000000000000000L</li> <li>• FLAG_DESTINATION_READ_ONLY 0x0000000000000100L</li> <li>• FLAG_DESTINATION_DELETE_ONLY 0x0000000000000200L</li> <li>• FLAG_DESTINATION_HIDDEN 0x0000000000000400L</li> <li>• FLAG_DURATION_EDITABLE 0x0000000000000000L</li> <li>• FLAG_DURATION_READ_ONLY 0x0000000000001000L</li> </ul> <p>The following flags can also be specified to alter the behavior of Glympse application with regards to notifying caller application on the</p>	long

	<p>result of Glympse creation:</p> <ul style="list-style-type: none"> <li> <code>FLAG_USE_ACTIVITY_RESULT</code>                      <code>0x0000000010000000L</code>  The flag has to be specified if caller application expects the result to be delivered through <code>onActivityResult()</code>. </li> <li> <code>FLAG_ENABLE_EVENTS</code>                              <code>0x0000000020000000L</code>  Application specifies this flag to be notified on all ticket events (duration changes, etc.). </li> </ul>	
<code>callback_package</code>	Glympse application is using this property to send targeted intents. The value passed here is referred as <code>CALLBACK_PACKAGE</code> further in this document.	String
<code>callback_action</code>	Intent that Glympse application fires back when any activity happens on the ticket. The value passed here is referred as <code>CALLBACK_ACTION</code> further in this document.	String
<code>context</code>	Optional meta data that is passed back to caller application along with all subsequent notifications regarding this ticket.	String
<code>initial_nickname</code>	Initial nickname to set for the user if it isn't already set.	String
<code>initial_avatar</code>	Initial avatar to set for the user if it isn't already set. Local image URI has to be passed here.	String

## ***CALLBACK\_ACTION***

`CALLBACK_ACTION` is sent exclusively to `CALLBACK_PACKAGE` (if it is specified).

### **Action**

<code>CALLBACK_ACTION</code>	
------------------------------	--

### **Extras**

Property	Description	Type
<code>context</code>	Optional meta data provided by 3rd party application along with <code>com.glympse.android.intent.CREATE</code> intent.	String
<code>recipients</code>	<p>The recipients to be added to the ticket.</p> <pre>{   "type": TYPE,   "subtype": SUBTYPE,   "name": NAME,   "address": ADDRESS,   "url": URL }</pre> <p>The following types are supported</p> <ul style="list-style-type: none"> <li>app</li> <li>link</li> <li>sms</li> <li>email</li> </ul>	Array of String (JSON)
<code>event</code>	<p>Possible values:</p> <ul style="list-style-type: none"> <li>creating</li> </ul>	String

	<ul style="list-style-type: none"><li>created</li><li>failed_to_create</li><li>done_sending</li><li>duration_changed</li></ul>	
duration	Ticket duration in milliseconds.	long
remaining	Ticket remaining time in milliseconds.	long
message	Ticket message.	String
destination	Ticket destination. { "name": NAME, "latitude": LATITUDE, "longitude": LONGITUDE }	String (JSON)

Viewing

*com.glympse.android.intent.VIEW*

Action

com.glympse.android.intent.VIEW	
---------------------------------	--

Extras

Property	Description	Type
codes	Array of entities to start following on the map to start watching. Each item on the array is a Glympse invite code or Glympse group name. Group names have to be prefixed by '! '.	Array of String
flags	A combination of the following flags to customize appearance of Send a Glympse wizard: <ul style="list-style-type: none"><li>FLAG_SHOW_SELF0x00000000000000001L</li></ul>	long