

Package ‘R4MFCL’

June 26, 2013

Title R functions for MFCL

Version 0.1

Author Simon Hoyle

Description miscellaneous funtions for dealing with input to and output from MFCL

Maintainer <simonh@spc.int>

License GPL-2

Date 2011-05-25

R topics documented:

| | |
|----------------------------------|----|
| add.catch.frq | 4 |
| add.cpue.frq | 4 |
| add.flag | 5 |
| alb.clean.lfdata | 5 |
| alb.initial_clean_2008 | 6 |
| alb.initial_clean_2009 | 6 |
| alb.initial_clean_2011 | 7 |
| alb.pagocatch_2009 | 7 |
| carry.effort.frq | 8 |
| change.fishflag | 8 |
| change.flag | 9 |
| change.negflag | 9 |
| change.size.frq | 10 |
| change_data | 10 |
| check.eff.devs | 11 |
| check_flag_value | 11 |
| clean.lfdata | 12 |
| compare.ce.frq | 12 |
| compare.frq | 13 |
| compare.size.frq | 13 |
| compare.size.frq2 | 14 |
| compare_par_flags | 14 |
| condor.go | 15 |
| condor.go2 | 15 |
| Convert.frq.ver6 | 16 |

| | |
|--|----|
| create.missing.ce | 16 |
| create.ver6.frq | 17 |
| crit.fishery.summary | 17 |
| crit.summary | 18 |
| datfromstr | 18 |
| do.critical.calcs | 19 |
| doit.rm_flag | 19 |
| effortcreep | 20 |
| fix_growth | 20 |
| frq.change.nint | 21 |
| frq.remove.size.or.weight.data | 21 |
| get.critical.age | 22 |
| get.length.output | 22 |
| get.outcomes | 23 |
| get.outcomes.alb | 23 |
| get.outcomes.test | 24 |
| get.weight.output | 24 |
| initial_clean_2008 | 25 |
| labels_store | 25 |
| load.LFdata | 25 |
| make.projection.betyft.frq | 26 |
| map_all_pacific | 26 |
| merge.frq | 27 |
| merge.tag | 27 |
| merge_tag_objs | 28 |
| NZtrollglm | 28 |
| oldsetup | 29 |
| pack.fisheries.frq | 29 |
| pagocatch | 29 |
| plot.base.comparison | 30 |
| plot.biomass | 30 |
| plot.biomass.combined | 31 |
| plot.F.time | 31 |
| plot.fishery.impact.r | 32 |
| plot.Kobe | 32 |
| plot.Kobe.template.bw | 33 |
| plot.Kobe.template.col | 33 |
| plot.mfcl.betyft09 | 34 |
| plot.nofishing | 34 |
| plot.nofishing.combined | 35 |
| plot.pacific.alb | 35 |
| plot.pacific.skj | 36 |
| plot.pacific.species | 36 |
| plot.pacific.WCPFC | 37 |
| plot.pacific.yft | 37 |
| plot.recruitment | 38 |
| plot.recruitment.combined | 38 |
| plot_cpue_cv_frq | 39 |
| read.catchrep | 39 |
| read.ests | 40 |
| read.fit | 40 |
| read.frq | 41 |

| | |
|------------------------------|----|
| read.impact | 41 |
| read.ini | 42 |
| read.par | 42 |
| read.rep | 42 |
| read.tag | 43 |
| read.tags.JP | 43 |
| read.var | 44 |
| read_nmd.frq | 44 |
| read_nmd.par | 45 |
| reconstruct.frq.ce | 45 |
| reconstruct.frq.ce2008 | 46 |
| reconstruct.frq.size | 46 |
| region_single_frq | 47 |
| region_single_ini | 47 |
| region_single_tag | 48 |
| regroup_fishery_grps.doitall | 48 |
| rename.fisheries.doitall | 49 |
| rename.fisheries.frq | 49 |
| rename.fisheries.tag | 50 |
| rename.fishery_grps.doitall | 50 |
| retro.frq | 51 |
| retro.tag | 51 |
| rm_fisheries.doitall | 52 |
| rm_fisheries.frq | 52 |
| rm_fisheries.tag | 53 |
| rm_fishflag | 53 |
| rm_flag.doitall | 54 |
| run.profile | 54 |
| seas.flag | 55 |
| seas.frq | 55 |
| seas.tag | 56 |
| setup.cpue | 56 |
| setup.effcreep | 57 |
| setup.growth | 57 |
| setup.growth.offsets | 58 |
| setup.idphcatch | 58 |
| setup.lensel | 59 |
| setup.LFwt | 59 |
| setup.M | 60 |
| setup.pscatch | 60 |
| setup.startyr | 61 |
| setup.steepness | 61 |
| setup.timesplit | 62 |
| sort.frq | 62 |
| start_year.frq | 63 |
| steepness.doit | 63 |
| summarise.size.frq.bet | 64 |
| tag_grps_rm | 64 |
| timesplit.doitall | 65 |
| timesplit.frq | 65 |
| timesplit.tag | 66 |
| varfromstr | 66 |

| | |
|-------------------------|----|
| write.frq | 67 |
| write.ini | 67 |
| write.par | 68 |
| write.tag | 68 |
| write_nmd.frq | 69 |
| write_nmd.par | 69 |

| | |
|--------------|-----------|
| Index | 70 |
|--------------|-----------|

| | |
|---------------|-------------------------|
| add.catch.frq | <i>add.catch.frq.Rd</i> |
|---------------|-------------------------|

Usage

```
add.catch.frq(frq, filepath, fshries)
```

Arguments

```
frq
filepath
fshries
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| add.cpue.frq | <i>add.cpue.frq.Rd</i> |
|--------------|------------------------|

Usage

```
add.cpue.frq(CPUE.file = "P:/yft/2009/Data Preparation/CPUE/indices/yft_JPstd_R1
```

Arguments

```
CPUE.file
data
fishery
add.cv
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| add.flag | <i>add.flag.Rd</i> |
|----------|--------------------|

Usage

```
add.flag(doitall, flagtype, flagnum, newval, phase)
```

Arguments

```
doitall
flagtype
flagnum
newval
phase
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------------|----------------------------|
| alb.clean.lfdata | <i>alb.clean.lfdata.Rd</i> |
|------------------|----------------------------|

Usage

```
alb.clean.lfdata(infrq)
```

Arguments

```
infrq
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
alb.initial_clean_2008  
    alb.initial_clean_2008.Rd
```

Usage

```
alb.initial_clean_2008(frq.obj)
```

Arguments

```
frq.obj
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
alb.initial_clean_2009  
    alb.initial_clean_2009.Rd
```

Usage

```
alb.initial_clean_2009(frq.obj)
```

Arguments

```
frq.obj
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
alb.initial_clean_2011  
    alb.initial_clean_2011.Rd
```

Usage

```
alb.initial_clean_2011(frq.obj)
```

Arguments

```
freq.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
alb.pagocatch_2009 alb.pagocatch_2009.Rd
```

Usage

```
alb.pagocatch_2009(frq.obj)
```

Arguments

```
freq.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
carry.effort.frq    carry.effort.frq.Rd
```

Usage

```
carry.effort.frq(data = out.data, fishery = 1, last = 2008)
```

Arguments

```
data
fishery
last
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
change.fishflag    change.fishflag.Rd
```

Usage

```
change.fishflag(a, fisheries, flagnum, newvals)
```

Arguments

```
a
fisheries
flagnum
newvals
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

| | |
|-------------|-----------------------|
| change.flag | <i>change.flag.Rd</i> |
|-------------|-----------------------|

Usage

```
change.flag(doitall, flagtype, flagnum, newval)
```

Arguments

```
doitall
flagtype
flagnum
newval
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| change.negflag | <i>change.negflag.Rd</i> |
|----------------|--------------------------|

Usage

```
change.negflag(doitall, flagtype, flagnum, newval)
```

Arguments

```
doitall
flagtype
flagnum
newval
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------------|---------------------------|
| change.size.frq | <i>change.size.frq.Rd</i> |
|-----------------|---------------------------|

Usage

```
change.size.frq(ver = 6, data = data, FISH = 1, LF.FILE = "P:/yft/2009/Data Prep
```

Arguments

```
ver
data
FISH
LF.FILE
WT.FILE
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------|-----------------------|
| change_data | <i>change_data.Rd</i> |
|-------------|-----------------------|

Usage

```
change_data(obj, searchtext, xlines, newline)
```

Arguments

```
obj
searchtext
xlines
newline
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| check.eff.devs | <i>check.eff.devs.Rd</i> |
|----------------|--------------------------|

Usage

```
check.eff.devs(parfile, repfile, frqfile, parlim = 5.9)
```

Arguments

```
parfile  
repfile  
frqfile  
parlim
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|------------------|----------------------------|
| check_flag_value | <i>check_flag_value.Rd</i> |
|------------------|----------------------------|

Usage

```
check_flag_value(parname, flagtype, flagnums, fishery = NA, flaglist = T)
```

Arguments

```
parname  
flagtype  
flagnums  
fishery  
flaglist
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| clean.lfdata | <i>clean.lfdata.Rd</i> |
|--------------|------------------------|

Usage

```
clean.lfdata(infrq)
```

Arguments

```
infrq
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| compare.ce.frq | <i>compare.ce.frq.Rd</i> |
|----------------|--------------------------|

Usage

```
compare.ce.frq(file1, file2, fm, plotname, fdesc = "")
```

Arguments

```
file1
```

```
file2
```

```
fm
```

```
plotname
```

```
fdesc
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------|-----------------------|
| compare.frq | <i>compare.frq.Rd</i> |
|-------------|-----------------------|

Usage

```
compare.frq(file1, file2, fm = "all", plotname, fdesc = "")
```

Arguments

```
file1
file2
fm
plotname
fdesc
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------------|----------------------------|
| compare.size.frq | <i>compare.size.frq.Rd</i> |
|------------------|----------------------------|

Usage

```
compare.size.frq(frq1, frq2, fishery = 5)
```

Arguments

```
frq1
frq2
fishery
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
compare.size.frq2  compare.size.frq2.Rd
```

Usage

```
compare.size.frq2(frq1, frq2, fishery = 5, wt = T)
```

Arguments

```
frq1
frq2
fishery
wt
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
compare_par_flags  compare_par_flags.Rd
```

Usage

```
compare_par_flags(par1, par2, flaglist = T)
```

Arguments

```
par1
par2
flaglist
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

`condor.go`*condor.go.Rd*

Usage

```
condor.go(run.dir, frq.obj, tag.obj, doitall.obj, ini.obj, sub.obj = suball, spe
```

Arguments

```
run.dir
frq.obj
tag.obj
doitall.obj
ini.obj
sub.obj
species
condor_f
par.obj
run_now
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

`condor.go2`*condor.go2.Rd*

Usage

```
condor.go2(run.dir, frq.obj, tag.obj, doitall.obj, ini.obj, sub.obj = suball, sp
```

Arguments

```
run.dir
frq.obj
tag.obj
doitall.obj
ini.obj
sub.obj
species
condor_f
par.obj
run_now
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
Convert.frq.ver6    Convert.frq.ver6.Rd
```

Usage

```
Convert.frq.ver6(a)
```

Arguments

```
a
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
create.missing.ce    create.missing.ce.Rd
```

Usage

```
create.missing.ce(data = data, year = 2008)
```

Arguments

```
data
year
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------------|---------------------------|
| create.ver6.frq | <i>create.ver6.frq.Rd</i> |
|-----------------|---------------------------|

Usage

```
create.ver6.frq(frq = base.frq)
```

Arguments

```
frq
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------------|--------------------------------|
| crit.fishery.summary | <i>crit.fishery.summary.Rd</i> |
|----------------------|--------------------------------|

Usage

```
crit.fishery.summary(crit)
```

Arguments

```
crit
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| crit.summary | <i>crit.summary.Rd</i> |
|--------------|------------------------|

Usage

```
crit.summary(crit, years)
```

Arguments

```
crit
years
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------|----------------------|
| datfromstr | <i>datfromstr.Rd</i> |
|------------|----------------------|

Usage

```
datfromstr(datstring)
```

Arguments

```
datstring
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------------|-----------------------------|
| do.critical.calcs | <i>do.critical.calcs.Rd</i> |
|-------------------|-----------------------------|

Usage

```
do.critical.calcs(repfile = "P:/yft/2007/BaseYFT/yftfinal2007.rep", ests = "P:/y
```

Arguments

```
repfile
ests
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

| | |
|--------------|------------------------|
| doit.rm_flag | <i>doit.rm_flag.Rd</i> |
|--------------|------------------------|

Usage

```
doit.rm_flag(a, flagtype, flag, value)
```

Arguments

```
a
flagtype
flag
value
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

| | |
|-------------|-----------------------|
| effortcreep | <i>effortcreep.Rd</i> |
|-------------|-----------------------|

Usage

```
effortcreep(frq.obj, fisheries, creep)
```

Arguments

```
freq.obj
fisheries
creep
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------|----------------------|
| fix_growth | <i>fix_growth.Rd</i> |
|------------|----------------------|

Usage

```
fix_growth(a)
```

Arguments

```
a
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

frq.change.nint *frq.change.nint.Rd*

Usage

```
frq.change.nint(in.frq, add.lfint, add.wfint)
```

Arguments

```
in.frq
add.lfint
add.wfint
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

frq.remove.size.or.weight.data
frq.remove.size.or.weight.data.Rd

Usage

```
frq.remove.size.or.weight.data(data = test.data, exclude = exclude, size = T, weight = weight)
```

Arguments

```
data
exclude
size
weight
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
get.critical.age    get.critical.age.Rd
```

Usage

```
get.critical.age(data = Base.rep)
```

Arguments

```
data
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

```
get.length.output    get.length.output.Rd
```

Usage

```
get.length.output(REGION = 1, DIR = "P:/yft/2009/Data Preparation/size data/")
```

Arguments

```
REGION
```

```
DIR
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

| | |
|--------------|------------------------|
| get.outcomes | <i>get.outcomes.Rd</i> |
|--------------|------------------------|

Usage

```
get.outcomes(file.rep, file.par, nofish = T)
```

Arguments

```
file.rep  
file.par  
nofish
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|------------------|----------------------------|
| get.outcomes.alb | <i>get.outcomes.alb.Rd</i> |
|------------------|----------------------------|

Usage

```
get.outcomes.alb(file.rep, file.par, catch.rep, nofish = T, SBcurr_1yr = F)
```

Arguments

```
file.rep  
file.par  
catch.rep  
nofish  
SBcurr_1yr
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
get.outcomes.test  get.outcomes.test.Rd
```

Usage

```
get.outcomes.test(file.rep, file.par, catch.rep, nofish = T)
```

Arguments

```
file.rep
file.par
catch.rep
nofish
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
get.weight.output  get.weight.output.Rd
```

Usage

```
get.weight.output(REGION = 1, DIR = "P:/yft/2009/Data Preparation/size data/")
```

Arguments

```
REGION
DIR
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

| | |
|--------------------|------------------------------|
| initial_clean_2008 | <i>initial_clean_2008.Rd</i> |
|--------------------|------------------------------|

Usage

```
initial_clean_2008(frq.obj)
```

Arguments

```
freq.obj
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| labels_store | <i>labels_store.Rd</i> |
|--------------|------------------------|

Usage

```
labels_store(labelfile = basecase.labels)
```

Arguments

```
labelfile
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------|-----------------------|
| load.LFdata | <i>load.LFdata.Rd</i> |
|-------------|-----------------------|

Usage

```
load.LFdata(species = "ALB", gear = "L")
```

Arguments

```
species  
gear
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
make.projection.betyft.frq
      make.projection.betyft.frq.Rd
```

Usage

```
make.projection.betyft.frq(frq.in = base.frq, fish = 1:24, years = 10)
```

Arguments

```
frq.in
fish
years
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
map_all_pacific      map_all_pacific.Rd
```

Usage

```
map_all_pacific(plot_title = "", lims = c(100, 300, -45, 45), eezfile = "L:/alb/
```

Arguments

```
plot_title
lims
eezfile
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

`merge.frq`*merge.frq.Rd*

Usage

```
merge.frq(frq.obj, oldf, newf, mergelf = FALSE)
```

Arguments`frq.obj``oldf``newf``mergelf`**Examples**

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

`merge.tag`*merge.tag.Rd*

Usage

```
merge.tag(tag.obj, oldf, newf)
```

Arguments`tag.obj``oldf``newf`**Examples**

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| merge_tag_objs | <i>merge_tag_objs.Rd</i> |
|----------------|--------------------------|

Usage

```
merge_tag_objs(obj1, obj2, relgrps)
```

Arguments

```
obj1
obj2
relgrps
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------|----------------------|
| NZtrollglm | <i>NZtrollglm.Rd</i> |
|------------|----------------------|

Usage

```
NZtrollglm(frq.obj, fishery, coef.file)
```

Arguments

```
frq.obj
fishery
coef.file
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| oldsetup | <i>oldsetup.Rd</i> |
|----------|--------------------|

Usage

```
oldsetup(olddbasedir)
```

Arguments

```
olddbasedir
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------------|------------------------------|
| pack.fisheries.frq | <i>pack.fisheries.frq.Rd</i> |
|--------------------|------------------------------|

Usage

```
pack.fisheries.frq(frq.obj)
```

Arguments

```
frq.obj
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| pagocatch | <i>pagocatch.Rd</i> |
|-----------|---------------------|

Usage

```
pagocatch(frq.obj)
```

Arguments

```
frq.obj
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
plot.base.comparison
      plot.base.comparison.Rd
```

Usage

```
plot.base.comparison(baseres, labs)
```

Arguments

```
baseres
labs
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
plot.biomass      plot.biomass.Rd
```

Usage

```
plot.biomass(plotdir = "H:/rmfcl/test/figs/", plotrep = test, varfile = NULL, ty
```

Arguments

```
plotdir
plotrep
varfile
type
plotname
plottype
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
plot.biomass.combined  
plot.biomass.combined.Rd
```

Usage

```
plot.biomass.combined(plotdir = "H:/rmfcl/test/figs/", plotrep = test, varfile =
```

Arguments

```
plotdir  
plotrep  
varfile  
type  
plotname  
plottype
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
plot.F.time          plot.F.time.Rd
```

Usage

```
plot.F.time(plotdir = "H:/rmfcl/test/figs/", plotrep = "C:/assessments/alb/2008/
```

Arguments

```
plotdir  
plotrep  
infile  
plotname  
plottype  
COL
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
plot.fishery.impact.r
      plot.fishery.impact.r.Rd
```

Usage

```
plot.fishery.impact.r(plotdir = "H:/rmfcl/test/figs/", type = "Total", plotrep =
```

Arguments

```
plotdir
type
plotrep
impnames
plotname
plottype
COL
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
plot.Kobe      plot.Kobe.Rd
```

Usage

```
plot.Kobe(plotdir = "S:/OFP Publications/Tuna Fishery Assessment Report/2007/Fig
```

Arguments

```
plotdir
plotrep
type
plotname
plottype
COL
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
plot.Kobe.template.bw
plot.Kobe.template.bw.Rd
```

Usage

```
plot.Kobe.template.bw (Type)
```

Arguments

Type

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
plot.Kobe.template.col
plot.Kobe.template.col.Rd
```

Usage

```
plot.Kobe.template.col (Type)
```

Arguments

Type

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
plot.mfcl.betyft09 plot.mfcl.betyft09.Rd
```

Usage

```
plot.mfcl.betyft09(lims = c(100, 260, -45, 45))
```

Arguments

```
lims
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
plot.nofishing plot.nofishing.Rd
```

Usage

```
plot.nofishing(plotdir = "H:/rmfcl/test/figs/", plotrep = testq0, type = "SSB",
```

Arguments

```
plotdir
plotrep
type
plotname
plottype
COL
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
plot.nofishing.combined  
plot.nofishing.combined.Rd
```

Usage

```
plot.nofishing.combined(plotdir = "H:/rmfcl/test/figs/", plotrep = testq0, type
```

Arguments

```
plotdir  
plotrep  
type  
plotname  
plottype  
COL
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
plot.pacific.alb plot.pacific.alb.Rd
```

Usage

```
plot.pacific.alb(plot_title = "", eez_dir = "I:/assessments/Pop dy modeling/MFCL
```

Arguments

```
plot_title  
eez_dir  
plot_eez
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
plot.pacific.skj    plot.pacific.skj.Rd
```

Usage

```
plot.pacific.skj(plot_title = "")
```

Arguments

```
plot_title
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

```
plot.pacific.species  
    plot.pacific.species.Rd
```

Usage

```
plot.pacific.species(plot_title = "", uselims = NA, add.WCPFC = F, add.EPO = F,
```

Arguments

```
plot_title  
uselims  
add.WCPFC  
add.EPO  
sp  
add.EEZ  
eez_file
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

`plot.pacific.WCPFC` *plot.pacific.WCPFC.Rd*

Usage

```
plot.pacific.WCPFC(plot_title = "", lims = c(100, 260, -45, 45))
```

Arguments

```
plot_title  
lims
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

`plot.pacific.yft` *plot.pacific.yft.Rd*

Usage

```
plot.pacific.yft(plot_title = "", lims = c(100, 260, -45, 45), add.WCPFC = F)
```

Arguments

```
plot_title  
lims  
add.WCPFC
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

plot.recruitment *plot.recruitment.Rd*

Usage

```
plot.recruitment(plotdir = "H:/rmfcl/test/figs/", plotrep = test, varfile = NULL)
```

Arguments

```
plotdir
plotrep
varfile
plotname
plotype
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

plot.recruitment.combined
 plot.recruitment.combined.Rd

Usage

```
plot.recruitment.combined(plotdir = "H:/rmfcl/test/figs/", plotrep = test, varfile = NULL)
```

Arguments

```
plotdir
plotrep
varfile
plotname
plotype
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

| | |
|------------------|----------------------------|
| plot_cpue_cv_frq | <i>plot_cpue_cv_frq.Rd</i> |
|------------------|----------------------------|

Usage

```
plot_cpue_cv_frq(frq, parf, fisheries)
```

Arguments

```
frq
parf
fisheries
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|---------------|-------------------------|
| read.catchrep | <i>read.catchrep.Rd</i> |
|---------------|-------------------------|

Usage

```
read.catchrep(catchrep.file)
```

Arguments

```
catchrep.file
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| read.ests | <i>read.ests.Rd</i> |
|-----------|---------------------|

Usage

```
read.ests(rep.obj, ests = "C:/assessments/alb/2008/6_area/28.splitgr3/ests.rep",
```

Arguments

```
rep.obj
```

```
ests
```

```
x
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.fit | <i>read.fit.Rd</i> |
|----------|--------------------|

Usage

```
read.fit(fit.file)
```

Arguments

```
fit.file
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.frq | <i>read.frq.Rd</i> |
|----------|--------------------|

Usage

```
read.frq(frq.file, frq.title = "", ntop = 0, fishdefs = NA)
```

Arguments

```
frq.file
frq.title
ntop
fishdefs
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------|-----------------------|
| read.impact | <i>read.impact.Rd</i> |
|-------------|-----------------------|

Usage

```
read.impact(impdir = "H:/rmfcl/test/", impnames = c("ll", "psassoc", "psunassoc"))
```

Arguments

```
impdir
impnames
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.ini | <i>read.ini.Rd</i> |
|----------|--------------------|

Usage

```
read.ini(ini.file)
```

Arguments

```
ini.file
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.par | <i>read.par.Rd</i> |
|----------|--------------------|

Usage

```
read.par(par.file)
```

Arguments

```
par.file
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.rep | <i>read.rep.Rd</i> |
|----------|--------------------|

Usage

```
read.rep(rep.file)
```

Arguments

```
rep.file
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.tag | <i>read.tag.Rd</i> |
|----------|--------------------|

Usage

```
read.tag(tagfile)
```

Arguments

```
tagfile
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| read.tags.JP | <i>read.tags.JP.Rd</i> |
|--------------|------------------------|

Usage

```
read.tags.JP(tagfile, reg_areas, fisheries)
```

Arguments

```
tagfile
reg_areas
fisheries
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| read.var | <i>read.var.Rd</i> |
|----------|--------------------|

Usage

```
read.var(var.file)
```

Arguments

```
var.file
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| read_nmd.frq | <i>read_nmd.frq.Rd</i> |
|--------------|------------------------|

Usage

```
read_nmd.frq(frq.file, frq.title = "", ntop = 0, fishdefs = NA)
```

Arguments

```
frq.file
frq.title
ntop
fishdefs
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| read_nmd.par | <i>read_nmd.par.Rd</i> |
|--------------|------------------------|

Usage

```
read_nmd.par(par.file)
```

Arguments

```
par.file
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
reconstruct.frq.ce reconstruct.frq.ce.Rd
```

Usage

```
reconstruct.frq.ce(CPUE.file = "X:/yft/2009/Data Preparation/CPUE/indices/yft_JP
```

Arguments

```
CPUE.file
```

```
data
```

```
fishery
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
reconstruct.frq.ce2008  
reconstruct.frq.ce2008.Rd
```

Usage

```
reconstruct.frq.ce2008(data = out.data, fishery = 1)
```

Arguments

```
data  
fishery
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
reconstruct.frq.size  
reconstruct.frq.size.Rd
```

Usage

```
reconstruct.frq.size(data = data, FISH = 1, LF.FILE = "P:/yft/2009/Data Preparat
```

Arguments

```
data  
FISH  
LF.FILE  
WT.FILE
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
region_single_frq  region_single_frq.Rd
```

Usage

```
region_single_frq(frq, region)
```

Arguments

```
frq  
region
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

```
region_single_ini  region_single_ini.Rd
```

Usage

```
region_single_ini(ini)
```

Arguments

```
ini
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

```
region_single_tag  region_single_tag.Rd
```

Usage

```
region_single_tag(tag, region, keepfish)
```

Arguments

```
tag
region
keepfish
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==>  Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
regroup_fishery_grps.doitall
      regroup_fishery_grps.doitall.Rd
```

Usage

```
regroup_fishery_grps.doitall(doitall, f, flag, newgrps)
```

Arguments

```
doitall
f
flag
newgrps
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==>  Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
rename.fisheries.doitall  
      rename.fisheries.doitall.Rd
```

Usage

```
rename.fisheries.doitall(doitall, oldfs, newfs)
```

Arguments

```
doitall  
oldfs  
newfs
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

```
rename.fisheries.frq  
      rename.fisheries.frq.Rd
```

Usage

```
rename.fisheries.frq(frq.obj, oldfish, newfish)
```

Arguments

```
frq.obj  
oldfish  
newfish
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do  help(data=index)  for the standard data sets.
```

```
rename.fisheries.tag  
    rename.fisheries.tag.Rd
```

Usage

```
rename.fisheries.tag(tag.obj, oldfish, newfish)
```

Arguments

```
tag.obj  
oldfish  
newfish
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
rename.fishery.grps.doitall  
    rename.fishery.grps.doitall.Rd
```

Usage

```
rename.fishery.grps.doitall(doitall, oldfs, newfs, flag, keep = T, newgrps = c(0
```

Arguments

```
doitall  
oldfs  
newfs  
flag  
keep  
newgrps
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| retro.frq | <i>retro.frq.Rd</i> |
|-----------|---------------------|

Usage

```
retro.frq(frq.obj, retro.tag.obj = NA)
```

Arguments

```
frq.obj
retro.tag.obj
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| retro.tag | <i>retro.tag.Rd</i> |
|-----------|---------------------|

Usage

```
retro.tag(tag.obj, yr)
```

Arguments

```
tag.obj
yr
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

```
rm_fisheries.doitall  
rm_fisheries.doitall.Rd
```

Usage

```
rm_fisheries.doitall(a, rmfisheries)
```

Arguments

```
a  
rmfisheries
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
rm_fisheries.frq  rm_fisheries.frq.Rd
```

Usage

```
rm_fisheries.frq(frq.obj, fishery)
```

Arguments

```
frq.obj  
fishery
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|------------------|----------------------------|
| rm_fisheries.tag | <i>rm_fisheries.tag.Rd</i> |
|------------------|----------------------------|

Usage

```
rm_fisheries.tag(tag.obj, fisheries)
```

Arguments

```
tag.obj  
fisheries
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------|-----------------------|
| rm_fishflag | <i>rm_fishflag.Rd</i> |
|-------------|-----------------------|

Usage

```
rm_fishflag(doitall, flag)
```

Arguments

```
doitall  
flag
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------------|---------------------------|
| rm_flag.doitall | <i>rm_flag.doitall.Rd</i> |
|-----------------|---------------------------|

Usage

```
rm_flag.doitall(a, flagtype, flag, value)
```

Arguments

```
a  
flagtype  
flag  
value
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-------------|-----------------------|
| run.profile | <i>run.profile.Rd</i> |
|-------------|-----------------------|

Usage

```
run.profile(rundir, rungrp, startpar = NA, ptype = "Fmult", target, nsteps = 300)
```

Arguments

```
rundir  
rungrp  
startpar  
ptype  
target  
nsteps  
penalty
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| seas.flag | <i>seas.flag.Rd</i> |
|-----------|---------------------|

Usage

```
seas.flag(a, fishery, flagnum, seasf.list)
```

Arguments

```
a  
fishery  
flagnum  
seasf.list
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| seas.frq | <i>seas.frq.Rd</i> |
|----------|--------------------|

Usage

```
seas.frq(frq.obj, seas.fish)
```

Arguments

```
frq.obj  
seas.fish
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| seas.tag | <i>seas.tag.Rd</i> |
|----------|--------------------|

Usage

```
seas.tag(tag.obj, fishlist)
```

Arguments

```
tag.obj  
fishlist
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|------------|----------------------|
| setup.cpue | <i>setup.cpue.Rd</i> |
|------------|----------------------|

Usage

```
setup.cpue(rungrp, sourcedir, cpue, spp)
```

Arguments

```
rungrp  
sourcedir  
cpue  
spp
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| setup.ffcreeep | <i>setup.ffcreeep.Rd</i> |
|----------------|--------------------------|

Usage

```
setup.ffcreeep(rungrp, creeprate)
```

Arguments

```
rungrp
```

```
creeprate
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| setup.growth | <i>setup.growth.Rd</i> |
|--------------|------------------------|

Usage

```
setup.growth(rungrp, VBopt)
```

Arguments

```
rungrp
```

```
VBopt
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
setup.growth.offsets  
      setup.growth.offsets.Rd
```

Usage

```
setup.growth.offsets(rungrp, ageclasses, penwt, phase, tog)
```

Arguments

```
rungrp  
ageclasses  
penwt  
phase  
tog
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
setup.idphcatch      setup.idphcatch.Rd
```

Usage

```
setup.idphcatch(rungrp, sourcedir, idph, spp)
```

Arguments

```
rungrp  
sourcedir  
idph  
spp
```

Examples

```
##---- Should be DIRECTLY executable !! ----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|--------------|------------------------|
| setup.lensel | <i>setup.lensel.Rd</i> |
|--------------|------------------------|

Usage

```
setup.lensel(rungrp, fisheries, tog)
```

Arguments

```
rungrp
fisheries
tog
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------|----------------------|
| setup.LFwt | <i>setup.LFwt.Rd</i> |
|------------|----------------------|

Usage

```
setup.LFwt(rungrp, newLFwt)
```

Arguments

```
rungrp
newLFwt
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|---------|-------------------|
| setup.M | <i>setup.M.Rd</i> |
|---------|-------------------|

Usage

```
setup.M(rungrp, newM)
```

Arguments

```
rungrp
```

```
newM
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|---------------|-------------------------|
| setup.pscatch | <i>setup.pscatch.Rd</i> |
|---------------|-------------------------|

Usage

```
setup.pscatch(rungrp, sourcedir, PScatch, spp)
```

Arguments

```
rungrp
```

```
sourcedir
```

```
PScatch
```

```
spp
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|---------------|-------------------------|
| setup.startyr | <i>setup.startyr.Rd</i> |
|---------------|-------------------------|

Usage

```
setup.startyr(rungrp, newstartyr)
```

Arguments

```
rungrp
```

```
newstartyr
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------------|---------------------------|
| setup.steepness | <i>setup.steepness.Rd</i> |
|-----------------|---------------------------|

Usage

```
setup.steepness(rungrp, newsteep)
```

Arguments

```
rungrp
```

```
newsteep
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------------|---------------------------|
| setup.timesplit | <i>setup.timesplit.Rd</i> |
|-----------------|---------------------------|

Usage

```
setup.timesplit(rungrp, splitx, storefish)
```

Arguments

```
rungrp  
splitx  
storefish
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------|--------------------|
| sort.frq | <i>sort.frq.Rd</i> |
|----------|--------------------|

Usage

```
sort.frq(frq.obj)
```

Arguments

```
frq.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| start_year.frq | <i>start_year.frq.Rd</i> |
|----------------|--------------------------|

Usage

```
start_year.frq(frq.obj, start_yr, halfyr = F)
```

Arguments

```
frq.obj  
start_yr  
halfyr
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|----------------|--------------------------|
| steepness.doit | <i>steepness.doit.Rd</i> |
|----------------|--------------------------|

Usage

```
steepness.doit(doitall, new.steepness, add_header = T, gap = 2)
```

Arguments

```
doitall  
new.steepness  
  
add_header  
gap
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

```
summarise.size.frq.bet
      summarise.size.frq.bet.Rd
```

Usage

```
summarise.size.frq.bet(frql, fishery = 5)
```

Arguments

```
frql
fishery
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

```
tag_grps_rm      tag_grps_rm.Rd
```

Usage

```
tag_grps_rm(tag.obj, keep)
```

Arguments

```
tag.obj
keep
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

`timesplit.doitall` *timesplit.doitall.Rd*

Usage

```
timesplit.doitall(doitall, fishsplit, qsplit = T)
```

Arguments

```
doitall
fishsplit
qsplit
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

`timesplit.frq` *timesplit.frq.Rd*

Usage

```
timesplit.frq(frq.obj, divyrs, div.fish)
```

Arguments

```
frq.obj
divyrs
div.fish
```

Examples

```
##---- Should be DIRECTLY executable !! ----
##-- ==> Define data, use random,
##--or do  help(data=index)  for the standard data sets.
```

| | |
|---------------|-------------------------|
| timesplit.tag | <i>timesplit.tag.Rd</i> |
|---------------|-------------------------|

Usage

```
timesplit.tag(tag.obj, fishsplit)
```

Arguments

```
tag.obj
fishsplit
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|------------|----------------------|
| varfromstr | <i>varfromstr.Rd</i> |
|------------|----------------------|

Usage

```
varfromstr(datstring, cols = c(2:3))
```

Arguments

```
datstring
cols
```

Examples

```
##----- Should be DIRECTLY executable !! -----
##-- ==> Define data, use random,
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| write.frq | <i>write.frq.Rd</i> |
|-----------|---------------------|

Usage

```
write.frq(new.frq, frq.obj)
```

Arguments

```
new.frq  
frq.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| write.ini | <i>write.ini.Rd</i> |
|-----------|---------------------|

Usage

```
write.ini(ini.file, ini.obj)
```

Arguments

```
ini.file  
ini.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| write.par | <i>write.par.Rd</i> |
|-----------|---------------------|

Usage

```
write.par(par.file, par.obj)
```

Arguments

```
par.file
```

```
par.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|-----------|---------------------|
| write.tag | <i>write.tag.Rd</i> |
|-----------|---------------------|

Usage

```
write.tag(tagfile, tag.obj)
```

Arguments

```
tagfile
```

```
tag.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|---------------|-------------------------|
| write_nmd.frq | <i>write_nmd.frq.Rd</i> |
|---------------|-------------------------|

Usage

```
write_nmd.frq(new.frq, frq.obj)
```

Arguments

```
new.frq  
frq.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

| | |
|---------------|-------------------------|
| write_nmd.par | <i>write_nmd.par.Rd</i> |
|---------------|-------------------------|

Usage

```
write_nmd.par(par.file, par.obj)
```

Arguments

```
par.file  
par.obj
```

Examples

```
##----- Should be DIRECTLY executable !! -----  
##-- ==> Define data, use random,  
##--or do help(data=index) for the standard data sets.
```

Index

*Topic \textasciitilde\dekwd1

add.catch.frq, [4](#)
add.cpue.frq, [4](#)
add.flag, [5](#)
alb.clean.lfdata, [5](#)
alb.initial_clean_2008, [6](#)
alb.initial_clean_2009, [6](#)
alb.initial_clean_2011, [7](#)
carry.effort.frq, [8](#)
change.fishflag, [8](#)
change.flag, [9](#)
change.negflag, [9](#)
change.size.frq, [10](#)
change_data, [10](#)
check.eff.devs, [11](#)
check_flag_value, [11](#)
clean.lfdata, [12](#)
compare.ce.frq, [12](#)
compare.frq, [13](#)
compare.size.frq, [13](#)
compare.size.frq2, [14](#)
compare_par_flags, [14](#)
condor.go, [15](#)
condor.go2, [15](#)
Convert.frq.ver6, [16](#)
create.missing.ce, [16](#)
create.ver6.frq, [17](#)
crit.fishery.summary, [17](#)
crit.summary, [18](#)
datfromstr, [18](#)
do.critical.calcs, [19](#)
doit.rm_flag, [19](#)
effortcreep, [20](#)
fix_growth, [20](#)
frq.change.nint, [21](#)
frq.remove.size.or.weight.data,
[21](#)
get.critical.age, [22](#)
get.length.output, [22](#)
get.outcomes, [23](#)
get.outcomes.alb, [23](#)
get.outcomes.test, [24](#)
get.weight.output, [24](#)
initial_clean_2008, [25](#)
labels_store, [25](#)
load.LFdata, [25](#)
make.projection.betyft.frq,
[26](#)
map_all_pacific, [26](#)
merge.frq, [27](#)
merge.tag, [27](#)
merge_tag_objs, [28](#)
NZtrollglm, [28](#)
oldsetup, [29](#)
pack.fisheries.frq, [29](#)
pagocatch, [29](#)
plot.base.comparison, [30](#)
plot.biomass, [30](#)
plot.biomass.combined, [31](#)
plot.F.time, [31](#)
plot.fishery.impact.r, [32](#)
plot.Kobe, [32](#)
plot.Kobe.template.bw, [33](#)
plot.Kobe.template.col, [33](#)
plot.mfcl.betyft09, [34](#)
plot.nofishing, [34](#)
plot.nofishing.combined, [35](#)
plot.pacific.alb, [35](#)
plot.pacific.skj, [36](#)
plot.pacific.species, [36](#)
plot.pacific.WCPFC, [37](#)
plot.pacific.yft, [37](#)
plot.recruitment, [38](#)
plot.recruitment.combined, [38](#)
plot_cpue_cv_frq, [39](#)
read.catchrep, [39](#)
read.ests, [40](#)
read.fit, [40](#)
read.frq, [41](#)
read.impact, [41](#)
read.ini, [42](#)
read.par, [42](#)
read.rep, [42](#)
read.tag, [43](#)
read.tags.JP, [43](#)
read.var, [44](#)

read_nmd.frq, 44
 read_nmd.par, 45
 reconstruct.frq.ce, 45
 reconstruct.frq.ce2008, 46
 reconstruct.frq.size, 46
 region_single_frq, 47
 region_single_ini, 47
 region_single_tag, 48
 regroup_fishery_grps.doitall, 48
 rename.fisheries.doitall, 49
 rename.fisheries.frq, 49
 rename.fisheries.tag, 50
 rename.fishery.grps.doitall, 50
 retro.frq, 51
 retro.tag, 51
 rm_fisheries.doitall, 52
 rm_fisheries.frq, 52
 rm_fisheries.tag, 53
 rm_fishflag, 53
 rm_flag.doitall, 54
 run.profile, 54
 seas.flag, 55
 seas.frq, 55
 seas.tag, 56
 setup.cpue, 56
 setup.effcreep, 57
 setup.growth, 57
 setup.growth.offsets, 58
 setup.idphcatch, 58
 setup.lensel, 59
 setup.LFwt, 59
 setup.M, 60
 setup.pscatch, 60
 setup.startyr, 61
 setup.steepness, 61
 setup.timesplit, 62
 sort.frq, 62
 start_year.frq, 63
 steepness.doit, 63
 summarise.size.frq.bet, 64
 tag_grps_rm, 64
 timesplit.doitall, 65
 timesplit.frq, 65
 timesplit.tag, 66
 varfromstr, 66
 write.frq, 67
 write.ini, 67
 write.par, 68
 write.tag, 68
 write_nmd.frq, 69
 write_nmd.par, 69
***Topic \textasciitildekw2**
 add.catch.frq, 4
 add.cpue.frq, 4
 add.flag, 5
 alb.clean.lfdata, 5
 alb.initial_clean_2008, 6
 alb.initial_clean_2009, 6
 alb.initial_clean_2011, 7
 carry.effort.frq, 8
 change.fishflag, 8
 change.flag, 9
 change.negflag, 9
 change.size.frq, 10
 change_data, 10
 check.eff.devs, 11
 check_flag_value, 11
 clean.lfdata, 12
 compare.ce.frq, 12
 compare.frq, 13
 compare.size.frq, 13
 compare.size.frq2, 14
 compare_par_flags, 14
 condor.go, 15
 condor.go2, 15
 Convert.frq.ver6, 16
 create.missing.ce, 16
 create.ver6.frq, 17
 crit.fishery.summary, 17
 crit.summary, 18
 datfromstr, 18
 do.critical.calcs, 19
 doit.rm_flag, 19
 effortcreep, 20
 fix_growth, 20
 frq.change.nint, 21
 frq.remove.size.or.weight.data, 21
 get.critical.age, 22
 get.length.output, 22
 get.outcomes, 23
 get.outcomes.alb, 23
 get.outcomes.test, 24
 get.weight.output, 24
 initial_clean_2008, 25
 labels_store, 25
 load.LFdata, 25
 make.projection.betyft.frq, 26
 map_all_pacific, 26
 merge.frq, 27
 merge.tag, 27

- merge_tag_objs, 28
- NZtrollglm, 28
- oldsetup, 29
- pack.fisheries.frq, 29
- pagocatch, 29
- plot.base.comparison, 30
- plot.biomass, 30
- plot.biomass.combined, 31
- plot.F.time, 31
- plot.fishery.impact.r, 32
- plot.Kobe, 32
- plot.Kobe.template.bw, 33
- plot.Kobe.template.col, 33
- plot.mfcl.betyft09, 34
- plot.nofishing, 34
- plot.nofishing.combined, 35
- plot.pacific.alb, 35
- plot.pacific.skj, 36
- plot.pacific.species, 36
- plot.pacific.WCPFC, 37
- plot.pacific.yft, 37
- plot.recruitment, 38
- plot.recruitment.combined, 38
- plot_cpue_cv_frq, 39
- read.catchrep, 39
- read.ests, 40
- read.fit, 40
- read.frq, 41
- read.impact, 41
- read.ini, 42
- read.par, 42
- read.rep, 42
- read.tag, 43
- read.tags.JP, 43
- read.var, 44
- read_nmd.frq, 44
- read_nmd.par, 45
- reconstruct.frq.ce, 45
- reconstruct.frq.ce2008, 46
- reconstruct.frq.size, 46
- region_single_frq, 47
- region_single_ini, 47
- region_single_tag, 48
- regroup_fishery_grps.doitall, 48
- rename.fisheries.doitall, 49
- rename.fisheries.frq, 49
- rename.fisheries.tag, 50
- rename.fishery_grps.doitall, 50
- retro.frq, 51
- retro.tag, 51
- rm_fisheries.doitall, 52
- rm_fisheries.frq, 52
- rm_fisheries.tag, 53
- rm_fishflag, 53
- rm_flag.doitall, 54
- run.profile, 54
- seas.flag, 55
- seas.frq, 55
- seas.tag, 56
- setup.cpue, 56
- setup.effcreep, 57
- setup.growth, 57
- setup.growth.offsets, 58
- setup.idphcatch, 58
- setup.lensel, 59
- setup.LFwt, 59
- setup.M, 60
- setup.pscatch, 60
- setup.startyr, 61
- setup.steepness, 61
- setup.timesplit, 62
- sort.frq, 62
- start_year.frq, 63
- steepness.doit, 63
- summarise.size.frq.bet, 64
- tag_grps_rm, 64
- timesplit.doitall, 65
- timesplit.frq, 65
- timesplit.tag, 66
- varfromstr, 66
- write.frq, 67
- write.ini, 67
- write.par, 68
- write.tag, 68
- write_nmd.frq, 69
- write_nmd.par, 69
- add.catch.frq, 4
- add.cpue.frq, 4
- add.flag, 5
- alb.clean.lfdata, 5
- alb.initial_clean_2008, 6
- alb.initial_clean_2009, 6
- alb.initial_clean_2011, 7
- alb.pagocatch_2009, 7
- carry.effort.frq, 8
- change.fishflag, 8
- change.flag, 9
- change.negflag, 9
- change.size.frq, 10
- change_data, 10
- check.eff.devs, 11

check_flag_value, 11
 clean.lfdata, 12
 compare.ce.frq, 12
 compare.frq, 13
 compare.size.frq, 13
 compare.size.frq2, 14
 compare_par_flags, 14
 condor.go, 15
 condor.go2, 15
 Convert.frq.ver6, 16
 create.missing.ce, 16
 create.ver6.frq, 17
 crit.fishery.summary, 17
 crit.summary, 18

 datfromstr, 18
 do.critical.calcs, 19
 doit.rm_flag, 19

 effortcreep, 20

 fix_growth, 20
 frq.change.nint, 21
 frq.remove.size.or.weight.data,
 21

 get.critical.age, 22
 get.length.output, 22
 get.outcomes, 23
 get.outcomes.alb, 23
 get.outcomes.test, 24
 get.weight.output, 24

 initial_clean_2008, 25

 labels_store, 25
 load.LFdata, 25

 make.projection.betyft.frq, 26
 map_all_pacific, 26
 merge.frq, 27
 merge.tag, 27
 merge_tag_objs, 28

 NZtrollglm, 28

 oldsetup, 29

 pack.fisheries.frq, 29
 pagocatch, 29
 plot.base.comparison, 30
 plot.biomass, 30
 plot.biomass.combined, 31
 plot.F.time, 31

 plot.fishery.impact.r, 32
 plot.Kobe, 32
 plot.Kobe.template.bw, 33
 plot.Kobe.template.col, 33
 plot.mfcl.betyft09, 34
 plot.nofishing, 34
 plot.nofishing.combined, 35
 plot.pacific.alb, 35
 plot.pacific.skj, 36
 plot.pacific.species, 36
 plot.pacific.WCPFC, 37
 plot.pacific.yft, 37
 plot.recruitment, 38
 plot.recruitment.combined, 38
 plot_cpue_cv_frq, 39

 read.catchrep, 39
 read.ests, 40
 read.fit, 40
 read.frq, 41
 read.impact, 41
 read.ini, 42
 read.par, 42
 read.rep, 42
 read.tag, 43
 read.tags.JP, 43
 read.var, 44
 read_nmd.frq, 44
 read_nmd.par, 45
 reconstruct.frq.ce, 45
 reconstruct.frq.ce2008, 46
 reconstruct.frq.size, 46
 region_single_frq, 47
 region_single_ini, 47
 region_single_tag, 48
 regroup_fishery_grps.doitall, 48
 rename.fisheries.doitall, 49
 rename.fisheries.frq, 49
 rename.fisheries.tag, 50
 rename.fishery.grps.doitall, 50
 retro.frq, 51
 retro.tag, 51
 rm_fisheries.doitall, 52
 rm_fisheries.frq, 52
 rm_fisheries.tag, 53
 rm_fishflag, 53
 rm_flag.doitall, 54
 run.profile, 54

 seas.flag, 55
 seas.frq, 55
 seas.tag, 56
 setup.cpue, 56

setup.effcreep, [57](#)
setup.growth, [57](#)
setup.growth.offsets, [58](#)
setup.idphcatch, [58](#)
setup.lensel, [59](#)
setup.LFwt, [59](#)
setup.M, [60](#)
setup.pscatch, [60](#)
setup.startyr, [61](#)
setup.steepness, [61](#)
setup.timesplit, [62](#)
sort.frq, [62](#)
start_year.frq, [63](#)
steepness.doit, [63](#)
summarise.size.frq.bet, [64](#)

tag_grps_rm, [64](#)
timesplit.doitall, [65](#)
timesplit.frq, [65](#)
timesplit.tag, [66](#)

varfromstr, [66](#)

write.frq, [67](#)
write.ini, [67](#)
write.par, [68](#)
write.tag, [68](#)
write_nmd.frq, [69](#)
write_nmd.par, [69](#)