1. what are semantic elements :-

A semantic element clearly describes it's meaning to both the browser and developers.

Ex:

Semantic element : <From> <Table> and <article>

(clearly defines it's content)

non-semantic element : and

2. Position :-

* The position property specifies the type of position methods used for an element.

Position properties (static, relative, Fixed, absolute, sticky)

i) Static :-

* static positioned element are not affected by the top, bottom, left, and right.

* static is not positioned in any special way. It positioned according to normal flow of the page.

ii) Relative :-

* position relative to it's normal position.

* setting on the top, right bottom and left properties of relatively- positioned element to be adjusted away from it's normal position

* other content will not be adjust to fit into any gap left by element.

iii) Fixed :-

* Fixed is always's in the same place even if the page is scrolled.

* top, bottom, right and left properties are used to position the element.

iv) absolute :-

* absolute is position relative to the nearest position ancestor.

* if absolute position has no positioned ancestors, it uses the document body and move along with page scrolling.

v) sticky :-

* It position based on the user's scroll position

* A sticky element toggles between relative and Fixed. on the scroll position

* It is positioned relative until a given offset position is met in the viewport.

3. difference between inline element and inline block :-

inline Element	block element.
i) Displays an element as an inline element. ans height and width properties will have no effect	i) Displays an element as an inline-level block container. you can set height and width values.
ii) the element doesn't start on new line and only ocupy just the width requires. you can't set the width or height.	ii) It's Formated just like the inline element where it doesn't start on a new line. you can set width/hight values.

4. what is the use of doctype HTML :-

* The HTML type declaration also known as DOCTYPE, is the First line of code require in every HTML or XHTML document.

* The DOCTYPE declaration is an instruction to the web browser what version of HTML the page is written in.

5. Purpose of meta tag :-

* The <meta> tag defines metadata about an HTML document metadata is data information about data.

* <meta> tags always go inside the <head> element, and are typically used to specify charactor set page description keywords author of document and viewport settings.

6. Diffrance between :-

Pseudo - classes	Psudo - elements
i) Pseudo-classes represents a state of a selector. Ex: hover, active, (these start with (:) single colon.	i) Similarly a Pseudo-element is used to select virtual element. Ex: after, before (it's start with double colon (::)
ii) Pseudo-classes select regular elements but under conditions like, position relative to siblings.	ii) Pseudo-element effectively create new element that are not specified in the mark up the document manipulated much like regular element.

7. Animation Iration Properties:

* Set's the number of times an animatio sequance should be played before stopping.

Properties:-

i) number

ii) infinite

iii) inherit

iv) initial

i) Number :-

number is How many time's runs the animation. count.

ii) infinite :.

* infinite is runs the Animation in infinite.

8. Svg and Canvas uses :-

* Svg gives better performance with Smaller of object (or) large surface.

Canvas gives better performance with Smaller surface (or) larger of objects.

Svg can be modified through script and css.

Canvas can be modified through Script only.

9. Media Query :-

* A media query consists of an media type zero (or) more expressions that match the type of and conditions of a particular media features such as device width of screen resolution

10. orientation :-

* the orientation CSS media feature can be used to test the orientation of the viewport.
* this feathers does not correspond to device orientation.

Keyword value :-

* potrait
* Landscape.

Potrait :-

* The viewport is in a potrait orientation.

Exa :

* the height is greater than (or) equal to the width.

Landscape :-

* this in a landscape orientation.

Exa : the width is greater than the height.

12. Set time out and set interval difference.

* Set timeout allows us to run a function once after the interval of time.

* Set interval allows us to run a function repeatedly, starting after the interval of time then repeating continuously at that interval.

13. Box-model :-

* The CSS box model is a container that the contains multiple properties including borders, margin, padding, and the content itself.

14. Attributes :-

* An HTML attributes is a piece of markup language used to adjust the behaviour (or) display of an HTML element

Ex :

attributes can be used to change the color size, or functionality of HTML elements.

CSS Reset:

* A CSS Reset style sheet is a list of values that 'reset' all the default browser styles.

* we reset the browser styles for two reason.

Primary Reason:-

* Not all the browsers apply the same default values. they may be similar, but not exact.

* once you start designing and coding all of the fine details of your site you may discover that a lot what you are doing is simply overriding default browser styles.