

1.5.34

RAVULA SHASHANK REDDY - EE25BTECH11047

September 3, 2025

Question

The point P which divides the line segment joining the points A (2, -5) and B (5,2) in the ratio 2 : 3 lies in which quadrant?

The formula for internal division of vectors is where P divides A and B in the ratio k:1

$$\mathbf{P} = \frac{k\mathbf{B} + \mathbf{A}}{1 + k}$$

Theoretical Solution

Given:

$$\mathbf{A} = \begin{pmatrix} 2 \\ -5 \end{pmatrix} \quad (1)$$

$$\mathbf{B} = \begin{pmatrix} 5 \\ 2 \end{pmatrix} \quad (2)$$

Now the matrix form for \mathbf{A} and \mathbf{B} is :

$$(\mathbf{A} \quad \mathbf{B}) = \begin{pmatrix} 2 & 5 \\ -5 & 2 \end{pmatrix} \quad (3)$$

The point P dividing the segment AB in the ratio 2:3 internally , has the position vector :

$$\mathbf{P} = \frac{3\mathbf{A} + 2\mathbf{B}}{3 + 2} \quad (4)$$

Thus by using the section formula

$$\mathbf{P} = \frac{1}{5} \cdot (\mathbf{A} \quad \mathbf{B}) \begin{pmatrix} 3 \\ 2 \end{pmatrix} \quad (5)$$

$$\mathbf{P} = \frac{1}{5} \cdot \begin{pmatrix} 2 & 5 \\ -5 & 2 \end{pmatrix} \begin{pmatrix} 3 \\ 2 \end{pmatrix} \quad (6)$$

$$\mathbf{P} = \frac{1}{5} \cdot \begin{pmatrix} 6 + 10 \\ -15 + 4 \end{pmatrix} \quad (7)$$

$$\therefore \mathbf{P} = \frac{\begin{pmatrix} 16 \\ -11 \end{pmatrix}}{5}. \quad (8)$$

Hence the vector \mathbf{P} is $\begin{pmatrix} \frac{16}{5} \\ \frac{-11}{5} \end{pmatrix} = \begin{pmatrix} 3.2 \\ -2.2 \end{pmatrix}$

Since $x > 0$ and $y < 0$, \mathbf{P} lies in the **IV (fourth) quadrant**.

C Code - Section formula function

```
// section_formula.c
#include <stdio.h>

void find_section_point(double x1, double y1, double x2, double
    y2, double m, double n, double* x, double* y) {
    *x = (m * x2 + n * x1) / (m + n);
    *y = (m * y2 + n * y1) / (m + n);
}
```

Python Code through shared output

```
# Section Formula Problem

import numpy as np
import matplotlib.pyplot as plt

# Given points
A = np.array([2, -5]).reshape(-1,1)
B = np.array([5, 2]).reshape(-1,1)

# Ratio m:n = 2:3
m, n = 2, 3

# Point dividing AB in ratio m:n
P = (n*A + m*B) / (m+n)

# Determine Quadrant
x, y = P[0,0], P[1,0]
```

```
if x > 0 and y > 0:
    quadrant = First Quadrant
elif x < 0 and y > 0:
    quadrant = Second Quadrant
elif x < 0 and y < 0:
    quadrant = Third Quadrant
elif x > 0 and y < 0:
    quadrant = Fourth Quadrant
else:
    quadrant = On Axis

print(fCoordinates of P: ({x:.2f}, {y:.2f}))
print(fP lies in the {quadrant})

# Generate line AB
x_AB = np.linspace(A[0,0], B[0,0], 100)
y_AB = np.linspace(A[1,0], B[1,0], 100)
```



```

# Plot line AB
plt.plot(x_AB, y_AB, label='$AB$')

# Plot points A, B, P
plt.scatter([A[0,0], B[0,0], P[0,0]], [A[1,0], B[1,0], P[1,0]],
            color='red')
labels = ['A(2,-5)', 'B(5,2)', f'P({x:.2f},{y:.2f})']
for i, txt in enumerate(labels):
    plt.annotate(txt, ( [A[0,0], B[0,0], P[0,0]][i],
                        [A[1,0], B[1,0], P[1,0]][i]),
                  textcoords=offset points, xytext=(10,-10))

```

```
# Styling axes
ax = plt.gca()
ax.spines['left'].set_position('zero')
ax.spines['bottom'].set_position('zero')
ax.spines['top'].set_color('none')
ax.spines['right'].set_color('none')

plt.legend(loc='best')
plt.grid(True)
plt.axis('equal')
plt.show()
```

Python code : Direct

```
import numpy as np
import matplotlib.pyplot as plt
#local imports
from libs.line.funcs import *
from libs.triangle.funcs import *
from libs.conics.funcs import circ_gen

# Given points
A = np.array([2,-5]).reshape(-1,1)
B = np.array([5,2]).reshape(-1,1)

# Ratio m:n = 2:3
m, n = 2, 3

# Point dividing AB in ratio m:n
P = (n*A + m*B) / (m+n)
```

```
# Generating line AB
def line_gen(A,B):

    len = 100
    dim = A.shape[0]
    x_AB = np.zeros((dim,len))
    lam_1 = np.linspace(0,1,len)

    for i in range(len):
        temp1 = A + lam_1[i]*(B-A)
        x_AB[:,i]= temp1.T
    return x_AB

x_AB = line_gen(A,B)

# Plotting line AB
plt.plot(x_AB[0,:], x_AB[1,:], label='$AB$')

# Plotting points A, B, P
```

```

tri_coords = np.block([[A,B,P]])
plt.scatter(tri_coords[0,:], tri_coords[1,:])
vert_labels = ['A','B','P']


for i, txt in enumerate(vert_labels):
    plt.annotate(f'{txt}\n({tri_coords[0,i]:.1f}, {tri_coords[1,i]:.1f})',
                (tri_coords[0,i], tri_coords[1,i]),
                textcoords=offset points,
                xytext=(20,-10), ha='center')

# Axis styling
ax = plt.gca()
ax.spines['left'].set_position('zero')
ax.spines['bottom'].set_position('zero')
ax.spines['top'].set_color('none')
ax.spines['right'].set_color('none')

```

```
plt.legend(loc='best')
plt.grid()
plt.axis('equal')
plt.show()
```

Plot by python using shared output from c



Plot by python only

