

Grails3 配置单独的数据库 properties

在 `build.gradle` 中加入 `bootRun`，这是加在最后面的，这里随意，貌似会加载 `application` 开头的 `properties` 的配置文件。

```
bootRun {  
    systemProperties = System.properties  
}
```

在 `grails-app/conf` 下面新建 `application.properties`，定义好数据库信息

```
jdbc.username=root  
jdbc.password=root  
jdbc.created=update  
jdbc.driver=com.mysql.jdbc.Driver  
jdbc.url=jdbc:mysql://localhost:3306/test?useUnicode=true&characterEncoding=UTF-8
```

接下来就是在 `grails-app/conf/application.yml` 中动态调用 `application.properties` 配置

```
---  
hibernate:  
  cache:  
    queries: false  
    use_second_level_cache: true  
    use_query_cache: false  
    region.factory_class: 'org.hibernate.cache.ehcache.EhCacheRegionFactory'  
  
dataSource:  
  pooled: true  
  jmxExport: true  
  driverClassName: '${jdbc.driver}'  
  username: '${jdbc.username}'  
  password: '${jdbc.password}'  
  
environments:  
  development:  
    dataSource:  
      dbCreate: '${jdbc.created}'  
      url: '${jdbc.url}'  
  test:  
    dataSource:  
      dbCreate: '${jdbc.created}'  
      url: '${jdbc.url}'  
  production:  
    dataSource:  
      dbCreate: '${jdbc.created}'  
      url: '${jdbc.url}'  
    properties:  
      jmxEnabled: true  
      initialSize: 5  
      maxActive: 50  
      minIdle: 5  
      maxIdle: 25  
      maxWait: 10000  
      maxAge: 600000  
      timeBetweenEvictionRunsMillis: 5000  
      minEvictableIdleTimeMillis: 60000  
      validationQuery: SELECT 1  
      validationQueryTimeout: 3  
      validationInterval: 15000  
      testOnBorrow: true  
      testWhileIdle: true
```

```

testOnReturn: false
jdbcInterceptors: ConnectionState
defaultTransactionIsolation: 2 # TRANSACTION_READ_COMMITTED
---
---
grails:
  profile: web
  codegen:
    defaultPackage: frame
  spring:
    transactionManagement:
      proxies: false
info:
  app:
    name: '@info.app.name@'
    version: '@info.app.version@'
    grailsVersion: '@info.app.grailsVersion@'
spring:
  groovy:
    template:
      check-template-location: false
---
grails:
  mime:
    disable:
      accept:
        header:
          userAgent:
            - Gecko
            - WebKit
            - Presto
            - Trident
  types:
    all: '*/*'
    atom: application/atom+xml
    css: text/css
    csv: text/csv
    form: application/x-www-form-urlencoded
    html:
      - text/html
      - application/xhtml+xml
    js: text/javascript
    json:
      - application/json
      - text/json
    multipartForm: multipart/form-data
    pdf: application/pdf
    rss: application/rss+xml
    text: text/plain
    hal:
      - application/hal+json
      - application/hal+xml
    xml:
      - text/xml
      - application/xml

```

```
urlmapping:
  cache:
    maxsize: 1000
controllers:
  defaultScope: singleton
converters:
  encoding: UTF-8
views:
  default:
    codec: html
  gsp:
    encoding: UTF-8
    htmlcodec: xml
    codecs:
      expression: html
      scriptlets: html
      taglib: none
      staticparts: none
endpoints:
  jmx:
    unique-names: true
```