

### Exercise 1:

Having mastered the intricacies of random forests, our medical research team has set eyes on yet another (and indeed very central) topic in machine learning: **tuning**. Researcher Lisa, who has vigorously studied the I2ML lecture materials, is asked to explain tuning in simple terms to her colleagues: *"Hyperparameter tuning, often abbreviated as tuning, can be broken down to one simple formula:*

$$\min_{\boldsymbol{\lambda} \in \boldsymbol{\Lambda}} \widehat{\text{GE}}_{\mathcal{D}_{\text{test}}}(\mathcal{I}(\mathcal{D}_{\text{train}}, \boldsymbol{\lambda})). \quad (1)$$

Researchers Son and Holger seem to have not studied the materials as engaged as Lisa, since they cannot make sense of the expression above.

- 1) **Explain hyperparameter tuning in your own words, using the formula above. What do data scientists mean when they call it a bi-level optimization problem?**

A tuning problem consists of several elements:

- A data set  $\mathcal{D}$ ,
- A learner  $\mathcal{I}$ ,
- $d$  hyperparameters of the learner and their configuration space  $\boldsymbol{\Lambda} = \Lambda_1 \times \Lambda_2 \times \dots \times \Lambda_d$ ,
- A performance measure  $\rho$  to estimate the generalization error, as determined by the application
- A (resampling) procedure for estimating the predictive performance

Son finds himself wondering how this would translate to their specific research problem. As before, they try to predict whether a patient admitted to the hospital will require intensive care, a binary classification task with target space  $\mathcal{Y} = \{0, 1\}$ . The feature space is the same as before:  $\mathcal{X} = (\mathbb{R}_0^+)^3$ , with  $\mathbf{x}^{(i)} = (x_{\text{age}}, x_{\text{blood pressure}}, x_{\text{weight}})^{(i)} \in \mathcal{X}$  for  $i = 1, 2, \dots, n$  observations.

- 2) **Given a data set  $\mathcal{D}$ , a random forest learner  $\mathcal{I}$ , and our research group's problem, write down an example for a specific tuning problem using the list above.**

The research group wants to apply the tuning procedure and get as best an estimate of the generalization error as they can. Holger tunes a learner with a simple 5-fold cross-validation (CV), training 5 models for each of the 100 hyperparameter configurations  $\boldsymbol{\lambda}_i$ ,  $i = 1, \dots, 100$  generated by random search. The unseen CV splits are used to estimate the performance, and the best-performing hyperparameter configuration  $\boldsymbol{\lambda}^*$ , which yielded an average accuracy of  $\rho_{ACC} = 0.92$ , is chosen to train the final model on the entire data set.

- 3) **Does the final model result in an expected accuracy  $\rho_{ACC}$  wrt new, unseen observations equal to, lower or higher than 0.92?**