EXPLANATORY REPORT

Quantum Memory Certification

A finite storage-gap bound

1 The question and the answer

A device receives a string of qubits. Each qubit encodes a classical bit in one of two incompatible measurement bases. The device may process the entire collection, measure part of it, and keep any classical record it wants. Only after a prescribed storage cut does it learn the bases. It must then recover the entire hidden bit string.

Keeping the original quantum states would allow perfect readout once the bases arrive. A premature measurement generally loses the option of choosing the right measurement later. The question is how much this loss matters when the device retains almost, but not quite, enough quantum memory for the whole input.

Let the integer $n \geq 1$ count the input qubits and let $D \geq 1$ be the dimension of all quantum information that survives the cut and is later accessible. For a fixed encoder, P_{guess} is the best probability of exact whole-string recovery over all allowed decoders, averaged over the random bits, bases, and processing outcomes. Every encoder obeys the finite, unsmoothed bound

$$P_{\text{guess}} \leq \min\left\{1, \left(\frac{D}{2^n}\right)^{1/6}\right\}. \tag{1}$$

For at most m retained qubits, with $D \leq 2^m$ and $0 \leq m \leq n$, the missing-qubit gap $t = n - m$ gives

$$P_{\text{guess}} \leq 2^{-t/6}. \tag{2}$$

These are bounds for exact recovery of the whole string, allowing joint processing and unlimited classical storage.

The dependence on t is the central feature. To force ideal cheating probability to at most a fixed $\delta \in (0, 1)$, it suffices to supply $\lceil 6 \log_2(1/\delta) \rceil$ more qubits than the device can retain. This sufficient gap has no additional dependence on the stored block size. An explicit strategy shows that the logarithmic order cannot be improved within this ideal test, although the constants remain unmatched.

A second layer uses a computationally secure preparation protocol to let a verifier conduct the test using classical interaction. Under its precise assumptions, the false-acceptance bound becomes

$$P_{\text{accept}} \leq \min\{1, \varepsilon_{\text{RSP}} + 2^{-t/6}\}, \tag{3}$$

where ε_{RSP} is the remote-state-preparation simulation error. Write $\varepsilon \in (0, 1)$ for a target total false-acceptance probability, while δ denotes a target ideal guessing probability. The ideal bound is unconditional; the classical realization inherits a quantum-hardness assumption and applies to the efficient adversaries in its preparation guarantee.

The report develops the experiment first, then proves the finite bound, explains the conditional realization, and tests its boundaries. Exact recovery, error-tolerant acceptance, and erasures are treated separately because they certify different storage restrictions. A final application shows

how the same guessing task can imply a processing budget under a specified fully noisy device model.

2 The experiment and its information budget

2.1 Two bases, one hidden string


The computational basis is $\{|0\rangle, |1\rangle\}$, where these two unit vectors are orthogonal. The second basis is $\{|+\rangle, |-\rangle\}$, with

$$|+\rangle = \frac{|0\rangle + |1\rangle}{\sqrt{2}}, \qquad |-\rangle = \frac{|0\rangle - |1\rangle}{\sqrt{2}}.$$

The Hadamard matrix $\mathsf{H} = 2^{-1/2}\left(\begin{smallmatrix} 1 & 1 \\ 1 & -1 \end{smallmatrix}\right)$ maps the first basis to the second. Independently uniform strings $X, \Theta \in \{0,1\}^n$ specify bit values and bases. The supplied state is

$$|x\rangle_\theta = U_\theta |x\rangle, \qquad U_\theta = \bigotimes_{i=1}^{n} \mathsf{H}^{\theta_i}.$$

This four-state encoding is called BB84. A state is described by a density operator: a positive matrix ρ with $\operatorname{Tr}\rho = 1$, where Tr sums diagonal entries. Write I_k for the identity in dimension k. For either basis, averaging over the uniformly random bit gives $I_2/2$, so the input alone does not reveal the selected basis.



2.2 What the encoder and decoder may do

Before learning Θ, the device applies any quantum instrument: a joint operation with classical outcome C and retained quantum output Q. It may measure, transform, or discard subsystems, with no size bound on C. The dimension restriction counts every quantum system accessible after the cut, including remotely held ancillas and previously correlated references.

After disclosure, the decoder uses a measurement depending on (C, Θ). Its positive operators M_x sum to the identity and form a positive operator-valued measure (POVM); on state ρ, outcome x has probability $\operatorname{Tr}(M_x\rho)$. Exact success is $\widehat{X} = X$. The ideal analysis permits arbitrary computational power and fresh, uncorrelated decoding workspace, which can be absorbed into the POVM. An environment returned later must be counted in Q.

Symbol	Meaning
$n, d = 2^n$	Input qubit count and Hilbert-space dimension.
D, m	Retained quantum dimension and a qubit budget with $D \leq 2^m$.
$t = n - m$	Missing-qubit gap, used when $0 \leq m \leq n$.
$X, \Theta, \widehat{X}$	Hidden bits, later-revealed bases, and returned guess.
C, Q	Classical record and all charged persistent quantum information.

Logarithms written as $\log_2$ have base two; ln denotes the natural logarithm. The waiting duration is a separate experimental parameter. For a classical hidden variable, conditional min-entropy is the operational quantity

$$H_{\min}(X \mid CQ\Theta) = -\log_2 P_{\text{guess}}(X \mid CQ\Theta).$$

Thus (2) also states $H_{\min}(X \mid CQ\Theta) \geq t/6$, without a smoothing parameter or asymptotic remainder.

3 A strategy that makes the gap tangible

3.1 One stored qubit and one premature measurement

For $n = 2$ and $m = 1$, store the first qubit untouched. Once its basis is revealed, measure it correctly. For the second qubit, use the intermediate measurement axis

$$B = \frac{\mathsf{X} + \mathsf{Z}}{\sqrt{2}}, \qquad \mathsf{X} = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}, \quad \mathsf{Z} = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix}.$$

The two eigenvectors can be chosen as

$$|b_0\rangle = \cos(\pi/8)|0\rangle + \sin(\pi/8)|1\rangle, \qquad |b_1\rangle = -\sin(\pi/8)|0\rangle + \cos(\pi/8)|1\rangle.$$

For input vector $|\psi\rangle$, outcome c has probability $|\langle b_c \mid \psi\rangle|^2$; the bra $\langle b_c|$ is the conjugate transpose of the ket $|b_c\rangle$. Record $c \in \{0, 1\}$ and return it as the bit guess in either announced basis. For example,

$$|\langle b_0 \mid 0\rangle|^2 = |\langle b_0 \mid +\rangle|^2 = \beta, \qquad \beta = \cos^2(\pi/8) = \frac{1 + 1/\sqrt{2}}{2} \simeq 0.853553.$$

The same success probability holds for bit one and the other outcome. This intermediate-axis measurement is often called the Breidbart measurement. Measuring in one of the two encoding bases instead would give average bit success 3/4, which is lower.

The stored bit is recovered perfectly, so this one-qubit-memory strategy achieves whole-string success β. The universal upper bound is $2^{-1/6} \simeq 0.890899$.

3.2 Store a block and measure the remainder

For integer $0 \leq m \leq n$, store any m positions and apply the intermediate measurement to each of the remaining $t = n - m$ positions. The product source and this product strategy yield

$$P_{\text{ach}} = \beta^t. \tag{4}$$

This supplies a lower bound on the optimal cheating probability; the theorem supplies the upper bound:

$$\beta^t \leq P^*_{n,m} \leq 2^{-t/6}. \tag{5}$$

Here $P^*_{n,m}$ is the optimum over both encoders and decoders. A measurement record helps, but it does not preserve the ability to choose an arbitrary measurement after disclosure.

At full memory, $m = n$, storing every input gives success one. At zero quantum memory, the bound is $2^{-n/6}$ and the displayed strategy achieves β^n. The constants are examined in Section 9.

4 A proof representation that preserves the memory budget

The proof first resolves a general strategy into pure conditional branches, where memory dimension limits Schmidt rank. It then converts guessing into an averaged quadratic expression and uses the rank restriction to bound that expression.

4.1 Delay the verifier's measurement

Consider a more general experiment. Before the basis is chosen, the verifier holds an n-qubit register A, jointly in any state ρ_{ACQ} with the device's records. Being classical on C means a mixture of distinguishable labels c and their conditional quantum states. Assume $\dim Q \leq D$. Select Θ uniformly and independently of this state, then measure A in basis Θ. Call the result X. The device, given (C, Q, Θ), guesses X.

The theorem will hold in this arbitrary-state model. It includes the original preparation task by a delayed-measurement representation. Start with n copies of

$$|\Phi\rangle_{AB} = \frac{|00\rangle + |11\rangle}{\sqrt{2}}.$$

For the full block write $|\Phi_d\rangle = d^{-1/2} \sum_z |z\rangle_A |z\rangle_B$. The identity

$$(\langle x|U_\theta^\dagger \otimes I)|\Phi_d\rangle = d^{-1/2} U_\theta^* |x\rangle = d^{-1/2} |x\rangle_\theta$$

uses the reality of the BB84 matrices. It shows that each outcome x has probability $1/d$ and prepares the corresponding state on B. If $\mathcal{E}$ is the device's encoding instrument, its action on B commutes with the measurement on A. Uniformly choosing θ therefore gives the joint output

$$\frac{1}{d^2} \sum_{x,\theta} |x, \theta\rangle\langle x, \theta| \otimes \mathcal{E}(|x\rangle_\theta \langle x|_\theta).$$

This is exactly the original source and encoder, including their probability weights. The verifier's measurement can be placed after the storage cut in the analysis. The physical classical verifier is implemented separately by the preparation protocol below.

In the original preparation task, (X, Θ) is uniform by construction. In the arbitrary-state model, X need not be uniform, even conditioned on a classical branch. The proof must retain its actual probability weights.

4.2 Use pure branches without adding quantum memory

Condition on $C = c$ and decompose the remaining state into normalized pure states:

$$\rho_{AQ}^c = \sum_j p(j \mid c) |\psi_{cj}\rangle\langle\psi_{cj}|.$$

For an upper bound on guessing, give the hypothetical decomposition label j to the decoder as extra classical information. A decoder may ignore it, so this can only increase optimal success. No additional quantum system is supplied. Because Θ is independent of the premeasurement state, revealing (c, j) does not bias its distribution.

It remains to prove the same bound for each pure branch $|\psi\rangle_{AQ}$. Its Schmidt decomposition has the form

$$|\psi\rangle = \sum_{j=1}^{r} \sqrt{\lambda_j} |a_j\rangle_A |b_j\rangle_Q, \qquad \lambda_j > 0, \quad \sum_j \lambda_j = 1. \tag{6}$$

Here both vector families are orthonormal, and the Schmidt rank obeys $r \leq \min(D, d)$. The reduced state $\rho = \mathrm{Tr}_Q |\psi\rangle\langle\psi|$ has exactly these r nonzero eigenvalues. The partial trace Tr_Q discards Q while preserving every measurement probability on A.

The rank restriction applies to a pure conditional branch. An arbitrary mixed ρ_{AQ} can have $\rho_A = I_d/d$ even when Q is one-dimensional. Giving away a quantum purification would change the charged memory; revealing a classical decomposition label does not.

5 Control every decoder through one specified measurement

For a fixed pure branch and announced basis, the possible outcomes define a quantum state-discrimination problem. We first prove a general comparison that avoids optimizing the decoder explicitly.

Let $\{\sigma_x\}$ be positive, subnormalized operators on Q, with

$$S = \sum_x \sigma_x, \qquad \mathrm{Tr}\, S = 1.$$

The operator $\sigma_x = p_x \rho_x$ combines a label's probability p_x and its normalized conditional state ρ_x, so $\mathrm{Tr}\, \sigma_x = p_x$. For a POVM $\{M_x\}$, success is $\sum_x \mathrm{Tr}(M_x \sigma_x)$; write P_{opt} for its supremum over all POVMs. The square-root, or pretty-good, measurement has effects $S^{-1/2}\sigma_x S^{-1/2}$ on the support of S: the span of its eigenvectors with nonzero eigenvalues. Outside that support it can be completed arbitrarily, because the ensemble never occupies it. Its success is

$$P_{\mathrm{pgm}} = \sum_x \mathrm{Tr}(\sigma_x S^{-1/2} \sigma_x S^{-1/2}). \tag{7}$$

Inverse powers act only on this support, so zero eigenvalues cause no ambiguity.

For any decoder, define Hermitian positive operators

$$A_x = S^{-1/4} \sigma_x S^{-1/4}, \qquad B_x = S^{1/4} M_x S^{1/4}.$$

Cyclicity of trace gives $\sum_x \mathrm{Tr}(A_x B_x) = \sum_x \mathrm{Tr}(M_x \sigma_x)$. Cauchy–Schwarz for the direct sum of the matrix spaces gives

$$\left(\sum_x \mathrm{Tr}\, M_x \sigma_x \right)^2 \leq \left(\sum_x \mathrm{Tr}\, A_x^2 \right) \left(\sum_x \mathrm{Tr}\, B_x^2 \right).$$

The first factor equals (7). For the second, $\sum_x B_x = S^{1/2}$ and positivity implies $\mathrm{Tr}(B_x B_y) \geq 0$. Consequently,

$$1 = \mathrm{Tr}\, S = \mathrm{Tr} \left(\sum_x B_x \right)^2 \geq \sum_x \mathrm{Tr}\, B_x^2.$$

Taking the supremum over all decoding POVMs proves

$$P_{\mathrm{opt}}^2 \leq P_{\mathrm{pgm}}, \qquad P_{\mathrm{opt}} \leq \sqrt{P_{\mathrm{pgm}}}. \tag{8}$$

This established inequality controls every decoder through the tractable quantity P_{pgm}; the square-root measurement itself need not be optimal.

6 Why the square root of a marginal appears

Return to the Schmidt decomposition (6). Set $R = \sqrt{\rho}$, where powers are taken spectrally: an eigenvalue λ of ρ becomes $\sqrt{\lambda}$ in R. For a fixed basis string θ, measuring A gives the subnormalized vector

$$|v_x\rangle = \sum_{j=1}^{r} \sqrt{\lambda_j}\langle x_\theta \mid a_j\rangle |b_j\rangle, \qquad \sigma_x = |v_x\rangle\langle v_x|.$$

Its squared norm is the actual probability of x. Summing over all basis vectors gives

$$S = \sum_x \sigma_x = \sum_{j=1}^{r} \lambda_j |b_j\rangle\langle b_j|,$$

which is independent of θ. Hence

$$\begin{aligned}\langle v_x|S^{-1/2}|v_x\rangle &= \sum_{j=1}^{r} \sqrt{\lambda_j}|\langle x_\theta \mid a_j\rangle|^2 \\ &= \langle x_\theta|R|x_\theta\rangle.\end{aligned}$$

For a rank-one σ_x, its contribution to (7) is the square of this overlap. Therefore the exact identity is

$$P_{\text{pgm}}(\theta) = \sum_x \langle x_\theta|R|x_\theta\rangle^2. \tag{9}$$

The diagonal entries are real and nonnegative because R is positive. There is no additional division by an outcome probability and no uniform-outcome assumption.

6.1 The two-qubit example inside the proof

In the earlier strategy, condition on the intermediate-axis measurement result c. The delayed-measurement state is a Bell pair on A_1Q tensored with $|b_c\rangle$ on A_2. Thus

$$\rho = \frac{I_2}{2} \otimes |b_c\rangle\langle b_c|, \qquad R = \frac{I_2}{\sqrt{2}} \otimes |b_c\rangle\langle b_c|.$$

Its rank is two. In either basis, the second register's probabilities are β and $1-\beta$. Summing (9) over the first bit and the second bit yields

$$P_{\text{pgm}} = \beta^2 + (1-\beta)^2 = \frac{3}{4}.$$

For this branch the optimal decoder attains β: the first bit can be read perfectly and the second is best guessed by its larger conditional probability. The proof chain gives

$$0.853553 \simeq \beta \le \sqrt{3/4} \simeq 0.866025 \le 2^{-1/6} \simeq 0.890899.$$

The example makes the slack introduced by the inequalities visible.

7 Average the bases using Pauli coordinates

7.1 Measurement averaging as dephasing

Dephasing in a basis deletes off-diagonal matrix entries in that basis. Write these maps as Δ_Z and Δ_X for the computational and Hadamard bases, and define

$$\mathcal{T} = \frac{\Delta_Z + \Delta_X}{2}.$$

For one basis, the squared diagonal sum in (9) equals $\mathrm{Tr}[R\Delta(R)]$. Independent choices of the n bases therefore give

$$\mathbb{E}_\Theta P_{\mathrm{pgm}}(\Theta) = \mathrm{Tr}\left[R\mathcal{T}^{\otimes n}(R)\right]. \tag{10}$$

This product of averaging maps comes from the random basis choices. It imposes no product structure on R, the encoder, or the decoder.

The Pauli matrices $I_2, \mathsf{X}, \mathsf{Y}, \mathsf{Z}$, with $\mathsf{Y} = \left(\begin{smallmatrix} 0 & -i \\ i & 0 \end{smallmatrix}\right)$, form an orthogonal operator basis under $\mathrm{Tr}(A^\dagger B)$. The identity component survives either dephasing, each of the x, z components survives half the time, and the y component is removed:

Map eigenvalue on	I_2	X	Y	Z
$\mathcal{T}$	1	1/2	0	1/2
$\mathcal{D}_{1/2}$	1	1/2	1/2	1/2

Here the depolarizing map on a single qubit, for $0 \le \eta \le 1$, is

$$\mathcal{D}_\eta(A) = \eta A + (1-\eta)\,\mathrm{Tr}(A) I_2/2.$$

7.2 A comparison of quadratic forms

Expand $R = \sum_P a_P P$ in n-qubit Pauli words, with $a_P = d^{-1}\,\mathrm{Tr}(PR)$. A word is a tensor product of the four Pauli matrices; its weight $w(P)$ counts nonidentity factors. Hermiticity makes a_P real, and $\mathrm{Tr}(PP') = d$ when $P = P'$ and zero otherwise. Each term of the quadratic form is therefore da_P^2 times the map's eigenvalue.

A word containing Y has $\mathcal{T}$ eigenvalue zero. Any other word has eigenvalue $2^{-w(P)}$, equal to its depolarizing eigenvalue. Term by term,

$$\begin{aligned} \mathrm{Tr}[R\mathcal{T}^{\otimes n}(R)] &\le \mathrm{Tr}[R\mathcal{D}_{1/2}^{\otimes n}(R)] \\ &= \mathrm{Tr}\left[\mathcal{D}_{1/\sqrt{2}}^{\otimes n}(R)^2\right]. \end{aligned} \tag{11}$$

The equality uses self-adjointness and $\mathcal{D}_\eta \mathcal{D}_\zeta = \mathcal{D}_{\eta\zeta}$. The comparison is between quadratic forms, rather than an ordering by completely positive maps. Depolarization is used to analyse the basis average; its parameter is a proof parameter, separate from physical noise in a device.

8 The dimension-sensitive step and the finite theorem

8.1 A standard tensor-power norm inequality

For an operator on a $d = 2^n$ dimensional space, define the normalized Schatten norm

$$\|A\|_{p,\mathrm{n}} = \left(d^{-1}\,\mathrm{Tr}\,|A|^p\right)^{1/p}, \qquad |A| = \sqrt{A^\dagger A}.$$

All other traces in this report are ordinary, unnormalized traces. In particular, a density operator satisfies $\mathrm{Tr}\,\rho = 1$, whereas $d^{-1}\,\mathrm{Tr}\,I_d = 1$.

The substantial standard input to the proof is qubit hypercontractivity. For Hermitian A, $1 \le p \le 2 \le q < \infty$, and $0 \le \eta \le \sqrt{(p-1)/(q-1)}$, it states

$$\|\mathcal{D}_\eta^{\otimes n}(A)\|_{q,\mathrm{n}} \le \|A\|_{p,\mathrm{n}}. \tag{12}$$

It says that sufficient damping of the Pauli components controls a stronger norm by a weaker one, with a constant independent of the number of qubits. Its tensor-power scope makes it applicable to entangled operators across the entire block.

8.2 Keep the normalization factor

Choose $p = 3/2$, $q = 2$, and $\eta = 1/\sqrt{2}$. Equations (10)–(11) imply

$$\begin{aligned}\mathbb{E}_\Theta P_{\mathrm{pgm}}(\Theta) &\le d\,\|\mathcal{D}_{1/\sqrt{2}}^{\otimes n}(R)\|_{2,\mathrm{n}}^2 \\ &\le d\,\|R\|_{3/2,\mathrm{n}}^2 \\ &= d^{-1/3}\big(\operatorname{Tr}\rho^{3/4}\big)^{4/3}. \end{aligned} \tag{13}$$

The factor $d^{-1/3}$ follows from $d(d^{-1})^{4/3}$. Dropping this factor would destroy the storage-gap dependence.

The r nonzero eigenvalues of ρ sum to one. Concavity gives

$$\frac{1}{r}\sum_{j=1}^{r}\lambda_j^{3/4} \le \left(\frac{1}{r}\sum_{j=1}^{r}\lambda_j\right)^{3/4}, \quad \text{hence} \quad \operatorname{Tr}\rho^{3/4} \le r^{1/4}.$$

Thus $\mathbb{E}P_{\mathrm{pgm}} \le (r/d)^{1/3}$. Finally, use (8) and Cauchy–Schwarz for the classical basis average:

$$\mathbb{E}_\Theta P_{\mathrm{opt}}(\Theta) \le \mathbb{E}_\Theta\sqrt{P_{\mathrm{pgm}}(\Theta)} \le \sqrt{\mathbb{E}_\Theta P_{\mathrm{pgm}}(\Theta)} \le (r/d)^{1/6} \le (D/d)^{1/6}. \tag{14}$$

This holds on every refined pure branch. Averaging those branch bounds and removing the extra label returns the original mixed-state experiment. General classical records use the same conditional-state average; there is no alphabet-size penalty. Adding the trivial probability bound one proves (1), including non-power-of-two D.

9 What the logarithmic overhead means

9.1 Sufficient and necessary gaps


For an ideal target $\delta \in (0, 1)$, the upper bound guarantees success at most δ when

$$t \ge \lceil 6\log_2(1/\delta)\rceil\,.$$

The explicit strategy (4) forces any gap that suppresses every strategy to at most δ to satisfy

$$t \ge \frac{\log_2(1/\delta)}{-\log_2\beta} \simeq 4.37739\log_2(1/\delta).$$

For integer gaps, round the lower threshold upward. The gap therefore has order $\Theta(\log(1/\delta))$ uniformly in m, with the constants 4.37739 and 6 still unmatched. The product strategy need not be optimal at intermediate memory sizes.



The optimal value $-\log_2 P^*_{n,m}$ lies between the two lines; larger values mean smaller success probability.

9.2 A finite comparison, with a precise scope

An earlier uncertainty relation permits storage rates approaching one. To specialize it using only the memory dimension, one needs conditional min-entropy with a quantum first register. Its operator definition is

$$2^{-H_{\min}(A|E)_\rho} = \inf_{\omega_E \geq 0} \{\operatorname{Tr} \omega_E : \rho_{AE} \leq I_A \otimes \omega_E\}.$$

Here E denotes the available side information, and ω_E ranges over positive operators whose trace is unrestricted. When A is classical this definition agrees with the guessing-probability definition above. The dimension bound gives $H_{\min}(A \mid CQ) \geq -\log_2 D \geq -m$. Indeed, Cauchy–Schwarz on a pure Schmidt decomposition gives $\rho_{AQ} \leq D I_A \otimes \rho_Q$; averaging pure branches and classical records preserves this inequality. Thus $\omega_{CQ} = D\rho_{CQ}$ is a feasible choice of trace D. Substituting the resulting entropy bound into the earlier relation gives the particular sufficient bound

$$H_{\min}(X \mid CQ\Theta) \geq \frac{n\gamma(-m/n) - 1}{2},$$

where $H_{\min} = -\log_2 P_{\text{guess}}$ is the conditional min-entropy, and $\gamma(u)$ inverts $h_2(a) + a - 1$ on $0 \leq a \leq 1/2$. The binary entropy is $h_2(a) = -a\log_2 a - (1-a)\log_2(1-a)$, with $0\log_2 0 = 0$. Writing $a = \gamma(-m/n)$ gives $t = n[h_2(a) + a]$. To reach $H_{\min} \geq \log_2(1/\delta)$, it suffices that $a \geq a_* = [1 + 2\log_2(1/\delta)]/n$. When $a_* \leq 1/2$ and the gap is feasible, this yields $\lceil n[h_2(a_*) + a_*] \rceil$. At $\delta = 2^{-20}$, this gives the sufficient gaps below.

Input size n	This bound	Earlier specialization
1,024	120	290
10,000	120	426
1,000,000	120	698

At a fixed target δ, this earlier specialization retains a logarithmic block-size dependence. To see it, put $s = 1 + 2\log_2(1/\delta)$, so $a_* = s/n$. For large n,

$$nh_2(s/n) = s\log_2(n/s) + s\log_2 e + O(s^2/n).$$

Here e is the base of the natural logarithm. Thus its sufficient gap grows as $s\log_2 n + O_\delta(1)$, whereas (2) supplies a gap independent of n. The comparison fixes the two displayed unsmoothed guessing bounds and the dimension-only substitution. Additional state information or smoothing would define a different comparison.

10 How classical interaction can supply the test

10.1 The extra preparation problem

The ideal experiment supplies actual BB84 states. A verifier restricted to classical computation and communication uses a remote-state-preparation protocol instead: the verifier ends with hidden labels and a pass flag, and an honest quantum device ends with the corresponding qubits. Efficiency is measured in the security parameter λ. The preparation guarantee uses nonuniform quantum polynomial-time adversaries, simulators, and continuations: they may use advice depending on λ, but must remain within the specified polynomial resource bound. Its security inequalities hold for all sufficiently large λ and polynomially bounded output length.

The imported construction relies on quantum hardness of learning with errors (LWE). At the level of notation, LWE involves noisy modular linear equations

$$b = \langle a, s \rangle + e \pmod{q},$$

where q is an integer modulus, a, s are vectors over integers modulo q, and e follows a specified error distribution. The construction imports a hardness assumption for its parameter family and quantum adversary class. That computational assumption supplies preparation security; the finite guessing theorem is an independent information-theoretic statement.

10.2 The exact simulation interface

For every efficient malicious preparation prover, the imported guarantee supplies an efficient simulator whose input is the ideal quantum BB84 state alone. It produces a simulated pass flag and the prover's output system. The simulator does not receive the classical hidden labels x, θ.

For every efficient continuation and its acceptance test, the real and simulated probabilities of the joint event

$$\{\text{preparation passes and continuation accepts}\}$$

differ by at most $\varepsilon_{\mathrm{RSP}}$. The continuation may use the verifier's hidden labels to evaluate its test. The simulator's quantum input and the verifier's classical knowledge play different roles.

> The comparison is pass weighted: it directly bounds the joint event of preparation passing and the continuation accepting, without conditioning on a pass. The same simulator, chosen for the malicious preparation prover, must satisfy this comparison for every efficient continuation.

Honest preparation has a separate property: its joint state, including the verifier labels, is negligibly close in trace distance to the ideal BB84 source with a passing flag. Here trace distance is $\frac{1}{2}\|\rho - \sigma\|_1$ for normalized states, with the ordinary trace norm $\|A\|_1 = \operatorname{Tr}|A|$. It bounds the difference in any acceptance probability. This honest-state trace-distance property is separate from the computational comparison for malicious provers.

Under its polynomial quantum-hardness assumption, the construction supports polynomial-length output and inverse-polynomial simulation error using polynomially many rounds. The ideal inequality (1) remains unconditional.

11 Compose preparation with the storage bound

11.1 A reduction without conditioning on a pass

Run the preparation protocol for n output qubits. The verifier keeps its hidden strings and its flag. After the storage cut, send Θ; accept exactly when preparation passed and the returned string equals X. On failed preparation the verifier may still send an independent dummy basis and always reject. The proof requires no early disclosure of the flag.

Fix an efficient adversary whose total retained quantum dimension at the cut is at most 2^m. Let E be its actual preprocessing and compression up to that cut. Use the imported simulation guarantee with the continuation that runs E, discloses the verifier's bases, runs the decoder, and checks the guessed string. It gives

$$\begin{aligned} P_{\text{real accept}} &\le \varepsilon_{\mathrm{RSP}} + P_{\text{sim pass and correct}} \\ &\le \varepsilon_{\mathrm{RSP}} + P_{\text{sim correct}}. \end{aligned}$$

The simulator composed with E is an encoder on ideal quantum BB84 inputs. As a map, E has a charged quantum output register Q of dimension at most 2^m; applying it to the simulated state does not enlarge that register. Temporary workspace before the cut may be larger, but all quantum information accessible across the cut is charged. Classical transcripts and flags can be added to C. A discarded simulator environment is not later returned.

Giving arbitrary guesses to failed simulated branches makes a complete strategy covered by the ideal theorem. Thus

$$P_{\text{real accept}} \leq \min\{1, \varepsilon_{\text{RSP}} + 2^{-(n-m)/6}\}.$$

The joint-event comparison keeps rare passing branches weighted by their actual probabilities throughout the argument.

11.2 Allocate the error budget and state the efficient regime

For target total false-acceptance probability $\varepsilon \in (0, 1)$, it is sufficient to obtain $\varepsilon_{\text{RSP}} \leq \varepsilon/2$ and choose

$$n = m + \lceil 6 \log_2(2/\varepsilon) \rceil . \tag{15}$$

For example, an ideal storage term at most 2^{-20} requires gap 120. Total false acceptance at most 2^{-20} with equal allocation requires gap 126 and preparation error at most 2^{-21}. These numbers illustrate the algebraic allocation of the two error terms.

More precisely, let $m(\lambda) \geq 0$ be integer valued, efficiently computable, and polynomially bounded, and let $p(\lambda) \geq 1$ be a polynomial target. The imported construction supplies error $1/[2p(\lambda)]$ efficiently. Choosing

$$n(\lambda) = m(\lambda) + \lceil 6 \log_2(2p(\lambda)) \rceil$$

yields a polynomial-round protocol with soundness at most $1/p(\lambda)$. Honest completeness is $1 - \text{negl}(\lambda)$ for ideal honest storage, where negligible means eventually smaller than every inverse polynomial. This finite storage estimate applies without a condition $m(\lambda) = \omega(\log \lambda)$. Efficient negligible-soundness compilation would require a preparation guarantee at the corresponding error scale; the imported efficient guarantee supplies the inverse-polynomial regime.

12 Lists and tolerated wrong answers

12.1 Prove the list cost before changing the test

In the ideal storage model, suppose a decoder output y specifies a set $\mathcal{L}_y$ of at most $L \geq 1$ candidate strings. Success means $X \in \mathcal{L}_y$. The list can depend on the basis and available records, but the unknown X enters only through the decoder's actual information. For its POVM $\{M_y\}$, define

$$F_x = \sum_{y : x \in \mathcal{L}_y} M_y.$$

Then $0 \leq F_x \leq I$ and $\sum_x F_x \leq LI$. Reuse $A_x = S^{-1/4} \sigma_x S^{-1/4}$ and set $B_x = S^{1/4} F_x S^{1/4}$. Now $0 \leq B_x \leq S^{1/2}$, so

$$\sum_x \operatorname{Tr} B_x^2 \leq \sum_x \operatorname{Tr}(B_x S^{1/2}) = \operatorname{Tr}\left(S \sum_x F_x \right) \leq L.$$

The first inequality uses $\operatorname{Tr}[B_x(S^{1/2} - B_x)] \geq 0$; positivity suffices even when the two operators do not commute. The same matrix Cauchy–Schwarz argument gives $P_{\text{list}}^2 \leq L P_{\text{pgm}}$. On each

pure branch, average its square root over the bases and use the rank estimate from Section 8. This gives $P_{\text{list}} \le \sqrt{L}(r/d)^{1/6}$. Averaging the branches yields

$$\begin{aligned} P_{\text{list}} &\le \min\{1, \sqrt{L}(D/2^n)^{1/6}\} \\ &\le \min\{1, \sqrt{L}\, 2^{-(n-m)/6}\} \qquad (D \le 2^m). \end{aligned} \tag{16}$$

This proof applies separately to every basis, so the list can depend on the basis. Randomized list selection is included in the measurement outcome y. The list inequality is a direct scored-discrimination extension of the same square-root-measurement argument.

12.2 Hamming tolerance changes the claim

Allow at most h wrong bits, where h is an integer between zero and n. A returned string accepts all strings differing from it in at most h positions: a Hamming ball of size

$$V(n,h) = \sum_{j=0}^{h} \binom{n}{j}.$$

Equation (16) gives ideal cheating probability at most $\min\{1, \sqrt{V(n,h)}\, 2^{-(n-m)/6}\}$. With preparation error $\varepsilon/2$, the sufficient gap becomes

$$n - m \ge 3 \log_2 V(n,h) + 6 \log_2(2/\varepsilon).$$

For $h \le n/2$, $V(n,h) \le 2^{nh_2(h/n)}$. A fixed positive error fraction therefore adds an extensive term to this sufficient estimate, which may become vacuous.

There is also a direct obstruction. A device storing $n - h$ designated qubits can recover those positions perfectly and guess the other h arbitrarily. It always makes at most h errors. For $n = 1{,}000$ and allowance $h = 10$, storing 990 qubits guarantees acceptance. Thus the unmodified tolerant test cannot certify such a deficit with small false acceptance.

For the store-and-measure witness, an achieved tolerant success is

$$\sum_{j=0}^{\min(h,t)} \binom{t}{j} (1-\beta)^j \beta^{t-j}.$$

The obstruction concerns this acceptance rule and leaves other noise-tolerant certification protocols open.

13 Erasures, honest noise, and preparation perturbations

13.1 The time of an erasure declaration matters

Let $0 \le \ell \le n$ be an integer. Write P_{pre} and P_{post} for ideal acceptance probabilities when erased positions are declared before or after basis disclosure. For a pre-basis declaration, condition on the erased set S and earlier classical records in the delayed-measurement model. Discard the untested A registers and put $k = n - |S|$. The surviving state may be arbitrary and mixed, but its remaining bases are independent and uniform. For $k \ge 1$, the stronger theorem gives

$$P_{\text{pre}|S} \le \min\{1, 2^{-(k-m)/6}\}.$$

For $k = 0$ the upper bound is one. Since $k \ge n - \ell$, averaging over the declaration gives

$$P_{\text{pre}} \le \min\{1, 2^{-(n-\ell-m)/6}\}. \tag{17}$$

Earlier measurement records may determine the declaration; the conditional bits need not be uniform.

If up to h errors are also allowed, condition on the actual surviving length before applying the list bound. The conditional upper bound is

$$\min\{1, \sqrt{V(k, \min\{h, k\})}\, 2^{-(k-m)/6}\}.$$

The radius is capped at k because accepting k or more errors accepts every surviving string. At $k = 0$, $V(0, 0) = 1$ and the displayed minimum gives the trivial bound one. For a variable number of erasures, take the maximum over the permitted k: both the Hamming volume and the deficit depend on that length.

If instead the erased positions can be chosen after basis disclosure, a particular output with ℓ erasures accepts 2^ℓ full strings. Applying the basis-dependent list bound gives

$$P_{\text{post}} \leq \min\{1, 2^{\ell/2} 2^{-(n-m)/6}\}. \tag{18}$$

The output itself specifies the erased set, so its list size already accounts for that selection; there is no extra factor for the number of possible erased sets. With exactly ℓ erasures and at most h wrong surviving bits, the list size is

$$L = 2^\ell V(n - \ell, \min\{h, n - \ell\}).$$

With variable erasure count, take the largest permitted actual list size. These two guarantees distinguish a pre-basis commitment from an adaptive post-basis declaration. They are sufficient bounds for those acceptance rules, with their optimum constants left open.

13.2 Completeness is a separate physical requirement

If an honest device's recovered bits have independent error probability e, exact-string completeness is

$$P_{\text{honest correct}} = (1 - e)^n.$$

A fixed positive independent error rate therefore destroys completeness as n grows. Without independence, the union bound still gives failure at most $\sum_i e_i$, where e_i is the marginal probability of an error in bit i. To keep this failure contribution below η, it suffices that $\sum_i e_i \leq \eta$; uniform $e_i \leq \eta/n$ is one sufficient option.

An error-correction implementation would require its own physical resource accounting. The present ideal logical-qubit test supplies neither such an architecture nor a fixed-noise-rate threshold.

13.3 A trace-distance perturbation is a different guarantee

Let actual and ideal joint source states, including the verifier labels, be ω and ω_{id}, with $\xi = \frac{1}{2}\|\omega - \omega_{\text{id}}\|_1$. Any fixed acceptance test has an effect $0 \leq M \leq I$, and

$$|\text{Tr}(M\omega) - \text{Tr}(M\omega_{\text{id}})| \leq \xi.$$

Thus a specified physical source perturbation changes acceptance by at most ξ. The malicious-prover preparation guarantee instead compares computationally accessible joint pass-and-accept probabilities. Each guarantee must be used with its own premise.

14 A conditional processing consequence in a noisy device

14.1 A different resource question, with an explicit chronology

For this noisy-device application, use k challenge qubits, total noisy physical width n, and D noise rounds. These local meanings replace the earlier input-length n and retained-dimension D. Width counts every persistent data, controller, syndrome and resource register.

Supply only $|X\rangle_\Theta$ for independent uniform $X, \Theta \in \{0,1\}^k$. Keep X secret; disclose only Θ after all charged storage. The final decoder may depend arbitrarily on Θ. Unconditional whole-string success is $p = \Pr[\widehat{X} = X]$, with aborts counted as failures.

Each round applies independent depolarization to every persistent register:

$$\mathcal{N}_\gamma(A) = qA + (1-q)\frac{I}{2}\operatorname{Tr} A, \qquad q = 1-\gamma \in (0,1).$$

The fixed circuit has free ideal Clifford operations and input-independent replacement resets. Every internal T/T-dagger is counted; other operations need a proved support-growth charge. Controllers obey these same rules: noisy counted bits do not make arbitrary feedback or data-dependent resets free. Arbitrary endpoints have no protected side channel across storage.

14.2 Why a temporal cut is a quantum-plus-classical encoder

Start one backward Pauli envelope at the full physical output before basis-dependent readout, with rank $M = 2n$. At each cut, average earlier noise into a CPTP prefix. Every independent future-noise branch has tail-adjoint range in

$$\mathcal{A}_V \simeq M_{2^s} \otimes \mathrm{Diag}_{2^c} \otimes I_G, \qquad r := \dim V = 2s + c.$$

The trace-preserving conditional expectation $\mathcal{E}_V$ is a CPTP map on the full physical memory. It factors as $\mathcal{E}_V = \mathcal{J}_V \mathcal{F}_V$: $\mathcal{F}_V$ changes to canonical coordinates, dephases the c-bit factor and traces out G, while $\mathcal{J}_V$ reinserts $I_G/\dim G$ and reverses the coordinate change. The tail satisfies $\mathcal{S} = \mathcal{S}\mathcal{E}_V$. Thus $\mathcal{F}_V$ composed with the prefix is a genuine s-qubit, c-bit encoder; composing $\mathcal{J}_V$ with the tail and readout reproduces the original outcome distribution.

Let $p_{b,t}$ be the actual endpoint decoder's success probability on the sampled channel. The finite guessing theorem and a separate finite-output count imply

$$p_{b,t} \le \min\{1, 2^{(s-k)/6}, 2^{s+c-k}\}. \tag{19}$$

For the last bound, fix a basis. The 2^k equiprobable inputs give output density matrices $\rho_x \le I$ on a space of dimension 2^{s+c}, so any POVM has success at most 2^{s+c-k}. Apply this count to the original normalized encoder, before the mathematical classical refinement used in the proof of the ideal theorem.

Noise flags select independent CPTP channels; they are proof aids, not postselection outcomes or device information. Branch-specific decoder optimization only raises the upper bound. Linearity gives $p = \mathbb{E}_b p_{b,t}$ at every primitive cut, on both sides of each gate and noise layer.

For $k \ge 8$, the branch inequalities yield the useful uniform floor

$$R_t := \mathbb{E}_b \dim V_{b,t} \ge a_p := 2k\frac{[p - 2^{-k}]_+}{1 - 2^{-k}}. \tag{20}$$

It is positive for every score above random guessing, including scores below one half.

Maximizing (19) at fixed r gives 2^{r-k} up to $5k/6$, then $2^{(r-2k)/7}$ up to $2k$, and one thereafter. For $k \geq 8$, both convex pieces lie below the chord from $(0, 2^{-k})$ to $(2k, 1)$; averaging proves (20). For all $k \geq 1$, finite-output counting gives the weaker floor $k[p - 2^{-k}]_+/(1 - 2^{-k})$.

14.3 The same floor controls gates in every interval

For the backward envelope, a noise layer obeys $R' \leq qR$, each T or T-dagger adds at most one binary generator, and free primitives add none. Put $\kappa = -\ln q$. Summing logarithmic changes at cuts with $R_t \geq a_p > 0$ gives

$$m_T \geq \frac{[D\kappa - \ln(2n/a_p)]_+}{\ln(1 + 1/a_p)}. \tag{21}$$

Round the right side upward for the integer gate count. The weaker structural-charge form is $B \geq a_p[D\kappa - \ln(2n/a_p)]_+$ when a gate of charge b_g can add at most b_g generators and $B = \sum_g b_g$.

Every contiguous interval inherits the same floor. In (21), use its own noise-layer and T counts and an entering expected-rank bound $M_I \leq 2n$. Interval noise is independent of the later suffix; boundary gates are assigned once. Gates outside a long interval supply only this finite reserve.

For example, $k = 12, p = 0.4, n = 120, \gamma = 0.01, D = 2000$ gives $a_p \simeq 9.59648$ and requires at least 171 internal T/T-dagger gates. With the same score and width, every 700-round contiguous interval requires at least 39 such gates by (21). The scalar injection bound alone gives 37. These are necessary processing budgets; their attainability and the device assumptions require separate evidence.

14.4 What the recovery comparison and boundaries imply

The recovery comparison remains informative even at scores at or below one half. For one complete branch channel, let F_{rec} be its optimum squared Bell-overlap recovery fidelity, $F_{\mathrm{pg}} \leq F_{\mathrm{rec}}$ its pretty-good value, u its average pretty-good guessing success, and $p_* \geq 1/d$ its optimized guessing score. With $d = 2^k$, established discrimination and recovery estimates give

$$p_*^2 + \frac{(1 - p_*)^2}{d - 1} \leq u, \qquad F_{\mathrm{rec}} \geq p_*/d,$$
$$u \leq \tau_\ell + A_\ell F_{\mathrm{pg}}, \qquad 0 \leq \ell \leq k,$$
$$A_\ell = \sum_{j=0}^{\ell} \binom{k}{j} (1 - 2^j \tau_\ell),$$

where $\tau_\ell = 2^{-\ell-1}$ for $\ell < k$ and $\tau_k = 0$. The underlying spectral reduction writes $u = \sum_v \lambda_v w_v$, where $w_v \geq 0$, $\sum_v w_v = 1$, and $w_v \leq F_{\mathrm{pg}}$. Its nonzero eigenvalues are 2^{-j} with multiplicities $2^j \binom{k}{j}$. Bounding all terms at or below τ_ℓ by that threshold, then applying the cap to the excess, gives $u \leq \tau_\ell + F_{\mathrm{pg}} \sum_{\lambda_v > \tau_\ell} (\lambda_v - \tau_\ell)$, which is the displayed estimate. At $\ell = 0$ it gives $u \leq (1 + F_{\mathrm{pg}})/2$. The actual branch score is at most p_*, and every branch satisfies $F_{\mathrm{rec}} \leq \min\{1, 2^{r-2k}\}$. These estimates reproduce (20) for every $k \geq 8$ when applied branchwise *before* averaging. Exact finite-rank checks also imply the weaker floor stated above for $1 \leq k \leq 7$. Thus these mean-rank floors and their gate or interval consequences already follow from the recovery route. The direct encoder factorization gives a short operational explanation; this comparison does not identify the optimal attainable score or exclude stronger bounds.

14.5 Keeping the actual noise distribution gives a stronger budget

The mean-rank comparison does not exhaust the specified noisy dynamics. For a fixed real $1 < z \le 2$, retain the exponential moment of the common full-output envelope:

$$X_z(t) := \log_z \mathbb{E}_b z^{r_{b,t}}, \qquad \alpha_z := \frac{\ln(1-q+qz^2)}{2\ln z} \in (0,1). \tag{22}$$

This potential has terminal value $2n$. It uses the same counted registers, fixed primitives and mathematical noise flags as the preceding argument.

To see the contraction, choose r binary pivot coordinates that identify a rank-r envelope. Let $d_j \in \{0,1,2\}$ be the number of pivots on qubit j, so $\sum_j d_j = r$. If noise retains the site set S, then $\dim(V \cap W_S) \le \sum_{j\in S} d_j$. Independence and the inequality $(1-q+qz)^2 \le 1-q+qz^2$ imply

$$\mathbb{E}[z^{r'} \mid V] \le \prod_j (1-q+qz^{d_j}) \le (1-q+qz^2)^{r/2}.$$

Concavity of x^{α_z} gives $X'_z \le \alpha_z X_z$ at a noise layer. A T/T-dagger adds at most one to X_z; Clifford gates and input-independent resets cannot increase it. This retains information about the noise law that the mean-rank chord discarded, without assuming rank concentration.

Use the preceding discrimination and recovery estimates on the averaged channel to the full physical output. For $p \ge 1/d$, define

$$F_0(p) := \max\left\{ d^{-2}, \frac{p}{d}, \max_{0\le\ell\le k} \frac{[g_d(p)-\tau_\ell]_+}{A_\ell} \right\}, \quad g_d(p) = p^2 + \frac{(1-p)^2}{d-1}. \tag{23}$$

For $p < 1/d$, use $F_0 = d^{-2}$ and a zero floor. Fix one CPTP recovery with squared Bell fidelity at least $F_0(p)$. At each cut, averaging its recovered future-noise branches gives the same fidelity. Every branch has fidelity at most $\min\{1, 2^{r-2k}\}$. For $b = 4^{-k}$ and $w = (F_0 - b)/(1-b)$, the secant in the variable z^r gives

$$\min\{1, 2^{r-2k}\} \le b + (1-b)\frac{z^r - 1}{z^{2k} - 1}.$$

Thus every primitive cut has the positive moment floor

$$X_z(t) \ge a_z^{\mathrm{rec}} := \log_z\Big[1 + w(z^{2k} - 1)\Big] \tag{24}$$

whenever $p > 2^{-k}$. At chance, $a_z^{\mathrm{rec}} = 0$. The recovery is fixed across the proof branches and requires no knowledge of their flags.

The direct profile in (19) supplies another floor. Write $b_0 = 2^{-k}$, $H_k = 2^{-k/6}$, $Y_t = z^{5k/6}$ and $Y_e = z^{2k}$. For $1 < z \le 2^{1/7}$, its two exponential pieces are convex in $Y = z^r$. Let $P_z(Y)$ be the concave polygon through $(1, b_0), (Y_t, H_k), (Y_e, 1)$, constant after Y_e, omitting the middle point if it is below the endpoint chord. Then $p \le P_z(\mathbb{E}z^r)$ and

$$a_z^{\mathrm{dir}} = \log_z P_z^{-1}(p).$$

The inverse is linear in p on each retained segment. If the middle point is omitted it is $1 + (p - b_0)(Y_e - 1)/(1 - b_0)$. Otherwise it is $1 + (p - b_0)(Y_t - 1)/(H_k - b_0)$ below H_k, and $Y_t + (p - H_k)(Y_e - Y_t)/(1 - H_k)$ above it. Set the floor to zero at or below chance. Use the larger available direct or recovery floor, denoted a_z. Both are positive above chance. The earlier comparison of mean-rank floors does not imply dominance over this refinement.

Putting $\kappa_z = -\ln \alpha_z$, the same gate-balance argument gives

$$m_T \geq \left\lceil \frac{[D\kappa_z - \ln(2n/a_z)]_+}{\ln(1 + 1/a_z)} \right\rceil . \tag{25}$$

The companion discrete injection ledger applies with its contraction parameter replaced by α_z and floor replaced by a_z. Take the strongest result over z and the earlier mean-rank bounds. For a contiguous interval, the entering reserve must bound $\log_z \mathbb{E}z^r$; $2n$ is safe. The earlier reserve on $\mathbb{E}r$ alone is insufficient for this substitution.

At fixed positive score, both b_0 and H_k decay exponentially. Choosing $\ln z = 1/\sqrt{k}$ for large k yields $a_z = 2k - O_p(\sqrt{k})$ and $\alpha_z = q + O_q(k^{-1/2})$. The recovery bridge also reaches $a_z = 2k - o(k)$, using its polynomial lower bound on $F_0(p)$. If $q \in (0, 1)$ is fixed, $n \geq k$, $D \to \infty$, and $\ln(n/k) = o(D)$, the discrete ledger therefore implies

$$m_T \geq (2 - o(1))\, k\, \frac{1-q}{q}\, D. \tag{26}$$

The previous chord gives leading coefficient $2p$ under the same conditions. The moment argument strengthens the fixed-score dependence while retaining the weak-noise order $k\gamma D$. It supplies a necessary rate along feasible families, without constructing a memory or determining its optimum physical cost.

The analytic polygon can be sharpened by combining all available bounds at each integer pair (s, c). For $k = 12$, a rational certificate checks all 169 pairs with $0 \leq 2s + c \leq 24$, using the direct, recovery and output-dimension caps and the established classical cap β^{12} for $s = 0$, where $\beta = (1 + 1/\sqrt{2})/2$. At $z = 27/25$, the concave polygon through $(1, 1/4096), (z^{11}, 1/4), (z^{24}, 1)$, constant afterward, majorizes each branch cap. The classical bound follows from the Gram-matrix row-sum estimate for selected product-BB84 vectors.

For the earlier example $k = 12, p = 0.4, n = 120, q = 0.99$, it gives $M_z \geq (4z^{11} + z^{24})/5$, $a_z \simeq 14.84082963$ and $\alpha_z \simeq 0.99072498$. Certified logarithm bounds make the individual-gate requirement at least 244 for $D = 2000$, compared with 171 from mean rank. Every 700-round contiguous interval with moment reserve at most 240 requires at least 58 such gates, compared with 39. The interval bound uses its own moment reserve, and both numbers are necessary conditions rather than physical feasibility or optimality claims.

At chance, discarding the challenge and guessing needs zero processing. Full-register replacement gives

$$p \leq 2^{-k} + (1 - 2^{-k})(1 - \gamma^n)^D$$

regardless of gates. Fixed width cannot sustain a fixed above-chance score indefinitely. Success does not verify noise, controller or side-channel premises. The remote-preparation reduction of Section 11 needs a separate model- and resource-preserving argument to compile this witness.

15 Resources and interpretation

15.1 Which resource improves

The earlier polynomial-hardness construction used $\lceil 9.1m \rceil$ honest stored qubits in its stated asymptotic regime. In the same preparation framework, the finite bound replaces that multiplicative persistent-storage overhead by the additive gap (15). The protocol wrapper and preparation construction supply the classical-verifier realization. Their separate constant-round variants use stronger assumptions and address a different resource tradeoff.

Resource	What is counted
Honest persistent storage	n ideal logical qubits through the waiting period.
Adversarial storage	Joint dimension of all later-accessible quantum systems at the cut, at most 2^m.
Classical records	Unbounded in the ideal theorem; efficiently generated in the computational protocol.
Preparation and workspace	Imported preparation work and temporary ancillas; polynomial in its supported regime, with no optimized total-cost estimate here.
Communication and rounds	Classical interaction inherited from preparation; polynomially many rounds in the stated polynomial-hardness regime.
Readout and timing	Honest product-basis readout and classical checking; waiting duration is specified externally, with no new timing-enforcement mechanism.
Physical protection	Any additional physical qubits used for error correction remain physical quantum storage.

No free state-loading oracle or quantum random-access memory is assumed. The ideal source is an explicit quantum input resource; its classical realization pays for the imported preparation protocol.

15.2 What supports the claims

The ideal result follows from the analytical chain in Sections 4–8, using the standard tensor-power norm theorem as its substantial mathematical input. Section 11 supplies the separate computational reduction under its cryptographic assumption. Finite matrix checks test the intermediate identities and normalization conventions against those analytical expressions. The noisy-processing checks also compare the explicit quantum-plus-classical factorization with the Pauli-algebra projection and verify the resulting endpoint probabilities. Independent moment checks enumerate all subspaces at widths one through three and certify the pivot, noise and gate inequalities; exact logarithm enclosures check the finite moment-budget comparison. They do not test a physical device's noise or controller assumptions.

An accepted run is not a deterministic measurement of a device's qubit count. Soundness bounds every dimension-limited strategy in the ideal model; the compiled protocol covers the efficient adversaries in its imported assumptions. A low-memory device can occasionally pass. Claims based on repeated runs must account for their joint strategy and information across cuts rather than assuming independent trials without justification.