Architecture for a Century-Scale Autonomous Virtual World: A Sovereign, Serverless Peer-to-Peer MMO Protocol

Foundational Paradigm: Digital Physics and Century-Scale Invariance

Engineering a massively multiplayer online virtual world capable of persisting across centuries without centralized operational infrastructure demands a foundational shift from client-server gaming toward sovereign state machine replication[1]. Traditional commercial game architectures rely on authoritative cloud servers to advance universal simulation clocks, resolve state conflicts, and enforce relational consistency. When operating corporations succumb to insolvency or shift product priorities, the simulated universe vanishes[3].

Conversely, attempting to deploy a real-time virtual environment onto general-purpose public blockchains introduces fundamental execution ceilings: gas execution fees render continuous spatial computations economically unviable, while block finality latencies prevent real-time, reactive mechanical interactions[4].

A self-sovereign simulation requires an autonomous substrate wherein the virtual world operates as a closed physical continuum governed strictly by deterministic computational rules[3]. The operational laws of the world—its digital physics—must exist independently of institutional stewardship[3].

To guarantee that this virtual universe does not succumb to sociotechnical decay or protocol drift over century-long horizons—such as mutating into an unstructured communication utility, a speculative tokenized asset registry, or an arbitrary distributed file distribution channel—the underlying protocol must implement an architectural freezing model inspired by Kelvin versioning[8].

In a Kelvin-versioned protocol architecture, software releases count downward by integer degrees toward absolute zero ($0\ \mathrm{K}$)[9]. Once the digital physics kernel cools to zero Kelvin, the mathematical state transition function is permanently frozen: no further modifications, extensions, or soft forks can be integrated into the fundamental execution layer[9].

Extensibility across successive generations of human and machine participants is achieved strictly through user-space composability within the simulation's bounded virtual machine, rather than protocol-level mutations[3].

The digital physics constitution is codified through a minimal, formally verified WebAssembly (Wasm) execution kernel. This kernel enforces an Entity Component System (ECS) architecture wherein components represent strongly typed numerical data structures and systems dictate invariant procedural logic[3].

By defining physical primitives—such as mass, momentum, spatial occupation, thermodynamic work, and anatomical collision—directly within the immutable Wasm kernel, the universe maintains structural integrity across generational epochs[3]. A rogue participant cannot alter local gravitational parameters to $0.5\times$ because peer nodes independently verify all state transformations against the immutable genesis kernel hash. Any mathematical deviation produces an invalid cryptographic state delta that neighboring verification nodes discard at the network transport layer[1].

Spatial Partitioning and Network Topology

Serverless real-time virtual environments face the fundamental scaling limit of distributed communication: an unpartitioned mesh network of N participants incurs an all-to-all message complexity of $\mathcal{O}(N^2)$ per simulation tick[4]. If hundreds of players congregate within a shared environment, consumer-grade network interfaces suffer catastrophic saturation[4]. To overcome this constraint, the protocol implements a dual-layer spatial network topology combining continuous Voronoi-based Overlay Networks (VON) with hierarchical, dynamic spatial decomposition[14].

At the continuous spatial layer, avatars interact using a Voronoi-based overlay where each participant acts as a site in a distributed planar Voronoi diagram[15]. Dynamic Delaunay triangulation enables each node to discover and maintain transport channels exclusively with its immediate spatial neighbors[15].

Each avatar establishes an Area of Interest (AOI) boundary[15]. When an avatar navigates through coordinate space, the Voronoi neighbor graph recalculates locally, establishing direct peer connections over QUIC and WebRTC DataChannels with newly encountered entities while pruning links to departed peers[15]. This architecture limits peer-to-peer messaging overhead to local visibility horizons, preserving network efficiency across expansive territories[14].

To maintain topological stability during extreme node churn or regional depopulation, continuous space is anchored by a structured Kademlia Distributed Hash Table (DHT) mapped across discrete, three-dimensional spatial bounding boxes known as Volumetric Chunks, sized at $128\ \mathrm{m} \times 128\ \mathrm{m} \times 128\ \mathrm{m}$. The spatial coordinates of each chunk serve as keys within the DHT, mapping to the network addresses of the active node ensemble currently situated within or near that bounding volume.

The physical boundaries where adjacent spatial partitions meet introduce critical edge conditions that have historically undermined peer-to-peer virtual worlds[15]. If an avatar situated in Chunk A discharges a projectile toward an avatar in Chunk B, disparate validation groups could disagree on temporal ordering or collision registration.

To resolve boundary seams, the protocol enforces an Overlapping Halo Boundary. Every spatial chunk projects an active validation margin extending $16\ \mathrm{meters}$ into all adjacent volumes.

Entities existing within this halo belong simultaneously to both peer groups, requiring a two-phase cross-quorum cryptographic attestation before any state modification crossing the border is committed to history.

When spatial concentration escalates—such as hundreds of avatars converging on a central citadel—the network dynamic shifts. To prevent localized $\mathcal{O}(N^2)$ collapse, the protocol triggers dynamic recursive spatial partitioning. The affected chunk subdivides into an octree of eight micro-volumes, each bounded by its own micro-consensus quorum.

If spatial density surpasses the limits of physical subdivision, the protocol transitions from direct mesh synchronization to an Ephemeral Committee Relay. The top tier of longest-lived, highest-bandwidth nodes within that micro-volume is deterministically elected to sequence inputs, aggregate state deltas, and broadcast compressed cryptographic updates, scaling the communication complexity down to $\mathcal{O}(N \log N)$ without compromising determinism[13].

Architectural Layer	**Structural Mechanism**	**Primary Function**	**Theoretical Complexity**
Continuous Spatial Layer	Voronoi-based Overlay Network (VON)	Real-time neighbor discovery and dynamic Area of Interest management[15]	$\mathcal{O}(\text{local neighbors}$ [cite: 14, 15]
Topological Anchor Layer	Kademlia Distributed Hash Table	Volumetric chunk routing and long-term peer rendezvous	$\mathcal{O}(\log N)$ lookup[15]
Boundary Interface Layer	Overlapping Halo Boundary (16 m)	Seam-free spatial transitions and cross-quorum validation	Two-phase consensus commit
High-Density Fallback	Ephemeral Committee Relay (ECR)	Dynamic octree sharding and input aggregation under crowd conditions[13]	$\mathcal{O}(N \log N)$ message scaling[13]

Consensus, Validation, and Byzantine Fault Tolerance

Maintaining a serverless virtual world requires a consensus mechanism capable of executing at

two conflicting operational speeds: sub-50-millisecond reactive combat and definitive, tamper-proof long-term state commitment[4]. The protocol resolves this trade-off using a dual-track validation pipeline combining optimistic deterministic rollback loops with Byzantine Fault Tolerant (BFT) enclave finality[1].

During real-time interaction, peer clusters execute a local optimistic state engine modeled on rollback networking[19]. Clients broadcast cryptographically signed input intents (such as directional vectors, tool applications, and skill activations) rather than raw coordinate updates. Every node simulates the world forward using an identical fixed-point software-emulated mathematics pipeline, eliminating non-deterministic divergence across divergent CPU instruction sets[19]. When network transit delays cause an input packet from a peer to arrive late, the local engine automatically rolls back the simulation history to the timestamp of the late input, splices the input into the deterministic queue, and resimulates forward to the current frame[19].

To elevate this speculative simulation to immutable reality, the local spatial ensemble executes a lightweight, leaderless BFT consensus protocol within each tick epoch[1]. A state transition becomes canonical only when a supermajority ($>$) of the active nodes within the spatial quorum sign the Merkle root of the resulting state delta[1].

However, this mechanism faces a critical vulnerability when an avatar travels into unpopulated wilderness where no peer ensemble exists to form a BFT quorum. In classical distributed systems, solitary exploration invites arbitrary state manipulation, as an unobserved node could manufacture infinite raw resources or alter historical attributes without resistance[4].

The protocol neutralizes solitary exploitation by integrating Zero-Knowledge Virtual Machine (zk-VM) execution traces[5]. When a node operates without peer witnesses, its execution client transitions into provable computing mode. The sandboxed Wasm kernel generates an algebraic intermediate representation of its execution trace, compiling state transformations into a succinct zero-knowledge argument (zk-STARK).

When the solitary avatar re-enters populated space and intersects a peer quorum, it does not submit raw state data; it presents the succinct STARK proof verifying that every inventory acquisition, damage calculation, and spatial step computed during its isolation conformed with mathematical precision to the genesis Wasm kernel. The receiving quorum verifies this cryptographic proof within milliseconds, guaranteeing that unobserved gameplay remains mathematically honest without continuous network consensus[5].

Probabilistic game resolutions—such as physical combat accuracy, resource yield harvesting, and status effect rolls—introduce another critical vector for manipulation. If a client computes its own probability outcomes, it can exploit the system to roll maximum successes[22]. If neighboring peers compute it, they can withhold packets when outcomes disfavor them[4].

The protocol resolves non-deterministic combat rolls using the Pairwise Random Protocol (PRP) alongside continuous Verifiable Delay Functions (VDFs)[4]. Under PRP, when an interaction occurs between adversarial entities, both nodes commit cryptographic hashes of locally generated random nonces:

$$\text{Commit}_A = H(\text{Nonce}_A), \quad \text{Commit}_B = H(\text{Nonce}_B)$$

Once both commitment hashes are anchored in the local quorum log, both nodes reveal their underlying nonces[26]. The canonical outcome of the probabilistic interaction is derived strictly through the combined entropy:

$$\text{Entropy} = H(\text{Nonce}_A \oplus \text{Nonce}_B)$$

Neither party can bias the outcome without solving a cryptographic pre-image collision under sub-millisecond network deadlines[24]. For ambient world probabilistic events lacking direct adversarial pairing (such as weather system shifts or rare creature spawns), the network integrates an iterative VDF beacon, forcing sequential, un-parallelizable mathematical evaluations that prevent any network participant from predicting or manipulating future world states[24].

Exploit Mitigation, Cheating Defense, and Threat Vectors

A decentralized, ownerless architecture functions in an adversarial environment without central oversight, platform telemetry, or kernel-level anti-cheat binaries[28]. Consequently, security and integrity must be built directly into the mathematical structure of the protocol.

The most catastrophic technical failure in distributed virtual environments is cross-platform floating-point divergence[19]. Standard modern hardware executes floating-point arithmetic according to IEEE 754 specifications, but differences in compiler optimization flags, extended precision registers, fused multiply-add (FMA) instructions, and CPU microarchitectures (such as x86-64 versus ARM64) produce discrepancies in the least significant bits of floating-point results[19]. In a deterministic state machine, a divergence of 0.0000001 units cascades through spatial collision routines, culminating in hard simulation desynchronization within dozens of frames[19].

The protocol completely prohibits native hardware floating-point operations within the physics and logic loops. All spatial coordinates, velocities, impulse vectors, angular moments, and collision envelopes are computed strictly through software-emulated fixed-point arithmetic (Q32.32 or Q64.64) or soft-float integer packages[19]. Every arithmetic calculation evaluates identically on any standards-compliant hardware across decades of processor evolution[19].

Sybil attacks represent another fundamental threat to decentralized peer validation[22]. A malicious participant could launch dozens of virtual machines on a single physical host, route them through diverse proxy IP addresses into a targeted spatial chunk, and command a malicious $>$ quorum majority to rewrite chunk history or transfer assets illegally[1].

The protocol defends against Sybil infiltration through Proof-of-Gameplay Stake coupled with asynchronous sentinel auditing[22]. A node cannot participate in BFT quorum voting merely by presenting an IP address; voting rights require an active avatar identity carrying accumulated,

verifiable historical proof-of-work and state-age, evidenced by a cryptographic audit trail proving historical in-game existence, resource consumption, and verified state transitions over significant temporal epochs.

Complementing this stake, the network continuously selects random, non-local peer nodes via DHT hashing to act as detached witness auditors[22]. These sentinel nodes periodically receive compressed state-delta snapshots and input logs from active chunk quorums[22]. If a localized collusive quorum attests to an illegal state delta that violates Wasm execution rules, the distant witness nodes identify the mathematical contradiction, broadcast an irrefutable fraud proof across the global DHT, and slash the colluders' cryptographic identity credentials and accumulated progress[22].

A critical vulnerability unique to open distributed storage networks is the Arbitrary Data Carrier Attack[29]. If an immutable peer-to-peer network permits participants to broadcast and permanently store arbitrary binary blobs, adversaries exploit the infrastructure to distribute pirated media, copyright-infringing content, malware command-and-control packages, or illicit files[29]. Peer node operators who unknowingly replicate and store these foreign chunks on their personal machines face severe civil and criminal liability, leading to network abandonment and operational collapse[28].

To make arbitrary media hosting technically and structurally impossible, the protocol enforces rigorous semantic data constraints. The wire serialization format rejects raw byte buffers, requiring every packet transmitted across the network to conform strictly to typed ECS schemas[2]. Unrecognized schemas are dropped immediately by peer transport filters before hitting memory or disk[29].

User-authored content, such as player-built structures, heraldry, or visual textures, cannot exceed strict mathematical limits: a structural asset is capped at a fixed vertex count (maximum 2,048 vertices) and restricted to low-precision, fixed-point relative coordinate arrays, while textures are bound to rigid color-indexed palettes with maximum dimensions of 128×128 pixels.

Furthermore, any custom visual asset submitted to the network passes through a mandatory Wasm transcode pipeline during consensus validation. Verifying nodes re-quantize vertex buffers, discard unused texture bit-planes, re-index color maps, and normalize geometric normals. This destructive transformation eliminates steganographic storage channels, ensuring that arbitrary file payloads become corrupted and unextractable[29].

Finally, long-term historical state segments distributed across storage peers are encrypted with transient, spatially derived keys and split into erasure-coded parity slivers[36]. Individual storage nodes hold only disconnected mathematical parity fragments rather than complete, functional, or reconstructible data objects, ensuring that node operators cannot be classified as intentional file hosts under distributed carrier liability frameworks[36].

Threat Vector	Underlying Exploitation	Protocol Structural Defense	Verification Layer

	Mechanism		
Float Divergence	IEEE 754 microarchitectural discrepancies across x86/ARM[19]	Pure software fixed-point arithmetic (Q64.64) / soft-floats[20]	Wasm sandboxed deterministic runtime[1]
Sybil Infiltration	Virtual machine flooding to hijack local $>$ quorum[1]	Proof-of-Gameplay Stake + Asynchronous Sentinel Witnesses[22]	DHT-routed detached Carbon audits[22]
Solitary Cheating	Arbitrary state fabrication in unpopulated wilderness chunks[4]	Local zk-VM algebraic execution trace generation (zk-STARK)[5]	Boundary peer verification of succinct proof[5]
RNG Prediction	Biased outcome reporting or packet suppression during combat[4]	Pairwise Random Protocol (PRP) + Sequential VDF beacons[24]	Local BFT hash commit-reveal locking[24]
Arbitrary Data Carrier	Hosting pirated files or malware inside immutable state[29]	Strict typed schemas, vertex limits, and destructive transcoding[29]	Wire deserialization filter and Wasm pipeline[2]

Data Durability and the 0.1% Survival Guarantee

A resilient architecture must guarantee that the universe survives prolonged catastrophe, including scenarios where global concurrent engagement drops by 99.9%, leaving only 0.1% of historical nodes online. Under such extreme network attrition, ordinary distributed databases fracture into disconnected partitions and suffer unrecoverable state loss. The protocol achieves total survivability through procedural compression, sparse state tracking, and liquid fountain erasure codes[36].

The foundation of the universe's geography requires virtually zero persistent bytes. World terrain, geological formations, river networks, biome distributions, vegetation placement, and subterranean resource veins are derived procedurally from an immutable 32-byte cryptographic Genesis Seed:

$$\text{TerrainElevation}(x, z) = \mathcal{F}_{\text{Wasm}}(\text{GenesisSeed}, x, z)$$

Because the procedural synthesis algorithms are codified within the frozen Wasm kernel using deterministic fixed-point mathematics, every client independently recalculates identical mountain ranges, ocean basins, and cave systems on the fly[20]. Hundreds of square kilometers of virgin world landscape require zero distributed disk storage[3].

Storage overhead is strictly confined to Sparse State Deltas representing deliberate modifications made to the world by entities, such as excavated earth, harvested timber, erected fortresses, item crafting, and character progression[3]. These state transformations are organized into Sparse Merkle Trees (SMTs) maintained as an append-only directed acyclic graph (DAG)[13].

To ensure historical deltas endure severe network collapses, state DAGs are encoded using RaptorQ Forward Error Correction fountain codes (IETF RFC 6330)[36]. RaptorQ represents an advanced class of linear-time erasure codes capable of transforming a discrete state block of K source symbols into an effectively infinite stream of interchangeable repair symbols[36].

A recovering node does not need to identify and download specific missing fragments; it simply collects any $K + \epsilon$ symbols (where ϵ represents a negligible mathematical overhead, typically less than 1%) from any surviving peers on the network to fully reconstruct the underlying world state[36].

By configuring high-redundancy parity distributions across the global DHT, state fragments are mirrored widely across the network. If a network of 100,000 active nodes collapses to merely 100 surviving nodes distributed across continents, the remaining nodes hold a sufficient density of RaptorQ repair symbols to guarantee complete, bit-for-bit reconstruction of the entire historical world database[36].

When human concurrency recovers and new players rejoin, nodes ingest these liquid repair symbols, reconstruct the sparse Merkle roots, overlay the deltas onto the procedurally generated geography, and resume the continuous simulation without historical fracture or data loss[36].

Storage Subsystem	Implementation Primitive	Storage Resource Profile	Recovery Characteristic
Planetary Topography	Deterministic procedural Wasm noise functions	Invariant 32-byte Genesis Seed	Zero-cost local recomputation[3]
Dynamic World State	Sparse Merkle Trees (SMT) over	Compact, delta-only spatial	Cryptographic root verification[1]

	delta DAGs[13]	logging[3]	
Historical Resilience	RaptorQ Fountain Codes (RFC 6330)[37]	K source symbols expanded to redundant streams[36]	Reconstructible from any $K + \epsilon$ symbols[36]
Physical Partitioning	Volumetric Chunks ($128\ \mathrm{m}^3$) via Kademlia DHT	Sharded storage across localized node ensembles	Redundant cross-peer mirroring[15]

Autonomous Ecological Agents and Closed Thermodynamic Economics

Treating automated agents as hostile bots requiring programmatic elimination is incompatible with serverless protocol longevity. In an ownerless virtual universe spanning generations, the protocol redefines autonomous software agents as first-class algorithmic citizens[12]. These agents serve as non-player characters (NPCs), wildlife, trading merchants, and ambient infrastructure maintainers[12].

Every autonomous agent operates via the exact same cryptographic and operational interfaces as a human participant. An agent controls an Ed25519 keypair, signs action intents, and maintains state records within the decentralized ECS tables.

However, running large language models or deep reinforcement learning networks within deterministic consensus validation is computationally intractable and fundamentally non-deterministic. To resolve this, the protocol enforces a strict bifurcation between Cognition and Action:

The cognitive architecture of an agent (its neural planner, utility heuristics, or rule engines) executes entirely off-chain on the host machine running that agent node. Conversely, the agent's emitted choices are translated into standard, signed input intents (Move, Harvest, Trade, Attack) submitted directly to the local chunk quorum. The physical validity of these actions is evaluated against the same deterministic Wasm rules that govern human players, ensuring that agents cannot bypass cooldowns, move faster than maximum physical velocities, or manifest unearned advantages.

To prevent an unchecked proliferation of autonomous agents from degrading network bandwidth, exhausting storage space, or triggering runaway economic hyperinflation, the simulation enforces a closed thermodynamic economic loop[12]. In typical commercial MMOs, currency and resources are created out of nothing: NPCs possess infinite gold pools, defeated creatures spawn items from randomized tables, and systems suffer persistent inflation that destroys economic utility over time. Under the sovereign protocol, the simulation obeys strict conservation laws[12].

Asset conservation mandates that no currency unit or material item can be generated ex nihilo. All physical mass originates from procedurally bounded harvestable matter (mineral veins, lumber stocks, flora yields) that deplete upon extraction. Furthermore, every manufactured structure, weapon, piece of armor, and automated agent incurs continuous thermodynamic decay. Structures degrade and collapse if not maintained with physical resources; tools wear out and break through usage; agents require consumable energy units (food, fuel, or repaired parts) to pay the execution upkeep of their in-world entity status[12].

This structural framework creates rigorous market-driven survival pressure. An autonomous blacksmith NPC cannot stand motionless behind a counter indefinitely. To avoid entity death, it must purchase raw iron from miners (human or algorithmic), smelt weapons using deterministic recipes, sell tools to adventurers at market-clearing rates, and generate sufficient profit to pay rent on its workshop and consume daily sustenance.

If its trading balance sheet fails, the NPC goes bankrupt, its entity assets are liquidated, and its operational footprint naturally dissolves from the chunk quorum. If human players abandon a territory for months, autonomous agents step into the economic vacuum, maintaining municipal infrastructure, trading along arterial trade routes, harvesting crops, and defending settlement boundaries. When human populations return, they re-enter a living world that has aged, evolved, and adapted through autonomous, rule-bound competition rather than freezing in static suspension[3].

Architectural Synthesis and Comparative Evaluation

The holistic architecture of the proposed protocol diverges fundamentally from traditional centralized virtual environments, tokenized blockchain games, and early academic peer-to-peer designs.

Architectural Dimension	**Traditional Commercial MMO (e.g., WoW, EVE)**	**Fully On-Chain Blockchain Game (e.g., MUD, Dojo)**	**Academic P2P DVE (e.g., Solipsis, VON)**	**The Sovereign Century Protocol (Aetheria Architecture)**
Hosting & Settlement Layer	Centralized cloud infrastructure (AWS, Azure)	Public L1/L2 consensus ledgers (EVM, Starknet)	Pure P2P unstructured overlay networks	Self-sovereign spatial DHT + Local BFT Enclaves[13]
Physics & Math Execution	Non-deterministic native floats on game servers	Abstracted turn-based or discrete grid logic[5]	Non-deterministic local client floating point[20]	Soft-float / Fixed-point arithmetic in sandboxed Wasm[19]

Century-Scale Governance	Corporate ownership; servers terminated at will	DAO governance contracts or upgradeable proxies	No formal governance mechanism	Kelvin Versioning ($0\ \mathrm{K}$ kernel) with immutability[9]
Single-Player Wilderness Integrity	Server evaluates all isolated actions	Base chain settles all transactions globally	Vulnerable to unchecked client manipulation[4]	Local zk-VM (zk-STARK) validity proof generation[5]
Probabilistic Event Resolution	Server CPU pseudorandom number generator	Verifiable Random Functions (VRF) on-chain	Unverifiable local random number generation	Pairwise Random Protocol (PRP) + Sequential VDFs[24]
Catastrophic Attrition Resilience	0% survivability if corporate provider terminates	Survives via public ledger if gas fees are paid	State fractures and collapses upon node churn[4]	100% recovery from 0.1% nodes via RaptorQ RFC 6330[36]
Data Carrier / Piracy Protection	Central legal compliance and content deletion	Storage gas costs act as minor disincentive[29]	High vulnerability to arbitrary payload seeding[33]	Strict typing, vertex caps, and destructive transcoding[29]
Autonomous Agent (NPC) Role	Hardcoded, script-driven server entities	Algorithmic trading bots and smart contracts[5]	Ephemeral client-side simulation scripts	First-class sovereign cryptographic entities under thermodynamic sinks[12]

By integrating these technological innovations into a cohesive stack, the virtual universe breaks free from commercial dependency. It establishes an un-censorable, mathematically self-consistent reality designed to operate seamlessly across century-long spans of technological, institutional, and social transformation[3].

Implementation Specification Prompt for an Autonomous AI Systems Architect

The following architectural specification prompt is designed for direct transfer to an advanced AI systems engineering agent to generate the formal protocol specifications, cryptographic definitions, and core codebase for this simulation.

System Engineering Task Directive: The Aetheria Protocol Core Engine

You are tasked with engineering the foundational implementation of the Aetheria Protocol: a serverless, self-sovereign, peer-to-peer Massively Multiplayer Online (MMO) simulation engine and autonomous world designed for century-scale operational longevity without reliance on external public blockchains (e.g., Ethereum, Bitcoin) or centralized infrastructure.
Your objective is to produce the core architecture, data schemas, mathematical specifications, and Rust production-ready code primitives for this system. Adhere strictly to the architectural constraints, cryptographic guarantees, and systems engineering parameters detailed below:

1. Immutable Digital Physics Kernel (Kelvin 0K Architecture)

- Implement the core state transition machine using a sandboxed WebAssembly (Wasm) runtime executing an Entity Component System (ECS) pattern.
- The Wasm execution environment must be strictly deterministic across disparate CPU architectures (x86-64, ARM64, RISC-V). Eliminate all hardware floating-point operations. Implement all spatial transformations, physical velocities, collision queries, and accelerations using 64.64 fixed-point arithmetic or deterministic soft-float integers.
- Codify a Kelvin 0K immutability model: design the genesis physics engine specification such that the state transition kernel hash is frozen permanently, preventing any functional drift into unstructured chat protocols, arbitrary distributed file storage networks, or speculative financial platforms.

2. Spatial Topology and Mesh Networking

- Implement a Voronoi-based Overlay Network (VON) utilizing Delaunay triangulation for dynamic Area of Interest (AOI) discovery in continuous coordinate space.
- Couple the continuous spatial layer to a 3D volumetric chunking system indexed via an internal Kademlia Distributed Hash Table (DHT) implemented over libp2p, utilizing QUIC and WebRTC DataChannels for low-latency peer transit.
- Design an Overlapping Halo Boundary (OHB) protocol (16-meter margin) to manage seamless inter-chunk spatial transitions and eliminate collision boundary seams through two-phase cross-quorum commitments.
- Implement an Ephemeral Committee Relay (ECR) fallback mechanism that dynamically subdivides congested spatial chunks into hierarchical octrees, mitigating quadratic packet saturation during extreme avatar density.

3. Consensus, Hybrid Validation, and Integrity

- Build a dual-track execution pipeline: (a) sub-50ms optimistic rollback simulation using fixed-point input prediction for local client frames, and (b) leaderless Local Quorum Byzantine Fault Tolerance (BFT) reaching finality on state deltas when greater than two-thirds of local chunk peers attest to the Merkle state root.
- Solitary Node Resolution: For avatars traversing uninhabited space without peer witnesses, construct a zero-knowledge execution tracer (compatible with RISC Zero or SP1 zk-VM architectures). The client must generate a succinct zk-STARK proof certifying that its isolated movements, resource gathering, and combat strictly conformed to the Wasm genesis rules.
- Deterministic Randomness: Implement the Pairwise Random Protocol (PRP) for adversarial player interactions (commit-reveal scheme over XORed entropy seeds) and a Verifiable Delay Function (VDF) beacon for ambient world probabilistic state changes.

4. Data Carrier Abuse and Piracy Elimination

- Defend the storage substrate against Arbitrary Data Carrier Attacks, preventing the network from being weaponized as a pirated media or malware distribution network.
- Implement strict schema serialization (Cap'n Proto or FlatBuffers style) that completely rejects unstructured arbitrary byte buffers at the transport layer.
- Enforce strict content envelopes: 3D meshes capped at 2,048 vertices in fixed-point relative arrays; textures restricted to 128x128 indexed palette maps.
- Implement a mandatory deterministic Wasm transcode sanitization pipeline during consensus validation that re-quantizes geometry, strips non-vertex metadata, and destroys steganographic channels.

5. Data Durability and 0.1% Attrition Survival

- Design a zero-storage procedural terrain engine: generate base planetary geography deterministically from an immutable 32-byte Genesis Seed via procedural noise evaluated locally on the client.
- Maintain human-induced world transformations exclusively as Sparse Merkle Tree (SMT) delta logs.
- Encode historical world state deltas using RaptorQ Forward Error Correction fountain codes (IETF RFC 6330). Demonstrate mathematically and programmatically how the network reconstructs 100% of the persistent world state from any $K + \epsilon$ repair symbols even if 99.9% of peer nodes abruptly disconnect.

6. Autonomous Ecological Agents and Thermodynamic Economy

- Model all Non-Player Characters (NPCs) as sovereign autonomous agents bearing individual Ed25519 keypairs, executing standard signed action intents within the ECS.
- Decouple off-chain cognitive planning (heuristics, LLM planners) from on-chain physics execution, subjecting agent actions to the same physical bounds, cooldowns, and validation checks as human players.
- Implement a closed-loop thermodynamic economic model: conservation of physical

matter (no fiat item spawning), continuous entropy/decay degradation on all tools, structures, and entities, and mandatory energy-consumption upkeep to maintain active entity survival.

Deliverables Required

1. Complete system architecture specification with formal component interfaces and data flows.
2. Formal mathematical formulations for the deterministic fixed-point physics loop, the Pairwise Random Protocol, and the RaptorQ state recovery threshold.
3. Production-grade Rust implementation of:
    - The Fixed-Point Vector/Physics Primitive (Q64.64).
    - The Typed ECS State Delta and Sparse Merkle Tree verification structs.
    - The Local Quorum BFT validation engine and consensus message envelope.
    - The RaptorQ state chunk encoder/decoder integration.
    - The input-sanitization and destructive asset transcoding filter.

Execute this specification with rigorous systems programming principles, zero extraneous conversational filler, and uncompromising cryptographic precision.

Works cited

1. SAMMANTICS, https://sammantics.io/
2. State machine replication - Wikipedia, https://en.wikipedia.org/wiki/State_machine_replication
3. Making of OPCraft (Part 3): What happened in two weeks of ... - Lattice, https://lattice.xyz/blog/making-of-opcraft-part-3-what-happened-in-two-weeks-of-opcraft
4. Distributed virtual environment scalability and security, https://www.cl.cam.ac.uk/techreports/UCAM-CL-TR-809.pdf
5. Exploring Onchain Game Development with MUD and Dojo, https://www.bitkraft.vc/insights/dungeons-and-dojos-exploring-onchain-game-development-with-mud-and-dojo/
6. Provenance Tracking of In-game Virtual Items via the Blockchain, https://theses.ncl.ac.uk/jspui/bitstream/10443/6655/1/Lu%20Yiang%20190100771%20ecopy.pdf
7. Autonomous Worlds Assembly @Devconnect Istanbul 2023, https://cryptoevents.global/autonomous-worlds-assembly-devconnect-istanbul-2023/
8. (PDF) Software, Sovereignty and the Post-Neoliberal Politics of Exit, https://www.academia.edu/96651191/Software_Sovereignty_and_the_Post_Neoliberal_Politics_of_Exit
9. Urbit: functional programming from scratch - Moron Lab, http://moronlab.blogspot.com/2010/01/urbit-functional-programming-from.html
10. Toward a Frozen Operating System • Blog - Urbit, https://urbit.org/blog/toward-a-frozen-operating-system

11. Kelvin Versioning - jtobin.io ·, https://jtobin.io/kelvin-versioning?ref=snakecharmers.ethereum.org
12. Look Before You Leap: Thermodynamic Arbitration of Parametric, https://arxiv.org/html/2610.05223v1
13. hellas-ai/awesome-consensus: A bibliography for protocol design, https://github.com/hellas-ai/awesome-consensus
14. System high-level design of MMOG. - ResearchGate, https://www.researchgate.net/figure/System-high-level-design-of-MMOG_fig5_220686424
15. A Spatial Publish Subscribe Overlay for Massively Multiuser ... - VAST, https://vast.sourceforge.net/docs/pub/VAST-TR-03-2010.pdf
16. A Framework for Client-Server Objects Streaming in VR, https://thesis.unipd.it/retrieve/ed64e304-7f60-4245-a44e-a2d2d17ffff0/Carboni_Federico.pdf
17. Voronoi diagram VON is a P2P NVE building by Voronoi diagram. It, https://www.researchgate.net/figure/oronoi-diagram-VON-is-a-P2P-NVE-building-by-Voronoi-diagram-It-supports-nodes-to-join_fig4_4319651
18. Combining Peer-to-Peer and Cloud Computing for Large Scale On, https://arxiv.org/html/1510.08940v1
19. Space Crash - Cal Poly Digital Commons, https://digitalcommons.calpoly.edu/cgi/viewcontent.cgi?article=1225&context=cscsp
20. Cross-platform deterministic physics with Unity DOTS ... - Reddit, https://www.reddit.com/r/Unity3D/comments/lkxb9d/crossplatform_deterministic_physics_with_unity/
21. Beyond Bitcoin: Recent Trends and Perspectives in Distributed, https://www.mdpi.com/2410-387X/5/4/36
22. Low Latency and Cheat-proof Event Ordering for Peer-to-Peer Games, https://zappala.byu.edu/pubs/neo-nossdav-2004.pdf
23. Decentralized Consensus Protocol - Emergent Mind, https://www.emergentmind.com/topics/decentralized-consensus-protocol
24. A Blockchain Protocol for Real-Time Application Migration on the Edge, https://pmc.ncbi.nlm.nih.gov/articles/PMC10181778/
25. Non-interactive Cryptographic Timestamping based on Verifiable, https://ir.cwi.nl/pub/29378/29378.pdf
26. NOSSDAV 2009, http://www.nossdav.org/2009/extprogram.html
27. Fairledger: a Fair Proof-of-Sequential-Work based Lightweight, https://par.nsf.gov/servlets/purl/10359382
28. Carbon: trusted auditing for P2P distributed virtual environments, https://www.cl.cam.ac.uk/techreports/UCAM-CL-TR-753.pdf
29. Smart Contracts for C&C: How ClearFake Hid in Plain Sight on BSC, https://www.trendmicro.com/en_us/research/26/e/smart-contracts-for-command-and-control.html
30. Math — list of Rust libraries/crates // Lib.rs, https://lib.rs/science/math
31. Project settings to use soft float and fixed point backends for float type,

https://github.com/godotengine/godot-proposals/issues/7128
32. Blocks | ethereum.org, https://ethereum.org/developers/docs/blocks/
33. Omnistealer uses the blockchain to steal everything it can, https://www.malwarebytes.com/blog/news/2026/04/omnistealer-uses-the-blockchain-to-steal-everything-it-can
34. Analysis of Arbitrary Content on Blockchain-Based Systems using, https://arxiv.org/html/2203.09379v1
35. Blockchain malware's neverending novelty - MetaMask, https://metamask.io/news/blockchain-malwares-neverending-novelty
36. Walrus: An Efficient Decentralized Storage Network - Alberto Sonnino, https://sonnino.com/papers/walrus-whitepaper.pdf
37. Jeffrey Emanuel: Agentic Coding Tooling, AI Infrastructure & Markets, https://jeffreyemanuel.com/
38. A Survey and Ontology of Blockchain Consensus Algorithms ... - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC9657616/
39. ETSI TS 103 973 V1.1.1 (2024-10), https://www.etsi.org/deliver/etsi_ts/103900_103999/103973/01.01.01_60/ts_103973v010101p.pdf
40. International Journal of Research and Analytical Reviews - IJRAR, https://ijrar.com/uploads/conference/ijrar_47.pdf
41. [2607.02514] Distributed Attacks in Persistent-State AI Control - arXiv, https://arxiv.org/abs/2607.02514
42. Century-Scale Storage - Library Innovation Lab, https://lil.law.harvard.edu/century-scale-storage/