

they need a SS administrator to reset their password and enable their account.

- **RADIUS Client Port Range:** Allowed computer ports for RADIUS.
- **RADIUS Login Explanation:** Text that appears, explaining the RADIUS login.
- **RADIUS Default Username:** The default username that appears at RADIUS login.
- **RADIUS Server Port:** The default RADIUS port.
- **Require Two Factor for these Login Types:** When enabled on a specific user logging into SS, you can choose from a list to enable it for website, Web service, or both.
- **Time Out (seconds):** RADIUS timeout in minutes.
- **Use RADIUS Username for Duo:** Pass the RADIUS username to Duo.
- **Visual Encrypted Keyboard Enabled:** Enables or disables the visual encrypted keyboard for logins.
- **Visual Encrypted Keyboard Required:** Require the visual keyboard for logins.

Security Tab

The Security tab contains the following configuration options:

- **Additional Certificate Chain Policy Options:** Valid values for certificate chain policy options are any of the values in the Microsoft enumerations [listed here](#).
- **Allow HTTP Get:** Allows the HTTP Get verb for Web services. This allows REST-style calls to many Web service methods but reduces security.
- **Apply TLS Certificate Chain Policy and Error Auditing:** Add audits for TLS certificate validation. Auditing will apply to all Active Directory domains using LDAPS and Syslog using TLS. The default policy is very strict.
- **Enable Database Integrity Monitoring:** Database Integrity Monitoring is a SS tool for detecting changes made to primary database tables outside SS's user interface. It sends e-mails to configured addresses when it detects database changes made outside of SS.
- **Enable FIPS Compliance:** See [FIPS Compliance](#).
- **Enable File Restrictions:** Allow administrators to configure what kind of file attachments can be uploaded to secrets. This helps protect users from being tricked into downloading a malicious secret attachment. The file extension can be specified, such as: *.7z, *.bmp, *.ca-bundle, *.cer, *.config, *.crt, *.csr, *.csv, *.dat, *.doc, *.docx, *.gif, *.gz, *.id-rsa, *.jpeg, *.jpg, *.json, *.key, *.lic, *.p7b, *.pcf, *.pdf
- **Enable Frame Blocking:** Allow SS to be opened in an <iframe> HTML tag on another, potentially malicious, site.
- **Enable HSTS:** Enable HTTP Strict Transport Security. Not available if Force HTTPS/SSL is turned off.
- **Enable TLS Debugging and Connection Tracking:** When enabled, SS sends information logs to your audit server about when TLS connections are opened or closed.
- **Encrypt Key using DPAPI:** This encrypts the SS AES 256 key using the machine key. It provides protection from admins copying SS from the server to their own machine. Note that a backup of the encryption key should be made before using this option. Otherwise, disaster recovery is impossible if the server dies. After encrypting the key, an administrator of SS can decrypt it.
- **Force HTTPS/SSL:** Require HTTPS; users cannot access SS using HTTP.
- **Frame Blocking:** Prevents users from accessing the SS site if it is embedded in an iFrame.
- **Hide Secret Server Version Numbers:** Hide SS version numbers from users.
- **Ignore Certificate Revocation Failures:** Ignore certificate revocation failures for syslog using TLS.
- **Last Secret Key Rotation:** When the last rotation occurred.
- **Last Secret Key Rotation Status:** What was the result when the last rotation occurred.
- **Rotate Secret Keys (button):** Key rotation is the process by which the encryption key, used for securing Secret data, is changed and Secret data is re-encrypted.

SAML Tab

See [SAML 2.0 Configuration Guide](#).

Session Recording Tab