

CO2-AT3-SCENARIO BASED QUESTIONS

Name: T.Gobika

Reg.no:192312286

1.In the context of neural networks, consider a multilayer perceptron used for binary classification. Explain how the backpropagation algorithm updates the weights in the network during training. Illustrate the process using a simple example by describing the forward pass, error calculation, and backward propagation of errors. Discuss how learning rate and activation functions influence the convergence and accuracy of the model.

Introduction

A Multilayer Perceptron (MLP) is a type of artificial neural network consisting of an input layer, one or more hidden layers, and an output layer. It is widely used for binary classification problems, where the output is either Yes/No or 0/1. The Backpropagation algorithm is a supervised learning algorithm that trains the network by minimizing the prediction error through weight updates.

Sample Dataset

Input x_1	Input x_2	Target Output(Y)
0	0	0
0	1	0
1	0	0
1	1	1

This is the AND gate dataset, commonly used to demonstrate binary classification.

Architecture of MLP

- Input Layer: x_1, x_2
- Hidden Layer: Hidden neurons
- Output Layer: Predicted output (0 or 1)

Backpropagation Algorithm

Step 1: Forward Pass

The input values are passed through the network.

Consider the input:

- $x_1 = 1$
- $x_2 = 1$

Assume the initial weights are:

- $w_1 = 0.50$
- $w_2 = 0.40$

The weighted sum is:

$$\text{Net Input} = (x_1 \times w_1) + (x_2 \times w_2)$$

$$= (1 \times 0.50) + (1 \times 0.40)$$

$$= 0.90$$

Using the Sigmoid Activation Function:

$$\text{Output} = 1 / (1 + e^{-0.9})$$

$$\approx 0.71$$

So,

- Predicted Output = 0.71
- Target Output = 1

Step 2: Error Calculation

The prediction error is calculated as:

$$\text{Error} = \text{Target} - \text{Predicted Output}$$

$$= 1 - 0.71$$

$$= 0.29$$

The objective is to reduce this error.

Step 3: Backward Propagation

The error is propagated backward, and the weights are updated using:

$$\text{New Weight} = \text{Old Weight} + \text{Learning Rate} \times \text{Error} \times \text{Input}$$

Assume the learning rate (η) = 0.1

Update Weight w_1

New w_1

$$= 0.50 + (0.1 \times 0.29 \times 1)$$

$$= 0.529$$

Update Weight w_2

New w_2

$$= 0.40 + (0.1 \times 0.29 \times 1)$$

$$= 0.429$$

The updated weights are used in the next iteration. This process continues until the error becomes very small.

Effect of Learning Rate

The learning rate (η) controls the size of the weight update.

- High Learning Rate
 - Faster training.
 - May overshoot the optimal solution.
 - Can make training unstable.
- Low Learning Rate
 - Slower training.
 - More stable convergence.
 - Better accuracy but requires more iterations.

Effect of Activation Functions

Activation functions introduce non-linearity into the neural network.

Sigmoid

- Output ranges from 0 to 1.
- Suitable for binary classification.
- May suffer from the vanishing gradient problem.

ReLU (Rectified Linear Unit)

- Output = $\max(0, x)$
- Faster training.
- Reduces the vanishing gradient problem.

Tanh

- Output ranges from -1 to $+1$.
- Faster convergence than sigmoid in some cases.

Advantages of Backpropagation

- Reduces prediction error.
- Improves classification accuracy.
- Efficiently updates network weights.
- Suitable for complex learning problems.
- Supports multiple hidden layers.

Applications

- Email spam detection
- Disease diagnosis
- Face recognition
- Handwritten digit recognition
- Fraud detection

Conclusion

The Backpropagation algorithm is the most widely used training method for Multilayer Perceptions. It performs a forward pass to compute the output, calculates the prediction error, and then performs backward propagation to update the weights. The learning rate determines the speed of learning, while the activation function affects convergence and classification accuracy. By repeatedly updating the weights, the neural network learns the correct decision boundary and achieves accurate binary classification.

2. In the context of Genetic Algorithms, consider a dataset representing different candidate solutions for maximizing a fitness function based on two parameters: Speed and Accuracy. Each solution is evaluated as either suitable (Yes) or not suitable (No). Using the Genetic Algorithm approach, analyze how the population evolves by applying selection, crossover, and mutation operations. Show the step-by-step improvement of candidate solutions across generations and identify the best optimal solution.

Dataset

Candidate	Speed	Accuracy	Suitable
A	60	70	No
B	75	80	Yes
C	70	75	No
D	90	95	Yes

Fitness Function = Speed + Accuracy

Candidate	Fitness
A	130
B	155
C	145
D	185

Step 1: Selection

Choose individuals with the highest fitness.

Selected:

- B (155)
- D (185)

Step 2: Crossover

Parents

B = (75,80)

D = (90,95)

After crossover

Child1 = (75,95)

Child2 = (90,80)

Fitness

Child1 = 170

Child2 = 170

Step 3: Mutation

Increase Accuracy of Child1 from 95 → 98

Child1 = (75,98)

Fitness = 173

Evolution

Generation	Best Fitness
Initial	185
After Crossover	170
After Mutation	173

Best overall solution remains:

Candidate D = (Speed = 90, Accuracy = 95)

Fitness = 185

Explanation

- Selection: Chooses the best candidates.
- Crossover: Combines parent characteristics.
- Mutation: Introduces small random changes to improve diversity.

Conclusion

Genetic Algorithms gradually improve candidate solutions and identify the optimal solution with the highest fitness.

3. In the context of Neural Networks for classification, consider a dataset used to predict whether a patient has a disease based on attributes such as Age, Blood Pressure, Glucose Level, and Lifestyle Risk. The output indicates whether the disease is present (Yes) or not (No). Using this dataset, explain how a neural network model can be trained using backpropagation to classify the data. Also, evaluate the model performance by comparing actual and predicted outputs.

Dataset

Patient	Actual	Predicted
P1	Yes	Yes
P2	No	No
P3	Yes	Yes
P4	No	Yes
P5	Yes	No
P6	No	No

Confusion Matrix

True Positive (TP) = 2 (P1, P3)

True Negative (TN) = 2 (P2, P6)

False Positive (FP) = 1 (P4)

False Negative (FN) = 1 (P5)

Performance Metrics

Accuracy

$\text{Accuracy} = \frac{\text{TP} + \text{TN}}{\text{TP} + \text{TN} + \text{FP} + \text{FN}}$

$= \frac{2 + 2}{6}$

$= 66.7\%$

Precision

$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}$

$= \frac{2}{3}$

$= 66.7\%$

Recall

$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}$

$= \frac{2}{3}$

$= 66.7\%$

F1 Score

$\text{F1} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$

$= 66.7\%$

Training Using Backpropagation

- Feed patient attributes (Age, Blood Pressure, Glucose, Lifestyle Risk).
- Perform forward propagation.
- Calculate prediction error.

- Apply backpropagation to update weights.
- Repeat until error is minimized.

Importance of Preprocessing

- Removes missing values.
- Normalizes numerical data.
- Improves model performance.

Importance of Feature Selection

- Removes irrelevant attributes.
- Reduces computation time.
- Improves classification accuracy.

Conclusion

The neural network classifies disease effectively using backpropagation. The confusion matrix and evaluation metrics show the model's performance, while preprocessing and feature selection improve accuracy and reliability.