

```
"token": "eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJhZG1pb1IsImNyZW0iOiJlZjE2MzZkMTU5MjUwNjksImV4cCI6MTYzOTkyMDcyNX0.FWTyFChf1_-YB_mOfUypbjv9",
"tokenHead": "Bearer"
```

The screenshot shows the Swagger UI interface. On the left, there is a sidebar with a list of API endpoints. The 'Authorize' button is highlighted in blue. In the main area, the 'Authorize' tab is selected, showing a table with the following columns: '参数key', '参数名称', 'in', '参数值', and '操作'. The table contains one row with the following data:

参数key	参数名称	in	参数值	操作
Authorization(apikey)	Authorization	header	Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6Ikp1bmU9IyZldWl0aWZG1pbls1bmYiZWZvZWQ0JE2	保存

Red arrows point to the 'Authorize' button, the 'Authorization' parameter, and the 'Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6Ikp1bmU9IyZldWl0aWZG1pbls1bmYiZWZvZWQ0JE2' token.

后台设置：

```
jwt:
# JWT 存储的请求头
tokenHeader: Authorization
# JWT 加解密使用的密钥
secret: mall-secret
# JWT 的超期限时间 (60*60*24)
expiration: 604800
# JWT 负载中拿到的开头
tokenHead: Bearer
```

3. 注意事项

GET

/book/certainType

☒

全选

参数类型

参数名称

参数值

☒

query(integer)

typeId

书本类别id

☒

query(integer)

pageNumber

页码(默认是1, 即显示第一页)

☒

query(integer)

pageSize

每页显示多少条信息 (默认是10, 即每一页显示10条数据)

类似上图，勾了参数就一定要填

因为@RequestBody和@Validation在一起使用把之前的参数校验都搞失效了

所以接口现在约等于没有参数校验