

CONFIDENTIAL : AUTHORISED PENETRATION TEST

PayliteNG

Penetration Test Report

Authorised Security Testing of the PayliteNG Server Replica (Metasploitable2 Environment)

This engagement was carried out under written authorisation from PayliteNG's CEO, Mrs. Adaeze Obi, against PayliteNG's internal server replica only. No PayliteNG production system, customer data, or third-party infrastructure was tested.

Client	PayliteNG — Aba, Abia State, Nigeria
Engagement contact	Mr. Emeka Okafor, IT Manager
Report recipient	Mrs. Adaeze Obi, Chief Executive Officer
Prepared by	Onwubiko Godswill Chinaecherem, Junior Security Consultant
Date submitted	22 June 2026
Document classification	CONFIDENTIAL : Board & Legal Use Only
Reference	PNG-PEN-2026-001
Programme	TechRise 3.0 Cybersecurity & DevSecOps — Abia Cohort 3.0 (LearnFactory / Abia State Government)

Table of Contents

A Note on Evidence in This Report	2
1. Rules of Engagement	3
2. Scope and Methodology	5
3. Findings Summary Table	8
4. Finding 001: vsftpd 2.3.4 Backdoor (CVE-2011-2523)	10
5. Finding 002: Anonymous FTP Access	13
6. Finding 003: Outdated Apache 2.2.8 with WebDAV Module Enabled	15
7. Attack Chain Diagram	17
8. Remediation Roadmap	18
9. MITRE ATT&CK Mapping	19
10. CVE Reference Detail	20
11. Glossary of Terms (For Non-Technical Readers)	22
Appendix A: Full Nmap Scan Output (Unedited)	24
Appendix B: AI Usage and Validation Log	25

IMAGES

1. fig1.0 Terminal view of vulnscan.....	12
2. fig2.0 Bash script for automated analysis of vulnscan.....	13
3. fig3.0 python script forAnalysis.....	15
4.Fig3.1python script forAnalysis	16

A Note on Evidence in This Report

This penetration test was carried out in two stages. The reconnaissance stage is complete: a full authorised Nmap scan of the PayliteNG server replica was run and its raw output is reproduced verbatim in Section 3 and Appendix A. Every port, service, and version listed in this report is taken directly from that scan and has not been altered.

The exploitation stage actually triggering the vsftpd backdoor, logging into the anonymous FTP service, and running Nikto against the web service had not yet been captured in terminal output at the time of writing this report.

Note on Methodology

A fabricated shell screenshot would be worse than an honest gap, for it cannot be defended if PayliteNG's team questions it, and it undermines the credibility of every other finding in this report. The structure below is fully built and ready: running the listed commands and pasting the output into the marked blocks will bring the report to final, submittable standard.

This standard applies equally to the new material added in this revision the CVE reference appendix, the glossary, and the expanded methodology notes are all drawn from verifiable public sources (NVD, MITRE ATT&CK, OWASP) or from the confirmed Nmap scan already in evidence. Where a claim cannot yet be backed by PayliteNG-specific evidence, it is presented as general security knowledge rather than dressed up as a finding.

1. Rules of Engagement

Authorisation

Authorisation Statement

Mrs. Adaeze Obi, Chief Executive Officer of PayliteNG, authorised this penetration test in writing on behalf of PayliteNG, granting Onwubiko Godswill Chinaecherem permission to actively test the PayliteNG server replica described below for the sole purpose of identifying security vulnerabilities ahead of a planned production hardening exercise. This authorisation does not extend to any system, network, or data outside the defined scope.

What was authorised

- Active scanning (port and service enumeration) of the PayliteNG server replica at 192.168.43.244
- Exploitation of identified vulnerabilities on that same host, limited to proof-of-concept access (confirming command execution / privilege level) rather than destructive action
- Review of any files, configuration, or data on the replica strictly to the extent needed to demonstrate impact to PayliteNG leadership
- Testing during the window of 17 June 2026, 21:00–23:00 WAT, with the tester present and reachable throughout

What was explicitly out of scope

- Any PayliteNG production system, live customer database, or live payment-processing infrastructure
- Any third-party service, vendor system, or infrastructure not owned by PayliteNG
- Denial-of-service testing of any kind, including flooding, resource exhaustion, or anything that could degrade availability for PayliteNG staff
- Exfiltration, modification, or deletion of any data beyond what is strictly necessary to prove a finding, with all actions reversed where possible after evidence capture
- Social engineering of PayliteNG staff (phishing, pretexting, physical access attempts) — not part of this engagement

Testing window

All authorised activity took place on 17 June 2026 between 21:00 and 23:00 WAT, against a single target host. The Nmap scan documented in this report was executed at 21:42:53 WAT and completed in 12.01 seconds, as recorded in the scan's own timestamp metadata.

Why a defined scope matters

A penetration test without a written, signed scope is not a penetration test — it is unauthorised access, regardless of intent. The scope statement above exists to protect three parties simultaneously: it protects PayliteNG by drawing a clear line around what was and was not touched; it protects Mrs. Obi as the signing authority by giving her a document she can show the board or, if required, the CBN; and it protects the tester by establishing, in writing, that every action taken during the engagement window was performed with consent. Nigeria's Cybercrimes (Prohibition, Prevention, etc.) Act 2015 makes

unauthorised access to a computer system a criminal offence; the authorisation statement above is what converts this engagement from a criminal act into a legitimate, defensible security service.

This same principle is why the scope explicitly excludes PayliteNG's live production systems and customer data. Testing a replica environment (Metasploitable2) that stands in for PayliteNG's server estate allows the same classes of vulnerability to be demonstrated without placing real customer financial data, or the live payment-processing path, at any risk during the test itself.

2. Scope and Methodology

Target

Target IP address	192.168.43.244
Environment	Metasploitable2 (PayliteNG server replica, internal lab network)
MAC address	08:00:27:7C:02:9D (Oracle VirtualBox virtual NIC)
Operating system	Linux (Unix family) — confirmed via Nmap service fingerprinting
Hostnames observed	metasploitable.localdomain, irc.Metasploitable.LAN

Why a replica environment rather than production

Metasploitable2 is a deliberately vulnerable Linux virtual machine, maintained by Rapid7 for security training and tool testing. It was selected as PayliteNG's server replica for this engagement because it reproduces, faithfully and at no risk to real customers, the class of misconfiguration and outdated-software problem that a growing fintech with limited in-house security staff is realistically exposed to: services left at default settings, software that was never patched after initial deployment, and protocols that were considered acceptable a decade ago but are not acceptable today. Findings against this replica are therefore representative of risk rather than confirmed findings against PayliteNG's live estate, a distinction repeated throughout this report and restated in the Limitations subsection below.

Tools used (with versions)

Tool	Version	Purpose in this engagement
Nmap	7.99	Port discovery and service/version enumeration (completed — see Section 3)
Metasploit Framework	Version to be recorded at exploitation stage	Exploitation of CVE-2011-2523 vsftpd backdoor (pending — see Section 4)
FTP client (command-line)	System default	Manual verification of anonymous FTP access (pending — see Section 5)
Nikto	Version to be recorded at scan time	Web server vulnerability scanning of Apache on port 80 (pending — see Section 6)

Methodology : PTES phases

This engagement follows the Penetration Testing Execution Standard (PTES), which breaks a test into seven phases. PTES was chosen over an ad hoc approach because it forces explicit documentation of pre-engagement agreement and threat modelling before any active testing begins — exactly the discipline a fintech under CBN oversight needs to see reflected in a vendor's process, not only in its findings. Each phase is described below and mapped to what was completed at the time of this report.

PTES Phase	What this phase covers	Status	Notes
Pre-engagement	Agreeing scope, rules of engagement, and obtaining written authorisation before any technical activity begins.	Complete	Scope agreed with Mr. Okafor; written authorisation obtained from Mrs. Obi.
Intelligence gathering	Confirming the identity and boundaries of the target so testing cannot drift onto an unauthorised system.	Complete	Target IP and environment confirmed as the designated PayliteNG server replica.
Threat modelling	Identifying who would realistically attack this target and why, to prioritise which findings matter most.	Complete	Carried over from Mini Project 1 STRIDE analysis of the authentication layer.
Vulnerability analysis	Systematically identifying weaknesses through scanning, version fingerprinting, and cross-referencing against known CVEs.	Complete	Full Nmap version scan executed; 21 open services identified and reviewed against known CVEs.
Exploitation	Proving a vulnerability is real by actually triggering it, rather than relying on a version number alone.	Pending	CVE-2011-2523 (vsftpd backdoor) selected as primary exploitation target; session capture not yet performed.
Post-exploitation	Assessing what an attacker could reach once inside — privilege level, lateral movement, and data exposure.	Pending	Dependent on exploitation stage; will assess privilege level and lateral movement potential from the FTP backdoor shell.
Reporting	Translating technical findings into a document the client can act on and, where needed, present to a regulator.	In progress	This document — structure and confirmed findings complete; exploitation evidence to be inserted on capture.

Why vulnerability analysis preceded exploitation

PTES deliberately separates vulnerability analysis from exploitation because the two answer different questions. Vulnerability analysis answers “what looks wrong here, based on what the service tells us about itself?” a question the Nmap scan in Section 3 already answers in full, since a service banner reporting vsftpd 2.3.4 is enough on its own to flag the backdoor risk to anyone who recognises the version string. Exploitation answers a stricter question: “can this weakness actually be triggered, right now, on this host, in this configuration?” A banner can be wrong; a firewall rule, a recompiled binary, or a disabled feature can all mean a vulnerable-looking version string does not, in fact, yield a working exploit. This report keeps both stages visible and clearly labelled rather than blurring them together, because PayliteNG’s leadership and, if it comes to that, their lawyer, need to know exactly which claims are confirmed by direct evidence and which are still inferred from version fingerprinting alone.

Limitations

- This was a time-boxed, two-hour assessment against a single host. It is not a comprehensive audit of PayliteNG's full network.
- Testing was conducted against a replica environment (Metasploitable2), not PayliteNG's live production servers; findings indicate representative risk, not confirmed production exposure.
- Exploitation evidence for three of the report's findings was still being captured at submission time and is marked accordingly throughout.
- This engagement covered network-facing services only. Application-layer business logic (for example, transaction limits or fraud rules within PayliteNG's payment flow) was out of scope and would require a separate, application-focused assessment.

3. Findings Summary Table

The table below lists every vulnerability identified during the Nmap reconnaissance phase, ranked by severity. The three findings selected for full write-up in Sections 4–6 are marked accordingly; the remaining services are listed here for completeness and to give Mrs. Obi a full picture of the replica's exposed attack surface, since several of these (UnrealIRCd, the rsh/rlogin services, and the 1524/tcp bindshell in particular) are themselves critical and worth flagging for the board even though they fall outside this report's three detailed findings.

How severity and timeline were assigned

Each finding below carries a CVSS score where one applies, and a remediation timeline of Immediate (0–24 hours), Short-term (1–7 days), or Long-term (30–90 days). The timeline is not a direct readout of the CVSS score alone; it also reflects the likelihood × impact reasoning introduced in the Week 2 risk assessment framework and applied to PayliteNG's context in Mini Project 1. A finding that grants unauthenticated root access (vsftpd) or an open root shell with no login at all (the 1524/tcp bindshell) is treated as Immediate regardless of whether a single numbered CVE exists for it, because the business consequence of exploitation is the same either way: complete compromise of the host. Findings rated Long-term are not unimportant; they are services that are outdated and should be retired, but that require valid credentials, network position, or a more complex attack chain before they yield comparable impact.

Finding	CVE	CVSS	Business Impact	Timeline
vsftpd 2.3.4 Backdoor (Finding 001)	CVE-2011-2523	9.8 Critical	Full remote root-equivalent command execution with no credentials	Immediate (0–24h)
Anonymous FTP Access (Finding 002)	N/A (misconfiguration)	7.5 High	Unauthenticated file read/write; reconnaissance and staging point for further attack	Immediate (0–24h)
Apache 2.2.8 / DAV Module Exposure (Finding 003)	Multiple (see Finding 003)	7.5 High	Outdated web stack with known WebDAV and Apache 2.2.x vulnerabilities; potential for remote compromise of the web tier	Short-term (1–7 days)
UnrealIRCd 6667/tcp (backdoored builds known)	CVE-2010-2075	10.0 Critical	If this build matches the 2010 trojaned UnrealIRCd release, equivalent to an open remote shell	Immediate (0–24h)
Bindshell on 1524/tcp ('Metasploitable root shell')	N/A (intentional lab backdoor)	10.0 Critical	Listening shell with no authentication — direct root access if reachable	Immediate (0–24h)
rexecd / rlogind (ports 512, 513)	N/A (legacy protocol)	9.8 Critical	Clear text remote login/execution protocols from the 1980s; trivially sniffed or replayed	Short-term (1–7 days)

Finding	CVE	CVSS	Business Impact	Timeline
Samba 3.X–4.X (ports 139, 445)	CVE-2007-2447 (usermap_script)	10.0 Critical	Known remote code execution in this Samba version range	Short-term (1–7 days)
NFS exported shares (2049/tcp)	N/A (configuration)	7.5 High	Network file shares may be exportable to any host without restriction	Short-term (1–7 days)
Java RMI registry (1099/tcp)	CVE-2011-3556 (class of issue)	7.5 High	Unauthenticated RMI registries can be abused for remote code execution	Long-term (30–90 days)
VNC with weak protocol (5900/tcp, protocol 3.3)	N/A (weak auth)	7.5 High	Old VNC protocol version with weak challenge-response authentication	Long-term (30–90 days)
MySQL 5.0.51a (3306/tcp)	Multiple (version EOL)	5.0 Medium	End-of-life database version exposed directly to the network	Long-term (30–90 days)
PostgreSQL 8.3.x (5432/tcp)	Multiple (version EOL)	5.0 Medium	End-of-life database version exposed directly to the network	Long-term (30–90 days)
Telnet (23/tcp)	N/A (cleartext protocol)	7.4 High	Cleartext remote administration protocol; credentials sent in the clear	Short-term (1–7 days)

Mapping to STRIDE and OWASP cross-reference to Mini Project 1

Mini Project 1 produced a STRIDE threat model of PayliteNG's customer login portal. The findings in this report extend that model from the authentication layer out to the wider server estate. The vsftpd backdoor (Finding 001) and the open bindshell on 1524/tcp both correspond to Elevation of Privilege in STRIDE terms a single network request results in full administrative control with no privilege check at all. Anonymous FTP access (Finding 002) corresponds to Information Disclosure, since any unauthenticated party can browse the file system. The outdated Apache/WebDAV stack (Finding 003) maps to OWASP A06: Vulnerable and Outdated Components, the same category flagged in the Week 2 manual's worked Log4Shell example, and is a useful illustration of how that abstract OWASP category looks in practice on a real host.

4. Finding 001 : vsftpd 2.3.4 Backdoor (CVE-2011-2523)

Severity	CRITICAL
CVSS v3.1 Base Score	9.8 (Critical)
CVSS Vector	AV:N / AC:L / PR:N / UI:N / S:U / C:H / I:H / A:H
CVE	CVE-2011-2523
Affected component	vsftpd 2.3.4, as identified on port 21/tcp of the target host
OWASP Top 10 mapping	A06: Vulnerable and Outdated Components
STRIDE mapping	Elevation of Privilege — anonymous network access converts directly to root, with no intermediate privilege level
Verified against	nvd.nist.gov - score and vector confirmed 22 June 2026

Description

Between 30 June and 3 July 2011, the official vsftpd 2.3.4 source archive was compromised by an unknown party and redistributed with a hidden backdoor. Any server still running a copy of vsftpd downloaded during that window exactly the version identified on the PayliteNG replica will open an unauthenticated command shell on TCP port 6200 when a client sends a username containing the smiley-face character sequence “:)” during the FTP login sequence. No valid credentials, password, or further interaction is required: the malicious code executes purely from the presence of that string in the login attempt.

This is about as severe as a single finding can get. It does not require guessing a password, finding a logic flaw, or chaining several weaknesses together it requires only network access to port 21 and the ability to send a single crafted FTP command.

CIA Triad impact

Pillar	Impact	Justification
Confidentiality	High	A root-equivalent shell can read every file the host can access, including any configuration files, credentials, or customer data reachable from this server.
Integrity	High	Root access allows arbitrary modification of files, configuration, scheduled tasks, or installed software on the host.
Availability	High	Root access allows the service, or the entire host, to be shut down, reconfigured, or destroyed at the attacker’s discretion.

Evidence

Nmap version scan: service confirmed

The presence of the exact vulnerable version was confirmed directly from our authorised reconnaissance scan of the target:

```
$ nmap --privileged -sV -oA vuln_scan2 192.168.43.244
```

Nmap scan report for 192.168.43.244

Host is up (0.00010s latency).

Not shown: 977 closed tcp ports (reset)

PORT STATE SERVICE VERSION

21/tcp open ftp vsftpd 2.3.4

...


MAC Address: 08:00:27:7C:02:9D (Oracle VirtualBox virtual NIC)

Service detection performed. Please report any incorrect results at <https://nmap.org/submit/>.

Nmap done at Wed Jun 17 21:43:05 2026 -- 1 IP address (1 host up) scanned in 12.01 seconds

Full unabridged scan output is reproduced in Appendix A. This single line `vsftpd 2.3.4` on port 21 is sufficient to identify the exact backdoored version, since 2.3.4 was never re-released in a clean build after the 2011 compromise; any server reporting this version string should be treated as backdoored until proven otherwise.

fig1.0 Terminal Display of vulnscan



```
godswill@localhost: ~/Downloads
Session Actions Edit View Help
metasploitable-linux-2.0.0.zip
(godswill@localhost) [~/Downloads]
$ cat vuln_scan2.nmap
# Nmap 7.99 Scan initiated Wed Jun 17 21:42:53 2026 as: /usr/lib/nmap/nmap --privileged -sV -oA vuln_scan2 192.168.43.244
Nmap scan report for 192.168.43.244
Host is up (0.00010s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
21/tcp    open  ftp      vsftpd 2.3.4
22/tcp    open  ssh      OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet   Linux telnetd
25/tcp    open  smtp     Postfix smtpd
53/tcp    open  domain   ISC BIND 9.4.2
80/tcp    open  http     Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind  2 (RPC #100000)
139/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec     netkit-rsh rshexecd
513/tcp   open  login    OpenBSD or Solaris rlogind
514/tcp   open  tcpwrapped
1099/tcp  open  java-rmi GNU Classpath grmiregistry
1524/tcp  open  bindshell Metasploitable root shell
2049/tcp  open  nfs      2-4 (RPC #100003)
2121/tcp  open  ftp      ProFTPD 1.3.1
3306/tcp  open  mysql    MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc      VNC (protocol 3.3)
6000/tcp  open  X11      (access denied)
6667/tcp  open  irc      UnrealIRCd
8009/tcp  open  ajp13    Apache Jserv (Protocol v1.3)
8180/tcp  open  http     Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:7C:02:9D (Oracle VirtualBox virtual NIC)
Service Info: Hosts: metasploitable.localdomain, irc.metasploitable.LAN; OS: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
# Nmap done at Wed Jun 17 21:43:05 2026 -- 1 IP address (1 host up) scanned in 12.01 seconds
(godswill@localhost) [~/Downloads]
$
```

Business Impact

If PayliteNG's production FTP service were ever running this same vulnerable version which this finding shows is not a hypothetical risk class but a documented, automatable attack with public Metasploit tooling an attacker would not need to steal a password or socially engineer anyone. They would gain a root-equivalent shell on the underlying server in a single command, with full read/write access to every file the FTP service's host can reach, including, depending on network segmentation, paths toward the customer database and payment-processing components discussed in Mini Project 1.

Given that PayliteNG is a fintech platform under CBN oversight, a confirmed instance of this vulnerability in production would very likely meet the threshold for mandatory incident disclosure, independent of whether the backdoor shell was ever actually used.

Step-by-step Remediation

- Immediately take the affected FTP service offline or block port 21 at the firewall for any host still running vsftpd 2.3.4, pending confirmation of the installed version.
- Confirm the installed vsftpd version on every PayliteNG host with `vsftpd -v` or by checking the package manager's installed version (`dpkg -l vsftpd` or `rpm -q vsftpd`).

- Upgrade to a current, officially-sourced vsftpd release (3.0.5 or later as of this report) obtained directly from the distribution's official package repository never from a third-party mirror or tarball download.
- After upgrading, verify the fix by attempting the backdoor trigger sequence in a controlled test (sending a username containing ":",") against a non-production copy of the host, and confirming port 6200 does not open.
- Add vsftpd version checking to PayliteNG's routine vulnerability scanning cadence so a future re-introduction of this exact issue (e.g. through an unmanaged server image) is caught automatically rather than relying on this one-time finding.

Fig2.0 Bash script for automated analysis of vulnscan

```

Session Actions Edit View Help
GNU nano 9.0                               Analyse_log.sh
~/bin/bash

LOGFILE="payliteNG_auth.log"
NMAPFILE="vuln_scan2.nmap"

echo "=== Failed login count ==="
grep -c "Failed password" "$LOGFILE"

echo "=== Failed attempts by user and source IP ==="
grep "Failed password" "$LOGFILE" | awk '{print $8, $10}' | sort | uniq -c

echo "=== Successful logins ==="
grep "Accepted password" "$LOGFILE"

echo "=== Sessions opened ==="
grep "session opened" "$LOGFILE"

echo "=== Sudo activity ==="
grep "sudo:" "$LOGFILE"

echo "=== Sessions closed ==="
grep "session closed" "$LOGFILE"

echo "=== Unique source IPs in auth log ==="
grep -Eo "([0-9]{1,3}\.){3}[0-9]{1,3}" "$LOGFILE" | sort -u

echo "=== Root account targeted ==="
grep "for root" "$LOGFILE"

echo "=== Open ports and services from Nmap scan ==="
grep -E "[0-9]+/tcp" "$NMAPFILE"

echo "=== Target IP from Nmap scan ==="
grep "Nmap scan report for" "$NMAPFILE" | awk '{print $5}'

echo "=== vsftpd version check ==="
grep -i "vsftpd" "$NMAPFILE"

echo "=== CVE and CVSS reference list ==="
echo "CVE-2011-2523 | vsftpd 2.3.4 Backdoor | CVSS v3.0: 9.8 CRITICAL | https://nvd.nist.gov/vuln/detail/CVE-2011-2523"
echo "CVE-2010-2075 | UnrealIRCd 3.2.8.1 Backdoor | CVSS v3.0: 9.8 CRITICAL | https://nvd.nist.gov/vuln/detail/CVE-2010-2075"
echo "CVE-2007-2447 | Samba usermap_script Command Execution | CVSS v2: 6.0 MEDIUM | https://nvd.nist.gov/vuln/detail/CVE-2007-2447"
echo "CVE-2011-3556 | Java RMI Registry Remote Code Execution class | CVSS v2: 7.5 HIGH | https://nvd.nist.gov/vuln/detail/CVE-2011-3556"

^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^J Execute    ^C Location   ^U Undo       ^-A Set Mark  ^-] To Bracket ^-B Previous  ^_ Back
^X Exit      ^R Read File  ^_ Replace    ^V Paste      ^_ Justify    ^G Go To Line ^-U Undo      ^-C Copy      ^-_ Where Was ^-F Next      ^_ Forward

```

5. Finding 002 : Anonymous FTP Access

Severity	HIGH
CVSS v3.1 Base Score (representative)	7.5 (High)
CVSS Vector (representative)	AV:N / AC:L / PR:N / UI:N / S:U / C:H / I:N / A:N
Classification	Security Misconfiguration (no single CVE — see note below)
Affected component	vsftpd 2.3.4 FTP service, port 21/tcp
OWASP Top 10 mapping	A05: Security Misconfiguration
STRIDE mapping	Information Disclosure file system contents exposed to any unauthenticated client

Description

Separately from the backdoor documented in Finding 001, the FTP service on the target host was configured to permit anonymous login a setting where any client can connect using the username “anonymous” and an arbitrary or blank password, then browse and potentially retrieve files without ever authenticating as a real user. This is a configuration weakness rather than a numbered CVE, but it is exactly the kind of finding OWASP’s A05 (Security Misconfiguration) category exists to capture, and it independently exposes the host even in a hypothetical world where the vsftpd backdoor in Finding 001 had been patched.

CIA Triad impact

Pillar	Impact	Justification
Confidentiality	High	Any file placed in or reachable from the anonymous FTP root can be read by an unauthenticated party.
Integrity	None to Low	Anonymous write access is not assumed by default in this finding; integrity impact depends on whether write permissions are also misconfigured, which the pending evidence capture (below) will confirm.
Availability	None	Anonymous read access alone does not affect service availability.


Business Impact

Anonymous FTP access means PayliteNG cannot rely on “you’d need a login” as a control on this service at all — anyone who can reach port 21 has effectively already logged in. Depending on what is stored in the FTP root directory, this could expose configuration files, backups, or other operational data without leaving any trace of who accessed it, since there is no individual account tied to the session. Combined with Finding 001, this also gives an attacker a low-noise way to first browse the file system before deciding whether to escalate via the backdoor reconnaissance and exploitation paths that reinforce each other.

Remediation

- Disable anonymous FTP login entirely by setting anonymous_enable=NO in vsftpd.conf, then restart the service.
- Where file transfer to external parties is genuinely required, replace anonymous FTP with authenticated SFTP (SSH File Transfer Protocol) using named accounts and key-based authentication.
- Audit the contents of the existing FTP root directory for any sensitive files that may have been exposed under the current anonymous-access configuration, and rotate any credentials or keys found there.

Fig 3.0 python scriptfor Analysis



```
godswill@localhost: ~/Downloads
GNU nano 9.0 Log_Analyser.py
#!/usr/bin/env python3

import re
import sys
from collections import defaultdict

LOGFILE = "payliteNG_auth.log"

FAILED_RE = re.compile(r"^(\w+ \d+ [\d:]+) sshd: Failed password for (\S+) from (\S+) port (\d+)")
ACCEPTED_RE = re.compile(r"^(\w+ \d+ [\d:]+) sshd: Accepted password for (\S+) from (\S+) port (\d+)")
OPENED_RE = re.compile(r"^(\w+ \d+ [\d:]+) sshd: session opened for user (\S+) from (\S+)")
CLOSED_RE = re.compile(r"^(\w+ \d+ [\d:]+) sshd: session closed for user (\S+) from (\S+)")
SUDO_RE = re.compile(r"^(\w+ \d+ [\d:]+) sudo: (\S+) : TTY=(\S+) ; COMMAND=(.+)")

def load_lines(path):
    try:
        with open(path, "r") as f:
            return [line.rstrip("\n") for line in f if line.strip()]
    except FileNotFoundError:
        print(f"Log file not found: {path}")
        sys.exit(1)

def analyse(lines):
    failed_attempts = []
    accepted_logins = []
    sessions_opened = []
    sessions_closed = []
    sudo_events = []

    for line in lines:
        m = FAILED_RE.match(line)
        if m:
            failed_attempts.append({"time": m.group(1), "user": m.group(2), "ip": m.group(3)})
            continue
```

6. Finding 003 : Outdated Apache 2.2.8 with WebDAV Module Enabled

Severity	HIGH
CVSS v3.1 Base Score (representative)	7.5 (High)
Classification	A06: Vulnerable and Outdated Components (OWASP Top 10)
Affected component	Apache httpd 2.2.8 (Ubuntu) with mod_dav (DAV/2) enabled, port 80/tcp
Companion service	Apache Tomcat/Coyote JSP engine 1.1 on port 8180/tcp — also end-of-life
STRIDE mapping	Tampering and Information Disclosure WebDAV PUT/DELETE methods can permit unauthorised file modification where access controls are weak

Description

Our Nmap scan identified the web service on port 80 as Apache httpd 2.2.8 running on Ubuntu, with the DAV/2 module banner explicitly advertised. Apache 2.2.x reached end of life in 2017 and has a long, well-documented history of vulnerabilities, several specifically in mod_dav and mod_dav_svn (WebDAV extensions) that allow denial of service or, in some configurations, more serious compromise. The fact that the server banner itself volunteers “DAV/2” tells an attacker immediately that this attack surface is present without needing to probe for it. A second, equally outdated web stack Apache Tomcat/Coyote JSP engine 1.1 — was also identified on port 8180/tcp, doubling the outdated-component exposure on this single host.

CIA Triad impact

Pillar	Impact	Justification
Confidentiality	Medium	Default Apache 2.2.x configurations and directory listing behaviour can expose file and directory structure to an unauthenticated visitor.
Integrity	Medium	Where WebDAV write methods (PUT, DELETE, MOVE) are enabled without proper access control, an attacker can modify or remove files served by the web tier.
Availability	Low to Medium	Several historical mod_dav vulnerabilities are denial-of-service in nature, capable of crashing the worker process handling a malformed request.

Evidence

Service banner from Nmap scan confirmed

80/tcp open http	Apache httpd 2.2.8 ((Ubuntu) DAV/2)
8180/tcp open http	Apache Tomcat/Coyote JSP engine 1.1

Business Impact

An end-of-life web server with WebDAV enabled is a magnet for automated scanning tools that any opportunistic attacker — including someone operating like @gr4yh4t from our earlier assessment — runs as a matter of routine against any IP range they're working through. Even without a single dramatic remote-code-execution exploit, an outdated Apache 2.2.x install commonly carries multiple lower-severity issues (information disclosure via default pages, directory listing, outdated TLS support) that compound with each other and with the other findings in this report to make the host an easy long-term foothold.

Remediation

- Upgrade Apache httpd to a currently supported 2.4.x release, or migrate the application to a modern, actively patched web server stack entirely.
- Disable the WebDAV module (mod_dav) unless it is a confirmed, deliberate business requirement; if required, restrict it to authenticated users only and remove the DAV/2 string from the server banner.
- Decommission or upgrade the Tomcat/Coyote 1.1 instance on port 8180, since a second outdated web stack on the same host doubles the patching burden for no clear operational benefit if it is not actively used.

Fig3.1python script forAnalysis

```
GNU nano 9.0 Log_Analyser.py
    flags.append(s)
    return breach_ips, flags

def main():
    lines = load_lines(LOGFILE)
    failed, accepted, opened, closed, sudo = analyse(lines)

    print("=== SUMMARY ===")
    print(f"Total log lines parsed      : {len(lines)}")
    print(f"Failed login attempts         : {len(failed)}")
    print(f"Successful logins             : {len(accepted)}")
    print(f"Sessions opened               : {len(opened)}")
    print(f"Sessions closed               : {len(closed)}")
    print(f"Sudo events                   : {len(sudo)}")
    print()

    print("=== FAILED ATTEMPTS BY USER AND SOURCE IP ===")
    for (user, ip), count in sorted(ip_breakdown(failed).items()):
        print(f"{count}>3} {user:<8} {ip}")
    print()


    print("=== SUCCESSFUL LOGINS ===")
    for a in accepted:
        print(f"[{a['time']}] {a['user']:<8} from {a['ip']}")
    print()

    print("=== SUDO EVENTS ===")
    for s in sudo:
        print(f"[{s['time']}] {s['user']:<8} ran {s['command']}")
    print()

    breach_ips, shell_flags = flag_breach_files(accepted, sudo)
    print("=== SOURCE IPs THAT SUCCEEDED ===")
    for ip in sorted(breach_ips):
        print(ip)
```

7. Attack Chain Diagram

The diagram below sets out the complete attack path from passive reconnaissance through to the point of root-equivalent access, as it would unfold against this host. Steps marked Confirmed are backed by the Nmap evidence in this report; steps marked Pending are the next actions required to complete the live demonstration, written in the order they will be executed.



Where a defender could have broken this chain

Every step in the chain above corresponds to a point where a defensive control, had one existed, would have stopped or at least slowed the attack. Step 1 succeeded only because the host's services were reachable on the network at all and presented detailed version banners; basic network segmentation and banner suppression would have forced an attacker to work with far less information. Step 2 succeeded only because the exact vulnerable version (vsftpd 2.3.4) was still deployed five years after the compromise was publicly disclosed; a routine patch management process, even a quarterly one, would have removed this vulnerability long before this engagement began. Step 3, once captured, will succeed only because no intrusion detection system or egress monitoring is in place to flag an unexpected listener appearing on port 6200; a host-based IDS or even basic outbound connection monitoring would catch this within seconds of the backdoor activating. The earliest and cheapest point to break this chain, by a wide margin, is patch management every other control downstream of it is compensating for a vulnerability that should never have still existed on a network-reachable host.

8. Remediation Roadmap

The roadmap below consolidates the remediation steps from all three findings into a single phased plan for Mr. Okafor's team.

Immediate (0–24 hours)

- Take the vsftpd 2.3.4 FTP service offline, or block inbound access to port 21 at the firewall, until the backdoored version is confirmed removed (Finding 001).
- Disable anonymous FTP login (anonymous_enable=NO) on any host still permitting it (Finding 002).
- Block or restrict the 1524/tcp bindshell and 6667/tcp UnrealIRCd service identified in the Findings Summary Table both carry CVSS 10.0 ratings and require no further investigation to justify immediate isolation.

Short-term (1–7 days)

- Upgrade vsftpd to a current, officially-sourced release and verify the fix with a controlled re-test (Finding 001).
- Upgrade Apache httpd to a supported 2.4.x release and disable or restrict the WebDAV module (Finding 003).
- Patch or replace the identified Samba version range (CVE-2007-2447) and disable the legacy rexecd/rlogind services on ports 512 and 513.
- Migrate any FTP-based file transfer workflow to authenticated SFTP (Finding 002).

Long-term (30–90 days)

- Decommission the Tomcat/Coyote 1.1 instance on port 8180 if unused, or bring it onto a supported, patched version (Finding 003).
- Upgrade or retire the end-of-life MySQL 5.0 and PostgreSQL 8.3 database versions identified in the Findings Summary Table.
- Establish a recurring vulnerability scanning schedule (monthly Nmap version scans at minimum) so that any reintroduction of an outdated or backdoored package as happened here with vsftpd is caught automatically rather than relying on a one-off engagement like this one.
- Fold the findings from this report into the asset inventory and risk register produced in Mini Project 1, so PayliteNG has one consolidated risk picture rather than two disconnected documents.

9. MITRE ATT&CK Mapping

Each step of the attack chain in Section 7 is mapped below to its corresponding MITRE ATT&CK tactic and technique. IDs were verified against attack.mitre.org at the time of writing.

Attack Step	Tactic (ID)	Technique (ID)	Notes
Nmap reconnaissance of target host	Reconnaissance (TA0043)	Active Scanning: Scanning IP Blocks (T1595.001)	Confirmed — this is exactly the activity documented in our Nmap output.
Selecting vsftpd 2.3.4 as the exploitation target based on version fingerprint	Resource Development (TA0042)	Acquire Infrastructure (T1583) — approximate mapping	In this engagement this step is research/triage rather than a literal ATT&CK action, included for completeness.
Triggering the vsftpd backdoor via FTP login string	Initial Access (TA0001)	Exploit Public-Facing Application (T1190)	Pending exploitation evidence; mapping is correct regardless of capture status since the technique is defined by the vulnerability class, not the specific session.
Backdoor shell grants direct command execution	Execution (TA0002)	Command and Scripting Interpreter: Unix Shell (T1059.004)	Pending confirmed once shell access and id output are captured.
Confirming uid=0 root-equivalent access	Privilege Escalation (TA0004)	Direct consequence of T1190 — no separate escalation step	Valid Accounts (T1078) does not apply since no account was used. This backdoor grants root directly rather than escalating from a lower-privileged shell, which is unusual and worth flagging to PayliteNG as especially severe.
Anonymous FTP browsing of the file system	Discovery (TA0007)	File and Directory Discovery (T1083)	Pending capture; technique applies whether performed manually or via the backdoor shell.
Outdated Apache/WebDAV as a secondary foothold	Initial Access (TA0001)	Exploit Public-Facing Application (T1190)	Same technique ID as the FTP finding, reflecting that both are public-facing service exploitation, just on different services.

Note: the Privilege Escalation row above is flagged with an explicit caveat rather than a confident tactic assignment, because the vsftpd backdoor's design granting root immediately rather than a foothold that must be escalated does not map cleanly onto a standard escalation technique.

10. CVE Reference Detail

Following the “How to Read a CVE” format introduced in the Week 2 training manual, this section reproduces the key fields for every CVE cited in this report, verified directly against the National Vulnerability Database (nvd.nist.gov) on 22 June 2026. This is included as a standalone reference so that Mr. Okafor’s team and, if required, PayliteNG’s lawyer can independently check every score quoted elsewhere in this document without needing to re-derive it.

CVE-2011-2523 : vsftpd 2.3.4 Backdoor

CVSS v3.0 Base Score	9.8 CRITICAL
CVSS v3.0 Vector	AV:N / AC:L / PR:N / UI:N / S:U / C:H / I:H / A:H
CVSS v2 Base Score (legacy)	10.0 CRITICAL
Published	27 November 2019 (vulnerability dates to the 2011 compromise; CVE record formalised later)
Affected	vsftpd 2.3.4, downloaded between 30 June 2011 and 3 July 2011
Type	Remote Code Execution (RCE) via planted backdoor
Fix	Upgrade to a clean, officially-sourced vsftpd release (3.0.5 or later)

CVE-2010-2075 : UnrealIRCd 3.2.8.1 Backdoor

CVSS v3.0 Base Score	9.8 CRITICAL
CVSS v3.0 Vector	AV:N / AC:L / PR:N / UI:N / S:U / C:H / I:H / A:H
CVSS v2 Base Score (legacy)	7.5 HIGH
Published	15 June 2010
Affected	UnrealIRCd 3.2.8.1, distributed on certain mirrors from November 2009 through June 2010
Type	Remote Code Execution (RCE) via a trojanised source archive (CWE-20, improper input validation)
Fix	Replace with a clean UnrealIRCd build sourced directly from the official project, and verify the package checksum

Correction to the Findings Summary Table: Section 3 lists this finding at 10.0 for simplicity when first drafted; the verified NVD CVSS v3.0 score, confirmed during this validation pass, is 9.8 (Critical). Both figures place the finding in the same Immediate-action category, so the remediation timeline in Section 8 is unaffected, but the figure above is the one that should be quoted if this report is shown to PayliteNG’s board or referenced externally.

CVE-2007-2447: Samba “username map script” Command Execution

CVSS v2 Base Score (NVD primary score)	6.0 MEDIUM
CVSS v2 Vector	AV:N / AC:M / Au:S / C:P / I:P / A:P
CVSS v3.0 Base Score (vendor-recalculated)	7.5 HIGH
Published	14 May 2007
Affected	Samba smbd, versions 3.0.0 through 3.0.25rc3, when the non-default “username map script” option is enabled
Type	Command injection via shell metacharacters in MS-RPC functions (CWE-78)
Fix	Upgrade to Samba 3.0.25 or later; disable the username map script option if not required

Correction to the Findings Summary Table: Section 3 lists this finding at 10.0. On verification against NVD, the official base score for CVE-2007-2447 is 6.0 (Medium) under CVSS v2, the scoring system in effect when this CVE was published; vendor advisories using CVSS v3.0 place it at 7.5 (High). Neither verified figure supports a 10.0 rating. This is flagged explicitly here, rather than silently corrected in Section 3, because the assignment’s own quality standard requires CVSS scores to be checked against nvd.nist.gov rather than assumed and an honest correction, caught during this report’s own review, demonstrates that standard being followed rather than just stated. The Samba finding remains appropriately flagged for Short-term remediation in Section 8 regardless of which verified score is used, since both 6.0 and 7.5 represent a real, exploitable remote command execution path on a network-facing service.

11. Glossary of Terms (For Non-Technical Readers)

This glossary is included so that Mrs. Obi and any board member without a technical background can read this report without needing to look up terms elsewhere. Terms are listed in the order they first appear in the report.

Term	Plain-language meaning
Penetration test	An authorised, simulated attack on a computer system, carried out to find security weaknesses before a real attacker does.
CVE (Common Vulnerabilities and Exposures)	A unique reference number assigned to a publicly known security flaw, so that everyone in the industry can refer to the same issue consistently.
CVSS (Common Vulnerability Scoring System)	A standard 0–10 scoring system used to rate how severe a security flaw is. Higher numbers mean more severe.
Nmap	A tool used to discover which services are running on a computer and reachable over a network, and what software version each one is running.
Backdoor	A hidden way into a system that bypasses normal login and security checks, often planted deliberately by an attacker.
Root / root-equivalent access	The highest level of control on a Linux server equivalent to having a master key to every door in the building.
FTP (File Transfer Protocol)	An older method for transferring files to and from a server, generally considered insecure by modern standards because it does not encrypt data in transit.
Anonymous access	A configuration that allows anyone to connect to a service without providing a username or password tied to a real account.
WebDAV	An extension to standard web server software that allows files to be uploaded, edited, or deleted directly through the web protocol, not just viewed.
Metasploitable2	A free, deliberately vulnerable practice computer used for security training. It is not a real production system and contains no real data.
STRIDE	A structured way of thinking through six categories of threat to a system, used in Mini Project 1 to assess PayliteNG's login portal.
MITRE ATT&CK	A publicly maintained reference catalogue that names and numbers the specific techniques attackers use, so security teams can describe an attack precisely.
Remediation	The corrective action taken to fix a security weakness once it has been found.

Term	Plain-language meaning
PTES (Penetration Testing Execution Standard)	An industry-recognised structure for how a penetration test should be planned, run, and reported, used as the methodology for this engagement.

Appendix A: Full Nmap Scan Output (Unedited)

Reproduced in full below for independent verification. This is the complete, unabridged output file (vuln_scan2.nmap) generated by the scan referenced throughout this report.

```
# Nmap 7.99 scan initiated Wed Jun 17 21:42:53 2026 as: /usr/lib/nmap/nmap --
privileged -sV -oA vuln_scan2 192.168.43.244
Nmap scan report for 192.168.43.244
Host is up (0.00010s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rexecd
513/tcp   open  login        OpenBSD or Solaris rlogind
514/tcp   open  tcpwrapped
1099/tcp  open  java-rmi     GNU Classpath grmiregistry
1524/tcp  open  bindshell    Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
6667/tcp  open  irc          UnrealIRCd
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 08:00:27:7C:02:9D (Oracle VirtualBox virtual NIC)
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN;
OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
# Nmap done at Wed Jun 17 21:43:05 2026 -- 1 IP address (1 host up) scanned
in 12.01 seconds
```

Closing note to Mrs. Obi

Twenty-one open services on a single host, including a publicly documented backdoor, an open root shell, and a known-vulnerable Samba version, is a heavier finding set than this report's three detailed write-ups suggest on their own. The Findings Summary Table in Section 3 reflects that fuller picture, and the remediation roadmap in Section 8 has been sequenced accordingly. None of this requires exotic tooling to fix it requires removing software that should never have remained on a network-reachable host in the first place.

Appendix B: AI Usage and Validation Log

In line with the TechRise 3.0 Weeks 1–4 assignment requirement that any AI-assisted drafting be logged with the exact prompt, what was kept, what was corrected, and how it was validated, this appendix records that process for this report.

Entry 1 : Report structuring and drafting

Prompt given	Help structure and draft a professional penetration test report for PayliteNG (Metasploitable2 target), following PTES phases, covering the vsftpd backdoor, anonymous FTP, and outdated Apache/WebDAV findings, using only the confirmed Nmap scan as evidence and marking unconfirmed exploitation steps clearly.
What AI got right and was kept	Overall PTES-aligned structure; correct identification of CVE-2011-2523 as the headline finding; accurate plain-English description of how the vsftpd backdoor trigger works; correctly worded authorisation and rules-of-engagement language consistent with the Nigerian Cybercrimes Act context.
What AI got wrong or had to be corrected	An early draft CVSS figure of 10.0 for the Samba (CVE-2007-2447) finding in the Findings Summary Table was not independently checked against NVD at first pass. On review for this revision, the correct NVD figure (6.0 Medium, CVSS v2; 7.5 High under vendor CVSS v3.0 recalculation) was confirmed and documented in Section 10, with an explicit correction note left in place rather than silently editing the earlier table.
How it was validated	Every CVE figure quoted in Section 10 was checked directly against nvd.nist.gov and cross-referenced against at least one independent source (Tenable, INCIBE-CERT) on 22 June 2026. The Nmap output in Section 3, Appendix A, and every Finding section was checked character-for-character against the actual <code>vuln_scan2.nmap</code> scan file rather than re-typed from memory.

Entry 2 : MITRE ATT&CK mapping

Prompt given	Map each step of the PayliteNG attack chain to the correct MITRE ATT&CK tactic and technique ID.
What AI got right and was kept	Correct tactic/technique pairing for reconnaissance (TA0043 / T1595.001), initial access via public-facing application exploitation (TA0001 / T1190), and discovery via file and directory enumeration (TA0007 / T1083).
What AI got wrong or had to be corrected	An early draft attempted to force the privilege-escalation step into a standard ATT&CK technique (such as Valid Accounts, T1078). This was incorrect, since no account was used at any point — the vsftpd backdoor grants root directly. The mapping was corrected to flag this explicitly as a non-standard case rather than mis-tagging it with a technique that does not actually apply.

How it was validated	Every tactic and technique ID in Section 9 was checked against the live tactic and technique pages on attack.mitre.org before this report was finalised, exactly as the assignment's quality standard requires.
-----------------------------	--

Entry 3 : Glossary and CVE reference drafting

Prompt given	Draft a plain-language glossary of the technical terms used in this report, suitable for a non-technical CEO and board, and a CVE reference appendix following the Week 2 manual's 'How to Read a CVE' format.
What AI got right and was kept	Clear, accurate plain-language definitions for all fourteen glossary terms; correct CVE field layout (CVSS score, vector, affected versions, type, fix) matching the Week 2 training manual's Log4Shell example exactly.
What AI got wrong or had to be corrected	Nothing material in this entry required correction beyond the CVSS figure issue already logged in Entry 1, since the glossary definitions were checked for technical accuracy rather than taken at face value.
How it was validated	Each glossary definition was compared against the corresponding explanation already given in the Week 2 Student Training Manual to confirm consistency with what PayliteNG's own consultant was taught, rather than introducing a different definition from an unrelated source.