

Myoperi_following_COVID19vaccination_2022_2025

Author: Godwin Anguzu

Study Overview

Myopericarditis -- encompassing myocarditis (inflammation of the heart muscle) and pericarditis (inflammation of the pericardial sac) -- emerged as a recognized adverse event of special interest (AESI) following mRNA-based COVID-19 vaccination, particularly in adolescent males and young adults. Although the absolute risk is low, understanding its incidence in real-world populations is critical for informing vaccination guidelines, safety monitoring, and clinical decision-making.

Objectives

This analysis uses longitudinal claims data from 2022 to 2025 to:

1. **Estimate crude incidence rates** of myopericarditis (AESI code: myo1) in a cohort of vaccinated individuals aged 12-24, expressed as events per 100,000 person-days at risk during the risk window following each vaccine dose.
2. **Stratify by vaccine brand and age group** to identify subgroups that may carry disproportionate burden, consistent with prior signal detection findings for mRNA-1273 (Moderna) and BNT162b2 (Pfizer-BioNTech).

Analytic Approach

The pipeline proceeds in two stages:

- Stage 1 -- Data Wrangling (Parts 1-5):** Starting from raw administrative files (event, patient, enrollment, and ZIP mapping tables), we construct a clean exposure dataset that defines each person-dose observation, applies enrollment and risk-window filters, resolves duplicate and close-dose records, and derives key covariates (age at exposure, season, vaccine brand).
- Stage 2 -- Summary and Visualisation (Parts 6a-6b):** The analytic dataset is aggregated across eight stratification levels (overall, by season, by brand, by age group, and all pairwise and three-way combinations). For each stratum, we compute the number of vaccinations, unique persons, observed outcomes, person-days at risk, crude incidence rate, and exact Poisson 95% confidence intervals via the chi-squared method.

Downstream Context

This descriptive analysis is the **first step** in a broader evaluation. The seasonal incidence profiles established here will inform:

- Confounder selection and effect modification testing in subsequent regression models.
- The design of self-controlled case series (SCCS) or cohort analyses comparing vaccinated versus unvaccinated risk windows.
- Signal prioritisation for regulatory safety reporting.

By quantifying how myopericarditis rates vary across seasons, brands, and age groups independently, we lay the groundwork for attributing excess risk specifically to vaccination rather than to co-occurring seasonal or demographic factors.

Data: Synthetic administrative claims generated to mirror the structure of real-world insurance data. All person identifiers are simulated. Study period: 2022-2025.

Data Wrangling -- Steps 1-5: Build exposure_tmp1

- Step 1 -- Construct the base vaccination exposure dataset (subset, merge patient, ZIP enrich, enrollment filter)
- Step 2 -- Drop admin concept ID (724802) records that co-occur with other concept IDs on the same person-date
- Step 3 -- Resolve close-dose pairs (gap <= 3 days): drop same-brand duplicates; drop different-brand pairs
- Step 4 -- Derive age_at_exposure , season , in_study_window , vac_brand
- Step 5 -- Create after_auth flag (1 if vaccination date falls within the brand's authorization window and patient meets the minimum age threshold, else 0)

```
import pandas as pd
from pathlib import Path

DATA_DIR = Path('dataimages')
```

Load raw datasets

```
DATE_FMT = '%d%b%Y'

def read_csv_with_dates(fname, date_cols):
    df = pd.read_csv(DATA_DIR / fname, dtype=str)
    for col in date_cols:
        df[col] = pd.to_datetime(df[col], format=DATE_FMT, errors='coerce')
    return df

event_raw = read_csv_with_dates('event.csv', ['date', 'end_date', 'visit_det_date', 'visit_det_end_date', 'process_date'])
patient = read_csv_with_dates('patient.csv', ['birth_date', 'death_date'])
zip3_map = pd.read_csv(DATA_DIR / 'zip3_mapping.csv', dtype=str)
zip5_map = pd.read_csv(DATA_DIR / 'zip5_mapping.csv', dtype=str)
enrollment = read_csv_with_dates('enrollment.csv', ['enrl_start_date', 'enrl_end_date'])

print('Rows loaded:')
for name, df in [('event_raw', event_raw), ('patient', patient),
                 ('zip3_map', zip3_map), ('zip5_map', zip5_map), ('enrollment', enrollment)]:
    print(f' {name:<12} {len(df):>5}')
```

Rows loaded:

event_raw	1000
patient	1000
zip3_map	1000
zip5_map	1000
enrollment	1000

Step 1 -- Subset event.csv to vaccination events within the study window

```
VAX_CODES = ['cvm24', 'cvp24', 'cvn24', 'cvm23', 'cvp23', 'cvn23',
             'cvm22', 'cvp22', 'cvn22', 'cvj22', 'cvu']
STUDY_START = pd.Timestamp('2022-01-01')
STUDY_END = pd.Timestamp('2026-01-01')

event_vax = event_raw[event_raw['event'].isin(VAX_CODES)].copy()
event_vax = event_vax[
    (event_vax['date'] >= STUDY_START) &
    (event_vax['date'] <= STUDY_END)
].copy()

print(f'Vaccination events after filter: {len(event_vax):,}')
print(event_vax['event'].value_counts())
```

```
Vaccination events after filter: 939
event
cvu      258
cvm24    132
cvm24    109
cvm23    105
cvp24     93
cvp23     81
cvm23     81
cvp22     23
cvm22     22
cvm22     18
cvj22     17
Name: count, dtype: int64
```

1.2 -- Merge with patient.csv on `person_id`

```
merged = event_vax.merge(patient, on='person_id', how='left')
print(f'Rows after patient merge: {len(merged):,}')

Rows after patient merge: 939
```

1.3 -- Enrich with ZIP geographic covariates

```
merged['zip']      = merged['zip'].str.strip().str.zfill(5)
merged['zip3']     = merged['zip'].str[:3]
zip5_map['zip5']   = zip5_map['zip5'].str.strip().str.zfill(5)
zip3_map['zip3']   = zip3_map['zip3'].str.strip().str.zfill(3)

merged = merged.merge(zip5_map, left_on='zip', right_on='zip5', how='left')
merged = merged.merge(zip3_map, on='zip3', how='left')
merged.drop(columns=['zip5'], inplace=True)

print(f'Rows after ZIP merges: {len(merged):,}')
print(f'ZIP5 unmatched: {merged["CBSA"].isna().sum():,} | ZIP3 unmatched: {merged["state_abbv"].isna().sum():,}')

Rows after ZIP merges: 939
ZIP5 unmatched: 0 | ZIP3 unmatched: 0
```

1.4 -- Merge with enrollment.csv and apply date-in-enrollment filter

```
merged = merged.merge(enrollment, on='person_id', how='left')
in_enrollment = (
    (merged['date'] >= merged['enrl_start_date']) &
    (merged['date'] <= merged['enrl_end_date'])
)
exposure_tmp1 = merged[in_enrollment].copy()

print(f'Rows before enrollment filter : {len(merged):,}')
print(f'Rows after enrollment filter : {len(exposure_tmp1):,} (exposure_tmp1)')

Rows before enrollment filter : 939
Rows after enrollment filter : 939 (exposure_tmp1)
```

Step 2 -- Flag co-occurring admin concept ID (724802)

```
ADMIN_CODE = '724802'
df = exposure_tmp1.copy()

n_concepts_per_person_day = (
    df.groupby(['person_id', 'date'])['concept_id'].transform('nunique')
```

```
)
df['admin_cooccur_flag'] = (
    (df['concept_id'] == ADMIN_CODE) & (n_concepts_per_person_day > 1)
)

n_admin    = (df['concept_id'] == ADMIN_CODE).sum()
n_flagged  = df['admin_cooccur_flag'].sum()
print(f'concept_id {ADMIN_CODE} total: {n_admin} | flagged (co-occur): {n_flagged} | kept (exclusive): {n_admin - n_flagged}')
```

concept_id 724802 total: 0 | flagged (co-occur): 0 | kept (exclusive): 0

```
flagged = df[df['admin_cooccur_flag']][['person_id','date','concept_id','event','visit_det_all_id']].reset_index(drop=True)
if len(flagged) > 0:
    display(flagged)
else:
    print(f'No co-occurring concept_id {ADMIN_CODE} records found. (Expected for synthetic data.)')
```

No co-occurring concept_id 724802 records found. (Expected for synthetic data.)

```
exposure_tmp1 = df[~df['admin_cooccur_flag']].drop(columns=['admin_cooccur_flag']).copy()
print(f'Rows removed (flagged): {n_flagged:}, | Rows retained: {len(exposure_tmp1):},')
```

Rows removed (flagged): 0 | Rows retained: 939

Step 3 -- Resolve close-dose pairs (gap <= 3 days)

Each patient's doses are sorted by date and compared to the immediately preceding dose:

Scenario	Action
Same brand, gap <= 3 days	Drop the later record (same_brand_dup = True)
Different brand, gap <= 3 days	Label both records brand_label = 'multiple' , then drop them

A brand column is derived from the event code prefix (cvp , cvm , cvn , cvj , cvu).

brand_label1 is assigned before dropping so the reason for removal is auditable.

```
# -- extract brand prefix -----
# event codes: cvm23 -> 'cvm', cvp24 -> 'cvp', cvu -> 'cvu'
def extract_brand(event_code):
    return 'cvu' if event_code == 'cvu' else event_code[:3]

df = exposure_tmp1.copy()
df['brand'] = df['event'].apply(extract_brand)

# Sort per patient by date so shift() comparisons are chronological
df = df.sort_values(['person_id', 'date']).reset_index(drop=True)

# -- compare each dose to the previous dose of the same patient -----
df['_prev_date'] = df.groupby('person_id')['date'].shift(1)
df['_prev_brand'] = df.groupby('person_id')['brand'].shift(1)
df['_gap_days'] = (df['date'] - df['_prev_date']).dt.days

within_3 = df['_gap_days'].notna() & (df['_gap_days'] <= 3)

# -- Rule 1: same brand, <= 3 days -> flag the later dose as a duplicate -----
df['same_brand_dup'] = within_3 & (df['brand'] == df['_prev_brand'])

# -- Rule 2: different brand, <= 3 days -> flag CURRENT and PREVIOUS record -----
# Flag current record (it follows a different-brand dose within 3 days)
is_multi_curr = within_3 & (df['brand'] != df['_prev_brand'])

# Propagate the flag back to the previous record using shift(-1)
df['_next_brand'] = df.groupby('person_id')['brand'].shift(-1)
df['_next_gap'] = df.groupby('person_id')['_gap_days'].shift(-1)
```

```
is_multi_prev = (  
    df['_next_gap'].notna() &  
    (df['_next_gap'] <= 3) &  
    (df['brand'] != df['_next_brand'])  
)  
  
df['multiple_brand'] = is_multi_curr | is_multi_prev  
  
# -- Summarise flags -----  
n_same_dup = df['same_brand_dup'].sum()  
n_multi     = df['multiple_brand'].sum()  
print(f'Same-brand duplicates to drop      : {n_same_dup}')  
print(f'Different-brand close pairs       : {n_multi} records will be labelled "multiple"')
```

```
Same-brand duplicates to drop      : 28  
Different-brand close pairs       : 8 records will be labelled "multiple"
```

```
# -- Inspect same-brand duplicates -----  
cols_inspect = ['person_id', 'date', 'event', 'brand', '_prev_date', '_gap_days']  
  
if n_same_dup > 0:  
    print(f'--- Same-brand duplicates (later dose dropped) ---')  
    display(df[df['same_brand_dup']][cols_inspect].reset_index(drop=True))  
else:  
    print('No same-brand duplicates within 3 days found.')  
  
print()  
  
# -- Inspect different-brand close pairs -----  
if n_multi > 0:  
    print(f'--- Different-brand close pairs (labelled "multiple") ---')  
    display(  
        df[df['multiple_brand']][cols_inspect]  
        .sort_values(['person_id', 'date'])  
        .reset_index(drop=True)  
    )  
else:  
    print('No different-brand pairs within 3 days found.')
```

```
--- Same-brand duplicates (later dose dropped) ---
```

	person_id	date	event	brand	_prev_date	_gap_days
0	1162230	2023-05-26	cvp23	cvp	2023-05-23	3.0
1	1212267	2023-06-06	cvm23	cvm	2023-06-05	1.0
2	1419610	2023-03-20	cvn23	cvn	2023-03-18	2.0
3	1452421	2024-07-06	cvn24	cvn	2024-07-05	1.0
4	1938483	2023-09-26	cvu	cvu	2023-09-23	3.0
5	2566777	2023-04-28	cvp23	cvp	2023-04-26	2.0
6	2622631	2022-06-06	cvu	cvu	2022-06-05	1.0
7	3500715	2022-11-05	cvj22	cvj	2022-11-04	1.0
8	3566765	2024-06-09	cvp24	cvp	2024-06-06	3.0
9	3762152	2024-02-03	cvm24	cvm	2024-01-31	3.0
10	4337174	2025-01-06	cvu	cvu	2025-01-04	2.0
11	4700025	2024-06-26	cvp24	cvp	2024-06-24	2.0
12	4841005	2024-06-25	cvu	cvu	2024-06-23	2.0
13	4993055	2022-09-08	cvn22	cvn	2022-09-07	1.0
14	5137722	2023-08-12	cvn23	cvn	2023-08-10	2.0
15	5186414	2022-12-06	cvn22	cvn	2022-12-04	2.0
16	5761145	2024-09-03	cvm24	cvm	2024-09-01	2.0
17	6038571	2023-07-30	cvu	cvu	2023-07-27	3.0
18	6492066	2023-12-31	cvp23	cvp	2023-12-30	1.0
19	6573147	2024-10-25	cvu	cvu	2024-10-23	2.0
20	6709938	2022-11-07	cvn22	cvn	2022-11-04	3.0
21	6770619	2023-10-20	cvn23	cvn	2023-10-18	2.0
22	7117837	2024-04-19	cvm24	cvm	2024-04-16	3.0
23	7374122	2022-07-03	cvp22	cvp	2022-06-30	3.0
24	7685149	2023-12-23	cvm23	cvm	2023-12-22	1.0
25	7812810	2024-07-27	cvu	cvu	2024-07-26	1.0
26	8290770	2023-09-05	cvp23	cvp	2023-09-04	1.0
27	8550917	2024-04-05	cvn24	cvn	2024-04-04	1.0

--- Different-brand close pairs (labelled "multiple") ---

	person_id	date	event	brand	_prev_date	_gap_days
0	2149597	2023-12-19	cvp23	cvp	NaT	NaN
1	2149597	2023-12-20	cvm23	cvm	2023-12-19	1.0
2	2737893	2024-04-13	cvp24	cvp	NaT	NaN
3	2737893	2024-04-16	cvn24	cvn	2024-04-13	3.0
4	7730428	2023-11-21	cvm23	cvm	NaT	NaN
5	7730428	2023-11-24	cvp23	cvp	2023-11-21	3.0
6	8425149	2023-09-24	cvm23	cvm	NaT	NaN
7	8425149	2023-09-25	cvp23	cvp	2023-09-24	1.0

```
# -- Apply Rule 1: drop same-brand duplicates -----
df = df[~df['same_brand_dup']].copy()

# -- Apply Rule 2: label different-brand close pairs, then drop them -----
df['brand_label'] = df['brand']
df.loc[df['multiple_brand'], 'brand_label'] = 'multiple'

n_multi_dropped = df['multiple_brand'].sum()
df = df[~df['multiple_brand']].copy()

# -- Drop working columns -----
working_cols = ['_prev_date', '_prev_brand', '_gap_days', '_next_brand', '_next_gap',
```



```
        'same_brand_dup', 'multiple_brand']
exposure_tmp1 = df.drop(columns=working_cols).copy()

print(f'Rows entering Step 3          : {len(exposure_tmp1) + n_same_dup + n_multi_dropped:,}')
print(f'Rows dropped  -- same-brand duplicate  : {n_same_dup:,}')
print(f'Rows dropped  -- different-brand close   : {n_multi_dropped:,}')
print(f'Rows retained (exposure_tmp1)          : {len(exposure_tmp1):,}')
print(f'\nbrand_label distribution:')
print(exposure_tmp1['brand_label'].value_counts())
```

Rows entering Step 3 : 939
Rows dropped -- same-brand duplicate : 28
Rows dropped -- different-brand close : 8
Rows retained (exposure_tmp1) : 903

brand_label distribution:
brand_label
cvu 251
cvm 247
cvn 203
cvp 186
cvj 16
Name: count, dtype: int64

```
print('Step 3 preview (brand and brand_label columns):')
exposure_tmp1[['person_id', 'date', 'event', 'brand', 'brand_label']].head(10)
```

Step 3 preview (brand and brand_label columns):

	person_id	date	event	brand	brand_label
0	1006810	2023-02-01	cvm23	cvm	cvm
1	1009594	2024-02-14	cvu	cvu	cvu
2	1009594	2024-05-08	cvu	cvu	cvu
3	1028374	2024-04-13	cvm24	cvm	cvm
4	1028374	2024-06-03	cvp24	cvp	cvp
5	1036161	2023-08-16	cvp23	cvp	cvp
6	1036161	2023-12-22	cvp23	cvp	cvp
7	1054447	2025-08-14	cvu	cvu	cvu
8	1059486	2023-08-03	cvn23	cvn	cvn
9	1059486	2023-09-03	cvm23	cvm	cvm

Step 4 -- Derive analytical variables

Variable	Definition
age_at_exposure	Completed years between birth_date and vaccination date (floor division of day difference by 365.25)
season	Flu-year season: 22_23 (01Jul2022-30Jun2023), 23_24 (01Jul2023-30Jun2024), 24_25 (01Jul2024-30Jun2025); None if outside all windows
in_study_window	1 if 01Jul2022 <= date <= 30Jun2025 , else 0
vac_brand	{brand_name}_{season} for all brands including cvu (e.g. moderna_23_24 , Unknown_brand_23_24); NaN for records outside defined season windows

```
df = exposure_tmp1.copy()

# -- 1. Age at exposure (completed years) -----
df['age_at_exposure'] = ((df['date'] - df['birth_date']).dt.days / 365.25).astype(int)

# -- 2. Season (Jul-Jun flu-year boundaries) -----
df['season'] = None
df.loc[(df['date'] >= '2022-07-01') & (df['date'] <= '2023-06-30'), 'season'] = '22_23'
df.loc[(df['date'] >= '2023-07-01') & (df['date'] <= '2024-06-30'), 'season'] = '23_24'
```

```
df.loc[(df['date'] >= '2024-07-01') & (df['date'] <= '2025-06-30'), 'season'] = '24_25'

# -- 3. in_study_window flag -----
df['in_study_window'] = (
    (df['date'] >= pd.Timestamp('2022-07-01')) &
    (df['date'] <= pd.Timestamp('2025-06-30'))
).astype(int)

print('age_at_exposure:')
print(f"  Range : {df['age_at_exposure'].min()} - {df['age_at_exposure'].max()} years")
print(f"  Mean  : {df['age_at_exposure'].mean():.1f} years")
print()
print('season distribution:')
print(df['season'].value_counts(dropna=False))
print()
print('in_study_window distribution:')
print(df['in_study_window'].value_counts())
```

```
age_at_exposure:
  Range : 11 - 28 years
  Mean  : 19.5 years
```

```
season distribution:
season
23_24    386
24_25    267
22_23    212
None      38
Name: count, dtype: int64
```

```
in_study_window distribution:
in_study_window
1      865
0       38
Name: count, dtype: int64
```

```
# -- 4. vac_brand -- brand x season label -----
BRAND_FULL = {
    'cvp': 'pfizer',
    'cvm': 'moderna',
    'cvn': 'novavax',
    'cvj': 'janssen',
    'cvu': 'Unknown_brand',  # season suffix appended just like named brands
}

df['_brand_full'] = df['brand'].map(BRAND_FULL)

# Combine brand name and season; NaN propagates where either is NaN
df['vac_brand'] = df['_brand_full'] + '_' + df['season']

df.drop(columns=['_brand_full'], inplace=True)

print('vac_brand distribution:')
print(df['vac_brand'].value_counts(dropna=False))
```



```
vac_brand distribution:
vac_brand
moderna_23_24      118
Unknown_brand_24_25 101
pfizer_23_24       91
novavax_23_24      90
Unknown_brand_23_24 87
moderna_24_25       67
moderna_22_23       59
novavax_24_25       58
novavax_22_23       53
pfizer_22_23        46
pfizer_24_25        41
Unknown_brand_22_23 41
NaN                 38
janssen_22_23       13
Name: count, dtype: int64
```

```
exposure_tmp1 = df.copy()

print('--- Step 4 summary ---')
print(f'Shape: {exposure_tmp1.shape}')
print()
new_cols = ['age_at_exposure', 'season', 'in_study_window', 'vac_brand']
print('Sample of new columns:')
print(exposure_tmp1[['person_id', 'date', 'brand'] + new_cols].head(12).to_string(index=False))
```

```
--- Step 4 summary ---
Shape: (903, 37)
```

Sample of new columns:

person_id	date	brand	age_at_exposure	season	in_study_window	vac_brand
1006810	2023-02-01	cvm	14	22_23	1	moderna_22_23
1009594	2024-02-14	cvu	13	23_24	1	Unknown_brand_23_24
1009594	2024-05-08	cvu	13	23_24	1	Unknown_brand_23_24
1028374	2024-04-13	cvm	23	23_24	1	moderna_23_24
1028374	2024-06-03	cvp	23	23_24	1	pfizer_23_24
1036161	2023-08-16	cvp	16	23_24	1	pfizer_23_24
1036161	2023-12-22	cvp	17	23_24	1	pfizer_23_24
1054447	2025-08-14	cvu	23	None	0	NaN
1059486	2023-08-03	cvn	16	23_24	1	novavax_23_24
1059486	2023-09-03	cvm	16	23_24	1	moderna_23_24
1093026	2023-08-04	cvp	19	23_24	1	pfizer_23_24
1093026	2023-09-22	cvp	19	23_24	1	pfizer_23_24

Step 5 -- After-authorization flag (after_auth)

after_auth = 1 when **all three** conditions are met; 0 otherwise:

- vac_brand matches a defined authorization entry
- age_at_exposure meets the brand's minimum age threshold
- date falls within the brand's authorization window

Brand group	Min age	Authorization window
moderna_22_23 , pfizer_22_23 , novavax_22_23 , Unknown_brand_22_23	>= 12	01Aug2022 - 30Jun2023
moderna_23_24 , pfizer_23_24 , novavax_23_24 , Unknown_brand_23_24	>= 12	01Aug2023 - 30Jun2024
moderna_24_25 , pfizer_24_25 , novavax_24_25 , Unknown_brand_24_25	>= 12	01Aug2024 - 30Jun2025
janssen_22_23	>= 18	01Aug2022 - 30Jun2023

Records with vac_brand = NaN (outside all season windows) receive after_auth = 0 .

```
# Authorization conditions per vac_brand: (min_age, auth_start, auth_end)
AUTH_CONDITIONS = {
    'moderna_22_23': (12, '2022-08-01', '2023-06-30'),
    'moderna_23_24': (12, '2023-08-01', '2024-06-30'),
    'moderna_24_25': (12, '2024-08-01', '2025-06-30'),
    'pfizer_22_23': (12, '2022-08-01', '2023-06-30'),
    'pfizer_23_24': (12, '2023-08-01', '2024-06-30'),
    'pfizer_24_25': (12, '2024-08-01', '2025-06-30'),
    'novavax_22_23': (12, '2022-08-01', '2023-06-30'),
    'novavax_23_24': (12, '2023-08-01', '2024-06-30'),
    'novavax_24_25': (12, '2024-08-01', '2025-06-30'),
    'janssen_22_23': (18, '2022-08-01', '2023-06-30'), # Janssen: age >= 18
    'Unknown_brand_22_23': (12, '2022-08-01', '2023-06-30'),
    'Unknown_brand_23_24': (12, '2023-08-01', '2024-06-30'),
    'Unknown_brand_24_25': (12, '2024-08-01', '2025-06-30'),
}

df = exposure_tmp1.copy()
df['after_auth'] = 0

for vac_brand, (min_age, auth_start, auth_end) in AUTH_CONDITIONS.items():
    mask = (
        (df['vac_brand'] == vac_brand) &
        (df['age_at_exposure'] >= min_age) &
        (df['date'] >= pd.Timestamp(auth_start)) &
        (df['date'] <= pd.Timestamp(auth_end))
    )
    df.loc[mask, 'after_auth'] = 1

print('after_auth distribution:')
print(df['after_auth'].value_counts())
print()
print('after_auth by vac_brand (1 = authorised, 0 = not):')
summary = (
    df.groupby('vac_brand', dropna=False)['after_auth']
    .agg(after_auth_1='sum', total='count')
    .assign(not_auth=lambda x: x['total'] - x['after_auth_1'])
)
print(summary.to_string())

after_auth distribution:
after_auth
1    791
0    112
Name: count, dtype: int64

after_auth by vac_brand (1 = authorised, 0 = not):
      vac_brand  after_auth_1  total  not_auth
Unknown_brand_22_23         41     41         0
Unknown_brand_23_24         78     87         9
Unknown_brand_24_25         93    101         8
janssen_22_23              11     13         2
moderna_22_23              56     59         3
moderna_23_24             111    118         7
moderna_24_25              52     67        15
novavax_22_23              52     53         1
novavax_23_24              84     90         6
novavax_24_25              48     58        10
pfizer_22_23              45     46         1
pfizer_23_24              87     91         4
pfizer_24_25              33     41         8
NaN                      0     38        38

exposure_tmp1 = df.copy()

print(f'Shape: {exposure_tmp1.shape}')
print()
print('Sample (after_auth column):')
```

```
print(
    exposure_tmp1[['person_id', 'date', 'age_at_exposure', 'vac_brand', 'after_auth']]
    .head(14)
    .to_string(index=False)
)
```

Shape: (903, 38)

Sample (after_auth column):

person_id	date	age_at_exposure	vac_brand	after_auth
1006810	2023-02-01	14	moderna_22_23	1
1009594	2024-02-14	13	Unknown_brand_23_24	1
1009594	2024-05-08	13	Unknown_brand_23_24	1
1028374	2024-04-13	23	moderna_23_24	1
1028374	2024-06-03	23	pfizer_23_24	1
1036161	2023-08-16	16	pfizer_23_24	1
1036161	2023-12-22	17	pfizer_23_24	1
1054447	2025-08-14	23	NaN	0
1059486	2023-08-03	16	novavax_23_24	1
1059486	2023-09-03	16	moderna_23_24	1
1093026	2023-08-04	19	pfizer_23_24	1
1093026	2023-09-22	19	pfizer_23_24	1
1098919	2024-09-06	23	Unknown_brand_24_25	1
1109031	2024-06-24	17	pfizer_23_24	1

Attrition Table -- Exposure Dataset Construction (Part 1)

Records excluded at each step from the raw event file through to exposure_enriched.csv .

```
# -- Attrition Table: Exposure Dataset Construction (Part 1) -----

# Re-read source files to reconstruct step-level record counts
_ev = pd.read_csv(DATA_DIR / 'event.csv')
_ev['date'] = pd.to_datetime(_ev['date'], format='%d%b%Y', errors='coerce')
_ev['concept_id'] = _ev['concept_id'].fillna('').astype(str)

_pt = pd.read_csv(DATA_DIR / 'patient.csv')
_en = pd.read_csv(DATA_DIR / 'enrollment.csv')
for _c in ['enrl_start_date', 'enrl_end_date']:
    _en[_c] = pd.to_datetime(_en[_c], format='%d%b%Y', errors='coerce')

# Step 0 -- raw event records
_n0 = len(_ev)

# Step 1.1 -- subset to vaccination event codes
_vax = _ev[_ev['event'].isin(VAX_CODES)].copy()
_n1 = len(_vax)

# Step 1.2 -- inner merge with patient file (must have matching person_id)
_vax_pt = _vax.merge(_pt[['person_id']], on='person_id', how='inner')
_n2 = len(_vax_pt)

# Step 1.3 -- ZIP geographic enrichment (left join -- no row loss)
_n3 = _n2

# Step 1.4 -- restrict to enrollment window (date within enrl_start/end)
_vax_enrl = _vax_pt.merge(_en[['person_id', 'enrl_start_date', 'enrl_end_date']],
    on='person_id', how='left')
_vax_enrl_in = _vax_enrl[
    _vax_enrl['date'].notna() &
    (_vax_enrl['date'] >= _vax_enrl['enrl_start_date']) &
    (_vax_enrl['date'] <= _vax_enrl['enrl_end_date'])
].copy()
_n4 = len(_vax_enrl_in)
```

```
# Step 2 -- remove admin concept co-occurrence (concept_id == ADMIN_CODE on same person+date)
_admin_pairs = set(zip(
    _ev.loc[_ev['concept_id'] == ADMIN_CODE, 'person_id'].astype(str),
    _ev.loc[_ev['concept_id'] == ADMIN_CODE, 'date'].astype(str)
))
_keep_mask = ~_vax_enrl_in.apply(
    lambda r: (str(r['person_id']), str(r['date'])) in _admin_pairs, axis=1
)
_n5 = int(_keep_mask.sum())

# Step 3 -- close-dose pair resolution (final count = current exposure_tmp1)
# Steps 4 & 5 only add columns; row count unchanged.
_n6 = len(exposure_tmp1)

# -- Build attrition DataFrame -----
_rows = [
    ('All records in event.csv', _n0, '--'),
    ('Step 1.1 Subset to vaccination event codes', _n1, _n0 - _n1),
    ('Step 1.2 Inner merge with patient file', _n2, _n1 - _n2),
    ('Step 1.3 ZIP geographic enrichment (left join)', _n3, 0),
    ('Step 1.4 Restrict to enrollment window', _n4, _n3 - _n4),
    ('Step 2 Remove admin concept co-occurrence (724802)', _n5, _n4 - _n5),
    ('Step 3 Resolve close-dose pairs (<=3 days)', _n6, _n5 - _n6),
    ('Step 4 Derive analytical variables (columns added only)', _n6, 0),
    ('Step 5 Apply after-authorization flag (column added only)', _n6, 0),
]

_attrition = pd.DataFrame(_rows, columns=['Step', 'N Remaining', 'N Excluded'])
_attrition['N Excluded'] = _attrition['N Excluded'].apply(
    lambda x: x if x == '--' else (0 if int(x) == 0 else f'-{int(x)}')
)
_attrition.index = range(1, len(_attrition) + 1)
_attrition.index.name = '#'

print('Attrition Table -- Exposure Dataset Construction (Part 1)')
print('=' * 75)
print(_attrition.to_string())
print()
print(f" -> Final exposure_enriched.csv : {_n6:>4} records | "
      f"{exposure_tmp1['person_id'].nunique()} unique persons")
```

Attrition Table -- Exposure Dataset Construction (Part 1)

=====			
	Step	N Remaining	N Excluded
#			
1	All records in event.csv	1000	--
2	Step 1.1 Subset to vaccination event codes	939	-61
3	Step 1.2 Inner merge with patient file	939	0
4	Step 1.3 ZIP geographic enrichment (left join)	939	0
5	Step 1.4 Restrict to enrollment window	939	0
6	Step 2 Remove admin concept co-occurrence (724802)	939	0
7	Step 3 Resolve close-dose pairs (<=3 days)	903	-36
8	Step 4 Derive analytical variables (columns added only)	903	0
9	Step 5 Apply after-authorization flag (column added only)	903	0

-> Final exposure_enriched.csv : 903 records | 539 unique persons

Save final dataset -- exposure_enriched.csv

```
out_path = DATA_DIR / 'exposure_enriched.csv'
try:
    exposure_tmp1.to_csv(out_path, index=False)
    print(f'Saved {len(exposure_tmp1):,} rows x {exposure_tmp1.shape[1]} columns -> {out_path}')
except PermissionError:
    print(f'Warning: {out_path.name} is locked by another application -- skipping save (in-memory copy is current).')
print(f'\nFinal columns:')
print(list(exposure_tmp1.columns))
```

Saved 903 rows x 38 columns -> dataimages\exposure_enriched.csv

Final columns:
['person_id', 'visit_det_all_id', 'event', 'concept_id', 'source_concept_id', 'date', 'end_date', 'event_num', 'dqc_posit_ion', 'rv_visit_details', 'visit_det_all_concept_pt_id', 'visit_det_date', 'visit_det_end_date', 'visit_det_aim', 'setting', 'facility', 'process_date', 'sex', 'birth_date', 'death_date', 'zip', 'zip3', 'CBSA', 'urban', 'state_fips', 'state_name', 'state_abbv', 'omb_region_label', 'census_region_label', 'enrl_start_date', 'enrl_end_date', 'brand', 'brand_label', 'age_at_exposure', 'season', 'in_study_window', 'vac_brand', 'after_auth']

Part 2 -- Outcome Data Cleaning

Outcome Step 1 -- Import `event.csv`, subset to myocarditis events within the study window

Filters applied:

- `event == 'myo'`
- `01Jul2022 <= date <= 30Jun2025`

Season boundaries (same Jul-Jun convention as exposure data):

Season	Period
22_23	01 Jul 2022 - 30 Jun 2023
23_24	01 Jul 2023 - 30 Jun 2024
24_25	01 Jul 2024 - 30 Jun 2025

```
# -- Outcome Step 1: Load, subset, and create season -----
MYO_START = pd.Timestamp('2022-07-01')
MYO_END   = pd.Timestamp('2025-06-30')

event_outcome = read_csv_with_dates(
    'event.csv',
    ['date', 'end_date', 'visit_det_date', 'visit_det_end_date', 'process_date']
)

myo_df = event_outcome[
    (event_outcome['event'] == 'myo') &
    (event_outcome['date'] >= MYO_START) &
    (event_outcome['date'] <= MYO_END)
].copy()

# Season variable (same Jul-Jun boundaries as exposure data)
myo_df['season'] = None
myo_df.loc[(myo_df['date'] >= '2022-07-01') & (myo_df['date'] <= '2023-06-30'), 'season'] = '22_23'
myo_df.loc[(myo_df['date'] >= '2023-07-01') & (myo_df['date'] <= '2024-06-30'), 'season'] = '23_24'
myo_df.loc[(myo_df['date'] >= '2024-07-01') & (myo_df['date'] <= '2025-06-30'), 'season'] = '24_25'

print(f'Total myo events in study window (01Jul2022-30Jun2025): {len(myo_df):,}')
print(f'Unique patients                               : {myo_df["person_id"].nunique():,}')
print()
print('Season distribution:')
print(myo_df['season'].value_counts(dropna=False))
print()
print('Date range:')
print(f"  Min: {myo_df['date'].min().date()} |  Max: {myo_df['date'].max().date()}")
```

```
Total myo events in study window (01Jul2022-30Jun2025): 58
Unique patients                : 58

Season distribution:
season
23_24    27
24_25    21
22_23    10
Name: count, dtype: int64

Date range:
  Min: 2022-09-30 | Max: 2025-06-14
```

Outcome Step 2 -- Create myo_event flag

myo_event = 1 for every myocarditis record retained in the outcome dataset (all rows satisfy the condition by construction after the Step 1 filter).
Where a patient has more than one myocarditis event within the same season, only the **first** event (earliest date) is kept as the index case.

```
# -- Step 2: myo_event flag -----
# Every record in myo_df is a myo event by construction -> flag = 1 for all
# Deduplicate to the FIRST event per person per season (index case only)
myo_df = (
    myo_df.sort_values(['person_id', 'season', 'date'])
           .drop_duplicates(subset=['person_id', 'season'], keep='first')
           .copy()
)

myo_df['myo_event'] = 1

print(f'Myo records (first event per person-season): {len(myo_df):,}')
print(f'Unique patients                : {myo_df["person_id"].nunique():,}')
print()
print('myo_event by season:')
print(myo_df.groupby('season')['myo_event'].sum())
print()
print('Preview:')
print(myo_df[['person_id', 'date', 'season', 'myo_event']].head(10).to_string(index=False))
```

```
Myo records (first event per person-season): 58
Unique patients                : 58

myo_event by season:
season
22_23    10
23_24    27
24_25    21
Name: myo_event, dtype: int64
```

```
Preview:
person_id      date season  myo_event
1093026 2023-10-08  23_24         1
1109031 2024-09-17  24_25         1
1192619 2024-08-11  24_25         1
1481506 2024-10-07  24_25         1
1533224 2024-09-06  24_25         1
1666754 2025-01-27  24_25         1
1841248 2023-11-18  23_24         1
1959074 2024-03-16  23_24         1
1971823 2023-06-01  22_23         1
2164686 2024-01-16  23_24         1
```

Outcome Step 3 -- 365-day washout between myocarditis events

Condition: For a given individual, consecutive myocarditis events must be >= **365 days apart** -- both within the same season and across seasons.

- Events are sorted chronologically per patient.
- The **first** event is always retained.
- Each subsequent event is retained only if it is ≥ 365 days from the last retained event; otherwise it is dropped.
- This prevents a single prolonged or recurrent episode from being counted multiple times across season boundaries.

```
# Apply 365-day washout using an explicit per-patient loop (avoids pandas groupby.apply warnings)
myo_flagged = myo_df.copy()
myo_flagged['keep_365d'] = False

for pid, grp in myo_df.groupby('person_id'):
    grp = grp.sort_values('date')
    keep_flags = [True]
    last_kept = grp.iloc[0]['date']
    for i in range(1, len(grp)):
        gap = (grp.iloc[i]['date'] - last_kept).days
        if gap >= 365:
            keep_flags.append(True)
            last_kept = grp.iloc[i]['date']
        else:
            keep_flags.append(False)
    myo_flagged.loc[grp.index, 'keep_365d'] = keep_flags

n_before = len(myo_flagged)
n_dropped = (~myo_flagged['keep_365d']).sum()
n_after = myo_flagged['keep_365d'].sum()

print(f'Myo events before 365-day washout : {n_before:,}')
print(f'Dropped (gap < 365 days)           : {n_dropped:,}')
print(f'Retained                             : {n_after:,}')

dropped = myo_flagged[~myo_flagged['keep_365d']][['person_id', 'date', 'season', 'myo_event']]
if len(dropped) > 0:
    print()
    print('Dropped records (too close to a prior myo event):')
    print(dropped.to_string(index=False))
else:
    print()
    print('No records dropped -- all myo events are >= 365 days apart for every individual.')

myo_df = myo_flagged[myo_flagged['keep_365d']].drop(columns=['keep_365d']).copy()

print()
print('Final myo_event counts by season:')
print(myo_df.groupby('season')['myo_event'].sum())
```

```
Myo events before 365-day washout : 58
Dropped (gap < 365 days)           : 0
Retained                             : 58
```

No records dropped -- all myo events are ≥ 365 days apart for every individual.

```
Final myo_event counts by season:
season
22_23    10
23_24    27
24_25    21
Name: myo_event, dtype: int64
```

```
out_path = DATA_DIR / 'myo_events.csv'
try:
    myo_df.to_csv(out_path, index=False)
    print(f'Saved {len(myo_df):,} rows x {myo_df.shape[1]} columns -> {out_path}')
except PermissionError:
    print(f'Warning: {out_path.name} is locked by another application -- skipping save (in-memory copy is current).')
print(f'\nColumns: {list(myo_df.columns)}')
```

Saved 58 rows x 19 columns -> dataimages\myo_events.csv

Columns: ['person_id', 'visit_det_all_id', 'event', 'concept_id', 'source_concept_id', 'date', 'end_date', 'event_num', 'dqc_posit_ion', 'rv_visit_details', 'visit_det_all_concept_pt_id', 'visit_det_date', 'visit_det_end_date', 'visit_det_aim', 'setting', 'facility', 'process_date', 'season', 'myo_event']

Part 3 -- Merge Exposure and Outcome Data

Standard approach: for each individual in a given season, a myocarditis event is linked to their vaccination record only if `myo_date > first_vax_date` (i.e., myocarditis occurred *after* the first vaccination in that season).

Steps:

- 1. Derive `first_vax_date` -- the earliest vaccination date per `(person_id, season)` in `exposure_enriched`
- 2. Left-join `myo_events` on `(person_id, season)` to bring in `myo_date`
- 3. Flag `myo_after_first_vax = 1` where `myo_date > first_vax_date` ; else `0`
- 4. Merge the flags back onto all vaccination records in `exposure_enriched`

```
# -- Load both clean datasets -----
exposure = pd.read_csv(DATA_DIR / 'exposure_enriched.csv')
myo       = pd.read_csv(DATA_DIR / 'myo_events.csv')

# Explicit date conversion (avoids dtype=str + parse_dates interaction issues)
for col in ['date', 'end_date', 'birth_date', 'death_date',
            'visit_det_date', 'visit_det_end_date', 'process_date',
            'enrl_start_date', 'enrl_end_date']:
    if col in exposure.columns:
        exposure[col] = pd.to_datetime(exposure[col], errors='coerce')

for col in ['date', 'end_date', 'visit_det_date', 'visit_det_end_date', 'process_date']:
    if col in myo.columns:
        myo[col] = pd.to_datetime(myo[col], errors='coerce')

exposure['person_id'] = exposure['person_id'].astype(str)
myo['person_id']      = myo['person_id'].astype(str)

print(f'exposure_enriched : {exposure.shape}')
print(f'myo_events       : {myo.shape}')

# -- Step 1: First vaccination date per person x season -----
first_vax = (
    exposure
    .groupby(['person_id', 'season'])['date']
    .min()
    .reset_index()
    .rename(columns={'date': 'first_vax_date'})
)

# -- Step 2: Myo events per person x season -----
myo_link = (
    myo[['person_id', 'season', 'date', 'myo_event']]
    .rename(columns={'date': 'myo_date'})
)

# Left join on person_id + season -- keep all vaccinated person-seasons
person_season = first_vax.merge(myo_link, on=['person_id', 'season'], how='left')

# -- Step 3: Flag myo only if it occurred AFTER the first vaccination -----
person_season['myo_after_first_vax'] = (
    person_season['myo_date'].notna() &
    (person_season['myo_date'] > person_season['first_vax_date'])
).astype('int64')
```



```

n_qualifying = person_season['myo_after_first_vax'].sum()
n_excluded   = (person_season['myo_date'].notna() & (person_season['myo_after_first_vax'] == 0)).sum()

print(f'\nPerson-season pairs with a myo event      : {person_season["myo_date"].notna().sum():,}')
print(f'  myo_date > first_vax_date  (myo_after_first_vax=1) : {n_qualifying:,}')
print(f'  myo_date <= first_vax_date  (excluded)           : {n_excluded:,}')

# -- Step 4: Merge flags back onto all vaccination records -----
merged = exposure.merge(
    person_season[['person_id', 'season', 'first_vax_date', 'myo_date', 'myo_after_first_vax']],
    on=['person_id', 'season'],
    how='left'
)
merged['myo_after_first_vax'] = merged['myo_after_first_vax'].fillna(0).astype('int64')

print(f'\nMerged dataset shape : {merged.shape}')
print(f'\nmyo_after_first_vax distribution:')
print(merged['myo_after_first_vax'].value_counts())
print()
print('myo_after_first_vax by season:')
print(merged.groupby('season')['myo_after_first_vax'].sum())
print()

# Preview -- use .dt.strftime directly since columns are already datetime
cols = ['person_id', 'date', 'season', 'first_vax_date', 'myo_date', 'myo_after_first_vax']
preview = (
    merged[merged['myo_after_first_vax'] == 1][cols]
    .drop_duplicates('person_id')
    .head(8)
    .copy()
)
preview['date']          = preview['date'].dt.strftime('%d%b%Y')
preview['first_vax_date'] = preview['first_vax_date'].dt.strftime('%d%b%Y')
preview['myo_date']      = preview['myo_date'].dt.strftime('%d%b%Y')
print('Preview -- confirmed cases (myo_date > first_vax_date):')
print(preview.to_string(index=False))

```

```
exposure_enriched : (903, 38)
myo_events         : (58, 19)

Person-season pairs with a myo event      : 57
  myo_date > first_vax_date  (myo_after_first_vax=1) : 57
  myo_date <= first_vax_date  (excluded)           : 0

Merged dataset shape : (903, 41)

myo_after_first_vax distribution:
myo_after_first_vax
0      822
1       81
Name: count, dtype: int64

myo_after_first_vax by season:
season
22_23      16
23_24      40
24_25      25
Name: myo_after_first_vax, dtype: int64

Preview -- confirmed cases (myo_date > first_vax_date):
person_id      date season first_vax_date  myo_date  myo_after_first_vax
1093026 04Aug2023  23_24      04Aug2023 08Oct2023           1
1109031 27Aug2024  24_25      27Aug2024 17Sep2024           1
1192619 19Jul2024  24_25      19Jul2024 11Aug2024           1
1481506 05Oct2024  24_25      05Oct2024 07Oct2024           1
1533224 17Aug2024  24_25      17Aug2024 06Sep2024           1
1666754 06Dec2024  24_25      06Dec2024 27Jan2025           1
1841248 29Oct2023  23_24      29Oct2023 18Nov2023           1
1959074 14Aug2023  23_24      14Aug2023 16Mar2024           1
```

Part 4 -- Age Categorisation and Inclusion Restrictions

Age category (age_cat)

Category	Condition
12_17	age_at_exposure >= 12 and < 18
18_24	age_at_exposure >= 18 and < 25
other	all else

Inclusion criteria (applied sequentially)

- after_auth = 1 -- vaccination within brand-specific authorization window, meeting minimum age
- in_study_window = 1 -- vaccination date within 01Jul2022-30Jun2025
- age_cat in {12_17, 18_24} -- exclude records outside the target age range
- Remove Unknown_brand -- exclude records where vac_brand contains Unknown_brand

```
df = merged.copy()
n_start = len(df)

# -- Age category -----
age = df['age_at_exposure'].astype(int)
df['age_cat'] = 'other'
df.loc[(age >= 12) & (age < 18), 'age_cat'] = '12_17'
df.loc[(age >= 18) & (age < 25), 'age_cat'] = '18_24'

print('age_cat distribution (before restrictions):')
print(df['age_cat'].value_counts(dropna=False))
```

```

print()

# -- Apply inclusion criteria -----
steps = [
    ('Start',          df.copy()),
]

# 1. after_auth = 1
df = df[df['after_auth'] == 1].copy()
steps.append(('after_auth = 1', df.copy()))

# 2. in_study_window = 1
df = df[df['in_study_window'] == 1].copy()
steps.append(('in_study_window = 1', df.copy()))

# 3. age_cat in target groups
df = df[df['age_cat'].isin(['12_17', '18_24'])].copy()
steps.append(('age_cat in {12_17, 18_24}', df.copy()))

# 4. Remove Unknown_brand
df = df[~df['vac_brand'].str.contains('Unknown_brand', na=True)].copy()
steps.append(('Remove Unknown_brand', df.copy()))

# -- Attrition table -----
print(f'{"Step":<30} {"N records":>10} {"Removed":>9}')
print('-' * 55)
prev_n = n_start
for label, frame in steps:
    n = len(frame)
    removed = prev_n - n if label != 'Start' else 0
    print(f'{label:<30} {n:>10,} {removed:>9,}')
    prev_n = n

analytic = df.copy()
print()
print(f'Analytic dataset shape : {analytic.shape}')
print()
print('age_cat:')
print(analytic['age_cat'].value_counts())
print()
print('vac_brand:')
print(analytic['vac_brand'].value_counts(dropna=False))
print()
print('myo_after_first_vax:')
print(analytic['myo_after_first_vax'].value_counts())

```

```
age_cat distribution (before restrictions):
age_cat
18_24    462
12_17    312
other     129
Name: count, dtype: int64
```

Step	N records	Removed
Start	903	0
after_auth = 1	791	112
in_study_window = 1	791	0
age_cat in {12_17, 18_24}	680	111
Remove Unknown_brand	501	179

Analytic dataset shape : (501, 42)

```
age_cat:
age_cat
18_24    312
12_17    189
Name: count, dtype: int64
```

```
vac_brand:
vac_brand
moderna_23_24    97
pfizer_23_24     74
novavax_23_24    72
moderna_22_23    52
novavax_22_23    44
pfizer_22_23    43
moderna_24_25    41
novavax_24_25    40
pfizer_24_25     27
janssen_22_23     11
Name: count, dtype: int64
```

```
myo_after_first_vax:
myo_after_first_vax
0      452
1       49
Name: count, dtype: int64
```

```
out_path = DATA_DIR / 'analytic_dataset.csv'
try:
    analytic.to_csv(out_path, index=False)
    print(f'Saved {len(analytic):,} rows x {analytic.shape[1]} columns -> {out_path}')
except PermissionError:
    print(f'Warning: {out_path.name} is locked by another application -- skipping save.')
print(f'\nColumns: {list(analytic.columns)}')
```

Saved 501 rows x 42 columns -> dataimages\analytic_dataset.csv

Columns: ['person_id', 'visit_det_all_id', 'event', 'concept_id', 'source_concept_id', 'date', 'end_date', 'event_num', 'dqc_posit_ion', 'rv_visit_details', 'visit_det_all_concept_pt_id', 'visit_det_date', 'visit_det_end_date', 'visit_det_aim', 'setting', 'facility', 'process_date', 'sex', 'birth_date', 'death_date', 'zip', 'zip3', 'CBSA', 'urban', 'state_fips', 'state_name', 'state_abbv', 'omb_region_label', 'census_region_label', 'enrl_start_date', 'enrl_end_date', 'brand', 'brand_label', 'age_at_exposure', 'season', 'in_study_window', 'vac_brand', 'after_auth', 'first_vax_date', 'myo_date', 'myo_after_first_vax', 'age_cat']

Part 5 -- Risk Windows and Follow-up Time

The analysis is anchored at the **first vaccination date per person x season** (`first_vax_date`).

Risk window

Parameter	Value
Risk window start	first_vax_date + 0 days (risk_start_dt)
Risk window end (uncensored)	first_vax_date + 28 days
Max follow-up	28 days

Censoring rules (minimum date wins)

Priority	Event	censor_reason
1	Disenrollment -- enr1_end_date	disenrollment
2	Death -- death_date	death
3	Season study end (30 Jun of each flu-year)	study_end
4	Risk window end -- first_vax_date + 28 d	observation_end
5	Day before next vaccination -- next_vax_date - 1 d	next_dose

Standard approach for next-dose censoring: identify the earliest vaccination date for that person that is strictly after first_vax_date (across all seasons). Censor at next_vax_date - 1 day so the observation window does not overlap with the risk period of the subsequent dose.

Derived variables

Variable	Formula
risk_end_dt	min(enr1_end_date, death_date, season_end, first_vax_date+28, next_vax_date-1)
risk_length	(risk_end_dt - risk_start_dt).days + 1 (inclusive interval)
obs_risk_length	equals risk_length -- person-days contributed in the risk window
outcome_in_risk	1 if risk_start_dt <= myo_date <= risk_end_dt ,else 0

```
RISK_WIN_START_DAYS = 0
RISK_WIN_END_DAYS   = 28

SEASON_END_DT = {
    '22_23': pd.Timestamp('2023-06-30'),
    '23_24': pd.Timestamp('2024-06-30'),
    '24_25': pd.Timestamp('2025-06-30'),
}

# -- Step 1: Collapse to first dose per person x season -----
keep_cols = [
    'person_id', 'season', 'first_vax_date', 'myo_date', 'myo_after_first_vax',
    'enr1_end_date', 'death_date', 'age_at_exposure', 'age_cat', 'sex',
    'vac_brand', 'brand', 'brand_label', 'after_auth', 'in_study_window',
    'state_abbv', 'urban', 'census_region_label', 'CBSA',
]
keep_cols = [c for c in keep_cols if c in analytic.columns]

person_season = (
    analytic
    .sort_values(['person_id', 'season', 'date'])
    .drop_duplicates(subset=['person_id', 'season'], keep='first')
    [keep_cols]
    .copy()
    .reset_index(drop=True)
)
print(f'Person-season records : {len(person_season):,}')
print(f'Unique persons       : {person_season["person_id"].nunique():,}')

# -- Step 2: Next vaccination date per person (standard approach) -----
```

```

# For each person, find the earliest vaccination date STRICTLY AFTER first_vax_date
# (any season). Censor observation at next_vax_date - 1 day.
all_vax = (
    analytic[['person_id', 'date']]
    .drop_duplicates()
    .rename(columns={'date': 'vax_date'})
)
candidates = (
    person_season[['person_id', 'season', 'first_vax_date']]
    .merge(all_vax, on='person_id', how='left')
)
candidates = candidates[candidates['vax_date'] > candidates['first_vax_date']]
next_dose = (
    candidates
    .groupby(['person_id', 'season'])['vax_date']
    .min()
    .reset_index()
    .rename(columns={'vax_date': 'next_vax_date'})
)
person_season = person_season.merge(next_dose, on=['person_id', 'season'], how='left')

# -- Step 3: Risk window boundaries -----
person_season['risk_start_dt'] = person_season['first_vax_date'] + pd.Timedelta(days=RISK_WIN_START_DAYS)
person_season['risk_end_uncensored'] = person_season['first_vax_date'] + pd.Timedelta(days=RISK_WIN_END_DAYS)
person_season['season_end_dt'] = person_season['season'].map(SEASON_END_DT)
person_season['next_dose_censor_dt'] = person_season['next_vax_date'] - pd.Timedelta(days=1)

# -- Step 4: Censored risk_end_dt = minimum of all candidate censor dates -----
censor_cols = {
    'disenrollment': person_season['enrl_end_date'],
    'death': person_season['death_date'],
    'study_end': person_season['season_end_dt'],
    'observation_end': person_season['risk_end_uncensored'],
    'next_dose': person_season['next_dose_censor_dt'],
}
censor_df = pd.DataFrame(censor_cols)

person_season['risk_end_dt'] = censor_df.min(axis=1) # NaT columns skipped
person_season['censor_reason'] = censor_df.idxmin(axis=1)

# Clamp: risk_end_dt cannot precede risk_start_dt (e.g. immediate disenrollment)
person_season['risk_end_dt'] = person_season[['risk_start_dt', 'risk_end_dt']].max(axis=1)

# -- Step 5: Risk length and observed person-time -----
# Standard: inclusive interval -> +1 day
person_season['risk_length'] = (person_season['risk_end_dt'] - person_season['risk_start_dt']).dt.days + 1
person_season['obs_risk_length'] = person_season['risk_length'] # person-days at risk

# -- Step 6: Outcome flag within risk window -----
person_season['outcome_in_risk'] = (
    person_season['myo_date'].notna() &
    (person_season['myo_date'] >= person_season['risk_start_dt']) &
    (person_season['myo_date'] <= person_season['risk_end_dt'])
).astype(int)

# -- Summary -----
print(f'\nRisk window (days 0-{RISK_WIN_END_DAYS})')
print()
print('Censor reason:')
print(person_season['censor_reason'].value_counts())
print()
print('risk_length distribution (days):')
print(person_season['risk_length'].describe().round(1))
print()
print('outcome_in_risk:')
print(person_season['outcome_in_risk'].value_counts())
print()
print('Persons with myo_after_first_vax=1 whose myo fell OUTSIDE risk window:')
outside = person_season[(person_season['myo_after_first_vax'] == 1) & (person_season['outcome_in_risk'] == 0)]

```



```
print(f'  {len(outside):,}  (censored before myo_date)')
print()
cols_show = ['person_id', 'season', 'first_vax_date', 'risk_end_dt',
             'censor_reason', 'risk_length', 'myo_date', 'outcome_in_risk']
print('Sample rows:')
print(person_season[cols_show].head(10).to_string(index=False))
```

Person-season records : 387
Unique persons : 335

Risk window (days 0-28)

Censor reason:
censor_reason
observation_end 353
study_end 29
death 4
next_dose 1
Name: count, dtype: int64

risk_length distribution (days):
count 387.0
mean 27.6
std 5.1
min 1.0
25% 29.0
50% 29.0
75% 29.0
max 29.0
Name: risk_length, dtype: float64

outcome_in_risk:
outcome_in_risk
0 365
1 22
Name: count, dtype: int64

Persons with myo_after_first_vax=1 whose myo fell OUTSIDE risk window:
15 (censored before myo_date)

Sample rows:

person_id	season	first_vax_date	risk_end_dt	censor_reason	risk_length	myo_date	outcome_in_risk
1006810	22_23	2023-02-01	2023-03-01	observation_end	29	NaT	0
1028374	23_24	2024-04-13	2024-05-11	observation_end	29	NaT	0
1036161	23_24	2023-08-16	2023-09-13	observation_end	29	NaT	0
1059486	23_24	2023-08-03	2023-08-31	observation_end	29	NaT	0
1093026	23_24	2023-08-04	2023-09-01	observation_end	29	2023-10-08	0
1109031	23_24	2024-06-24	2024-06-30	study_end	7	NaT	0
1109031	24_25	2024-08-27	2024-09-24	observation_end	29	2024-09-17	1
1120642	23_24	2024-05-24	2024-06-21	observation_end	29	NaT	0
1120642	24_25	2024-08-17	2024-09-14	observation_end	29	NaT	0
1131249	23_24	2023-11-03	2023-12-01	observation_end	29	NaT	0

Part 6 -- Summary Tables

Eight aggregation levels, each saved as a separate CSV. All rate statistics are expressed per **100,000 person-days**.

Variable	Definition
num_vax	Number of vaccination records (person-season rows)
num_unique_person	Number of distinct individuals
num_outcomes_risk	Myocarditis events within the 0-28 day risk window

Variable	Definition
pd_risk	Person-days at risk = $\text{sum}(\text{obs_risk_length})$
rate_risk	Crude incidence rate = $(\text{num_outcomes_risk} / \text{pd_risk}) \times 100,000$
rate_se	Standard error = $\text{sqrt}(\text{num_outcomes_risk}) / \text{pd_risk} \times 100,000$
lower_ci	Lower 95% CI -- exact Poisson (chi-squared method)
upper_ci	Upper 95% CI -- exact Poisson (chi-squared method)

Exact Poisson 95% CI: $\text{lower} = \text{chi}^2(0.025, 2d) / (2T)$, $\text{upper} = \text{chi}^2(0.975, 2(d+1)) / (2T)$ where d = events, T = person-days. When $d = 0$: lower = 0, upper uses $\text{chi}^2(0.975, 2)/(2T)$.

```
from scipy import stats as scipy_stats

# -- Readable brand name -----
BRAND_MAP = {'cvp': 'pfizer', 'cvm': 'moderna', 'cvn': 'novavax', 'cvj': 'janssen'}
person_season['brand_name'] = person_season['brand'].map(BRAND_MAP)

# -- Core statistics function (person-days as denominator) -----
def compute_stats(subdf):
    d = int(subdf['outcome_in_risk'].sum())
    T = subdf['obs_risk_length'].sum() # person-days (no /365.25)
    if T > 0:
        rate = d / T * 100_000
        se = d**0.5 / T * 100_000
        # Exact Poisson 95% CI (chi-squared method), T in person-days
        lo = (scipy_stats.chi2.ppf(0.025, 2 * d) / (2 * T) * 100_000) if d > 0 else 0.0
        hi = scipy_stats.chi2.ppf(0.975, 2 * (d + 1)) / (2 * T) * 100_000
    else:
        rate = se = lo = hi = float('nan')
    return {
        'num_vax': len(subdf),
        'num_unique_person': subdf['person_id'].nunique(),
        'num_outcomes_risk': d,
        'pd_risk': int(T),
        'rate_risk': round(rate, 4) if pd.notna(rate) else float('nan'),
        'lower_ci': round(lo, 4) if pd.notna(lo) else float('nan'),
        'upper_ci': round(hi, 4) if pd.notna(hi) else float('nan'),
        'rate_se': round(se, 4) if pd.notna(se) else float('nan'),
    }

def summarize_by(df, group_cols):
    """Aggregate df by group_cols and compute summary stats for each group."""
    if not group_cols:
        return pd.DataFrame([compute_stats(df)])
    rows = []
    for keys, grp in df.groupby(group_cols, sort=True):
        if not isinstance(keys, tuple):
            keys = (keys,)
        row = dict(zip(group_cols, keys))
        row.update(compute_stats(grp))
        rows.append(row)
    return pd.DataFrame(rows)

# -- Run all 8 aggregations -----
AGGREGATIONS = {
    'season_brand_age': ['season', 'brand_name', 'age_cat'],
    'season_brand': ['season', 'brand_name'],
    'season_age': ['season', 'age_cat'],
    'season': ['season'],
    'brand_age': ['brand_name', 'age_cat'],
    'brand': ['brand_name'],
    'age': ['age_cat'],
    'overall': [],
}

all_summaries = {}
print(f'{"Aggregation":<20} {"Groups":>6} {"Outcomes":>9} {"PD at risk":>12}')
```



```
print('-', * 55)

for agg_name, group_cols in AGGREGATIONS.items():
    df_out = summarize_by(person_season, group_cols)
    all_summaries[agg_name] = df_out
    out_path = DATA_DIR / f'summary_{agg_name}.csv'
    df_out.to_csv(out_path, index=False)
    print(f'{agg_name:<20} {len(df_out):>6} {int(df_out["num_outcomes_risk"].sum()):>9} {int(df_out["pd_risk"].sum()):>12,}')

# -- Display key tables -----
print()
print('--- Overall -----')
print(all_summaries['overall'].to_string(index=False))

print()
print('--- By season -----')
print(all_summaries['season'].to_string(index=False))

print()
print('--- By brand -----')
print(all_summaries['brand'].to_string(index=False))

print()
print('--- By age -----')
print(all_summaries['age'].to_string(index=False))

print()
print('--- Season x brand -----')
print(all_summaries['season_brand'].to_string(index=False))
```

Aggregation	Groups	Outcomes	PD at risk
season_brand_age	19	22	10,680
season_brand	10	22	10,680
season_age	6	22	10,680
season	3	22	10,680
brand_age	7	22	10,680
brand	4	22	10,680
age	2	22	10,680
overall	1	22	10,680

--- Overall -----
num_vax num_unique_person num_outcomes_risk pd_risk rate_risk lower_ci upper_ci rate_se
387 335 22 10680 205.9925 129.0944 311.8751 43.9178

--- By season -----
season num_vax num_unique_person num_outcomes_risk pd_risk rate_risk lower_ci upper_ci rate_se
22_23 110 110 3 3051 98.3284 20.2777 287.3574 56.7699
23_24 183 183 10 4960 201.6129 96.6812 370.7733 63.7556
24_25 94 94 9 2669 337.2049 154.1916 640.1200 112.4016

--- By brand -----
brand_name num_vax num_unique_person num_outcomes_risk pd_risk rate_risk lower_ci upper_ci rate_se
janssen 8 8 0 232 0.0000 0.0000 1590.0342 0.0000
moderna 144 131 8 3970 201.5113 86.9983 397.0577 71.2450
novavax 121 107 6 3324 180.5054 66.2423 392.8843 73.6910
pfizer 114 102 8 3154 253.6462 109.5064 499.7841 89.6775

--- By age -----
age_cat num_vax num_unique_person num_outcomes_risk pd_risk rate_risk lower_ci upper_ci rate_se
12_17 146 126 10 4065 246.0025 117.9677 452.4073 77.7928
18_24 241 211 12 6615 181.4059 93.7351 316.8796 52.3674

--- Season x brand -----
season brand_name num_vax num_unique_person num_outcomes_risk pd_risk rate_risk lower_ci upper_ci rate_se
22_23 janssen 8 8 0 232 0.0000 0.0000 1590.0342 0.0000
22_23 moderna 39 39 1 1068 93.6330 2.3706 521.6895 93.6330
22_23 novavax 32 32 1 866 115.4734 2.9235 643.3768 115.4734
22_23 pfizer 31 31 1 885 112.9944 2.8608 629.5642 112.9944
23_24 moderna 69 69 3 1859 161.3771 33.2798 471.6123 93.1711
23_24 novavax 57 57 2 1558 128.3697 15.5462 463.7155 90.7711
23_24 pfizer 57 57 5 1543 324.0441 105.2162 756.2108 144.9169
24_25 moderna 36 36 4 1043 383.5091 104.4933 981.9356 191.7546
24_25 novavax 32 32 3 900 333.3333 68.7413 974.1415 192.4501
24_25 pfizer 26 26 2 726 275.4821 33.3622 995.1360 194.7953

```
# Save person_season (risk-window dataset) and combined all_summaries

# person_season
_ps_path = DATA_DIR / 'person_season.csv'
try:
    person_season.to_csv(_ps_path, index=False)
    print(f'Saved: person_season.csv ({len(person_season):,} rows x {person_season.shape[1]} cols)')
except PermissionError:
    print('PermissionError: close person_season.csv and re-run.')

# Combined all_summaries (all 8 aggregation levels in one file)
_rows = []
for _lvl, _df in all_summaries.items():
    _tmp = _df.copy()
    _tmp.insert(0, 'aggregation_level', _lvl)
    _rows.append(_tmp)
all_summaries_combined = pd.concat(_rows, ignore_index=True, sort=False)

_comb_path = DATA_DIR / 'all_summaries_combined.csv'
try:
    all_summaries_combined.to_csv(_comb_path, index=False)
    print(f'Saved: all_summaries_combined.csv ({len(all_summaries_combined):,} rows x {all_summaries_combined.shape[1]} cols)')
except PermissionError:
```

```
print('PermissionError: close all_summaries_combined.csv and re-run.')

# Preview
print()
_cols = ['aggregation_level', 'num_vax', 'num_unique_person', 'num_outcomes_risk',
         'pd_risk', 'rate_risk', 'lower_ci', 'upper_ci']
print(all_summaries_combined[_cols].to_string(index=False))
```

Saved: person_season.csv (387 rows x 30 cols)

Saved: all_summaries_combined.csv (52 rows x 12 cols)

aggregation_level	num_vax	num_unique_person	num_outcomes_risk	pd_risk	rate_risk	lower_ci	upper_ci
season_brand_age	8	8	0	232	0.0000	0.0000	1590.0342
season_brand_age	14	14	1	384	260.4167	6.5932	1450.9488
season_brand_age	25	25	0	684	0.0000	0.0000	539.3099
season_brand_age	10	10	0	290	0.0000	0.0000	1272.0274
season_brand_age	22	22	1	576	173.6111	4.3955	967.2992
season_brand_age	7	7	0	189	0.0000	0.0000	1951.7881
season_brand_age	24	24	1	696	143.6782	3.6376	800.5235
season_brand_age	36	36	1	998	100.2004	2.5369	558.2809
season_brand_age	33	33	2	861	232.2880	28.1312	839.1043
season_brand_age	19	19	0	515	0.0000	0.0000	716.2873
season_brand_age	38	38	2	1043	191.7546	23.2224	692.6834
season_brand_age	20	20	2	530	377.3585	45.6999	1363.1486
season_brand_age	37	37	3	1013	296.1500	61.0733	865.4761
season_brand_age	18	18	4	521	767.7543	209.1872	1965.7560
season_brand_age	18	18	0	522	0.0000	0.0000	706.6819
season_brand_age	12	12	1	348	287.3563	7.2752	1601.0470
season_brand_age	20	20	2	552	362.3188	43.8785	1308.8202
season_brand_age	10	10	1	290	344.8276	8.7303	1921.2563
season_brand_age	16	16	1	436	229.3578	5.8068	1277.8999
season_brand	8	8	0	232	0.0000	0.0000	1590.0342
season_brand	39	39	1	1068	93.6330	2.3706	521.6895
season_brand	32	32	1	866	115.4734	2.9235	643.3768
season_brand	31	31	1	885	112.9944	2.8608	629.5642
season_brand	69	69	3	1859	161.3771	33.2798	471.6123
season_brand	57	57	2	1558	128.3697	15.5462	463.7155
season_brand	57	57	5	1543	324.0441	105.2162	756.2108
season_brand	36	36	4	1043	383.5091	104.4933	981.9356
season_brand	32	32	3	900	333.3333	68.7413	974.1415
season_brand	26	26	2	726	275.4821	33.3622	995.1360
season_age	31	31	1	863	115.8749	2.9337	645.6134
season_age	79	79	2	2188	91.4077	11.0699	330.1960
season_age	75	75	3	2043	146.8429	30.2825	429.1372
season_age	108	108	7	2917	239.9726	96.4814	494.4352
season_age	40	40	6	1159	517.6877	189.9822	1126.7881
season_age	54	54	3	1510	198.6755	40.9717	580.6141
season	110	110	3	3051	98.3284	20.2777	287.3574
season	183	183	10	4960	201.6129	96.6812	370.7733
season	94	94	9	2669	337.2049	154.1916	640.1200
brand_age	8	8	0	232	0.0000	0.0000	1590.0342
brand_age	68	59	6	1903	315.2916	115.7065	686.2572
brand_age	76	72	2	2067	96.7586	11.7179	349.5253
brand_age	41	37	1	1153	86.7303	2.1958	483.2301
brand_age	80	71	5	2171	230.3086	74.7806	537.4635
brand_age	37	31	3	1009	297.3241	61.3154	868.9071
brand_age	77	71	5	2145	233.1002	75.6870	543.9782
brand	8	8	0	232	0.0000	0.0000	1590.0342
brand	144	131	8	3970	201.5113	86.9983	397.0577
brand	121	107	6	3324	180.5054	66.2423	392.8843
brand	114	102	8	3154	253.6462	109.5064	499.7841
age	146	126	10	4065	246.0025	117.9677	452.4073
age	241	211	12	6615	181.4059	93.7351	316.8796
overall	387	335	22	10680	205.9925	129.0944	311.8751