

Question 1

Correct

Marked out of
3.00[Flag question](#)

Write a program to input a name (as a single character) and marks of three tests as m1, m2, and m3 of a student considering all the three marks have been given in integer format.

Now, you need to calculate the average of the given marks and print it along with the name as mentioned in the output format section.

All the test marks are in integers and hence calculate the average in integer as well. That is, you need to print the integer part of the average only and neglect the decimal part.

Input format :

Line 1 : Name(Single character)

Line 2 : Marks scored in the 3 tests separated by single space.

Output format :

First line of output prints the name of the student.

Second line of the output prints the average mark.

Constraints

Marks for each student lie in the range 0 to 100 (both inclusive)

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main(){
3     int m1,m2,m3,avg;
4     char name;
5     scanf("%c",&name);
6     scanf("%d%d%d",&m1,&m2,&m3);
7     printf("%c",name);
8     avg=m1+m2+m3;
9     printf("\n%d",avg/3);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	A 3 4 6	A 4	A 4	✓
✓	T 7 3 8	T 6	T 6	✓
✓	R 0 100 99	R 66	R 66	✓

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

[Flag question](#)

Some C data types, their format specifiers, and their most common bit widths are as follows:

- *Int* ("%d"): 32 Bit integer
- *Long* ("%ld"): 64 bit integer
- *Char* ("%c"): Character type
- *Float* ("%f"): 32 bit real value
- *Double* ("%lf"): 64 bit real value

Reading

To read a data type, use the following syntax:

```
scanf("format_specifier", &val)
```

For example, to read a *character* followed by a *double*:

```
char ch;
```

```
double d;
```

```
scanf("%c %lf", &ch, &d);
```

For the moment, we can ignore the spacing between format specifiers.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main(){
3     int a;
4     long b;
5     float c;
6     double d;
7     char e;
8     scanf("%d %ld %c %f %lf",&a,&b,&e,&c,&d);
9     printf("%d\n%ld\n%c\n%.3f\n%.9lf",a,b,e,c,d);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	3 12345678912345 a 334.23 14049.30493	3 12345678912345 a 334.230 14049.304930000	3 12345678912345 a 334.230 14049.304930000	✓

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00

Flag question

Write a program to print the ASCII value and the two adjacent characters of the given character.

Input

E

Output

69

D F

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main(){
3     char a;
4     int b;
5     scanf("%c",&a);
6     b=a;
7     printf("%d\n",b);
8     printf("%c %C",a-1,a+1);
9     return 0;
10 }
```

	Input	Expected	Got	
✓	E	69 D F	69 D F	✓

Passed all tests! ✓