

# *Software Design*

---

## *Static Modeling using the Unified Modeling Language (UML)*

Material based on  
[Booch99, Rumbaugh99, Jacobson99, Fowler97, Brown99]



Software Design (UML)

© SERG

## *Classes*

---

ClassName
attributes
operations

A *class* is a description of a set of objects that share the same attributes, operations, relationships, and semantics.

Graphically, a class is rendered as a rectangle, usually including its name, attributes, and operations in separate, designated compartments.



Software Design (UML)

© SERG

## Class Names

---

ClassName
attributes
operations

The name of the class is the only required tag in the graphical representation of a class. It always appears in the top-most compartment.



## Class Attributes

---

Person
name : String address : Address birthdate : Date ssn : Id

An *attribute* is a named property of a class that describes the object being modeled. In the class diagram, attributes appear in the second compartment just below the name-compartment.



## Class Attributes (Cont'd)

Attributes are usually listed in the form:

Person
name : String address : Address birthdate : Date / age : Date ssn : Id

attributeName : Type

A *derived* attribute is one that can be computed from other attributes, but doesn't actually exist. For example, a Person's age can be computed from his birth date. A derived attribute is designated by a preceding '/' as in:

/ age : Date



Software Design (UML)

© SERG

## Class Attributes (Cont'd)

Person
+ name : String # address : Address # birthdate : Date / age : Date - ssn : Id

Attributes can be:

+ public  
# protected  
- private  
/ derived



Software Design (UML)

© SERG

## Class Operations

---

Person
name : String address : Address birthdate : Date ssn : Id
eat sleep work play

*Operations* describe the class behavior and appear in the third compartment.



Software Design (UML)

© SERG

## Class Operations (Cont'd)

---

PhoneBook
newEntry (n : Name, a : Address, p : PhoneNumber, d : Description) getPhone ( n : Name, a : Address) : PhoneNumber

You can specify an operation by stating its signature: listing the name, type, and default value of all parameters, and, in the case of functions, a return type.




Software Design (UML)

© SERG

## Depicting Classes

When drawing a class, you needn't show attributes and operation in every diagram.




Software Design (UML)

© SERG

## Class Responsibilities

A class may also include its responsibilities in a class diagram.

A responsibility is a contract or obligation of a class to perform a particular service.



Software Design (UML)

© SERG

## Relationships

---

In UML, object interconnections (logical or physical), are modeled as relationships.

There are three kinds of relationships in UML:

- dependencies
- generalizations
- associations




Software Design (UML)

© SERG

## Dependency Relationships

---

A *dependency* indicates a semantic relationship between two or more elements. The dependency from *CourseSchedule* to *Course* exists because *Course* is used in both the **add** and **remove** operations of *CourseSchedule*.




Software Design (UML)

© SERG

## Generalization Relationships

---



A *generalization* connects a subclass to its superclass. It denotes an inheritance of attributes and behavior from the superclass to the subclass and indicates a specialization in the subclass of the more general superclass.




Software Design (UML)

© SERG

## Generalization Relationships (Cont'd)

---

UML permits a class to inherit from multiple superclasses, although some programming languages do not permit multiple inheritance.



Software Design (UML)


© SERG

## Association Relationships

---

If two classes in a model need to communicate with each other, there must be link between them.

An *association* denotes that link.



Software Design (UML)


© SERG

## Association Relationships (Cont'd)

---

We can indicate the *multiplicity* of an association by adding *multiplicity adornments* to the line denoting the association.

The example indicates that a *Student* has one or more *Instructors*:



Software Design (UML)


© SERG



## Association Relationships (Cont'd)

---

The example indicates that every *Instructor* has one or more *Students*:




Software Design (UML)

© SERG

## Association Relationships (Cont'd)

---

We can also indicate the behavior of an object in an association (*i.e.*, the *role* of an object) using *rolenames*.




Software Design (UML)

© SERG

## *Association Relationships (Cont'd)*

---

We can also name the association.




Software Design (UML)

© SERG

## *Association Relationships (Cont'd)*

---

We can specify dual associations.




Software Design (UML)

© SERG

## Association Relationships (Cont'd)

We can constrain the association relationship by defining the *navigability* of the association. Here, a *Router* object requests services from a *DNS* object by sending messages to (invoking the operations of) the server. The direction of the association indicates that the server has no knowledge of the *Router*.




Software Design (UML)

© SERG

## Association Relationships (Cont'd)

Associations can also be objects themselves, called *link classes* or an *association classes*.




Software Design (UML)

© SERG

## Association Relationships (Cont'd)

---

A class can have a *self association*.



Software Design (UML)


© SERG

## Association Relationships (Cont'd)

---

We can model objects that contain other objects by way of special associations called *aggregations* and *compositions*.

An *aggregation* specifies a whole-part relationship between an aggregate (a whole) and a constituent part, where the part can exist independently from the aggregate. Aggregations are denoted by a hollow-diamond adornment on the association.




Software Design (UML)

© SERG

## Association Relationships (Cont'd)

A *composition* indicates a strong ownership and coincident lifetime of parts by the whole (*i.e.*, they live and die as a whole). Compositions are denoted by a filled-diamond adornment on the association.



Software Design (UML)

© SERG

## Interfaces



An *interface* is a named set of operations that specifies the behavior of objects without showing their inner structure. It can be rendered in the model by a one- or two-compartment rectangle, with the *stereotype* `<<interface>>` above the interface name.




Software Design (UML)

© SERG

## Interface Services

---



Interfaces do not get instantiated. They have no attributes or state. Rather, they specify the services offered by a related class.




Software Design (UML)

© SERG

## Interface Realization Relationship

---




A *realization* relationship connects a class with an interface that supplies its behavioral specification. It is rendered by a dashed line with a hollow triangle towards the specifier.



Software Design (UML)

© SERG


## Interfaces



Software Design (UML)

© SERG

## Parameterized Class



A *parameterized class* or *template* defines a family of potential elements.

To use it, the parameter must be bound.


A *template* is rendered by a small dashed rectangle superimposed on the upper-right corner of the class rectangle. The dashed rectangle contains a list of formal parameters for the class.



Software Design (UML)

© SERG

## Parameterized Class (Cont'd)



*Binding* is done with the <<bind>> stereotype and a parameter to supply to the template. These are adornments to the dashed arrow denoting the realization relationship.


Here we create a linked-list of names for the Dean's List.



Software Design (UML)

© SERG

## Enumeration



An *enumeration* is a user-defined data type that consists of a name and an ordered list of enumeration literals.




Software Design (UML)

© SERG




## Exceptions



Software Design (UML)

© SERG

## Packages



A *package* is a container-like element for organizing other elements into groups.

A package can contain classes and other packages and diagrams.

Packages can be used to provide controlled access between classes in different packages.




Software Design (UML)

© SERG

## *Packages (Cont'd)*

Classes in the *FrontEnd* package and classes in the *BackEnd* package cannot access each other in this diagram.




Software Design (UML)

© SERG

## *Packages (Cont'd)*

Classes in the *BackEnd* package now have access to the classes in the *FrontEnd* package.



Software Design (UML)

© SERG

## *Packages (Cont'd)*

