

# *CENG513 Compiler Design and Construction*

## *Parsing*

Note by Işıl ÖZ:

Our slides are adapted from Cooper and Torczon's slides that are prepared for COMP 412 at Rice.


Copyright 2010, Keith D. Cooper & Linda Torczon, all rights reserved.

Students enrolled in Comp 412 at Rice University have explicit permission to make copies of these materials for their personal use.

Faculty from other educational institutions may use these materials for nonprofit educational purposes, provided this copyright notice is preserved.

# The Front End

---



## Parser

- Checks the stream of words and their parts of speech (produced by the scanner) for grammatical correctness
- Determines if the input is syntactically well formed
- Need a mathematical model of syntax — a grammar  $G$
- Need an algorithm for testing membership in  $L(G)$
- Builds an IR representation of the code

# The Study of Parsing

---

The process of discovering a *derivation* for some sentence

- If some string of words  $\underline{s}$  is in the language defined by  $\underline{G}$  we say that  $G$  derives  $s$
- For a stream of words  $s$  and a grammar  $G$ , the parser tries to build a constructive proof that  $s$  can be derived in  $G \rightarrow$  parsing
- Based on a mathematical model and an algorithm
- Need to keep in mind that our goal is building parsers, not studying the mathematics of arbitrary languages

# Parsing Algorithms

---

## Top-down parsing

- Match the input stream against the productions of the grammar by predicting the next word
- Generated LL(1) parsers & hand-coded recursive descent parsers

## Bottom-up parsing (will be skipped)

- Work from low-level detail—the actual sequence of words—and accumulate context until the derivation is apparent
- Generated LR(1) parsers

# Limits of Regular Languages

---

## Advantages of Regular Expressions

- Simple & powerful notation for specifying patterns
- Automatic construction of fast recognizers
- Many kinds of syntax can be specified with REs

## Example — a regular expression for arithmetic expressions

$Term \rightarrow [a-zA-Z] ([a-zA-Z] | [0-9])^*$

$Op \rightarrow + | - | * | /$

$Expr \rightarrow (Term Op)^* Term$

$([a-zA-Z] ([a-zA-Z] | [0-9])^* (+ | - | * | /))^* [a-zA-Z] ([a-zA-Z] | [0-9])^*$

Of course, this would generate a DFA ...

*If REs are so useful ... Why not use them for everything?*

*⇒ Cannot add parenthesis, brackets, begin-end pairs, ...*

# Why Not Use Regular Languages & DFAs?

---

Not all languages are regular

(RL's  $\subset$  CFL's  $\subset$  CSL's)

You cannot construct DFA's to recognize these languages  
(DFAs cannot count)

- $L = \{ a^n b^n \mid n \geq 0 \}$
- $L = \{ a^n b^m \mid n \geq 0, m > n \}$

Neither of these is a regular language

(nor an RE)

# Specifying Syntax with a Grammar

---

Syntax is specified by a *grammar*: a collection of rules that define, mathematically, which strings of symbols are valid sentences

A class of grammars called **context-free grammars** provides this power

Formally, a context-free grammar is a four tuple,  $G = (S, N, T, P)$

- $S$  is the *start/goal symbol* (set of strings in  $L(G)$ )
- $N$  is a set of *nonterminal symbols* (syntactic variables)
- $T$  is a set of *terminal symbols* (words)
- $P$  is a set of *productions or rewrite rules* ( $P: N \rightarrow (N \cup T)^+$ )

# Context-free Grammars

---

What makes a grammar “context free”?

The *CFG* that defines the set of noises sheep normally make, SheepNoise grammar:

$$\text{SheepNoise} \rightarrow \underline{\text{baa}} \text{ SheepNoise} \\ \quad \quad \quad | \quad \underline{\text{baa}}$$

Productions have a single nonterminal on the left hand side.  
Production rules can be applied to a nonterminal symbol regardless of its context.

⇒ The grammar is context-free.

A context-sensitive grammar can have  $\geq 1$  nonterminal on lhs.

Notice that  $L(\text{SheepNoise})$  is actually a regular language: baa<sup>+</sup>  
Backus-Naur Form (BNF)

```
<SheepNoise> ::= baa <SheepNoise>
               | baa
```



# Sample Derivations in Tabular Form

1. *SheepNoise* → *baa* *SheepNoise*
2. *SheepNoise* → *baa*

*S* = {*SheepNoise*}

*N* = {*SheepNoise*}

*T* = {*baa*}

*P* = { *SheepNoise* → *baa* *SheepNoise*  
*SheepNoise* → *baa* }

Rule	Sentential Form
	<i>SheepNoise</i>
2	<i>baa</i>

Rule	Sentential Form
	<i>SheepNoise</i>
1	<i>baa SheepNoise</i>
2	<i>baa baa</i>

Rule	Sentential Form
	<i>SheepNoise</i>
1	<i>baa SheepNoise</i>
1	<i>baa baa SheepNoise</i>
	... and so on ...
1	<i>baa ... baa SheepNoise</i>
2	<i>baa baa ... baa</i>

# A Useful Grammar

---

To explore the uses of CFGs, we need a grammar

0	$Expr$	$\rightarrow$	$Expr\ Op\ Expr$
1		$ $	<u>number</u>
2		$ $	<u>id</u>
3	$Op$	$\rightarrow$	$+$
4		$ $	$-$
5		$ $	$*$
6		$ $	$/$

$S = \{Expr\}$

$N = \{Expr, Op\}$

$T = \{\text{number}, \text{id}, +, -, *, /\}$

$P = \{$   $Expr \rightarrow Expr\ Op\ Expr$   
 $Expr \rightarrow \text{number}$   
 $Expr \rightarrow \text{id}$   
 $Op \rightarrow +$   
 $Op \rightarrow -$   
 $Op \rightarrow *$   
 $Op \rightarrow /$   
 $\}$

# A Useful Grammar

$\underline{x} - \underline{2} * \underline{y}$

0	$Expr \rightarrow Expr Op Expr$
1	<u>number</u>
2	<u>id</u>
3	$Op \rightarrow +$
4	-
5	*
6	/

Rule	Sentential Form
—	$Expr$
0	$Expr Op Expr$
2	$\langle id, \underline{x} \rangle Op Expr$
4	$\langle id, \underline{x} \rangle - Expr$
0	$\langle id, \underline{x} \rangle - Expr Op Expr$
1	$\langle id, \underline{x} \rangle - \langle num, \underline{2} \rangle Op Expr$
5	$\langle id, \underline{x} \rangle - \langle num, \underline{2} \rangle * Expr$
2	$\langle id, \underline{x} \rangle - \langle num, \underline{2} \rangle * \langle id, \underline{y} \rangle$

- Such a sequence of rewrites is called a *derivation*
- Process of discovering a derivation is called *parsing*

We denote this derivation:  $Expr \Rightarrow^* \underline{id} - \underline{num} * \underline{id}$

# Derivations

---

*The point of parsing is to construct a derivation*

- At each step, we choose a nonterminal to replace
- Different choices can lead to different derivations

Two derivations are of interest

- *Leftmost derivation* — replace leftmost NT at each step
- *Rightmost derivation* — replace rightmost NT at each step

These are the two *systematic* derivations

*(We don't care about randomly-ordered derivations!)*

The example on the preceding slide was a *leftmost* derivation

# The Two Derivations for $x - 2 * y$

Rule	Sentential Form
—	Expr
0	Expr Op Expr
2	<id,x> Op Expr
4	<id,x> - Expr
0	<id,x> - Expr Op Expr
1	<id,x> - <num,2> Op Expr
5	<id,x> - <num,2> * Expr
2	<id,x> - <num,2> * <id,y>

Leftmost derivation

Rule	Sentential Form
—	Expr
0	Expr Op Expr
2	Expr Op <id,y>
5	Expr * <id,y>
0	Expr Op Expr * <id,y>
1	Expr Op <num,2> * <id,y>
4	Expr - <num,2> * <id,y>
2	<id,x> - <num,2> * <id,y>

Rightmost derivation

In both cases,  $\text{Expr} \Rightarrow^* \underline{\text{id}} - \underline{\text{num}} * \underline{\text{id}}$

- The two derivations produce different parse trees
- The parse trees imply different evaluation orders!


0	Expr	→	Expr Op Expr
1	Expr		number
2	Expr		id
3	Op	→	+
4	Op		-
5	Op		*
6	Op		/

# Derivations and Parse Trees

## Leftmost derivation

Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<i>&lt;id,x&gt; Op Expr</i>
4	<i>&lt;id,x&gt; - Expr</i>
0	<i>&lt;id,x&gt; - Expr Op Expr</i>
1	<i>&lt;id,x&gt; - &lt;num,2&gt; Op Expr</i>
5	<i>&lt;id,x&gt; - &lt;num,2&gt; * Expr</i>
2	<i>&lt;id,x&gt; - &lt;num,2&gt; * &lt;id,y&gt;</i>

This evaluates as  $x - (2 * y)$




0	<i>Expr</i>	→	<i>Expr Op Expr</i>
1			<u>number</u>
2			<u>id</u>
3	<i>Op</i>	→	+
4			-
5			*
6			/

# Derivations and Parse Trees

## Rightmost derivation

Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<i>Expr Op</i> <id, <u>y</u> >
5	<i>Expr</i> * <id, <u>y</u> >
0	<i>Expr Op Expr</i> * <id, <u>y</u> >
1	<i>Expr Op</i> <num, <u>2</u> > * <id, <u>y</u> >
4	<i>Expr</i> - <num, <u>2</u> > * <id, <u>y</u> >
2	<id, <u>x</u> > - <num, <u>2</u> > * <id, <u>y</u> >



0	<i>Expr</i>	→	<i>Expr Op Expr</i>
1			<u>number</u>
2			<u>id</u>
3	<u>Op</u>	→	+
4			-
5			*
6			/

This evaluates as  $(x - 2) * y$

# Derivations and Precedence

---

*These two derivations point out a problem with the grammar:*

*It has no notion of precedence, or implied order of evaluation*

To add precedence

- Create a nonterminal for each *level of precedence*
- Isolate the corresponding part of the grammar
- Force the parser to recognize high precedence subexpressions first

For algebraic expressions

- Parentheses first (level 1)
- Multiplication and division, next (level 2)
- Subtraction and addition, last (level 3)



# Derivations and Precedence

Adding the standard algebraic precedence produces:

level 3	0	Goal	→	Expr
	1	Expr	→	Expr + Term
	2			Expr - Term
level 2	3			Term
	4	Term	→	Term * Factor
	5			Term / Factor
level 1	6			Factor
	7	Factor	→	( Expr )
	8			<u>number</u>
	9			<u>id</u>

Cannot handle precedence  
in an RE for expressions

This grammar is slightly larger

- Takes more rewriting to reach some of the terminal symbols
- Encodes expected precedence
- Produces the same parse tree under leftmost & rightmost derivations
- Correctness trumps the speed of the parser

Let's see how it parses  $x - 2 * y$


Introduced parentheses, too  
(beyond power of an RE)

One form of the "classic expression  
grammar"

# Derivations and Precedence

Rule	Sentential Form
—	Goal
0	Expr
2	Expr - Term
4	Expr - Term * Factor
9	Expr - Term * <id, <u>y</u> >
6	Expr - Factor * <id, <u>y</u> >
8	Expr - <num, <u>2</u> > * <id, <u>y</u> >
3	Term - <num, <u>2</u> > * <id, <u>y</u> >
6	Factor - <num, <u>2</u> > * <id, <u>y</u> >
9	<id, <u>x</u> > - <num, <u>2</u> > * <id, <u>y</u> >

The rightmost derivation



Its parse tree

0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			<u>number</u>
9			<u>id</u>

This evaluates as  $x - (2 * y)$ , along with an appropriate parse tree.

Both the leftmost and rightmost derivations give the same expression, because the grammar directly and explicitly encodes the desired precedence.

# Ambiguous Grammars

Let's leap back to our simple expression grammar.  
It had other problems.

0	$Expr \rightarrow Expr\ Op\ Expr$
1	<u>number</u>
2	<u>id</u>
3	$Op \rightarrow +$
4	-
5	*
6	/

Rule	Sentential Form
—	$Expr$
0	$Expr\ Op\ Expr$
②	$\langle id, \underline{x} \rangle\ Op\ Expr$
4	$\langle id, \underline{x} \rangle - Expr$
0	$\langle id, \underline{x} \rangle - Expr\ Op\ Expr$
1	$\langle id, \underline{x} \rangle - \langle num, \underline{2} \rangle\ Op\ Expr$
5	$\langle id, \underline{x} \rangle - \langle num, \underline{2} \rangle * Expr$
2	$\langle id, \underline{x} \rangle - \langle num, \underline{2} \rangle * \langle id, \underline{y} \rangle$

- This grammar allows multiple leftmost derivations for  $\underline{x} - \underline{2} * \underline{y}$
- Hard to automate derivation if  $> 1$  choice
- The grammar is *ambiguous*

# Two Leftmost Derivations for $x - 2 * y$

The Difference:

- Different productions chosen on the second step

0	Expr	→	Expr Op Expr
1			<u>number</u>
2			<u>id</u>
3	Op	→	+
4			-
5			*
6			/

Rule	Sentential Form
—	Expr
0	Expr Op Expr
②	<id, <u>x</u> > Op Expr
4	<id, <u>x</u> > - Expr
0	<id, <u>x</u> > - Expr Op Expr
1	<id, <u>x</u> > - <num, <u>2</u> > Op Expr
5	<id, <u>x</u> > - <num, <u>2</u> > * Expr
1	<id, <u>x</u> > - <num, <u>2</u> > * <id, <u>y</u> >

*Original choice*

- Both derivations succeed in producing  $x - 2 * y$

This evaluates as  $\underline{x} - (\underline{2} * \underline{y})$

Rule	Sentential Form
—	Expr
0	Expr Op Expr
①	Expr Op Expr Op Expr
2	<id, <u>x</u> > Op Expr Op Expr
4	<id, <u>x</u> > - Expr Op Expr
1	<id, <u>x</u> > - <num, <u>2</u> > Op Expr
5	<id, <u>x</u> > - <num, <u>2</u> > * Expr
2	<id, <u>x</u> > - <num, <u>2</u> > * <id, <u>y</u> >

*New choice*

This evaluates as  $(\underline{x} - \underline{2}) * \underline{y}$

# Ambiguous Grammars

---

## Definitions

- If a grammar has more than one leftmost derivation for a single *sentential form*, the grammar is *ambiguous*
- If a grammar has more than one rightmost derivation for a single *sentential form*, the grammar is *ambiguous*
- The leftmost and rightmost derivations for a *sentential form* may differ, even in an unambiguous grammar
  - However, they must have the same parse tree!

Classic example — the if-then-else problem

$$\begin{array}{l} \text{Stmt} \rightarrow \text{if Expr then Stmt} \\ \quad \quad | \text{if Expr then Stmt else Stmt} \\ \quad \quad | \text{... other stmts ...} \end{array}$$

*This ambiguity is inherent in the grammar*


# Ambiguity

$Stmt \rightarrow$  if Expr then Stmt  
 | if Expr then Stmt else Stmt  
 Stmt  
 |  
 ... other stmts ...

This sentential form has two derivations


if Expr<sub>1</sub> then if Expr<sub>2</sub> then Stmt<sub>1</sub> else Stmt<sub>2</sub>

if Expr<sub>1</sub> then  
if Expr<sub>2</sub> then Stmt<sub>1</sub>  
else Stmt<sub>2</sub>



production 2, then  
production 1

if Expr<sub>1</sub> then  
if Expr<sub>2</sub> then Str  
else Stmt<sub>2</sub>



production 1, then  
production 2

The grammar forces the structure  
to match the desired meaning.

# Ambiguity

## Removing the ambiguity

- Must rewrite the grammar to avoid generating the problem
- Match each else to innermost unmatched if (*common sense rule*)

0	<i>Stmt</i>	→	<u>if</u> <i>Expr</i> <u>then</u> <i>Stmt</i>
1			<u>if</u> <i>Expr</i> <u>then</u> <i>WithElse</i> <u>else</u> <i>Stmt</i>
2			<i>Other Statements</i>
3	<i>WithElse</i>	→	<u>if</u> <i>Expr</i> <u>then</u> <i>WithElse</i> <u>else</u> <i>WithElse</i>
4			<i>Other Statements</i>

With this grammar, example has only one rightmost derivation

Intuition: once into *WithElse*, we cannot generate an unmatched else

# No Ambiguity

if  $Expr_1$  then if  $Expr_2$  then  $Stmt_1$  else  $Stmt_2$

Rule	Sentential Form
—	$Stmt$
0	<u>if</u> $Expr$ <u>then</u> $Stmt$
1	<u>if</u> $Expr$ <u>then</u> <u>if</u> $Expr$ <u>then</u> $WithElse$ <u>else</u> $Stmt$
2	<u>if</u> $Expr$ <u>then</u> <u>if</u> $Expr$ <u>then</u> $WithElse$ <u>else</u> $S_2$
4	<u>if</u> $Expr$ <u>then</u> <u>if</u> $Expr$ <u>then</u> $S_1$ <u>else</u> $S_2$
?	<u>if</u> $Expr$ <u>then</u> <u>if</u> $E_2$ <u>then</u> $S_1$ <u>else</u> $S_2$
?	<u>if</u> $E_1$ <u>then</u> <u>if</u> $E_2$ <u>then</u> $S_1$ <u>else</u> $S_2$

Other productions to derive  $Exprs$

This grammar has only one rightmost derivation for the example



# No Ambiguity

if  $Expr_1$  then if  $Expr_2$  then  $Stmt_1$  else  $Stmt_2$

Rule	Sentential Form
—	$Stmt$
1	<u>if</u> $Expr$ <u>then</u> $WithElse$ <u>else</u> $Stmt$
2	<u>if</u> $Expr$ <u>then</u> $WithElse$ <u>else</u> $S_2$
4	<u>if</u> $Expr$ <u>then</u> $S_1$ <u>else</u> $S_2$
No derivation possible, with rule 1	

This grammar has only one rightmost derivation for the example


# Parsing

---

- We can derive sentences that are in our language  $L(G)$  for our grammar  $G$
- Compiler must infer a derivation for a given input string
- Parsing: Constructing a derivation from a specific input sentence

- Input: a stream of  $\langle \text{ident}, x \rangle - \langle \text{num}, 2 \rangle \times \langle \text{ident}, y \rangle$  syntactic categories (returned from the scanner)

- Output
  - Derivation for the input program  $\rightarrow$  Building a parse tree
  - Indication that the input is not a valid program



# Parsing Techniques

---

## *Top-down parsers (LL(1), recursive descent)*

- Start at the root of the parse tree and grow toward leaves
- Pick a production & try to match the input
- Bad “pick”  $\Rightarrow$  may need to backtrack
- Some grammars are backtrack-free

## *Bottom-up parsers (LR(1), operator precedence)*

- Start at the leaves and grow toward root
- As input is consumed, encode possibilities in an internal state
- Start in a state valid for legal first tokens
- Bottom-up parsers handle a large class of grammars

# Top-down Parsing

---

A top-down parser starts with the root of the parse tree

The root node is labeled with the goal symbol of the grammar

Top-down parsing algorithm:

Construct the root node of the parse tree

Repeat until lower fringe of the parse tree matches the input string  
(the input stream has been exhausted)

- 1 At a node labeled  $A$ , select a production with  $A$  on its lhs and, for each symbol on its rhs, construct the appropriate child
- 2 When a terminal symbol is added and it doesn't match the fringe, backtrack
- 3 Find the next node to be expanded ( $label \in NT$ )

The key is picking the right production in step 1

- *That choice should be guided by the input string*

# Classic Expression Grammar

---

0	<i>Goal</i>	$\rightarrow$	<i>Expr</i>
1	<i>Expr</i>	$\rightarrow$	<i>Expr</i> + <i>Term</i>
2			<i>Expr</i> - <i>Term</i>
3			<i>Term</i>
4	<i>Term</i>	$\rightarrow$	<i>Term</i> * <i>Factor</i>
5			<i>Term</i> / <i>Factor</i>
6			<i>Factor</i>
7	<i>Factor</i>	$\rightarrow$	( <i>Expr</i> )
8			<u>number</u>
9			<u>id</u>

And the input  $x - 2 * y$

# Example

Let's try  $x - 2 * y$ :

Rule	Sentential Form	Input
—	Goal	$\uparrow x - 2 * y$

Goal


0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			<u>number</u>
9			<u>id</u>

$\uparrow$  is the position in the input buffer

# Example

Let's try  $x - 2 * y$ :

Rule	Sentential Form	Input
—	Goal	$\uparrow x - 2 * y$
0	Expr	$\uparrow x - 2 * y$
1	Expr + Term	$\uparrow x - 2 * y$
3	Term + Term	$\uparrow x - 2 * y$
6	Factor + Term	$\uparrow x - 2 * y$
9	$\langle id, x \rangle + Term$	$\uparrow x - 2 * y$
→	$\langle id, x \rangle + Term$	$x \uparrow - 2 * y$



0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			<u>number</u>
9			<u>id</u>

This worked well, except that “-” doesn’t match “+”


backtrack

The parser must

# Example

Continuing with  $x - 2 * y$  :

Rule	Sentential Form	Input
—	Goal	$\uparrow x - 2 * y$
0	Expr	$\uparrow x - 2 * y$
2	Expr - Term	$\uparrow x - 2 * y$
3	Term - Term	$\uparrow x - 2 * y$
6	Factor - Term	$\uparrow x - 2 * y$
9	$\langle id, x \rangle$ - Term	$\uparrow x - 2 * y$
→	$\langle id, x \rangle$ - Term	$x \uparrow - 2 * y$
→	$\langle id, x \rangle$ - Term	$x - \uparrow 2 * y$



0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			<u>number</u>
9			<u>id</u>

Now, "-" and "-" match

Now we can expand Term to match "2"


⇒ Now, we need to expand Term - the last NT on the fringe



# Example

Trying to match the "2" in  $x - 2 * y$ :

Rule	Sentential Form	Input
→	$\langle id, x \rangle - Term$	$x - \uparrow 2 * y$
6	$\langle id, x \rangle - Factor$	$x - \uparrow 2 * y$
8	$\langle id, x \rangle - \langle num, 2 \rangle$	$x - \uparrow 2 * y$
→	$\langle id, x \rangle - \langle num, 2 \rangle$	$x - 2 \uparrow * y$



0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			number
9			id


Where are we?

- "2" matches "2"
  - We have more input, but no NTs left to expand
  - The expansion terminated too soon
- ⇒ Need to backtrack

# Example

Trying again with "2" in  $x - 2 * y$  :

Rule	Sentential Form	Input
→	$\langle id, x \rangle - Term$	$x - \uparrow 2 * y$
4	$\langle id, x \rangle - Term * Factor$	$x - \uparrow 2 * y$
6	$\langle id, x \rangle - Factor * Factor$	$x - \uparrow 2 * y$
8	$\langle id, x \rangle - \langle num, 2 \rangle * Factor$	$x - \uparrow 2 * y$
→	$\langle id, x \rangle - \langle num, 2 \rangle * Factor$	$x - 2 \uparrow * y$
→	$\langle id, x \rangle - \langle num, 2 \rangle * Factor$	$x - 2 * \uparrow y$
9	$\langle id, x \rangle - \langle num, 2 \rangle * \langle id, y \rangle$	$x - 2 * \uparrow y$
→	$\langle id, x \rangle - \langle num, 2 \rangle * \langle id, y \rangle$	$x - 2 * y \uparrow$



0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			number
9			id

The Point:

- ⇒ The parser must make the right choice when it expands a NT.
- Wrong choices lead to wasted effort.

## Another Possible Parse

Other choices for expansion are possible

Rule	Sentential Form	Input
—	Goal	$\uparrow x - \underline{2} * y$
0	Expr	$\uparrow x - \underline{2} * y$
1	Expr + Term	$\uparrow x - \underline{2} * y$
1	Expr + Term + Term	$\uparrow x - \underline{2} * y$
1	Expr + Term + Term + Term	$\uparrow x - \underline{2} * y$
1	And so on ....	$\uparrow x - \underline{2} * y$

Consumes no input!

0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			<u>number</u>
9			<u>id</u>

This expansion doesn't terminate

- Wrong choice of expansion leads to non-termination
- Non-termination is a bad property for a parser to have
- Parser must make the right choice

# Complications in Top-Down Parsing

---

- Grammars with left-recursion cause termination problems
  - Eliminate left recursion
- Choosing the wrong expansion necessitates backtracking
  - Eliminate the need to backtrack

# Left Recursion

*Top-down parsers cannot handle left-recursive grammars*

Formally,

A grammar is *left recursive* if  $\exists A \in NT$  such that  
 $\exists$  a derivation  $A \Rightarrow^+ A\alpha$ , for some string  $\alpha \in (NT \cup \Sigma)^*$

If the first symbol on its right-hand side is the same  
as the symbol on its left-hand side

0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	( Expr )
8			<u>number</u>
9			<u>id</u>

Our classic expression grammar is left recursive

- This can lead to non-termination in a top-down parser
- In a top-down parser, any recursion must be right recursion
- We would like to convert the left recursion to right recursion

*Non-termination is always a bad property in a compiler*

# Eliminating Left Recursion

---

To remove left recursion, we can transform the grammar

Consider a grammar fragment of the form

$$\begin{array}{l} X \rightarrow X \alpha \\ \quad | \beta \end{array}$$

where neither  $\alpha$  nor  $\beta$  start with  $X$

We can rewrite this fragment as

$$\begin{array}{l} X \rightarrow \beta X' \\ X' \rightarrow \alpha X' \\ \quad | \epsilon \end{array}$$

where  $X'$  is a new non-terminal

The new grammar defines the same language as the old grammar, using only right recursion.

Added a reference to the empty string

# Eliminating Left Recursion

---

The expression grammar contains two cases of left recursion

$$\begin{array}{ll} \text{Expr} & \rightarrow \text{Expr} + \text{Term} \\ & | \text{Expr} - \text{Term} \\ & | \text{Term} \end{array} \qquad \begin{array}{ll} \text{Term} & \rightarrow \text{Term} * \text{Factor} \\ & | \text{Term} / \text{Factor} \\ & | \text{Factor} \end{array}$$

Applying the transformation yields

$$\begin{array}{ll} \text{Expr} & \rightarrow \text{Term } \text{Expr}' \\ \text{Expr}' & \rightarrow + \text{Term } \text{Expr}' \\ & | - \text{Term } \text{Expr}' \\ & | \varepsilon \end{array} \qquad \begin{array}{ll} \text{Term} & \rightarrow \text{Factor } \text{Term}' \\ \text{Term}' & \rightarrow * \text{Factor } \text{Term}' \\ & | / \text{Factor } \text{Term}' \\ & | \varepsilon \end{array}$$

These fragments use only right recursion

# Eliminating Left Recursion

Substituting them back into the grammar yields

0	<i>Goal</i>	$\rightarrow$	<i>Expr</i>
1	<i>Expr</i>	$\rightarrow$	<i>Term Expr'</i>
2	<i>Expr'</i>	$\rightarrow$	$+ \textit{Term Expr'}$
3		$ $	$- \textit{Term Expr'}$
4		$ $	$\epsilon$
5	<i>Term</i>	$\rightarrow$	<i>Factor Term'</i>
6	<i>Term'</i>	$\rightarrow$	$* \textit{Factor Term'}$
7		$ $	$/ \textit{Factor Term'}$
8		$ $	$\epsilon$
9	<i>Factor</i>	$\rightarrow$	$( \textit{Expr} )$
10		$ $	<u>number</u>
11		$ $	<u>id</u>

- This grammar is correct, if somewhat non-intuitive.
- It is left associative, as was the original
  - $\Rightarrow$  The naïve transformation yields a right recursive grammar, which changes the implicit associativity
- A top-down parser will terminate using it.
- A top-down parser may need to backtrack with it.



# Right-Recursive Expression Grammar

Let's try  $x - 2 * y$ :

Rule	Sentential Form	Input
	<i>Expr</i>	↑ $x - 2 * y$
1	<i>Term Expr'</i>	↑ $x - 2 * y$
5	<i>Factor Term' Expr'</i>	↑ $x - 2 * y$
11	<i>ident Term' Expr'</i>	↑ $x - 2 * y$
→	<i>ident Term' Expr'</i>	$x$ ↑ $- 2 * y$
8	<i>ident Expr'</i>	$x$ ↑ $- 2 * y$
3	<i>ident - Term Expr'</i>	$x$ ↑ $- 2 * y$
→	<i>ident - Term Expr'</i>	$x -$ ↑ $2 * y$
5	<i>ident - Factor Term' Expr'</i>	$x -$ ↑ $2 * y$
10	<i>ident - num Term' Expr'</i>	$x -$ ↑ $2 * y$
→	<i>ident - num Term' Expr'</i>	$x - 2$ ↑ $* y$
6	<i>ident - num × Factor Term' Expr'</i>	$x - 2$ ↑ $* y$
→	<i>ident - num × Factor Term' Expr'</i>	$x - 2 *$ ↑ $y$
11	<i>ident - num × ident Term' Expr'</i>	$x - 2 *$ ↑ $y$
→	<i>ident - num × ident Term' Expr'</i>	$x - 2 * y$ ↑
8	<i>ident - num × ident Expr'</i>	$x - 2 * y$ ↑
4	<i>ident - num × ident</i>	$x - 2 * y$ ↑

0	<i>Goal</i>	→	<i>Expr</i>
1	<i>Expr</i>	→	<i>Term Expr'</i>
2	<i>Expr'</i>	→	$+$ <i>Term Expr'</i>
3			$-$ <i>Term Expr'</i>
4			$\epsilon$
5	<i>Term</i>	→	<i>Factor Term'</i>
6	<i>Term'</i>	→	$*$ <i>Factor Term'</i>
7			$/$ <i>Factor Term'</i>
8			$\epsilon$
9	<i>Factor</i>	→	$($ <i>Expr</i> $)$
10			<u>number</u>
11			<u>id</u>

⇒ Parse with no backtracking for this case

⇒ Parser can always make the correct choice by comparing the next word in the input stream

# Picking the "Right" Production

---

*If it picks the wrong production, a top-down parser may backtrack  
Alternative is to look ahead in input & use context to pick correctly*

How much lookahead is needed?

- In general, an arbitrarily large amount
- Use the Cocke-Younger, Kasami algorithm or Earley's algorithm

Fortunately,

- Large subclasses of CFGs can be parsed with limited lookahead
- Most programming language constructs fall in those subclasses

Among the interesting subclasses are  $LL(1)$  and  $LR(1)$  grammars

*We will focus on  $LL(1)$  grammars & predictive parsing*

# Predictive Parsing

## Basic idea

*Given  $A \rightarrow \alpha \mid \beta$ , the parser should be able to choose between  $\alpha$  and  $\beta$*

## FIRST sets

For some rhs  $\alpha \in G$ , define **FIRST( $\alpha$ )** as the set of tokens that appear as the first symbol in some string derived from  $\alpha$

For the terminals, + and -, their FIRST sets contain exactly one element—the symbol itself

0	Goal	→	Expr
1	Expr	→	Term Expr'
2	Expr'	→	+ Term Expr'
3			- Term Expr'
4			$\epsilon$
5	Term	→	Factor Term'
6	Term'	→	* Factor Term'
7			/ Factor Term'
8			$\epsilon$
9	Factor	→	( Expr )
10			<u>number</u>
11			<u>id</u>

# Predictive Parsing

---

What about  $\epsilon$ -productions?

The parser must compare the next word against the set of symbols that can appear immediately to the right of the  $\epsilon$  (or, equivalently, to the right of the Expr')

The set of symbols that can be derived from any symbol that follows Expr' in the rhs of some production

If  $A \rightarrow \alpha$  and  $A \rightarrow \beta$  and  $\epsilon \in \text{FIRST}(\alpha)$ , then we need to ensure that  $\text{FIRST}(\beta)$  is disjoint from  $\text{FOLLOW}(A)$ , where

$\text{FOLLOW}(A)$  = the set of terminal symbols that can immediately follow  $A$  in a sentential form

Define  $\text{FIRST}^+(A \rightarrow \alpha)$  as

- $\text{FIRST}(\alpha) \cup \text{FOLLOW}(A)$ , if  $\epsilon \in \text{FIRST}(\alpha)$
- $\text{FIRST}(\alpha)$ , otherwise

Then, a grammar is  $LL(1)$  iff  $A \rightarrow \alpha$  and  $A \rightarrow \beta$  implies

$$\text{FIRST}^+(A \rightarrow \alpha) \cap \text{FIRST}^+(A \rightarrow \beta) = \emptyset$$

# Predictive Parsing

Given a grammar that has the  $LL(1)$  property

- Can write a simple routine to recognize each *lhs*
- Code is both simple & fast

Consider  $A \rightarrow \beta_1 \mid \beta_2 \mid \beta_3$ , with  
 $\text{FIRST}^+(A \rightarrow \beta_i) \cap \text{FIRST}^+(A \rightarrow \beta_j) = \emptyset$  if  $i \neq j$

```
/* find an A */  
if (current_word  $\in$  FIRST( $A \rightarrow \beta_1$ ))  
    find a  $\beta_1$  and return true  
else if (current_word  $\in$  FIRST( $A \rightarrow \beta_2$ ))  
    find a  $\beta_2$  and return true  
else if (current_word  $\in$  FIRST( $A \rightarrow \beta_3$ ))  
    find a  $\beta_3$  and return true  
else  
    report an error and return false
```

Grammars with the  $LL(1)$  property are called predictive grammars because the parser can "predict" the correct expansion at each point in the parse.

Parsers that capitalize on the  $LL(1)$  property are called predictive parsers.

One kind of predictive parser is the recursive descent parser.

# Recursive Descent Parsing - An LL(1) Parser

---

Recall the expression grammar, after transformation

0	<i>Goal</i>	$\rightarrow$	<i>Expr</i>
1	<i>Expr</i>	$\rightarrow$	<i>Term Expr'</i>
2	<i>Expr'</i>	$\rightarrow$	$+ \textit{Term Expr'}$
3		$ $	$- \textit{Term Expr'}$
4		$ $	$\epsilon$
5	<i>Term</i>	$\rightarrow$	<i>Factor Term'</i>
6	<i>Term'</i>	$\rightarrow$	$* \textit{Factor Term'}$
7		$ $	$/ \textit{Factor Term'}$
8		$ $	$\epsilon$
9	<i>Factor</i>	$\rightarrow$	$( \textit{Expr} )$
10		$ $	<u>number</u>
11		$ $	<u>id</u>

This produces a parser with six mutually recursive routines:

- *Goal*
- *Expr*
- *EPrime*
- *Term*
- *TPrime*
- *Factor*

Each recognizes one *NT* or *T*

The term descent refers to the direction in which the parse tree is built.

# Recursive Descent Parsing

# (Procedural)

## Routines from the expression parser

*Main()*

```
/* Goal → Expr */
word ← NextWord();
if (Expr() and word = eof)
    then proceed to the next step
    else return false
```

*Expr()*

```
/* Expr → Term Expr' */
if (Term() = false)
    then return false
    else return EPrime()
```

*EPrime()*

```
/* Expr' → + Term Expr' */
/* Expr' → - Term Expr' */
if (word = + or word = -) then
    word ← NextWord()
    if (Term() = false)
        then return false
        else return EPrime()
/* Expr' → ε */
return true
```

*Term()*

```
/* Term → Factor Term' */
if (Factor() = false)
    then return false
    else return TPrime()
```

*TPrime()*

```
/* Term' → × Factor Term' */
/* Term' → ÷ Factor Term' */
if (word = × or word = ÷) then
    word ← NextWord()
    if (Factor() = false)
        then return false
        else return TPrime()
/* Term' → ε */
return true
```

*Factor()*

```
/* Factor → ( Expr ) */
if (word = ( ) then
    word ← NextWord()
    if (Expr() = false)
        then return false
        else if (word ≠ ) ) then
            report syntax error
            return false
/* Factor → num */
/* Factor → ident */
else if (word ≠ num and
        word ≠ ident) then
    report syntax error
    return false
word ← NextWord()
return true
```

0	Goal	→	Expr
1	Expr	→	Term Expr'
2	Expr'	→	+ Term Expr'
3			- Term Expr'
4			ε
5	Term	→	Factor Term'
6	Term'	→	* Factor Term'
7			/ Factor Term'
8			ε
9	Factor	→	( Expr )
10			<u>number</u>
11			<u>id</u>

# Classic Expression Grammar

0	<i>Goal</i>	$\rightarrow$	<i>Expr</i>
1	<i>Expr</i>	$\rightarrow$	<i>Term Expr'</i>
2	<i>Expr'</i>	$\rightarrow$	$+$ <i>Term Expr'</i>
3		$ $	$-$ <i>Term Expr'</i>
4		$ $	$\epsilon$
5	<i>Term</i>	$\rightarrow$	<i>Factor Term'</i>
6	<i>Term'</i>	$\rightarrow$	$*$ <i>Factor Term'</i>
7		$ $	$/$ <i>Factor Term'</i>
8		$ $	$\epsilon$
9	<i>Factor</i>	$\rightarrow$	<u>number</u>
10		$ $	<u>id</u>
11		$ $	$($ <i>Expr</i> $)$

$\text{FIRST}^+(A \rightarrow \beta)$  is identical to  $\text{FIRST}(\beta)$  except for productions 4 and 8

$\text{FIRST}^+(\text{Expr}' \rightarrow \epsilon)$  is  $\{\epsilon, ), \text{eof}\}$

$\text{FIRST}^+(\text{Term}' \rightarrow \epsilon)$  is  $\{\epsilon, +, -, ), \text{eof}\}$

Symbol	FIRST	FOLLOW
<u>num</u>	<u>num</u>	$\emptyset$
<u>id</u>	<u>id</u>	$\emptyset$
$+$	$+$	$\emptyset$
$-$	$-$	$\emptyset$
$*$	$*$	$\emptyset$
$/$	$/$	$\emptyset$
$($	$($	$\emptyset$
$)$	$)$	$\emptyset$
<u>eof</u>	<u>eof</u>	$\emptyset$
$\epsilon$	$\epsilon$	$\emptyset$
<i>Goal</i>	$(, \text{id}, \text{num}$	$\text{eof}$
<i>Expr</i>	$(, \text{id}, \text{num}$	$), \text{eof}$
<i>Expr'</i>	$+, -, \epsilon$	$), \text{eof}$
<i>Term</i>	$(, \text{id}, \text{num}$	$+, -, ), \text{eof}$
<i>Term'</i>	$*, /, \epsilon$	$+, -, ), \text{eof}$
<i>Factor</i>	$(, \text{id}, \text{num}$	$+, -, *, /, ), \text{eof}$



# Classic Expression Grammar

0	<i>Goal</i>	$\rightarrow$	<i>Expr</i>
1	<i>Expr</i>	$\rightarrow$	<i>Term Expr'</i>
2	<i>Expr'</i>	$\rightarrow$	$+ \text{Term Expr'}$
3		$ $	$- \text{Term Expr'}$
4		$ $	$\epsilon$
5	<i>Term</i>	$\rightarrow$	<i>Factor Term'</i>
6	<i>Term'</i>	$\rightarrow$	$* \text{Factor Term'}$
7		$ $	$/ \text{Factor Term'}$
8		$ $	$\epsilon$
9	<i>Factor</i>	$\rightarrow$	<u>number</u>
10		$ $	<u>id</u>
11		$ $	$( \text{Expr} )$

Prod'n	FIRST+
0	$(, \underline{\text{id}}, \underline{\text{num}}$
1	$(, \underline{\text{id}}, \underline{\text{num}}$
2	$+$
3	$-$
4	$\epsilon, ), \text{eof}$
5	$(, \underline{\text{id}}, \underline{\text{num}}$
6	$*$
7	$/$
8	$\epsilon, +, -, ), \text{eof}$
9	<u>number</u>
10	<u>id</u>
11	$($

# Building Top-down Parsers for LL(1) Grammars

---

Given an *LL(1)* grammar, and its FIRST & FOLLOW sets ...

- Emit a routine for each non-terminal
  - Nest of if-then-else statements to check alternate rhs's
  - Each returns true on success and throws an error on false
  - Simple, working (*perhaps ugly*) code
- This automatically constructs a recursive-descent parser

Improving matters

- Nest of if-then-else statements may be slow
  - Good case statement implementation would be better
- What about a table to encode the options?
  - Interpret the table with a skeleton, as we did in scanning

# Parsing Techniques

---

## *Top-down parsers (LL(1), recursive descent)*

- Start at the root of the parse tree and grow toward leaves
- Pick a production & try to match the input
- Bad “pick”  $\Rightarrow$  may need to backtrack
- Some grammars are backtrack-free

## *Bottom-up parsers (LR(1), operator precedence)*

- Start at the leaves and grow toward root
- As input is consumed, encode possibilities in an internal state
- Start in a state valid for legal first tokens
- Bottom-up parsers handle a large class of grammars

# Summary


---

	<i>Advantages</i>	<i>Disadvantages</i>
<i>Top-down Recursive descent, LL(1)</i>	Fast Good locality Simplicity Good error detection	Hand-coded High maintenance Right associativity
<i>LR(1)</i>	Fast Deterministic langs. Automatable Left associativity	Large working sets Poor error messages Large table sizes

# Abstract Syntax Tree

---

An abstract syntax tree is the procedure's parse tree with the nodes for most non-terminal nodes removed



- Can use linearized form of the tree
    - Easier to manipulate than pointers
- x 2 y \* - in postfix form  
- \* 2 y x in prefix form

# References

---

Chapter sections from the book:

- 3.1, 3.2, 3.3

Selected videos from compiler course from California State University:

- [https://www.youtube.com/watch?v=a4H30Af55No&list=PL6KMWPQP\\_DM97HhOPYNgJord-sANFTI3i&index=13](https://www.youtube.com/watch?v=a4H30Af55No&list=PL6KMWPQP_DM97HhOPYNgJord-sANFTI3i&index=13)
- [https://www.youtube.com/watch?v=HXN2AGMRZWg&list=PL6KMWPQP\\_DM97HhOPYNgJord-sANFTI3i&index=14](https://www.youtube.com/watch?v=HXN2AGMRZWg&list=PL6KMWPQP_DM97HhOPYNgJord-sANFTI3i&index=14)
- [https://www.youtube.com/watch?v=IAXJ3j2tB\\_Q&list=PL6KMWPQP\\_DM97HhOPYNgJord-sANFTI3i&index=15](https://www.youtube.com/watch?v=IAXJ3j2tB_Q&list=PL6KMWPQP_DM97HhOPYNgJord-sANFTI3i&index=15)
- [https://www.youtube.com/watch?v=Twv3q5NNPtM&list=PL6KMWPQP\\_DM97HhOPYNgJord-sANFTI3i&index=18](https://www.youtube.com/watch?v=Twv3q5NNPtM&list=PL6KMWPQP_DM97HhOPYNgJord-sANFTI3i&index=18)

Kaleidoscope Parser

- <https://llvm.org/docs/tutorial/MyFirstLanguageFrontend/LangImpl02.html>