

## DSA Practice Question Set - 9

### 1)Valid Palindrome :

A phrase is a palindrome if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers.

Given a string *s*, return true *if it is a palindrome*, or false *otherwise*.

#### Example 1:

**Input:** *s* = "A man, a plan, a canal: Panama"

**Output:** true

**Explanation:** "amanaplanacanalpanama" is a palindrome.

#### Example 2:

**Input:** *s* = "race a car"

**Output:** false

**Explanation:** "raceacar" is not a palindrome.

#### Example 3:

**Input:** *s* = " "

**Output:** true

**Explanation:** *s* is an empty string "" after removing non-alphanumeric characters.

Since an empty string reads the same forward and backward, it is a palindrome.


#### Program :

```
class Solution {  
    public boolean isPalindrome(String s) {  
        List<Character> input = new ArrayList<>();
```

```
for(char c : s.toLowerCase().toCharArray()){
    if (Character.isLetterOrDigit(c)){
        input.add(c);
    }
}
int left = 0;
int right = input.size()-1;
if(right<=0){
    return true;
}

while(left<right){
    if(input.get(left)!=input.get(right)){
        return false;
    }
    left++;
    right--;
}
return true;
}
}
```

**Output :**



**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

## 2) Is Subsequence

Given two strings  $s$  and  $t$ , return true *if  $s$  is a subsequence of  $t$ , or false otherwise.*

A subsequence of a string is a new string that is formed from the original string by deleting some (can be none) of the characters without disturbing the relative positions of the remaining characters. (i.e., "ace" is a subsequence of "abcde" while "aec" is not).

### Example 1:

**Input:**  $s = \text{"abc"}, t = \text{"ahbgdc"}$

**Output:** true

### Example 2:

**Input:** s = "axc", t = "ahbgdc"

**Output:** false

**Constraints:**

- $0 \leq s.length \leq 100$
- $0 \leq t.length \leq 104$
- s and t consist only of lowercase English letters.

**Follow up:** Suppose there are lots of incoming s, say s1, s2, ..., sk where  $k \geq 109$ , and you want to check one by one to see if t has its subsequence. In this scenario, how would you change your code?

**Program :**

```
class Solution {
    public boolean isSubsequence(String s, String t) {
        int i = 0;
        int j = 0;

        while(i < s.length() && j < t.length()){
            if(t.charAt(j) == s.charAt(i) ){
                i++;
            }
            j++;
        }

        return i == s.length();
    }
}
```

**Output :**

```
Accepted Runtime: 0 ms
• Case 1 • Case 2
Input
s =
"abc"
t =
"ahbgdc"
Output
true
Expected
true
```

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

### 3)TwoSum II

Given a 1-indexed array of integers numbers that is already *sorted in non-decreasing order*, find two numbers such that they add up to a specific target number. Let these two numbers be numbers[index1] and numbers[index2] where  $1 \leq \text{index1} < \text{index2} \leq \text{numbers.length}$ .

Return *the indices of the two numbers, index1 and index2, added by one as an integer array [index1, index2] of length 2.*

The tests are generated such that there is exactly one solution. You may not use the same element twice.

Your solution must use only constant extra space.

#### Example 1:

**Input:** numbers = [2,7,11,15], target = 9

**Output:** [1,2]

**Explanation:** The sum of 2 and 7 is 9. Therefore, index1 = 1, index2 = 2. We return [1, 2].

**Example 2:**

**Input:** numbers = [2,3,4], target = 6

**Output:** [1,3]

**Explanation:** The sum of 2 and 4 is 6. Therefore index1 = 1, index2 = 3. We return [1, 3].

**Example 3:**

**Input:** numbers = [-1,0], target = -1

**Output:** [1,2]

**Explanation:** The sum of -1 and 0 is -1. Therefore index1 = 1, index2 = 2. We return [1, 2].

**Program :**

```
class Solution {
    public int[] twoSum(int[] numbers, int target) {
        HashMap<Integer,Integer> map = new HashMap<>();

        for(int i = 0;i<numbers.length;i++){
            int complement = target - numbers[i];

            if(map.containsKey(complement)){
                return new int[] {map.get(complement),i+1};
            }
            map.put(numbers[i],i+1);
        }
        return new int[numbers.length];
    }
}
```

**Output :**

```
Accepted Runtime: 0 ms
• Case 1 • Case 2 • Case 3
Input
numbers =
[2, 7, 11, 15]
target =
9
Output
[1, 2]
Expected
[1, 2]
```

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

#### **4)Container with Most Water :**


You are given an integer array height of length n. There are n vertical lines drawn such that the two endpoints of the ith line are (i, 0) and (i, height[i]).

Find two lines that together with the x-axis form a container, such that the container contains the most water.

Return *the maximum amount of water a container can store.*

Notice that you may not slant the container.

**Example 1:**



**Input:** height = [1,8,6,2,5,4,8,3,7]

**Output:** 49

**Explanation:** The above vertical lines are represented by array [1,8,6,2,5,4,8,3,7]. In this case, the max area of water (blue section) the container can contain is 49.

**Example 2:**

**Input:** height = [1,1]

**Output:** 1

**Program :**

```
class Solution {
    public int maxArea(int[] height) {
        int left = 0;
        int right = height.length-1;
        int area = 0;

        while (left<right){
            int aea = Math.min(height[left],height[right])*(right-left);
            area = Math.max(area,aea);
            if(height[left]<height[right]){
                left+=1;
            }
        }
    }
}
```



```

        }else{
            right-=1;
        }

    }
    return area;
}
}

```

**Output :**

**Accepted** Runtime: 0 ms

• Case 1 • Case 2

Input

height =  
[1,8,6,2,5,4,8,3,7]

Output

49

Expected

49

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

### 5)3Sum :

Given an integer array nums, return all the triplets  $[nums[i], nums[j], nums[k]]$  such that  $i \neq j$ ,  $i \neq k$ , and  $j \neq k$ , and  $nums[i] + nums[j] + nums[k] == 0$ .

Notice that the solution set must not contain duplicate triplets.

#### Example 1:

**Input:** `nums = [-1,0,1,2,-1,-4]`

**Output:** `[[-1,-1,2],[-1,0,1]]`

#### Explanation:

$\text{nums}[0] + \text{nums}[1] + \text{nums}[2] = (-1) + 0 + 1 = 0.$

$\text{nums}[1] + \text{nums}[2] + \text{nums}[4] = 0 + 1 + (-1) = 0.$

$\text{nums}[0] + \text{nums}[3] + \text{nums}[4] = (-1) + 2 + (-1) = 0.$

The distinct triplets are `[-1,0,1]` and `[-1,-1,2]`.

**Notice that the order of the output and the order of the triplets does not matter.**

#### Example 2:

**Input:** `nums = [0,1,1]`

**Output:** `[]`

**Explanation:** The only possible triplet does not sum up to 0.

#### Example 3:

**Input:** `nums = [0,0,0]`

**Output:** `[[0,0,0]]`

**Explanation:** The only possible triplet sums up to 0.

#### Program :

```
import java.util.*;
```

```
class Solution {
```

```
    public List<List<Integer>> threeSum(int[] nums) {
```

```
        List<List<Integer>> three = new ArrayList<>();
```

```
        Arrays.sort(nums);
```

```
        for (int i = 0; i < nums.length - 2; i++) {
```

```
            if (i > 0 && nums[i] == nums[i - 1]) {
```

```

        continue;
    }

    int j = i + 1;
    int k = nums.length - 1;

    while (j < k) {
        int sum = nums[i] + nums[j] + nums[k];

        if (sum == 0) {
            three.add(Arrays.asList(nums[i], nums[j], nums[k]));

            while (j < k && nums[j] == nums[j + 1]) {
                j++;
            }
            while (j < k && nums[k] == nums[k - 1]) {
                k--;
            }

            j++;
            k--;
        } else if (sum < 0) {
            j++;
        } else {
            k--;
        }
    }
}

return three;
}
}

```

## Output :

Accepted Runtime: 0 ms

• Case 1 • Case 2 • Case 3

Input


```
nums =  
[-1,0,1,2,-1,-4]
```

Output

```
[[-1,-1,2], [-1,0,1]]
```

Expected

```
[[-1,-1,2], [-1,0,1]]
```

 Contribute to the solution

## 6) Minimize Subarray sum length

Given an array of positive integers *nums* and a positive integer *target*, return *the minimal length of a*

*subarray*

*whose sum is greater than or equal to target*. If there is no such subarray, return 0 instead.

### Example 1:

**Input:** target = 7, nums = [2,3,1,2,4,3]

**Output:** 2

**Explanation:** The subarray [4,3] has the minimal length under the problem constraint.

### Example 2:

**Input:** target = 4, nums = [1,4,4]

**Output:** 1

### Example 3:

Input: target = 11, nums = [1,1,1,1,1,1,1,1]

Output: 0

Program :

```
class Solution {
    public int minSubArrayLen(int target, int[] nums) {
        int left=0,right=0,sum =0;
        int ans = Integer.MAX_VALUE;

        for(right=0;right<nums.length;right++){
            sum +=nums[right];
            while(sum>=target){
                ans=Math.min(ans,right-left+1);
                sum -=nums[left++];
            }

        }
        return ans == Integer.MAX_VALUE ? 0:ans;
    }
}
```

Output :

• Case 1 • Case 2 • Case 3

Input

target =

7

nums =

[2, 3, 1, 2, 4, 3]

Output

2

Expected

2

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

**7) Longest Substring without repeating characters**

**Given a string s, find the length of the longest**

**substring**

**without repeating characters.**

**Example 1:**

**Input: s = "abcabcbb"**

**Output: 3**

**Explanation: The answer is "abc", with the length of 3.**

**Example 2:**

**Input: s = "bbbbbb"**

**Output: 1**

**Explanation:** The answer is "b", with the length of 1.

**Example 3:**

**Input:** s = "pwwkew"

**Output: 3**

**Explanation:** The answer is "wke", with the length of 3.

Notice that the answer must be a substring, "pwke" is a subsequence and not a substring.

**Program :**

```
class Solution {
    public int lengthOfLongestSubstring(String s) {
        int a = 0;
        int b = 0;
        int max = 0;

        HashSet<Character> hash_set = new HashSet<>();

        while(b<s.length()){
            if(!hash_set.contains(s.charAt(b))){
                hash_set.add(s.charAt(b));
                b++;
                max = Math.max(hash_set.size(),max);
            }
            else{
                hash_set.remove(s.charAt(a));
                a++;
            }
        }
    }
}
```

```
        return max;
    }
}
```

**Output :**

Accepted Runtime: 0 ms

• Case 1 • Case 2 • Case 3

Input

```
s =
"abcabcbb"
```

Output

3

Expected

3

 [Contribute a te](#)

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

### 8) Substring with Concatenation of All Words

**You are given a string  $s$  and an array of strings  $words$ . All the strings of  $words$  are of the same length.**

**A concatenated string is a string that exactly contains all the strings of any permutation of  $words$  concatenated.**

- For example, if  $words = ["ab", "cd", "ef"]$ , then "abcdef", "abefcd", "cdabef", "cdefab", "efabcd", and "efcdab" are all concatenated strings. "acdbef" is not a concatenated string because it is not the concatenation of any permutation of  $words$ .



Return an array of *the starting indices* of all the concatenated substrings in **s**. You can return the answer in any order.

**Example 1:**

**Input:** **s = "barfoothefoobarman", words = ["foo","bar"]**

**Output:** **[0,9]**

**Explanation:**

The substring starting at 0 is "barfoo". It is the concatenation of ["bar","foo"] which is a permutation of words.

The substring starting at 9 is "foobar". It is the concatenation of ["foo","bar"] which is a permutation of words.

**Example 2:**

**Input:** **s = "wordgoodgoodgoodbestword", words = ["word","good","best","word"]**

**Output:** **[]**

**Explanation:**

There is no concatenated substring.

**Example 3:**

**Input:** **s = "barfoofoobarthefoobarman", words = ["bar","foo","the"]**

**Output:** **[6,9,12]**

**Explanation:**

The substring starting at 6 is "foobarthe". It is the concatenation of ["foo","bar","the"].

The substring starting at 9 is "barthefoo". It is the concatenation of ["bar","the","foo"].

The substring starting at 12 is "thefoobar". It is the concatenation of ["the","foo","bar"].

**Program :**

```
class Solution {  
  
    public List<Integer> findSubstring(String s, String[] words) {  
  
        Map<String, Integer> dictionary = new HashMap<>();  
  
        Arrays.stream(words).forEach(word -> dictionary.merge(word, 1,  
Integer::sum));  
  
        int simpleWordLength = words[0].length();  
  
        int concatenatedWordLength = simpleWordLength * words.length;  
  
        if (s.length() < concatenatedWordLength) return new ArrayList<>();  
  
        StringBuilder currentWord = new StringBuilder(s.substring(0,  
concatenatedWordLength));  
  
        List<Integer> result = new ArrayList<>();  
  
        for (int i = concatenatedWordLength; i < s.length(); i++) {  
  
            if (containsFullDictionary(currentWord, new  
HashMap<>(dictionary), simpleWordLength))  
  
                result.add(i - concatenatedWordLength);  
  
            currentWord.deleteCharAt(0);  
  
            currentWord.append(s.charAt(i));  
  
        }  
  
        if (containsFullDictionary(currentWord, new HashMap<>(dictionary),  
simpleWordLength))  
  
            result.add(s.length() - concatenatedWordLength);  
  
    }  
}
```

```
        return result;
    }

    private boolean containsFullDictionary(StringBuilder currentWord,
        Map<String, Integer> dictionary, int simpleWordLength) {

        int start = 0;

        int end = simpleWordLength;

        while (start < currentWord.length()) {

            String word = currentWord.substring(start, end);

            if (dictionary.containsKey(word) && dictionary.get(word) > 0)
                dictionary.merge(word, -1, Integer::sum);

            else return false;

            start += simpleWordLength;

            end += simpleWordLength;

        }

        return true;
    }
}
```

**Output:**

```
• Case 1 • Case 2 • Case 3

Input
s =
"barfoothefoobarman"

words =
["foo","bar"]

Output
[0,9]

Expected
[0,9]
```

**Time Complexity :  $O(m*n*k)$**

**Space Complexity :  $O(m*k)$**

### 9)Minimum Window Substring :

Given two strings *s* and *t* of lengths *m* and *n* respectively, return *the minimum window*

*substring*

*of s such that every character in t (including duplicates) is included in the window. If there is no such substring, return the empty string "".*

The testcases will be generated such that the answer is unique.

**Example 1:**

**Input:** *s* = "ADOBECODEBANC", *t* = "ABC"

**Output:** "BANC"

**Explanation:** The minimum window substring "BANC" includes 'A', 'B', and 'C' from string *t*.

### Example 2:

**Input:** s = "a", t = "a"

**Output:** "a"

**Explanation:** The entire string s is the minimum window.

### Example 3:

**Input:** s = "a", t = "aa"

**Output:** ""

**Explanation:** Both 'a's from t must be included in the window.

Since the largest window of s only has one 'a', return empty string.

**Program :**

```
class Solution {  
  
    public String minWindow(String s, String t) {  
  
        if (s == null || t == null || s.length() == 0 || t.length() == 0 ||  
            s.length() < t.length()) {  
  
            return new String();  
        }  
  
        int[] map = new int[128];  
  
        int count = t.length();  
  
        int start = 0, end = 0, minLen = Integer.MAX_VALUE, startIndex = 0;  
  
        /// UPVOTE !  
    }  
}
```

```
for (char c : t.toCharArray()) {  
  
    map[c]++;  
  
}  
  
char[] chS = s.toCharArray();  
  
while (end < chS.length) {  
  
    if (map[chS[end++]]-- > 0) {  
  
        count--;  
  
    }  
  
    while (count == 0) {  
  
        if (end - start < minLen) {  
  
            startIndex = start;  
  
            minLen = end - start;  
  
        }  
  
        if (map[chS[start++]]++ == 0) {  
  
            count++;  
  
        }  
  
    }  
  
}
```

```

return minLen == Integer.MAX_VALUE ? new String() :

    new String(chS, startIndex, minLen);

}

}

```

**Output :**

• Case 1
• Case 2
• Case 3

Input

s =

"ADOBECODEBANC"

t =

"ABC"

Output

"BANC"

Expected

"BANC"

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(1)$**

**10)Valid Parenthesis :**

**Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.**

**An input string is valid if:**

- 1. Open brackets must be closed by the same type of brackets.**
- 2. Open brackets must be closed in the correct order.**

**3. Every close bracket has a corresponding open bracket of the same type.**

**Example 1:**

**Input: s = "()"**

**Output: true**

**Example 2:**

**Input: s = "()[]{}"**

**Output: true**

**Example 3:**

**Input: s = "("**

**Output: false**

**Example 4:**

**Input: s = "([])"**

**Output: true**

**Program :**

```
class Solution {  
  
    public boolean isValid(String s) {  
  
        Stack<Character> st = new Stack<>();  
  
        String open = "({[";  
        String close = ")}]";
```



```

for(int i = 0;i<s.length();i++){

    char current = s.charAt(i);

    if(open.contains(String.valueOf(current))) {

        st.push(current);

    }else{

        if(st.empty() || open.indexOf(st.pop())!=close.indexOf(s.charAt(i)) ){

            return false;

        }

    }

}

return st.empty();

}
}

```

**Output :**

Accepted Runtime: 0 ms

• Case 1 • Case 2 • Case 3 • Case 4

Input

```
s =  
"()"
```

Output

```
true
```

Expected

```
true
```

Time Complexity :  $O(n)$

Space Complexity :  $O(n)$

### 11 ) Simplify Path :

You are given an *absolute* path for a Unix-style file system, which always begins with a slash '/'. Your task is to transform this absolute path into its simplified canonical path.

The *rules* of a Unix-style file system are as follows:

- A single period '.' represents the current directory.
- A double period '..' represents the previous/parent directory.
- Multiple consecutive slashes such as '/' and '/' are treated as a single slash '/'.
- Any sequence of periods that does not match the rules above should be treated as a valid directory or file name. For example, '...' and '....' are valid directory or file names.

The simplified canonical path should follow these *rules*:

- The path must start with a single slash '/'.
- Directories within the path must be separated by exactly one slash '/'.

- The path must not end with a slash '/', unless it is the root directory.
- The path must not have any single or double periods ('.' and '..') used to denote current or parent directories.

**Return the simplified canonical path.**

**Example 1:**

**Input:** path = `"/home/"`

**Output:** `"/home"`

**Explanation:**

The trailing slash should be removed.

**Example 2:**

**Input:** path = `"/home//foo/"`

**Output:** `"/home/foo"`

**Explanation:**

Multiple consecutive slashes are replaced by a single one.

**Example 3:**

**Input:** path = `"/home/user/Documents/../Pictures"`

**Output:** `"/home/user/Pictures"`

**Explanation:**

A double period `".."` refers to the directory up a level (the parent directory).

**Example 4:**

**Input:** path = `"/../"`

**Output:** `"/"`

**Explanation:**

Going one level up from the root directory is not possible.

**Example 5:**

**Input:** path = "/.../a/../../b/c/../../d/.."

**Output:** "/.../b/d"

**Explanation:**

"..." is a valid name for a directory in this problem.

**Program :**

**Output :**

```
//Algo Used: Stack

// TC: O N , SC: O N

public class Solution {

    public static String simplifyPath(String path) {

        Stack<String> stack = new Stack<>();

        // Split the input path by "/"

        String[] components = path.split("/");

        // Traverse each component

        for (String component : components) {

            // Skip empty components and "." (current directory)

            if (component.equals("") || component.equals(".")) {
```

```
        continue;

    }

    // If "..", pop the stack if it's not empty (going back to the parent
directory)

    if (component.equals("..")) {

        if (!stack.isEmpty()) {

            stack.pop();

        }

    } else {

        // Push valid directory names onto the stack

        stack.push(component);

    }

}

// If stack is empty, return "/"

if (stack.isEmpty()) {

    return "/";

}

// Construct the simplified path

StringBuilder result = new StringBuilder();
```

```
for (String dir : stack) {  
  
    result.append("/").append(dir);  
  
}  
  
return result.toString();  
  
}  
}
```

**Time Complexity :**

**O(n)**

**Space Complexity :**

**O(n)**

## **12)Min Stack**

**Design a stack that supports push, pop, top, and retrieving the minimum element in constant time.**

**Implement the MinStack class:**

- **MinStack()** initializes the stack object.
- **void push(int val)** pushes the element val onto the stack.
- **void pop()** removes the element on the top of the stack.
- **int top()** gets the top element of the stack.
- **int getMin()** retrieves the minimum element in the stack.

**You must implement a solution with O(1) time complexity for each function.**

### Example 1:

#### Input

["MinStack","push","push","push","getMin","pop","top","getMin"]

[[],[-2],[0],[-3],[],[],[],[[]]

#### Output

[null,null,null,null,-3,null,0,-2]

#### Explanation

```
MinStack minStack = new MinStack();
```

```
minStack.push(-2);
```

```
minStack.push(0);
```

```
minStack.push(-3);
```

```
minStack.getMin(); // return -3
```

```
minStack.pop();
```

```
minStack.top();    // return 0
```

```
minStack.getMin(); // return -2
```

#### Program :

```
class MinStack {  
  
    int min = Integer.MAX_VALUE;  
  
    Stack<Integer> stack = new Stack<Integer>();  
  
    public void push(int x) {
```

```
// only push the old minimum value when the current  
  
// minimum value changes after pushing the new value x  
  
if(x <= min){  
  
    stack.push(min);  
  
    min=x;  
  
}  
  
stack.push(x);  
  
}  
  
public void pop() {  
  
    // if pop operation could result in the changing of the current minimum  
value,  
  
    // pop twice and change the current minimum value to the last  
minimum value.  
  
    if(stack.pop() == min) min=stack.pop();  
  
}  
  
public int top() {  
  
    return stack.peek();  
  
}
```



```

public int getMin() {

    return min;

}

}

```

**Output :**

Accepted Runtime: 0 ms

- Case 1

Input

```
["MinStack","push","push","push","getMin","pop","top","getMin"]
```

```
[[],[-2],[0],[-3],[],[],[],[ ]]
```

Output

```
[null,null,null,null,-3,null,0,-2]
```

Expected

```
[null,null,null,null,-3,null,0,-2]
```

**Time Complexity :  $O(1)$**

**Space Complexity :  $O(n)$**

**13) Evaluate reverse polished notation :**

**You are given an array of strings tokens that represents an arithmetic expression in a Reverse Polish Notation.**

**Evaluate the expression. Return *an integer that represents the value of the expression*.**

**Note that:**

- The valid operators are '+', '-', '\*', and '/'.
- Each operand may be an integer or another expression.
- The division between two integers always truncates toward zero.
- There will not be any division by zero.
- The input represents a valid arithmetic expression in a reverse polish notation.
- The answer and all the intermediate calculations can be represented in a 32-bit integer.

**Example 1:**

**Input:** tokens = ["2","1","+","3","\*"]

**Output:** 9

**Explanation:**  $((2 + 1) * 3) = 9$

**Example 2:**

**Input:** tokens = ["4","13","5","/","+"]

**Output:** 6

**Explanation:**  $(4 + (13 / 5)) = 6$

**Example 3:**

**Input:** tokens =

["10","6","9","3","+","-11","\*","/","\*","17","+","5","+"]

**Output:** 22

**Explanation:**  $((10 * (6 / ((9 + 3) * -11))) + 17) + 5$

$= ((10 * (6 / (12 * -11))) + 17) + 5$

**= ((10 \* (6 / -132)) + 17) + 5**

**= ((10 \* 0) + 17) + 5**

**= (0 + 17) + 5**

**= 17 + 5**

**= 22**

**Program :**

```
class Solution {  
  
    long resolves(long a, long b, char Operator) {  
  
        if (Operator == '+') return a + b;  
  
        else if (Operator == '-') return a - b;  
  
        else if (Operator == '*') return a * b;  
  
        return a / b;  
  
    }  
  
    public int evalRPN(String[] tokens) {  
  
        Stack<Long> stack = new Stack<>();  
  
        int n = tokens.length;  
  
        for (int i = 0; i < n; i++) {  
  
            if (tokens[i].length() == 1 && tokens[i].charAt(0) < 48) {  
  
                long integer2 = stack.pop();
```

```
        long integer1 = stack.pop();

        char operator = tokens[i].charAt(0);

        long resolvedAns = resolves(integer1, integer2, operator);

        stack.push(resolvedAns);

    } else {

        stack.push(Long.parseLong(tokens[i]));

    }

}

return stack.pop().intValue();

}

}
```

**Output :**

```
Accepted Runtime: 0 ms
• Case 1 • Case 2 • Case 3
Input
tokens =
["2", "1", "+", "3", "*"]
Output
9
Expected
9
```

**Time Complexity : $O(n)$**

**Space Complexity: $O(n)$**

#### **14)Basic Calculator :**

**Given a string  $s$  representing a valid expression, implement a basic calculator to evaluate it, and return *the result of the evaluation*.**

**Note: You are not allowed to use any built-in function which evaluates strings as mathematical expressions, such as `eval()`.**

**Example 1:**

**Input:  $s = "1 + 1"$**

**Output: 2**

**Example 2:**

**Input:  $s = "2-1 + 2 "$**

**Output: 3**

### Example 3:

**Input:** s = "(1+(4+5+2)-3)+(6+8)"

**Output:** 23

**Program :**

```
class Solution {  
  
    public int calculate(String s) {  
  
        int number = 0;  
  
        int signValue = 1;  
  
        int result = 0;  
  
        Stack<Integer> operationsStack = new Stack<>();  
  
        for (int i = 0; i < s.length(); i++) {  
  
            char c = s.charAt(i);  
  
            if (Character.isDigit(c)) {  
  
                number = number * 10 + (c - '0');  
  
            } else if (c == '+' || c == '-') {  
  
                result += number * signValue;  
  
                signValue = (c == '-') ? -1 : 1;  
  
                number = 0;  
  
            }  
  
            if (c == '(') {  
                operationsStack.push(signValue);  
                signValue = 1;  
                number = 0;  
            }  
  
            if (c == ')') {  
                result += number * signValue;  
                number = 0;  
                signValue = operationsStack.pop();  
            }  
  
        }  
  
        result += number * signValue;  
  
        return result;  
    }  
}
```

```
    } else if (c == '(') {  
  
        operationsStack.push(result);  
  
        operationsStack.push(signValue);  
  
        result = 0;  
  
        signValue = 1;  
  
    } else if (c == ')') {  
  
        result += signValue * number;  
  
        result *= operationsStack.pop();  
  
        result += operationsStack.pop();  
  
        number = 0;  
  
    }  
  
}  
  
return result + number * signValue;  
  
}  
}
```

**Output :**

```
Accepted Runtime: 0 ms
• Case 1 • Case 2 • Case 3
Input
s =
"1 + 1"
Output
2
Expected
2
```

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(n)$**

### **15)Search Insert Position**

**Given a sorted array of distinct integers and a target value, return the index if the target is found. If not, return the index where it would be if it were inserted in order.**

**You must write an algorithm with  $O(\log n)$  runtime complexity.**

**Example 1:**

**Input: nums = [1,3,5,6], target = 5**

**Output: 2**

**Example 2:**

**Input: nums = [1,3,5,6], target = 2**



**Output: 1**

**Example 3:**

**Input: nums = [1,3,5,6], target = 7**

**Output: 4**

**Program :**

```
class Solution {  
  
    public int searchInsert(int[] nums, int target) {  
  
        return binarySearch(nums, target);  
  
    }  
  
    private int binarySearch(int[] nums, int target) {  
  
        int low = 0;  
  
        int high = nums.length - 1;  
  
        while (low <= high) {  
  
            int mid = (low + high) / 2;  
  
            if (nums[mid] > target) {  
  
                high = mid - 1;  
  
            } else if (nums[mid] < target) {
```

```

        low = mid + 1;

    } else {

        return mid;

    }

}

return low;

}
}

```

**Output :**

• Case 1

• Case 2

• Case 3

Input

nums =

[1,3,5,6]

target =

5

Output

2

Expected

2

**Time Complexity:  $O(\log n)$**

**Space Complexity :  $O(1)$**

**16) Search a 2D Matrix :**

You are given an  $m \times n$  integer matrix with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer target, return true *if* target *is in* matrix *or* false *otherwise*.

You must write a solution in  $O(\log(m * n))$  time complexity.

**Example 1:**

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 3

Output: true

**Example 2:**

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 13

Output: false

Program :

```
class Solution {  
  
    public boolean searchMatrix(int[][] matrix, int target) {  
  
        int m = matrix.length;  
  
        int n = matrix[0].length;  
  
        int i=0;  
  
        int j=n-1;  
  
        while(i<m && j>=0){  
  
            if(matrix[i][j]==target) return true;  
  
            if(matrix[i][j]>target){  
  
                j--;  
  
            }  
  
            else{  
  

```

```
        i++;  
    }  
}  
  
return false;  
}  
}
```

**Output :**

**Accepted** Runtime: 0 ms

• Case 1 • Case 2

Input

matrix =  
[ [1,3,5,7], [10,11,16,20], [23,30,34,60] ]

target =  
3

Output

true

Expected

true

**Time Complexity :  $O(m+n)$**

**Space Complexity :  $O(1)$**

### 17)Find a Peak Element :

A peak element is an element that is strictly greater than its neighbors.

Given a 0-indexed integer array `nums`, find a peak element, and return its index. If the array contains multiple peaks, return the index to any of the peaks.

You may imagine that `nums[-1] = nums[n] = -∞`. In other words, an element is always considered to be strictly greater than a neighbor that is outside the array.

You must write an algorithm that runs in  $O(\log n)$  time.

#### Example 1:

Input: `nums = [1,2,3,1]`

Output: 2

Explanation: 3 is a peak element and your function should return the index number 2.

#### Example 2:

Input: `nums = [1,2,1,3,5,6,4]`

Output: 5

Explanation: Your function can return either index number 1 where the peak element is 2, or index number 5 where the peak element is 6.

Program :

```
class Solution {  
  
    public int findPeakElement(int[] nums) {  
  
        if(nums.length <= 1){  
  
            return 0;  
        }  
    }  
}
```

```
}

return helper(nums , 0 , nums.length - 1);

}

public int helper(int[] nums , int si , int ei) {

    if(ei-si <= 0)

        return -1;

    if(ei - si == 1) {

        if(nums[si] > nums[ei])

            return si;

        else

            return ei;

    }

    int mid = si + (ei - si)/2;

    if(nums[mid] > nums[mid+1] && nums[mid] > nums[mid-1]){

        return mid;

    }else if(nums[si] > nums[si+1])

        return si;

    else if(nums[ei] > nums[ei-1])

        return ei;

    else {

        int i = helper(nums , si , mid - 1);
```

```
int j = helper(nums,mid,ei);

if(i != -1 && j != -1) {

    if(nums[i] > nums[j])

        return i;

    else

        return j;

}else {

    if(i != -1)

        return i;

    else

        return j;

}

}

}

}
```

**Output :**



```
Accepted Runtime: 0 ms
• Case 1 • Case 2
Input
nums =
[1,2,3,1]
Output
2
Expected
2
```

**Time Complexity :  $O(n)$**

**Space Complexity :  $O(n)$**

### **18) Search in Rotated Sorted Array :**

**There is an integer array `nums` sorted in ascending order (with distinct values).**

**Prior to being passed to your function, `nums` is possibly rotated at an unknown pivot index `k` ( $1 \leq k < \text{nums.length}$ ) such that the resulting array is `[nums[k], nums[k+1], ..., nums[n-1], nums[0], nums[1], ..., nums[k-1]]` (0-indexed). For example, `[0,1,2,4,5,6,7]` might be rotated at pivot index 3 and become `[4,5,6,7,0,1,2]`.**

**Given the array `nums` after the possible rotation and an integer `target`, return *the index of target if it is in `nums`, or -1 if it is not in `nums`.***

**You must write an algorithm with  $O(\log n)$  runtime complexity.**

**Example 1:**

**Input: `nums = [4,5,6,7,0,1,2]`, `target = 0`**

**Output: 4**

**Example 2:**

**Input:** nums = [4,5,6,7,0,1,2], target = 3

**Output:** -1

**Example 3:**

**Input:** nums = [1], target = 0

**Output:** -1

**Program :**

```
class Solution {  
  
    public int search(int[] arr, int target) {  
  
        int n= arr.length;  
  
        int lo=0;  
  
        int hi=n-1;  
  
        while(lo<=hi){  
  
            int mid= lo+ (hi-lo)/2;  
  
            if(arr[mid]==target) return mid;  
  
            else if(arr[mid] <=arr[hi]){ // i am in right sorted array,mid to hi  
everything is sorted  
  
                if(target >arr[mid] && target <=arr[hi]) lo=mid+1;  
  
                else hi=mid-1;  
  
            }  
        }  
    }  
}
```

```
else { // i am in left sorted array lo to mid everything sorted

    if(target >=arr[lo] && target <arr[mid]){

        hi=mid-1;

    }

    else lo =mid+1;

}

}

return -1;

}

}
```

**Output :**

```
Accepted Runtime: 0 ms
• Case 1 • Case 2 • Case 3
Input
nums =
[4,5,6,7,0,1,2]
target =
0
Output
4
Expected
4
```

**Time Complexity :  $O(\log n)$**

**Space Complexity :  $O(1)$**

**19) Find First and Last position of an element in an Sorted Array :**

**Given an array of integers nums sorted in non-decreasing order, find the starting and ending position of a given target value.**

**If target is not found in the array, return [-1, -1].**

**You must write an algorithm with  $O(\log n)$  runtime complexity.**

**Example 1:**

**Input: nums = [5,7,7,8,8,10], target = 8**

**Output: [3,4]**

**Example 2:**

**Input:** nums = [5,7,7,8,8,10], target = 6

**Output:** [-1,-1]

**Example 3:**

**Input:** nums = [], target = 0

**Output:** [-1,-1]

**Program :**

```
class Solution {  
  
    public int[] searchRange(int[] arr, int target) {  
  
        int n= arr.length;  
  
        int[] ans={-1,-1};  
  
        // fist postion  
  
        int lo=0;  
  
        int hi=n-1;  
  
        int fp=-1;  
  
        while(lo<=hi){  
  
            int mid=lo +(hi-lo)/2;  
  
            if(arr[mid] == target){  
  
                if( mid>0 && arr[mid] == arr[mid-1]) hi=mid-1;
```

```
        else{

            fp=mid;

            break;

        }

    }

    else if(arr[mid]<target) lo=mid+1;

    else hi=mid-1;

}

// last position

lo=0;

hi=n-1;

int lp=-1;

while(lo<=hi){

    int mid=lo +(hi-lo)/2;

    if(arr[mid] == target){

        if( mid+1 <n && arr[mid] == arr[mid+1]) lo=mid+1;

        else{

            lp=mid;

            break;

        }

    }

}
```

```

        else if(arr[mid]<target) lo=mid+1;

        else hi=mid-1;

    }

    ans[0]=fp;

    ans[1]=lp;

    return ans;

}

}

```

**Output :**

**Accepted** Runtime: 0 ms

• Case 1 • Case 2 • Case 3

Input

nums =  
[5,7,7,8,8,10]

target =  
8

Output

[3,4]

Expected

[3,4]

**Time Complexity :  $O(\log n)$**

**Space Complexity :  $O(1)$**

## **20)Find Minimum in an rotated Sorted Array**

**Suppose an array of length  $n$  sorted in ascending order is rotated between 1 and  $n$  times. For example, the array  $\text{nums} = [0,1,2,4,5,6,7]$  might become:**

- **$[4,5,6,7,0,1,2]$  if it was rotated 4 times.**
- **$[0,1,2,4,5,6,7]$  if it was rotated 7 times.**

**Notice that rotating an array  $[a[0], a[1], a[2], \dots, a[n-1]]$  1 time results in the array  $[a[n-1], a[0], a[1], a[2], \dots, a[n-2]]$ .**

**Given the sorted rotated array  $\text{nums}$  of unique elements, return *the minimum element of this array*.**

**You must write an algorithm that runs in  $O(\log n)$  time.**

**Example 1:**

**Input:  $\text{nums} = [3,4,5,1,2]$**

**Output: 1**

**Explanation: The original array was  $[1,2,3,4,5]$  rotated 3 times.**

**Example 2:**

**Input:  $\text{nums} = [4,5,6,7,0,1,2]$**

**Output: 0**

**Explanation: The original array was  $[0,1,2,4,5,6,7]$  and it was rotated 4 times.**

**Example 3:**

**Input:  $\text{nums} = [11,13,15,17]$**



**Output: 11**

**Explanation:** The original array was [11,13,15,17] and it was rotated 4 times.

**Program :**

```
class Solution {

    public int findMin(int[] nums) {

        int start=0;

        int end=nums.length-1;

        if(nums[end] > nums[start]){

            return nums[start];

        }

        return minElement(nums, start, end);

    }

    public static int minElement(int[] nums, int start, int end) {

        while (start < end) {

            int mid = start + (end - start) / 2;

            if (nums[mid] > nums[mid + 1]) {

                return nums[mid+1];

            }

            if (nums[mid] >= nums[start]) {
```

```
        start = mid + 1;

    } else {

        end = mid;

    }

}

return nums[start];

}
```

## Output:

**Accepted** Runtime: 0 ms

• Case 1 • Case 2 • Case 3

Input

nums =  
[3,4,5,1,2]

Output

1

Expected

1

**Time Complexity :  $O(\log n)$**

**Space Complexity :  $O(1)$**

