API 1: DOM to Selenium Code

Model Used: openai/gpt-oss-120b

Request Body:

```
{
  "messages": [
    {
      "role": "user",
      "content": "Extract the below given DOM : \n\n<input type=\"text\" class=\"inputBox\"
        name=\"companyName\" size=\"30\" maxlength=\"100\"
        id=\"createLeadForm_companyName\">\n<input type=\"text\" class=\"inputBox\"
        name=\"lastName\" size=\"30\" maxlength=\"100\" id=\"createLeadForm_lastName\">\n<input
        type=\"text\" class=\"inputBox\" name=\"firstName\" size=\"30\" maxlength=\"100\"
        id=\"createLeadForm_firstName\">\n<input type=\"submit\" class=\"smallSubmit\"
        name=\"submitButton\" value=\"Create Lead\" id=\"ext-gen630\"> and provide me the selenium
        java code. Instructions: Do not use ID if the value has number in it. Provide only java
        code and no explanations needed"
    }
  ],
  "model": "openai/gpt-oss-120b",
  "temperature": 0.1,
  "include_reasoning":true
}
```

Response Body:

Body Cookies 1 Headers 20 Test Results 200 OK 1.38 s 2.03 KB Save Response

{} JSON Preview Visualize


```
{
    "id": "chatcmpl-7674de03-7ce3-4bf3-8705-62bd46763480",
    "object": "chat.completion",
    "created": 1775668618,
    "model": "openai/gpt-oss-120b",
    "choices": [
        {
            "index": 0,
            "message": {
                "role": "assistant",
                "content": "```java\nimport org.openqa.selenium.By;\nimport org.openqa.selenium.
                    WebDriver;\nimport org.openqa.selenium.WebElement;\nimport org.openqa.selenium.
                    chrome.ChromeDriver;\n\npublic class LeadFormAutomation {\n    public static void
                    main(String[] args) {\n        // Set the path to your chromedriver executable if
                    needed\n        // System.setProperty(\"webdriver.chrome.driver\", \"/path/to/
                    chromedriver\");\n\n        WebDriver driver = new ChromeDriver();\n\n        try
                    {\n            driver.get(\"YOUR_TARGET_URL\");   // replace with the actual
                    URL\n\n            // Locate the input fields using IDs (no numbers in the ID
                    values)\n            WebElement companyName = driver.findElement(By.id
                    (\"createLeadForm_companyName\"));\n            WebElement lastName    = driver.
                    findElement(By.id(\"createLeadForm_lastName\"));\n            WebElement
                    firstName   = driver.findElement(By.id(\"createLeadForm_firstName\"));
                    \n\n            // Locate the submit button without using its numeric
                    ID\n            WebElement submitBtn = driver.findElement(\n                    
                    By.cssSelector(\"input.smallSubmit[name='submitButton'][value='Create Lead']\"));
                    \n\n            // Example actions (fill the form and submit)\n            
                    companyName.sendKeys(\"Acme Corp\");\n            lastName.sendKeys(\"Doe\");
                    \n            firstName.sendKeys(\"John\");\n            submitBtn.click();
                    \n\n            // Add any additional verification or wait logic
                    here\n\n        } finally {\n            driver.quit();\n        }\n    }\n}
                    \n```",
```

Body Cookies 1 Headers 20 Test Results 200 OK 1.38 s 2.03 KB Save Response

{} JSON Preview Visualize


```
12                "reasoning": "We need to output Selenium Java code to extract the given DOM elements, but not use ID if the value has number in it. The IDs have numbers: createLeadForm_companyName (no number), createLeadForm_lastName (no number), createLeadForm_firstName (no number), ext-gen630 (has number). So we should not use ID for ext-gen630, but can use ID for others? The instruction: \"Do not use ID if the value has number in it.\" So for IDs containing numbers, avoid using ID. ext-gen630 contains number, so use other locator (e.g., By.cssSelector, By.xpath). For others, IDs have no numbers, so we can use By.id.\n\nWe need to \"Extract the below given DOM\" meaning locate elements? Provide Selenium Java code to locate them and maybe interact? Provide code only, no explanations. \n\nWe'll write code snippet: WebDriver driver = new ChromeDriver(); then locate elements:\n\nWebElement companyName = driver.findElement(By.id(\"createLeadForm_companyName\"));\nWebElement lastName = driver.findElement(By.id(\"createLeadForm_lastName\"));\nWebElement firstName = driver.findElement(By.id(\"createLeadForm_firstName\"));\nWebElement submitButton = driver.findElement(By.cssSelector(\"input.smallSubmit[name='submitButton'][value='Create Lead']\"));\n\nOr use xpath: //input[@type='submit' and @value='Create Lead'].\n\nWe'll provide code only. Ensure imports. Provide class with main method.\n\nLet's output Java code."
13            },
14            "logprobs": null,
15            "finish_reason": "stop"
16        }
17    ],
```



```
18    "usage": {
19        "queue_time": 0.042497366,
20        "prompt_tokens": 227,
21        "prompt_time": 0.010959549,
22        "completion_tokens": 604,
23        "completion_time": 1.270088226,
24        "total_tokens": 831,
25        "total_time": 1.281047775,
26        "completion_tokens_details": {
27            "reasoning_tokens": 310
28        }
29    },
30    "usage_breakdown": null,
31    "system_fingerprint": "fp_bc9a6c9b5f",
32    "x_groq": {
33        "id": "req_01knq1hrbkeye95pf9v8r09h2n",
34        "seed": 1232925471
35    },
36    "service_tier": "on_demand"
37 }
```

Response as plain text:

```
"message": {
                "role": "assistant",
                "content": "```java
import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.chrome.ChromeDriver;

public class LeadFormAutomation {
    public static void main(String[] args) {
        // Set the path to your chromedriver executable if needed
        // System.setProperty("webdriver.chrome.driver", "/path/to/chromedriver");

        WebDriver driver = new ChromeDriver();

        try {
            driver.get("YOUR_TARGET_URL");   // replace with the actual URL

            // Locate the input fields using IDs (no numbers in the ID values)
            WebElement companyName =
driver.findElement(By.id("createLeadForm_companyName"));
            WebElement lastName    =
driver.findElement(By.id("createLeadForm_lastName"));
            WebElement firstName   =
driver.findElement(By.id("createLeadForm_firstName"));

            // Locate the submit button without using its numeric ID
            WebElement submitBtn = driver.findElement(

By.cssSelector("input.smallSubmit[name='submitButton'][value='Create Lead']"));

            // Example actions (fill the form and submit)
            companyName.sendKeys("Acme Corp");
            lastName.sendKeys("Doe");
            firstName.sendKeys("John");
            submitBtn.click();

            // Add any additional verification or wait logic here

        } finally {
            driver.quit();
        }
    }
}
```",
                "reasoning": "We need to output Selenium Java code to extract the
given DOM elements, but not use ID if the value has number in it. The IDs have
numbers: createLeadForm_companyName (no number), createLeadForm_lastName (no number),
createLeadForm_firstName (no number), ext-gen630 (has number). So we should not use ID
for ext-gen630, but can use ID for others? The instruction: "Do not use ID if the
value has number in it." So for IDs containing numbers, avoid using ID. ext-gen630
```
```

```
contains number, so use other locator (e.g., By.cssSelector, By.xpath). For others,
IDs have no numbers, so we can use By.id.

We need to "Extract the below given DOM" meaning locate elements? Provide Selenium
Java code to locate them and maybe interact? Provide code only, no explanations.

We'll write code snippet: WebDriver driver = new ChromeDriver(); then locate elements:

WebElement companyName = driver.findElement(By.id("createLeadForm_companyName"));
WebElement lastName = driver.findElement(By.id("createLeadForm_lastName"));
WebElement firstName = driver.findElement(By.id("createLeadForm_firstName"));
WebElement submitButton =
driver.findElement(By.cssSelector("input.smallSubmit[name='submitButton'][value='Creat
e Lead']"));

Or use xpath: //input[@type='submit' and @value='Create Lead'].

We'll provide code only. Ensure imports. Provide class with main method.

Let's output Java code."
            }
```

API 2: Text from Image Url

Model Used: meta-llama/llama-4-scout-17b-16e-instruct

Request Body:

```
{
  "model": "meta-llama/llama-4-scout-17b-16e-instruct",
  "messages": [
    {
      "role": "user",
      "content": [
        {
          "type": "text",
          "text": "This is a image. Extract and return only the text exactly as shown, preserving case."
        },
        {
          "type": "image_url",
          "image_url": {
            "url": "https://contenthub-static.grammarly.com/blog/wp-content/uploads/2018/12/Beautiful-English-words.png"
          }
        }
      ]
    }
  ]
}
```

Response Body:

Body | Cookies 1 | Headers 20 | Test Results | 200 OK • 672 ms • 1.02 KB • Save Response

{} JSON | Preview | Visualize


```
{
    "id": "chatcmpl-5bd86547-3a7d-4d83-80b1-357d2f20a90a",
    "object": "chat.completion",
    "created": 1775670121,
    "model": "meta-llama/llama-4-scout-17b-16e-instruct",
    "choices": [
        {
            "index": 0,
            "message": {
                "role": "assistant",
                "content": "Beautiful English words"
            },
            "logprobs": null,
            "finish_reason": "stop"
        }
    ],
    "usage": {
        "queue_time": 0.243559798,
        "prompt_tokens": 2352,
        "prompt_time": 0.075929916,
        "completion_tokens": 4,
        "completion_time": 0.010250225,
        "total_tokens": 2356,
        "total_time": 0.086180141
    },
    "usage_breakdown": null,
    "system_fingerprint": "fp_37da608fc1",
    "x_groq": {
        "id": "req_01knq2zme6f6eb8ewx53ewc0kh",
        "seed": 653558920
    },
    "service_tier": "on_demand"
}
```

Image Url & Image used:

Url:
https://contenthub-static.grammarly.com/blog/wp-content/uploads/2018/12/Beautiful-English-words.png

Response as plain text:


```
"message": {
                "role": "assistant",
                "content": "Beautiful English words"
            }
```

API 3: Web Search

Model Used: groq/compound-mini

Request Body :


```
{
  "model": "groq/compound-mini",
  "messages": [
    {
      "role": "user",
      "content": "weather in chennai for jan 11 2026 --Only the temperatue for the date asked no probability or text and source from web with link no extrat text or markdown Give accurately with Web search no Halluciantion "
    }
  ]
}
```


Response Body:


```
    "created": 1775670596,
    "model": "groq/compound-mini",
    "choices": [
        {
            "index": 0,
            "message": {
                "role": "assistant",
                "content": "77°F https://world-weather.info/forecast/india/chennai_1/11-january/",
                "reasoning": "<tool>search(Chennai temperature Jan 11 2026)</tool>\n<output>Title: Weather in Chennai, January 11\nURL: https://world-weather.info/forecast/india/chennai_1/11-january/\nContent: Weather in Chennai, January 11. January 10 Date: Select a date January 12. Wind. Pressure. Humidity. January 11, 2026. Night. +77°. 13.9. 29.9. 86%. Morning. +\nScore: 0.9207\n\nTitle: Chennai January 2026 Historical Weather Data (Tamil Nadu, India)\nURL: https://weatherspark.com/h/m/110123/2026/1/Historical-Weather-in-January-2026-in-Chennai-Tamil-Nadu-India\nContent: average high (faint red line) and low (faint blue line) temperature, with 25th to 75th and 10th to 90th percentile bands.  Hourly Temperature in January 2026 in Chennai Winter 2026  Link  Download  Compare  Averages History:JanFMAMJJASOND2025202420232022  frigid  15°F freezing  32°F very cold  45°F cold  55°F cool  65°F comfortable  75°F warm  85°F hot  95°F sweltering  The hourly reported temperature, color coded into bands. The shaded overlays indicate night and civil twilight.  Map Marker  © OpenStreetMap contributors  Compare Chennai to another city:  Cloud Cover in January 2026 in Chennai Winter 2026  Link  Download  Compare  Averages History:JanFMAMJJASOND2025202420232022  0% clear  20% mostly clear  40% partly cloudy  60% mostly cloudy  80% overcast  100%  no [...] dry  55°F comfortable  60°F humid  65°F muggy  70°F oppressive  75°F miserable  The hourly reported humidity comfort level, categorized by dew point. The shaded overlays indicate night and civil twilight.  Wind Speed in January 2026 in Chennai Winter 2026  Link  Download  Compare  Averages History:JanFMAMJJASOND2025202420232022  The daily range of reported wind speeds
```

Screen shot from Testleaf-Learning LLM api with Groq

API 4: Multilingual

Model Used: llama-3.3-70b-versatile

Request Body :

none form-data x-www-form-urlencoded raw binary GraphQL JSON Schema Beautify

```
{
  "model": "llama-3.3-70b-versatile",
  "messages": [
    {"role": "system", "content": "You are an API Specialist. Always respond in the same language as the user."},
    {"role": "user", "content": "மிகவும் நன்றி! இந்த API-ஐ எப்படி பயன்படுத்துவது என்று சொல்லுங்கள்."}
  ]
}
```

Response Body:


```
{
    "id": "chatcmpl-477ba18f-b717-4f79-b3a0-9d60197b40a9",
    "object": "chat.completion",
    "created": 1775671419,
    "model": "llama-3.3-70b-versatile",
    "choices": [
        {
            "index": 0,
            "message": {
                "role": "assistant",
                "content": "நன்றி! இந்த API ஐ பயன்படுத்துவதற்கு, கீழே காணும் படிகளை
                    பின்பற்றவும்:\n\n1. **API கீ பெறுதல்**: முதலில், நீங்கள் ஒரு API கீ பெற வேண்டும்.
                    இது API ஐ அணுகுவதற்கான ஒரு அனுமதி குறியீடு.\n2. **API ஆவணங்களைப் படித்தல்**: API
                    ஆவணங்களைப் படித்து, அதன் செயல்பாடுகளைப் புரிந்து கொள்ளுங்கள்.\n3. **API
                    அழைப்புகளை உருவாக்குதல்**: API கீ மற்றும் ஆவணங்களின் அடிப்படையில், API அழைப்புகளை
                    உருவாக்குங்கள். இது ஒரு உரிமையைக் கோரி ஒரு வலை அடிப்படையிலான கோரிக்கை ஆகும்.\n4.
                    **API பதிலை பயன்படுத்துதல்**: API அழைப்பின் பதிலை பெற்று, அதை தேவையான வகையில்
                    பயன்படுத்துங்கள்.\n\nஉதாரணமாக, ஒரு காலநிலை API ஐ பயன்படுத்தும் போது, நீங்கள் ஒரு
                    நகரத்தின் காலநிலையைக் கோரி ஒரு கோரிக்கையை அனுப்பலாம். பதிலாக, API நகரத்தின்
                    தற்போதைய காலநிலையை திருப்பித் தரும்.\n\nஇந்த API ஐ பயன்படுத்துவதில் உங்களுக்கு
                    ஏதேனும் கேள்விகள் இருந்தால், தயங்காதீர்கள். நான் உங்களுக்கு உதவ முயற்சிப்பேன்."
            },
            "logprobs": null,
            "finish_reason": "stop"
        }
    ],
    "usage": {
        "queue_time": 0.16174312,
        "prompt_tokens": 133,
        "prompt_time": 0.020597602,
        "completion_tokens": 1057,
        "completion_time": 2.8865711210000002,
        "total_tokens": 1190,
        "total_time": 2.907168723
    },
    "usage_breakdown": null,
```


Response as plain text:


```
message": {
                "role": "assistant",
                "content": "நன்றி! இந்த API ஐ பயன்படுத்துவதற்கு, கீழே காணும் படிகளை பின்பற்றவும்:

1. **API கீ பெறுதல்**: முதலில், நீங்கள் ஒரு API கீ பெற வேண்டும். இது API ஐ அணுகுவதற்கான ஒரு அனுமதி குறியீடு.
2. **API ஆவணங்களைப் படித்தல்**: API ஆவணங்களைப் படித்து, அதன் செயல்பாடுகளைப் புரிந்து கொள்ளுங்கள்.
3. **API அழைப்புகளை உருவாக்குதல்**: API கீ மற்றும் ஆவணங்களின் அடிப்படையில், API அழைப்புகளை உருவாக்குங்கள். இது ஒரு உரிமையைக் கோரி ஒரு வலை அடிப்படையிலான கோரிக்கை ஆகும்.
4. **API பதிலை பயன்படுத்துதல்**: API அழைப்பின் பதிலை பெற்று, அதை தேவையான வகையில் பயன்படுத்துங்கள்.
```

உதாரணமாக, ஒரு காலநிலை API ஐ பயன்படுத்தும் போது, நீங்கள் ஒரு நகரத்தின் காலநிலையைக் கோரி ஒரு கோரிக்கையை அனுப்பலாம். பதிலாக, API நகரத்தின் தற்போதைய காலநிலையை திருப்பித் தரும்.

இந்த API ஐ பயன்படுத்துவதில் உங்களுக்கு ஏதேனும் கேள்விகள் இருந்தால், தயங்காதீர்கள். நான் உங்களுக்கு உதவ முயற்சிப்பேன்."

```
            }
```