

ThooviTickets

Mobile App API Documentation

For Flutter Mobile App Development

Organiser & Staff Scanner App

Base URL: <https://api.thoovitickets.com/api>

Authentication: JWT Bearer Token

Date: June 2026

Version: 1.0

This document covers all APIs needed for the Flutter mobile app:

- Login (Organiser & Staff)
- Event Listing & Details
- QR Code Ticket Scanning
- Manual Ticket Search (Email/Phone)
- Single & Batch Check-in
- Partial Check-in for Multi-Attendee Orders
- Dashboard & Stats

Table of Contents

1. Authentication

- 1.1 Mobile Login
- 1.2 Token Refresh
- 1.3 Auth Headers

2. Dashboard

- 2.1 Mobile Dashboard

3. Events

- 3.1 List Events (Mobile)
- 3.2 Event Details
- 3.3 Event Attendees

4. Ticket Scanning & Check-in

- 4.1 Scan QR Code (Verify Ticket)
- 4.2 Check-in Single Ticket
- 4.3 Batch Check-in (Partial)
- 4.4 Manual Search by Email/Phone

5. Staff Management

- 5.1 List Staff
- 5.2 Add Staff
- 5.3 Update Staff
- 5.4 Remove Staff
- 5.5 My Access (Staff View)

6. Tickets Module

- 6.1 Verify Ticket by Code
- 6.2 Check-in via Ticket Code

7. Notifications

8. Enums & Constants

9. Error Handling

1. Authentication

The mobile app uses JWT Bearer tokens for authentication. Login returns an access token (12h expiry) that must be sent in the Authorization header for all protected endpoints.

1.1 Mobile Login

Dedicated mobile login endpoint that validates credentials and checks scanner access for staff accounts.

POST

/api/mobile/auth/login

Public

Login for organiser or staff scanner accounts

Request Body:

```
{
  "email": "organiser@example.com",
  "password": "password123"
}
```

Success Response (Organiser):

```
{
  "user": {
    "id": "clxx1234567890",
    "firstName": "John",
    "lastName": "Doe",
    "email": "organiser@example.com",
    "role": "ORGANISER",
    "avatarUrl": "https://storage.example.com/avatars/john.jpg"
  },
  "accessToken": "eyJhbGciOiJIUzI1NiIs... ",
  "scannerAccess": []
}
```

Success Response (Staff Scanner):

```
{
  "user": {
    "id": "clxx9876543210",
    "firstName": "Jane",
    "lastName": "Smith",
    "email": "staff@example.com",
    "role": "CUSTOMER",
    "avatarUrl": null
  },
  "accessToken": "eyJhbGciOiJIUzI1NiIs... ",
  "scannerAccess": [
    {
      "organiserId": "clxx1234567890",
      "organiserName": "EventPro Org",
      "accessLevel": "SCANNER"
    }
  ]
}
```

Error Responses:

```
401 Unauthorized: { "message": "Invalid email or password" }
403 Forbidden:    { "message": "You do not have scanner access. Contact your organiser." }
403 Forbidden:    { "message": "Scanner login is only for organisers and scanner staff." }
```

Note: Staff users (role=CUSTOMER) must have an active StaffAccount with accessLevel SCANNER or FULL_ACCESS. The scannerAccess array tells the app which organisers this staff can scan for.

1.2 Auth Headers

Include the JWT token in all authenticated requests:

Authorization Header:

```
Authorization: Bearer eyJhbGciOiJIUzI1NiIs...
```

The access token contains: { sub: userId, email, role }. Token expires in 12 hours for mobile.

1.3 Standard Auth Endpoints

These web auth endpoints also work for the mobile app if needed:

POST	/api/auth/login Standard web login (sets refresh cookie, 15min access token)	Public
POST	/api/auth/refresh Refresh access token using httpOnly cookie	Public
POST	/api/auth/logout Clear refresh token	JWT Required
GET	/api/auth/me Get current user profile with full details	JWT Required

GET /api/auth/me Response:

```
{
  "id": "clxx1234567890",
  "email": "organiser@example.com",
  "firstName": "John",
  "lastName": "Doe",
  "role": "ORGANISER",
  "status": "ACTIVE",
  "phone": "9876543210",
  "emailVerified": true,
  "avatarUrl": "...",
  "orgName": "EventPro Org",
  "orgDescription": "We organize events",
  "profileCompleted": true,
  "createdAt": "2026-01-15T10:30:00.000Z",
  "updatedAt": "2026-06-20T15:45:00.000Z"
}
```

2. Dashboard

2.1 Mobile Dashboard

Returns today's events with check-in statistics. Shows events currently running (startDate <= tomorrow, endDate >= today).

GET

/api/mobile/dashboard
Get today's events and check-in stats

JWT Required (Organiser/Staff)

Response:

```
{
  "today": {
    "events": [
      {
        "id": "clxx_event_001",
        "title": "Summer Music Festival 2026",
        "venue": "Marina Beach Arena",
        "startDate": "2026-06-29T10:00:00.000Z"
      },
      {
        "id": "clxx_event_002",
        "title": "Tech Conference Chennai",
        "venue": "Chennai Trade Centre",
        "startDate": "2026-06-29T09:00:00.000Z"
      }
    ],
    "totalTickets": 450,
    "checkedIn": 123,
    "pending": 327
  }
}
```

Note: For staff users, only shows events from organisers they have scanner access to.

2.2 Organiser Analytics Dashboard

Detailed analytics available via the analytics module:

GET

/api/analytics/organiser/dashboard
Overall organiser dashboard stats

JWT Required (@Roles ORGANISER)

GET

/api/analytics/event/:eventId
Per-event detailed metrics

JWT Required (@Roles ORGANISER)

3. Events

3.1 List Events (Mobile)

Returns events accessible to the current user (organiser sees own events, staff sees their assigned organisers events). Limited to PUBLISHED and COMPLETED events, sorted by startDate desc.

GET

/api/mobile/events

JWT Required (Organiser/Staff)

Get events for mobile app (max 50)

Response:

```
[
  {
    "id": "clxx_event_001",
    "title": "Summer Music Festival 2026",
    "venue": "Marina Beach Arena",
    "city": "Chennai",
    "startDate": "2026-06-29T10:00:00.000Z",
    "endDate": "2026-06-29T22:00:00.000Z",
    "status": "PUBLISHED",
    "imageUrl": "https://storage.example.com/events/summer-fest.jpg",
    "ticketTypes": [
      { "totalQty": 500, "soldQty": 350 },
      { "totalQty": 100, "soldQty": 95 }
    ]
  }
]
```

Tip: Calculate total sold / total available from ticketTypes for progress display.

3.2 Event Details (by Slug)

Get full event details with ticket types. This is the public endpoint used for event pages.

GET

/api/events/detail/:slug

Public

Get event details by slug

Response:

```
{
  "id": "clxx_event_001",
  "title": "Summer Music Festival 2026",
  "slug": "summer-music-festival-2026",
  "description": "A grand summer music festival...",
  "shortDesc": "Summer's biggest music event",
  "venue": "Marina Beach Arena",
  "address": "123 Marina Beach Road",
  "city": "Chennai",
  "state": "Tamil Nadu",
  "country": "India",
  "startDate": "2026-06-29T10:00:00.000Z",
  "endDate": "2026-06-29T22:00:00.000Z",
  "imageUrl": "https://storage.example.com/events/banner.jpg",
  "bannerUrl": "https://storage.example.com/events/cover.jpg",
  "status": "PUBLISHED",
  "isFeatured": true,
  "maxAttendees": 600,
  "tags": ["music", "outdoor", "festival"],
  "timezone": "Asia/Kolkata",
  "organiser": {
    "id": "clxx1234567890",
    "orgName": "EventPro Org",
    "firstName": "John",
    "lastName": "Doe",
    "avatarUrl": "..."
  },
  "category": {
    "id": "cat_001",
    "name": "Music",
    "slug": "music",
    "icon": "music-note"
  },
  "ticketTypes": [
    {
      "id": "tt_001",
      "name": "General Admission",
      "description": "Standard entry",
      "price": "500.00",
      "currency": "INR",
      "totalQty": 500,
      "soldQty": 350,
      "maxPerOrder": 5,
      "saleStart": "2026-05-01T00:00:00.000Z",
      "saleEnd": "2026-06-29T08:00:00.000Z",
      "isActive": true,
      "sortOrder": 0
    },
    {
      "id": "tt_002",
      "name": "VIP Pass",
      "description": "VIP area + backstage",
      "price": "2000.00",
      "currency": "INR",
      "totalQty": 100,
      "soldQty": 95,
      "maxPerOrder": 3,
      "isActive": true,
      "sortOrder": 1
    }
  ]
}
```

3.3 Event Attendees List

Get all attendees (tickets) for an event. Supports search by name/email and filter by status. Useful for manual attendee lookup in the mobile app.

GET `/api/orders/organiser/event/:eventId/attendees`

JWT Required (@Roles
ORGANISER)

Get event attendee list (paginated)

Query Parameters:

```
{
  "page": 1,           // Page number (default: 1)
  "limit": 20,         // Items per page (default: 20)
  "search": "john",    // Search by attendeeName or attendeeEmail
  "status": "ACTIVE"   // Filter: ACTIVE | USED | CANCELLED
}
```

Response:

```
{
  "data": [
    {
      "id": "ticket_001",
      "ticketCode": "TT-EVP290626-A1B2",
      "status": "ACTIVE",
      "attendeeName": "Rahul Kumar",
      "attendeeEmail": "rahul@example.com",
      "attendeePhone": "9876543210",
      "checkedInAt": null,
      "qrData": "https://thoovitickets.com/verify/TT-EVP290626-A1B2",
      "orderItem": {
        "ticketType": { "name": "General Admission" },
        "event": { "id": "clxx_event_001", "title": "Summer Music Festival" }
      },
      "order": {
        "id": "order_001",
        "orderNumber": "TT-ABC123-XY78",
        "status": "CONFIRMED"
      }
    }
  ],
  "meta": {
    "total": 350,
    "page": 1,
    "limit": 20,
    "totalPages": 18
  }
}
```

Use the search parameter to implement the manual search feature in the app — search by email or phone number to find attendees.

4. Ticket Scanning & Check-in

The core feature of the mobile app. Supports QR code scanning, manual code entry, and batch check-in for multi-attendee orders.

4.1 Scan QR Code / Verify Ticket

After scanning a QR code, extract the ticket code from the URL. The QR data contains a URL like: <https://thoovitickets.com/verify/TT-EVP290626-A1B2>. Parse the last segment as the `ticketCode` and call this endpoint.

POST

/api/mobile/scan

JWT Required (Organiser/Staff)

Verify a ticket by code (QR or manual entry)

Request Body:

```
{
  "ticketCode": "TT-EVP290626-A1B2"
}
```

Response:

```

{
  "ticket": {
    "id": "ticket_001",
    "ticketCode": "TT-EVP290626-A1B2",
    "status": "ACTIVE",
    "attendeeName": "Rahul Kumar",
    "attendeeEmail": "rahul@example.com",
    "attendeePhone": "9876543210",
    "checkedInAt": null
  },
  "event": {
    "id": "clxx_event_001",
    "title": "Summer Music Festival 2026",
    "venue": "Marina Beach Arena",
    "startDate": "2026-06-29T10:00:00.000Z",
    "endDate": "2026-06-29T22:00:00.000Z",
    "status": "PUBLISHED"
  },
  "order": {
    "orderNumber": "TT-ABC123-XY78"
  },
  "allAttendees": [
    {
      "id": "ticket_001",
      "ticketCode": "TT-EVP290626-A1B2",
      "attendeeName": "Rahul Kumar",
      "attendeeEmail": "rahul@example.com",
      "attendeePhone": "9876543210",
      "ticketType": "General Admission",
      "status": "ACTIVE",
      "checkedInAt": null
    },
    {
      "id": "ticket_002",
      "ticketCode": "TT-EVP290626-C3D4",
      "attendeeName": "Priya Sharma",
      "attendeeEmail": "priya@example.com",
      "attendeePhone": "9876543211",
      "ticketType": "General Admission",
      "status": "USED",
      "checkedInAt": "2026-06-29T11:15:00.000Z"
    }
  ],
  "eventEnded": false,
  "orderStatus": "CONFIRMED",
  "canCheckIn": true
}

```

Key Fields:

- canCheckIn — true only if: event not ended + ticket ACTIVE + order CONFIRMED
- allAttendees — all tickets in the same order for this event (for partial check-in)
- eventEnded — boolean flag if current time > event endDate

4.2 Check-in Single Ticket

Check in one ticket by its ID (not ticketCode). Use after scanning to confirm entry.

POST **/api/mobile/check-in/:ticketId**

Check-in a single ticket

JWT Required (Organiser/Staff)

URL Example:

```
/api/mobile/check-in/ticket_001
```

Success Response:

```
{
  "ticketId": "ticket_001",
  "status": "CHECKED_IN",
  "checkedInAt": "2026-06-29T11:30:00.000Z"
}
```

Error Responses:

```
{
  "ticketId": "ticket_001",
  "status": "ALREADY_USED",
  "checkedInAt": "2026-06-29T11:15:00.000Z",
  "error": "Already checked in"
}

// Other possible status values:
// "NOT_FOUND"           - Ticket ID doesn't exist
// "FORBIDDEN"           - No access to this event
// "EVENT_ENDED"         - Event has already ended
// "ORDER_NOT_CONFIRMED" - Order is not in CONFIRMED status
// "CANCELLED"           - Ticket was cancelled
```

4.3 Batch Check-in (Partial Check-in for Multi-Attendee)

Check in multiple tickets at once. Perfect for when one order has multiple attendees — you can check in some now and the rest later (partial check-in).

POST **/api/mobile/check-in**

Batch check-in multiple tickets

JWT Required (Organiser/Staff)

Request Body:

```
{
  "ticketIds": [
    "ticket_001",
    "ticket_002",
    "ticket_003"
  ]
}
```

Response:

```
{
  "checkedIn": 2,
  "total": 3,
  "results": [
    {
      "ticketId": "ticket_001",
      "status": "CHECKED_IN",
      "checkedInAt": "2026-06-29T11:30:00.000Z"
    },
    {
      "ticketId": "ticket_002",
      "status": "CHECKED_IN",
      "checkedInAt": "2026-06-29T11:30:00.000Z"
    },
    {
      "ticketId": "ticket_003",
      "status": "ALREADY_USED",
      "checkedInAt": "2026-06-29T10:00:00.000Z",
      "error": "Already checked in"
    }
  ]
}
```

Partial Check-in Flow:

1. Scan QR !' POST /api/mobile/scan !' get allAttendees list
2. Show all attendees with their status (ACTIVE / USED)
3. User selects which ACTIVE tickets to check in
4. POST /api/mobile/check-in with selected ticketIds
5. Some attendees checked in now, rest can be checked in later

4.4 Manual Search by Email / Phone / Name

When QR scanning is not possible, use the attendees endpoint to search by email, phone, or name. This endpoint supports text search across attendeeName and attendeeEmail fields.

GET **/api/orders/organiser/event/:eventId/attendees?search=...**

Search attendees by email/name/phone

JWT Required (@Roles
ORGANISER)

Search Examples:

```
// Search by email
GET /api/orders/organiser/event/clxx_event_001/attendees?search=rahul@example.com
// Search by name
GET /api/orders/organiser/event/clxx_event_001/attendees?search=Rahul
// Search by phone (if stored in attendee data)
GET /api/orders/organiser/event/clxx_event_001/attendees?search=9876543210
// Filter only active (not yet checked in)
GET /api/orders/organiser/event/clxx_event_001/attendees?search=rahul&status=ACTIVE
```

Response format is the same as Section 3.3 (Event Attendees List).

Manual Check-in Flow:

1. Select event from events list
2. Enter email/phone/name in search box
3. GET attendees with search query !' show matching results
4. Tap on attendee !' show ticket details
5. Confirm check-in !' POST /api/mobile/check-in/:ticketId

4.5 Alternative: Verify Ticket by Code (Public)

A public endpoint to verify a ticket — useful for the web verification page. Also usable in the app for ticket details.

GET **/api/tickets/verify/:ticketCode**

Verify ticket by code (public)

Public

Response:

```
{
  "id": "ticket_001",
  "ticketCode": "TT-EVP290626-A1B2",
  "status": "ACTIVE",
  "attendeeName": "Rahul Kumar",
  "attendeeEmail": "rahul@example.com",
  "attendeePhone": "9876543210",
  "qrData": "https://thoovitickets.com/verify/TT-EVP290626-A1B2",
  "checkedInAt": null,
  "orderItem": {
    "ticketType": {
      "name": "General Admission",
      "description": "Standard entry",
      "price": "500.00"
    },
    "event": {
      "id": "clxx_event_001",
      "title": "Summer Music Festival 2026",
      "venue": "Marina Beach Arena",
      "startDate": "2026-06-29T10:00:00.000Z",
      "endDate": "2026-06-29T22:00:00.000Z",
      "organiserId": "clxx1234567890"
    }
  },
  "order": {
    "orderNumber": "TT-ABC123-XY78",
    "status": "CONFIRMED"
  }
}
```

5. Staff Management

Organisers can create staff accounts for their team. Staff with SCANNER or FULL_ACCESS can use the mobile app to scan tickets. Staff limits are controlled by the organiser subscription plan.

5.1 List Staff Members

GET

/api/staff

JWT Required (@Roles
ORGANISER)

Get all staff for current organiser

Response:

```
[
  {
    "id": "staff_001",
    "accessLevel": "SCANNER",
    "isActive": true,
    "organiserId": "clxx1234567890",
    "userId": "clxx9876543210",
    "createdAt": "2026-06-01T10:00:00.000Z",
    "updatedAt": "2026-06-01T10:00:00.000Z",
    "user": {
      "id": "clxx9876543210",
      "email": "staff@example.com",
      "firstName": "Jane",
      "lastName": "Smith",
      "phone": "9876543211",
      "avatarUrl": null
    }
  }
]
```

5.2 Add Staff Member

Add a staff member by their registered email. The user must have a CUSTOMER account.

POST

/api/staff

JWT Required (@Roles
ORGANISER)

Add a new staff member

Request Body:

```
{
  "email": "staff@example.com",
  "accessLevel": "SCANNER" // SCANNER | SUB_ADMIN | FULL_ACCESS
}
```

Success Response:

```
{
  "id": "staff_002",
  "accessLevel": "SCANNER",
  "isActive": true,
  "organiserId": "clxx1234567890",
  "userId": "clxx_newstaff",
  "user": {
    "id": "clxx_newstaff",
    "email": "staff@example.com",
    "firstName": "New",
    "lastName": "Staff",
    "phone": null,
    "avatarUrl": null
  }
}
```

Error Responses:

```
404: "No account found with this email. They must register as a customer first."
400: "Only customer accounts can be added as staff"
400: "Cannot add yourself as staff"
400: "This user is already a staff member"
400: "Staff limit reached (3/3). Upgrade your plan to add more."
```


5.3 Update Staff Member

PATCH **/api/staff/:id**

JWT Required (@Roles
ORGANISER)

Update access level or active status

Request Body:

```
{
  "accessLevel": "FULL_ACCESS", // optional: SCANNER | SUB_ADMIN | FULL_ACCESS
  "isActive": false             // optional: enable/disable app access
}
```

Setting isActive to false disables the staff member from logging into the mobile app.

5.4 Remove Staff Member

DELETE **/api/staff/:id**

JWT Required (@Roles
ORGANISER)

Remove staff member permanently

Response:

```
{ "message": "Staff member removed" }
```

5.5 My Access (Staff View)

For staff users to see which organisers they have access to.

GET **/api/staff/my-access**

JWT Required

Get current user staff access info

Response:

```
[
  {
    "id": "staff_001",
    "accessLevel": "SCANNER",
    "isActive": true,
    "organiserId": "clxx1234567890",
    "userId": "clxx9876543210",
    "organiser": {
      "id": "clxx1234567890",
      "firstName": "John",
      "lastName": "Doe",
      "orgName": "EventPro Org",
      "avatarUrl": "..."
    }
  }
]
```

5.6 Access Level Descriptions

SCANNER — Can only scan tickets and check-in attendees at events

SUB_ADMIN — Limited administrative access (future use)

FULL_ACCESS — Full organiser-level access to events and scanning

6. Tickets Module (Web Endpoints)

These are the web-based ticket endpoints. The mobile module wraps some of these with additional staff access checks.

6.1 Get Tickets by Order

GET

/api/tickets/order/:orderId

Get all tickets for an order

JWT Required (Order Owner)

6.2 Resend Ticket Email

POST

/api/tickets/order/:orderId/send-email

Resend ticket confirmation email

JWT Required (Order Owner)

6.3 Download Invoice

GET

/api/tickets/order/:orderId/invoice

Download order invoice as PDF

JWT Required (Order Owner)

6.4 Check-in via Ticket Code (Web)

Web-based check-in using ticket code. Only for organisers (not staff).

POST

/api/tickets/:ticketCode/check-in

Check-in ticket (organiser only)

JWT Required (@Roles
ORGANISER)

Response:

```
{
  "id": "ticket_001",
  "ticketCode": "TT-EVP290626-A1B2",
  "status": "USED",
  "attendeeName": "Rahul Kumar",
  "attendeeEmail": "rahul@example.com",
  "attendeePhone": "9876543210",
  "checkedInAt": "2026-06-29T11:30:00.000Z",
  "qrData": "...",
  "orderItemId": "oi_001",
  "orderId": "order_001"
}
```

7. Notifications

Get user notifications for the mobile app. Useful for showing alerts about events, check-in status, etc.

GET **/api/notifications**
Get paginated notifications

JWT Required

Query Parameters:

```
{
  "page": 1,      // Page number
  "limit": 20     // Items per page
}
```

Response:

```
{
  "data": [
    {
      "id": "notif_001",
      "type": "EVENT_REMINDER",
      "title": "Event Starting Soon",
      "message": "Summer Music Festival starts in 1 hour",
      "linkUrl": "/events/summer-music-festival-2026",
      "isRead": false,
      "createdAt": "2026-06-29T09:00:00.000Z"
    }
  ],
  "meta": {
    "total": 15,
    "page": 1,
    "limit": 20,
    "totalPages": 1
  }
}
```

GET **/api/notifications/unread-count**
Get unread notification count

JWT Required

Response:

```
{ "count": 5 }
```

POST **/api/notifications/:id/read**
Mark notification as read

JWT Required

POST **/api/notifications/read-all**
Mark all notifications as read

JWT Required

8. Enums & Constants

User Roles

CUSTOMER — Regular ticket buyer (can be staff if assigned)
ORGANISER — Event organiser (can scan own events)
ADMIN — Platform administrator

User Status

PENDING — Awaiting admin approval (organisers)
ACTIVE — Account is active
SUSPENDED — Account suspended by admin
REJECTED — Registration rejected by admin

Event Status

DRAFT — Not yet submitted
PENDING_APPROVAL — Submitted for admin review
APPROVED — Approved but not yet published
REJECTED — Rejected by admin
PUBLISHED — Live and visible to public
POSTPONED — Event postponed
CANCELLED — Event cancelled
COMPLETED — Event has concluded

Order Status

PENDING — Order created, awaiting payment
CONFIRMED — Payment received, tickets generated
CANCELLED — Order cancelled
REFUNDED — Payment refunded
EXPIRED — Order expired (payment timeout)

Ticket Status

ACTIVE — Valid ticket, not yet used
USED — Ticket has been checked in
CANCELLED — Ticket cancelled

Staff Access Levels

SCANNER — QR scanning and check-in only
SUB_ADMIN — Limited admin access (future)
FULL_ACCESS — Full organiser-level access

Payment Status

PENDING — Payment initiated
SUCCESS — Payment successful
FAILED — Payment failed
REFUNDED — Payment refunded

9. Error Handling

All API errors follow a consistent format. Handle these in the Flutter app globally.

Error Response Format

Standard Error:

```
{
  "statusCode": 401,
  "message": "Invalid email or password",
  "error": "Unauthorized"
}
```

Validation Error:

```
{
  "statusCode": 400,
  "message": [
    "email must be an email",
    "password must be longer than or equal to 6 characters"
  ],
  "error": "Bad Request"
}
```

HTTP Status Codes

- 200 — Success
- 201 — Created (new resource)
- 400 — Bad Request (validation error, business rule violation)
- 401 — Unauthorized (invalid/expired token, wrong credentials)
- 403 — Forbidden (no permission, wrong role, no scanner access)
- 404 — Not Found (ticket/event/order not found)
- 429 — Too Many Requests (rate limited)
- 500 — Internal Server Error

Common Error Scenarios for Mobile App

- Token Expired (401) !' Redirect to login screen
- No Scanner Access (403) !' Show "Contact your organiser" message
- Ticket Not Found (404) !' Show "Invalid QR code" message
- Already Checked In !' Show ticket with checkedInAt timestamp
- Event Ended !' Show "Event has ended" message
- Order Not Confirmed !' Show "Payment not completed" message

10. Recommended App Flows

10.1 Login Flow

1. User enters email + password
2. POST /api/mobile/auth/login
3. If role=ORGANISER !' Store token, go to dashboard
4. If role=CUSTOMER with scannerAccess !' Store token + organiser info
5. If error 403 !' Show "No scanner access" message
6. Store accessToken securely (Flutter secure storage)

10.2 QR Scan Flow

1. Open camera / QR scanner
2. Scan QR !' Extract ticketCode from URL
QR Data format: `https://thoovitickets.com/verify/{TICKET_CODE}`
Parse: split by "/" and take last segment
3. POST /api/mobile/scan { ticketCode }
4. Show scan result with ticket + all attendees in order
5. If canCheckIn=true !' Show "Check In" button
6. If multiple attendees !' Show checkboxes for selective check-in
7. POST /api/mobile/check-in { ticketIds: [...selected] }
8. Show success/failure for each ticket

10.3 Manual Search Flow

1. Select event from GET /api/mobile/events
2. Enter email/phone/name in search box
3. GET /api/orders/organiser/event/{eventId}/attendees?search={query}
4. Show matching attendees list
5. Tap attendee !' Show full ticket info
6. Check-in !' POST /api/mobile/check-in/{ticketId}

10.4 Partial Check-in Flow

When one order has 5 tickets (attendees) but only 3 arrive:

1. Scan any one ticket from the order
2. POST /api/mobile/scan !' Returns allAttendees (5 tickets)
3. Display all 5 attendees with checkboxes
4. Staff selects 3 present attendees
5. POST /api/mobile/check-in { ticketIds: [id1, id2, id3] }
6. Result: 3 CHECKED_IN, 2 remain ACTIVE
7. Later, remaining 2 can be checked in the same way

11. QR Code Format Reference

Ticket Code Format

Pattern: TT-{ORG}{DDMMYY}-{HEX}

Example: TT-EVP290626-A1B2C3D4

- TT — ThooviTickets prefix
- ORG — First 3 alphanumeric chars of organiser name (uppercase)
- DDMMYY — Event start date (day-month-year)
- HEX — Random 4-byte hex string

QR Data Content

The QR code contains a URL:

QR Data:

```
"https://thoovitickets.com/verify/TT-EVP290626-A1B2C3D4"
```

In the Flutter app, when scanning:

1. Read the QR code string
2. If it starts with http !' extract the last path segment
3. If it starts with "TT-" !' use directly as ticketCode
4. Pass to POST /api/mobile/scan { ticketCode }

QR Code Image

QR codes are generated as PNG data URLs (base64) and stored in the ticket record as qrDataUrl. These are 300x300px images embedded in ticket emails and invoices.

12. API Quick Reference

All endpoints used by the mobile app at a glance:

POST	/api/mobile/auth/login	Public	Login
GET	/api/auth/me	JWT	Get profile
GET	/api/mobile/dashboard	JWT	Dashboard
GET	/api/mobile/events	JWT	List events
GET	/api/events/detail/:slug	Public	Event details
POST	/api/mobile/scan	JWT	Scan/verify ticket
POST	/api/mobile/check-in/:ticketId	JWT	Check-in single
POST	/api/mobile/check-in	JWT	Batch check-in
GET	/api/orders/organiser/event/:id/attendees	JWT	Search attendees
GET	/api/tickets/verify/:code	Public	Verify ticket
GET	/api/staff	JWT/ORG	List staff
POST	/api/staff	JWT/ORG	Add staff
PATCH	/api/staff/:id	JWT/ORG	Update staff
DELETE	/api/staff/:id	JWT/ORG	Remove staff
GET	/api/staff/my-access	JWT	Staff access info
GET	/api/notifications	JWT	Notifications
GET	/api/notifications/unread-count	JWT	Unread count
POST	/api/notifications/:id/read	JWT	Mark read

All endpoints are prefixed with /api. Base URL in production: <https://api.thoovitickets.com>

JWT tokens should be stored securely using Flutter Secure Storage.

For any questions, contact the backend team.