

YOURSMARTENERGY

SMILE-T10

HOME SERIE

CAPACITY

2.9 kWh modular expandable to 23.0 kWh





UPS ability
Outdoor / Indoor
Modular design
24/7 Monitoring



STORION SMILE-T10



Model	Storion-SMILE-T10						
System Specification							
Nominal Output Power	10 000 VA						
Max. DC Input Power		13 0	000 W*	W* 12 000 W**			
Capacity Range	11.5 kWh ~ 23.0 kWh (90% DoD)						
Battery Chemistry	LFP (LiFePO4)						
IP Protection	IP21 (Indoor) / IP65 (Outdoor)						
Warranty	5 Year Product Warranty, 10 Year Performance Warranty						
Inverter Technical Specification							
Model	SMILE-	T10-INV	Max. AC Output Curre		ent 16.5	t 16.5 A	
Max. PV Input Current	12.5 / 12.5 A*	12.5 / 22 A**	Max. AC Input Current		t 22.7	22.7 A	
Max. PV Input Voltage	1000 V*	600 V**	Output Power Factor			1 (Adjustable from 0.8 leading to 0.8 lagging)	
Max. Short Current	15.2 / 15.2 A*	15.2 / 27.6 A**	Backup		UP	UPS	
MPPT Number	2		Display		LCD (in F	LCD (in HV50056)	
MPPT Voltage Range	200 ~ 850 V*	200 ~ 550 V**	Humidity	/	15% ~ 85% (No Condensing)	
Start-up Voltage	18	0 V	Dimension (W x D x H)		610 x 236 x 605 mm*	610 x 236 x 655 mm**	
Max. Charging / Discharging Current	25 A		Weight		40	kg	
Phase	Three-Phase		Grid Reg	julation	CEI 0-21, VDE4105-AR-N, EN50438, G98, G100*	AS/NZS 4777.2**	
Rated Voltage	400 / 380 V		Safety	y IEC 62109-1&-2, IEC 62040		2, IEC 62040-1	
Rated Frequency	50 / 60 Hz		EMC	EMC EN61000-6-1/2/3/4 EN61000-4-16/18/29			
Battery Technical Specification							
Module Model	M4856-S						
Module Capacity	ity			2.9 kWh			
Module Nominal Voltage			51.2 V				
Operating Temperature Range				-10 °C ~ 50 °C***			
Module Weight	42 kg						
Module Dimension (W x D	sion (W x D x H)			610 x 236 x 303 mm			
Cycle Life	/cle Life			≥ 6000			
Max. Charging/Discharging Current				6 A (1C)			
High Voltage Control Box Technical Specification							
BMU Model			H	HV50056			
DC Voltage Range				179 ~ 465 V			
Nominal Output Current	Iominal Output Current			56 A			
Battery Modules Connection			4 ~ 8 M4	856-S in seri	ies		
*except Australia and New Zealand						C C 150	



- ** +86 513 8060 6891

- ★ +86 513 8060 0891
 ★ info@alpha-ess.com
 ★ www.alpha-ess.com
 Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

- ***** +86 512 6828 7609

- info@alpha-ess.com

 www.alpha-ess.com

 Level 15,SIPC 158 Wangdun Road
 SIP Suzhou, 215028

- * +61 402 500 520 (Sales)

- +61 1300 968 933 (Technical Support)

 australia@alpha-ess.com

 www.alpha-ess.com.au

 Suite 1, Level 1, 530 Botany Road, Alexandria, NSW, 2015

- ***** +82 64 721 2004
- korea@alpha-ess.com
 25, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

uk@alpha-ess.com

☐ Drake House, Long Street,
Dursley, gl11 4hh

^{**}only for Australia and New Zealand

^{***}When the temperture is below 0 °C or above 40 °C, the performance will be limited.