

Tiger Pro 72HC 530-550 Watt

MONO-FACIAL MODULE

P-Type

Positive power tolerance of 0~+3%

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018

Occupational health and safety management systems



Key Features



Multi Busbar Technology

Better light trapping and current collection to improve module power output and reliability.



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.



Reduced Hot Spot Loss

Optimized electrical design and lower operating current for reduced hot spot loss and better temperature coefficient.



Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



Longer Life-time Power Yield

0.55% annual power degradation and 25 year linear power warranty.












LINEAR PERFORMANCE WARRANTY





- **12** Year Product Warranty
- 25 Year Linear Power Warranty
- 0.55% Annual Degradation Over 25 years

Engineering Drawings

Tolkomm Tol

Electrical Performance & Temperature Dependence





Packaging Configuration

(Two pallets = One stack)

31pcs/pallets, 62pcs/stack, 620pcs/ 40'HQ Container

Mechanical Characteristics							
Cell Type	P type Mono-crystalline						
No. of cells	144 (6×24)						
Dimensions	2278×1134×35mm (89.69×44.65×1.38 inch)						
Weight	28 kg (61.73 lbs)						
Front Glass	3.2mm,Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass						
Frame	Anodized Aluminium Alloy						
Junction Box	IP68 Rated						
Output Cables	TUV 1×4.0mm ² (+): 400mm (-): 200mm or Customized Length						

SPECIFICATIONS											
Module Type	JKM530M-72HL4 JKM530M-72HL4-V		JKM535M-72HL4 JKM535M-72HL4-V		JKM540M-72HL4 JKM540M-72HL4-V		JKM545M-72HL4 JKM545M-72HL4-V		JKM550M-72HL4 JKM550M-72HL4-V		
	STC	NOCT									
Maximum Power (Pmax)	530Wp	394Wp	535Wp	398Wp	540Wp	402Wp	545Wp	405Wp	550Wp	409Wp	
Maximum Power Voltage (Vmp)	40.56V	37.84V	40.63V	37.91V	40.70V	38.08V	40.80V	38.25V	40.90V	38.42V	
Maximum Power Current (Imp)	13.07A	10.42A	13.17A	10.50A	13.27A	10.55A	13.36A	10.60A	13.45A	10.65A	
Open-circuit Voltage (Voc)	49.26V	46.50V	49.34V	46.57V	49.42V	46.65V	49.52V	46.74V	49.62V	46.84V	
Short-circuit Current (Isc)	13.71A	11.07A	13.79A	11.14A	13.85A	11.19A	13.94A	11.26A	14.03A	11.33A	
Module Efficiency STC (%)	20.52%		20.71%		20.90%		21.10%		21.29%		
Operating Temperature(°C)	-40°C~+85°C										
Maximum system voltage	1000/1500VDC (IEC)										
Maximum series fuse rating	25A										
Power tolerance	0~+3%										
Temperature coefficients of Pmax	-0.35%/℃										
Temperature coefficients of Voc	-0.28%/℃										
Temperature coefficients of Isc	0.048%/℃										
Nominal operating cell temperatu	ure (NOCT) 45±2℃										













