

MethylPipeline User Manual

Operational runbook for package usage and staged workflows

MethylPipeline Team

2026-04-17

Table of contents

1	MethylPipeline User Manual	6
1.1	What this manual is	6
1.2	Reading paths	6
1.3	End-to-end workflow map	6
1.4	Scope boundaries	6
1.5	Canonical references	7
I	Part I: Setup and Package Orientation	8
2	Prerequisites and Environment	9
2.1	Purpose	9
2.2	Required tools	9
2.3	Environment bootstrap	9
2.4	Verify CLI availability	9
2.5	Runtime assumptions	10
2.6	Success checks	10
2.7	Common failures and fixes	10
2.8	See also	10
3	Project Config and Layout	11
3.1	Purpose	11
3.2	Minimum structure	11
3.3	Validation stage keys that matter most	11
3.4	Output layout	12
3.5	Handoff model	12
3.6	Do not do this	12
3.7	Success checks	13
3.8	See also	13
4	Package Reference (Individual Usage)	14
4.1	Purpose	14
4.2	Package quick map	14
4.3	Standalone examples	15
4.3.1	Alignment QC	15
4.3.2	Enrichment from mapper output	15
4.3.3	Blind prediction with frozen model	15
4.4	Orchestrated equivalents in <code>methy1-validation</code>	15
4.5	Integration diagram	15
4.6	Do not do this	16

4.7	See also	16
II	Part II: Staged Solution Workflow	17
5	Stage: Stability	18
5.1	Purpose	18
5.2	Entry command	18
5.3	Required config keys	18
5.4	Process model	19
5.5	Expected outputs	19
5.6	Success checks	19
5.7	Do not do this	19
5.8	Recovery	19
5.9	See also	20
6	Stage: Freeze	21
6.1	Purpose	21
6.2	Entry command	21
6.3	Prerequisites	21
6.4	Process model	21
6.5	Expected outputs	22
6.6	Success checks	22
6.7	Do not do this	22
6.8	Recovery	22
6.9	See also	22
7	Stage: Model	23
7.1	Purpose	23
7.2	Common execution patterns	23
7.2.1	Pattern A: Direct production model build	23
7.2.2	Pattern B: Backend model-MC comparison then select best	23
7.3	Backend behavior	23
7.4	Process model	24
7.5	Required config keys	24
7.6	Expected outputs	24
7.7	Success checks	25
7.8	Do not do this	25
7.9	See also	25
8	Stage: Post-model Validation	26
8.1	Purpose	26
8.2	Entry command	26
8.3	Prerequisites	26
8.4	Process model	27
8.5	Expected outputs	27
8.6	Success checks	27
8.7	Do not do this	28

8.8	Recovery	28
8.9	See also	28
9	Stage: Blind Prediction	29
9.1	Purpose	29
9.2	Important boundary	29
9.3	Entry command (standalone)	29
9.4	Process model	29
9.5	Required config pattern	29
9.6	Expected outputs	30
9.7	Success checks	30
9.8	Do not do this	30
9.9	Recovery	30
9.10	See also	30
III	Part III: Operations and Reliability	31
10	Artifacts and QA Checks	32
10.1	Purpose	32
10.2	Artifact map	32
10.3	Handoff integrity checks	33
10.4	QA checklist per stage	33
10.4.1	Stability	33
10.4.2	Freeze	33
10.4.3	Model	33
10.4.4	Post-model validation	33
10.4.5	Blind prediction	34
10.5	Escalation triggers	34
10.6	See also	34
11	Troubleshooting and Recovery	35
11.1	Purpose	35
11.2	Failure routing	35
11.3	Common problems	35
11.4	Safe recovery sequence	36
11.5	Resume examples	36
11.6	Operational guardrails	36
11.7	See also	36
12	Command Cookbook	37
12.1	Purpose	37
12.2	1) Full staged run (strict profile example)	37
12.3	2) Backend comparison and selection	37
12.4	3) Rollout comparison report	37
12.5	4) Standalone enricher run from mapper output	38
12.6	5) Standalone blind prediction	38
12.7	6) Manual rendering commands (this manual)	38

12.8 Execution notes	38
--------------------------------	----

1 MethylPipeline User Manual

1.1 What this manual is

This is the operational companion to the theory book. It is designed for execution teams who need:


- exact commands,
- required config keys,
- expected output artifacts,
- stage handoff checks,
- recovery actions when a run fails.

For statistical background, use `docs/theory/`.

1.2 Reading paths

- **Fast path (stage execution):** Chapters 04 to 08.
- **New project setup:** Chapters 01, 02, then 04.
- **Daily operations:** Chapters 09 to 11.
- **Standalone package usage:** Chapter 03.

1.3 End-to-end workflow map



1.4 Scope boundaries

- `methyl-validation` orchestrates stability, freeze, model, and post-model validation.
- Blind-only prediction is documented as a standalone `methyl-predictor` operation.
- Package behavior is documented from implementation in `packages/*`.

1.5 Canonical references

- Workflow reference: docs/WORKFLOW_DIAGRAM_PACK_Healthy_vs_PCa1-4-CG.md
- Validation orchestration: packages/methylvalidation/docs/USAGE.md
- Validation flags and config model:
 - packages/methylvalidation/methyl_validation/cli.py
 - packages/methylvalidation/methyl_validation/config.py

Part I

Part I: Setup and Package Orientation

2 Prerequisites and Environment

2.1 Purpose

Set up a reproducible execution environment for all package CLIs and workflow stages.

2.2 Required tools

- Python environment in repo-local `.venv`
- Installed package CLIs (`methyl-*`)
- Quarto for manual rendering (optional for pipeline runs)
- TeX engine for PDF rendering (`quarto install tinytex` recommended)

2.3 Environment bootstrap

From repo root:

```
python3.12 -m venv .venv
source .venv/bin/activate
bash scripts/install_all.sh
```

Optional dependency sets:

```
bash scripts/install_all.sh --pipeline-reqs
bash scripts/install_all.sh --gpu-reqs
```

2.4 Verify CLI availability

```
source .venv/bin/activate
methyl-validation --help
methyl-centroid --help
methyl-detector --help
methyl-mapper --help
methyl-enricher --help
methyl-predictor --help
```

2.5 Runtime assumptions

- Activate `.venv` before every run.
- Use absolute paths in project configs where possible.
- Keep `samples_base_path` consistent across stages.

2.6 Success checks

- `.venv` activates without import errors.
- `methy1-validation --help` prints options.
- Project JSON path resolves on the execution host.

2.7 Common failures and fixes

- **command not found:** activate `.venv` and reinstall with `scripts/install_all.sh`.
- **module import errors:** reinstall editable packages from repo root.
- **path mismatch between hosts:** set `step_config.validation.path_remap` or `--path-remap OLD=NEW`.

2.8 See also

- `README.md`
- `docs/DEPLOYMENT.md`

3 Project Config and Layout

3.1 Purpose

Define a project JSON that can run through stability, freeze, model, and evaluation without per-stage schema drift.

3.2 Minimum structure

Use one project file containing:

- global cohort metadata (`controls`, `diseases`, `comparisons`),
- filesystem anchors (`output_base`, `samples_base_path`),
- step-specific overrides under `step_config`.

Core stage driver:

- `step_config.validation` (parsed into `MonteCarloConfig` by `methy1-validation`).

3.3 Validation stage keys that matter most

- split policy: `train_fraction`, `n_iterations`, `seed`
- stability controls:
 - `run_stability`
 - `stability_dmp_freq`
 - `stability_min_balanced_accuracy`
 - `stability_gene_freq`
 - `stability_featurecuts_enabled`
 - `stability_target_balanced_accuracy`
 - `stability_min_selected_dmps`
- freeze/model paths:
 - `freeze_stable_dmp_csv` (optional)
 - `production_output_dir` (optional)
- backend/model:
 - `model_backend`
 - `feature_mode`
 - `ecdf_second_stage_enabled`
 - backend-specific `tabular_*` / `generative_*` keys

3.4 Output layout


Most runs write to:

`<output_base>/<project_name>/monte_carlo_runs/`

Important subtrees:

- `run_XXXX/` (per-iteration artifacts)
- `stability/` (stable panel and summaries)
- `production/` (freeze and final model outputs)
- `model_mc/` (backend comparison runs)
- `post_model_validation/` (frozen-model descriptive evaluation)

3.5 Handoff model



3.6 Do not do this

- Do not put blind-only predictor config (`predictor.blind`) into validation-driven runs.
- Do not change `samples_base_path` between stages without explicit remap.

- Do not run `--freeze` before stable panel exists.

3.7 Success checks

- Project loads in `methyl-validation --project ....`
- `step_config.validation` exists and parses.
- Run directories appear under expected root.

3.8 See also

- `docs/theory/chapters/11-project-configuration.qmd`
- `docs/theory/chapters/13-configuration-reference.qmd`

4 Package Reference (Individual Usage)

4.1 Purpose

Summarize each active package as a standalone tool, then map it to staged `methyl-validation` orchestration.

4.2 Package quick map

Package	CLI	Primary role	Typical standalone output
<code>methylalignmentqc</code>	<code>methyl-qc</code>	Parse alignment/dup metrics into normalized JSON	<code>alignment_qc/<sample>.json</code>
<code>methylcentroid</code>	<code>methyl-centroid</code>	Build cohort centroids from methylation files	centroid artifacts per group
<code>methyldetector</code>	<code>methyl-detector</code>	Discover/classify DMPs	<code>dmps-*-discovery.csv</code> , <code>result*.json</code>
<code>methylmapper</code>	<code>methyl-mapper</code>	Map DMP loci to genes/features	<code>all-gene_name-combined.csv</code>
<code>methylenricher</code>	<code>methyl-enricher</code>	Enrichment/module interpretation	<code>enrichment_merged.csv</code> , <code>modules_ranked.csv</code>
<code>methylclassifier</code>	<code>methyl-classifier</code>	Train production classifier (ECDF path)	<code>classifiers/*.pkl</code>
<code>methylpredictor</code>	<code>methyl-predictor</code>	Predict and report metrics/inference	<code>predictors/*/validation_metrics</code> or blind reports
<code>methylvalidation</code>	<code>methyl-validation</code>	Orchestrate MC/stability/freeze/model workflows	<code>monte_carlo_runs/*</code>
<code>methyl-disease-progression</code>	<code>methyl-disease-progression</code>	Cross-stage synthesis from mapper/enricher outputs	<code>progression/*.csv</code> , <code>summary.json</code>

4.3 Standalone examples

4.3.1 Alignment QC

```
source .venv/bin/activate
methyl-qc --metrics-root /data/metrics --output-dir /work/alignment_qc
```

4.3.2 Enrichment from mapper output

```
source .venv/bin/activate
methyl-enricher --input /work/project/mapper/pca_pca1/all-gene_name-combined.csv --modules --o
```


4.3.3 Blind prediction with frozen model

```
source .venv/bin/activate
methyl-predictor --project /work/project/monte_carlo_runs/production/project.json
```

4.4 Orchestrated equivalents in methyl-validation

- Stability stage runs centroid+detector per iteration.
- Freeze stage runs centroid->detector->mapper->enricher (and optional progression).
- Model stage runs:
 - ecdf: classifier->predictor
 - tabular_sklearn / generative_hybrid: in-process backend train/predict
- Post-model validation runs frozen-model descriptive holdouts.

4.5 Integration diagram



4.6 Do not do this

- Do not assume standalone package defaults match project-orchestrated overrides.
- Do not skip `project.json` artifact handoff checks when chaining packages manually.

4.7 See also

- `README.md`
- `packages/*/docs/USAGE.md`

Part II

Part II: Staged Solution Workflow

5 Stage: Stability

5.1 Purpose

Run repeated train/validation iterations to identify DMPs that recur across runs and materialize a stable production panel.

5.2 Entry command

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --
```

Optional strict FeatureCuts alignment:


```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json \
  --stability --stability-featurecuts --stability-target-ba 0.95 --stability-min-selected-dmps
```

5.3 Required config keys

Under `step_config.validation`:

- `n_iterations`, `train_fraction`, `seed`
- `run_stability`
- `stability_dmp_freq`
- `stability_min_balanced_accuracy`
- `stability_gene_freq`
- optional FeatureCuts controls:
 - `stability_featurecuts_enabled`
 - `stability_target_balanced_accuracy`
 - `stability_min_selected_dmps`

5.4 Process model



5.5 Expected outputs

- <mc_root>/stability/stable_dmps_production.csv
- <mc_root>/stability/stability_summary.json
- <mc_root>/all_metrics.csv
- <mc_root>/metrics_summary.json
- <mc_root>/baseline_manifest.json

Where <mc_root> is: <output_base>/<project_name>/monte_carlo_runs/

5.6 Success checks

- stable_dmps_production.csv exists and is non-empty.
- all_metrics.csv has successful rows near expected run count.
- stability_summary.json reports configured thresholds.

5.7 Do not do this

- Do not proceed to freeze when stable panel is missing or empty.
- Do not interpret blind outputs as stability quality evidence.

5.8 Recovery

- Resume interrupted run:

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --s
```

- If panel is too small: lower `stability_dmp_freq` or increase `n_iterations`.
- If run quality is too low: tune detector and/or adjust `stability_min_balanced_accuracy`.

5.9 See also

- [docs/theory/chapters/12-two-workflows.qmd](#)
- [docs/theory/chapters/15-model-creation-and-validation.qmd](#)

6 Stage: Freeze

6.1 Purpose

Create frozen production artifacts using the stable panel and generate biological interpretation outputs (mapper/enricher, optional progression).


6.2 Entry command

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --
```

6.3 Prerequisites

- Stability stage completed.
- Stable panel available at:
 - configured `step_config.validation.freeze_stable_dmp_csv`, or
 - default `<mc_root>/stability/stable_dmps_production.csv`.

6.4 Process model



6.5 Expected outputs

- `<mc_root>/production/project.json`
- `<mc_root>/production/production_summary.json`
- mapper outputs under `production/mapper/...`
- enricher outputs under `production/enricher/...`
- optional progression outputs under `production/progression/...`

6.6 Success checks

- `production/project.json` exists and includes fixed panel usage for detector.
- expected mapper and enricher files are present.
- stage-specific logs show successful return codes.

6.7 Do not do this

- Do not run freeze before stability panel exists.
- Do not delete `production/project.json`; later model and predictor stages depend on it.

6.8 Recovery

- If freeze fails because stable panel missing, rerun stability or set `freeze_stable_dmp_csv`.
- If path mismatch occurs across machines, use `path_remap` or `--path-remap`.

6.9 See also

- `packages/methylvalidation/docs/USAGE.md`
- `docs/theory/chapters/14-user-guide.qmd`

7 Stage: Model

7.1 Purpose

Train and select final production model artifacts after freeze.

7.2 Common execution patterns

7.2.1 Pattern A: Direct production model build

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --r
```

7.2.2 Pattern B: Backend model-MC comparison then select best


```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --r
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json \
  --select-best-model --model-mc-all --selection-metric balanced_accuracy --selection-stat med
```

7.3 Backend behavior

- ecdf: methyl-classifier -> methyl-predictor
- tabular_sklearn: in-process bundle -> train -> predict
- generative_hybrid: in-process bundle -> train -> predict

Configured by `step_config.validation.model_backend` or CLI override.

7.4 Process model



7.5 Required config keys

- `model_backend`
- `feature_mode`
- `ecdf_second_stage_enabled`
- tabular controls:
 - `tabular_methods` or `tabular_model_type`
 - `tabular_method_selection_metric`
- generative controls:
 - `generative_latent_dim`, `generative_epochs`, and related keys
- optional gate:
 - `require_biological_review_for_model`
 - `biological_review_confirmed`

7.6 Expected outputs

- `<mc_root>/production/classifiers/...`

- `<mc_root>/production/predictors/...`
- if model-MC:
 - `<mc_root>/model_mc/shared/run_XXXX/...`
 - `<mc_root>/model_mc/<backend>/all_metrics.csv`
 - `<mc_root>/model_mc/backend_ranking.csv`
 - `<mc_root>/production/selected_backend.json` (after selection)

7.7 Success checks

- final classifier/predictor artifacts exist in production root.
- selected backend metadata exists when using selection workflow.
- metrics summaries include expected selection metric fields.

7.8 Do not do this

- Do not run model before freeze.
- Do not claim backend superiority without model-MC summaries.

7.9 See also

- `docs/theory/chapters/15-model-creation-and-validation.qmd`
- `packages/methylvalidation/docs/ROLLOUT.md`

8 Stage: Post-model Validation

8.1 Purpose

Measure descriptive performance distributions using frozen production artifacts without retraining.

8.2 Entry command

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --]
```


Optional backend override:

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json \
  --post-model-validation --post-model-backend ecdf
```

8.3 Prerequisites

- Freeze/model artifacts already built in production root.
- Valid production/project.json.

8.4 Process model



8.5 Expected outputs

- `<mc_root>/post_model_validation/run_XXXX/...`
- `<mc_root>/post_model_validation/all_metrics.csv`
- `<mc_root>/post_model_validation/metrics_summary.json`
- `<mc_root>/post_model_validation/metrics_distributions_plotly.html`

8.6 Success checks

- run directories created under `post_model_validation`.
- metrics summary includes key metrics (`balanced_accuracy`, `macro_f1`, plus available calibration metrics).
- distribution plot generated.

8.7 Do not do this

- Do not treat post-model validation as model training.
- Do not compare candidate and baseline manually without fixed thresholds; use rollout comparison when promoting.

8.8 Recovery

- Resume interrupted post-model validation:

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json \
  --post-model-validation --resume
```

8.9 See also

- [packages/methylvalidation/docs/USAGE.md](#)
- [packages/methylvalidation/docs/ROLLOUT.md](#)

9 Stage: Blind Prediction

9.1 Purpose

Run inference on newly arrived unlabeled samples using frozen model artifacts.


9.2 Important boundary

Blind-only prediction is a standalone `methyl-predictor` operation. It is intentionally outside `methyl-validation` accuracy workflows.

9.3 Entry command (standalone)

```
source .venv/bin/activate
methyl-predictor --project /work/prostate-cancer/Healthy_vs_PCa1-4-CG/monte_carlo_runs/product.
```

9.4 Process model



9.5 Required config pattern

`step_config.predictor` should reference blind/test-blind inputs and model paths resolved from frozen production project.

9.6 Expected outputs

- blind prediction report JSON
- per-sample class probabilities and predicted subgroup labels

9.7 Success checks

- predictor completes without missing model-path errors.
- expected blind report file exists.
- per-sample prediction rows match input sample count.

9.8 Do not do this

- Do not use blind-only prediction results as labeled validation accuracy claims.
- Do not run blind-only predictor settings through `methy1-validation` MC paths.

9.9 Recovery

- If model path resolution fails, confirm `production/project.json` and classifier artifacts exist.
- If sample-id join fails, verify sample path naming and predictor input lists.

9.10 See also

- `packages/methylpredictor/docs/USAGE.md`
- `docs/theory/chapters/14-user-guide.qmd`

Part III

Part III: Operations and Reliability

10 Artifacts and QA Checks


10.1 Purpose

Provide a single checklist for expected files at each stage and quick quality gates before proceeding.

10.2 Artifact map

Stage	Required artifacts	Gate to proceed
Stability	<code>stability/stable_dmps_production/</code> , <code>stability_summary.json</code> , <code>all_metrics.csv</code>	Stable panel exists and is non-empty
Freeze	<code>production/project.json</code> , mapper/enricher outputs	Production project exists; fixed-panel detector run completed
Model	<code>production/classifiers/*</code> , <code>production/predictors/*</code>	Final classifier/predictor artifacts present
Post-model validation	<code>post_model_validation/all_metrics_summary.json</code> , plotly report	Distribution summaries generated
Blind prediction	blind prediction report + per-sample probabilities	All input blind samples receive predictions

10.3 Handoff integrity checks



10.4 QA checklist per stage

10.4.1 Stability

- Iteration count in metrics roughly matches configured `n_iterations`.
- Stable panel size is consistent with selected thresholds.

10.4.2 Freeze

- `production/project.json` references fixed panel detector mode.
- Mapper/enricher outputs exist for each expected comparison group.

10.4.3 Model

- Backend used is recorded and consistent with config.
- If selection used, ranking artifacts exist and chosen backend is traceable.

10.4.4 Post-model validation

- Metrics summary includes required decision metrics.
- Distribution artifacts generated and readable.

10.4.5 Blind prediction

- Prediction outputs include all requested samples.
- Operational report does not include false accuracy claims.

10.5 Escalation triggers

- Empty stable panel.
- Missing production project.
- No model artifacts after model stage.
- Repeated run failures in same step across resumed runs.

10.6 See also


- `packages/methylvalidation/docs/USAGE.md`
- `packages/methylvalidation/docs/IMPLEMENTATION.md`

11 Troubleshooting and Recovery

11.1 Purpose

Standardize response for common stage failures and reduce ad-hoc debugging.

11.2 Failure routing



11.3 Common problems

Symptom	Likely cause	Recovery
command not found: methyl-validation	.venv inactive or install missing	Activate .venv, rerun scripts/install_all.sh
freeze fails for missing stable panel	stability not run or wrong path	Run --stability or set freeze_stable_dmp_csv
model fails due to biological review gate	require_biological_review_for and not confirmed	set model=true biological_review_confirmed=true after review
path file-not-found across hosts	environment path differences	use path_remap/--path-remap OLD=NEW

Symptom	Likely cause	Recovery
blind predictor rejected in validation mode	blind settings passed to <code>methyl-validation</code>	run blind mode with standalone <code>methyl-predictor</code>

11.4 Safe recovery sequence

1. Validate environment and CLI availability.
2. Confirm previous-stage artifacts exist.
3. Re-run failed stage only.
4. Use resume mode where supported.
5. Re-check QA gates before advancing.

11.5 Resume examples

```
source .venv/bin/activate
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --resume
methyl-validation --project /work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json --resume
```

11.6 Operational guardrails

- Keep original run directories for traceability.
- Prefer additive reruns over manual artifact edits.
- Record config overrides used in reruns.

11.7 See also

- `docs/code_first_discovery_report.md`
- `docs/config_parameter_matrix.md`

12 Command Cookbook

12.1 Purpose

Provide copy-ready command sequences for the full solution lifecycle.

12.2 1) Full staged run (strict profile example)

```
source .venv/bin/activate
PROJECT="/work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json"

methyl-validation --project "$PROJECT" --stability
methyl-validation --project "$PROJECT" --freeze
methyl-validation --project "$PROJECT" --model
methyl-validation --project "$PROJECT" --post-model-validation
```

12.3 2) Backend comparison and selection

```
source .venv/bin/activate
PROJECT="/work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json"

methyl-validation --project "$PROJECT" --model-mc --model-mc-all
methyl-validation --project "$PROJECT" --select-best-model --model-mc-all \
  --selection-metric balanced_accuracy --selection-stat median
```

12.4 3) Rollout comparison report

```
source .venv/bin/activate
PROJECT="/work/prostate-cancer/configs/project_Healthy_vs_PCa1-4-CG.json"
BASE="/work/prostate-cancer/Healthy_vs_PCa1-4-CG/monte_carlo_runs/model_mc/ecdf/metrics_summary"
CAND="/work/prostate-cancer/Healthy_vs_PCa1-4-CG/monte_carlo_runs/model_mc/tabular_sklearn/metrics_summary"

methyl-validation --project "$PROJECT" --rollout-compare \
  --baseline-summary "$BASE" --candidate-summary "$CAND"
```

12.5 4) Standalone enricher run from mapper output

```
source .venv/bin/activate
methyl-enricher \
  --input /work/prostate-cancer/Healthy_vs_PCa1-4-CG/mapper/all/pca_pca1/all-gene_name-combined
  --modules \
  --library-preset cancer-extended \
  --outdir /work/prostate-cancer/Healthy_vs_PCa1-4-CG/enricher/all/pca_pca1
```

12.6 5) Standalone blind prediction

```
source .venv/bin/activate
methyl-predictor --project /work/prostate-cancer/Healthy_vs_PCa1-4-CG/monte_carlo_runs/product.
```

12.7 6) Manual rendering commands (this manual)

```
quarto render docs/user-manual --to html
quarto render docs/user-manual --to pdf
```

12.8 Execution notes

- Always activate `.venv` before `methyl-*` commands.
- Use absolute project paths in production scripts.
- Keep command logs with timestamp and git commit hash for audit.