PinPlace: CNN based location image search And its adaptation to social network

TEAM H Week 11



CNN Build

- **Check confusion matrix**

CHE SEUNG YUN

- **Modify image dataset**

HONG SEONGJUN

Front end

- **Work on web app page**

JEONG CHAEWON, LEE JI SEOP

CNN Model build > Week 9



CNN Build

“In this week?”

- Select the model
- Implement confusion matrix and check which dataset needs to be modified
- Modify the dataset

Choose 10 classes

Data Collect

Data processing

Data Learning

Simple CNN Model

various CNN Model

Deploy API

CNN Model build > Week 9

Select model

➢ Model spec

- ResNet50 model is adopted.
- Total image data : 25,450
- Training & validation data: 17,815
- Input Size : 128 * 128
- Train set, Validation set, Test set : 5:2:3
- Classes : 10
- Batch size : 32 epoch : 80
- Optimizer : Nadam

"Our selected model?"

conv5_block3_2_conv (Conv2D)	(None, 4, 4, 512)	2359296	conv5_block3_2_pad[0][0]
conv5_block3_2_bn (BatchNormali	(None, 4, 4, 512)	2048	conv5_block3_2_conv[0][0]
conv5_block3_2_relu (Activation	(None, 4, 4, 512)	0	conv5_block3_2_bn[0][0]
conv5_block3_3_conv (Conv2D)	(None, 4, 4, 2048)	1050624	conv5_block3_2_relu[0][0]
conv5_block3_out (Add)	(None, 4, 4, 2048)	0	conv5_block2_out[0][0] conv5_block3_3_conv[0][0]
post_bn (BatchNormalization)	(None, 4, 4, 2048)	8192	conv5_block3_out[0][0]
post_relu (Activation)	(None, 4, 4, 2048)	0	post_bn[0][0]
avg_pool (GlobalAveragePooling2	(None, 2048)	0	post_relu[0][0]
predictions (Dense)	(None, 10)	20490	avg_pool[0][0]

Total params: 23,585,290
Trainable params: 23,539,850
Non-trainable params: 45,440

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3)
```

```
history = model.fit(X_train, y_train, batch_size=32, epochs=80, validation_split=0.2)
```

```
model = ResNet50V2(include_top=True, weights=None, input_shape=(128,128,3), classes=10)
model.compile(loss='categorical_crossentropy', optimizer='Nadam', metrics=['accuracy'])
```

CNN Model build > Week 9

Result of Select model

- Accuracy of model is 89.86%

```
#모델 정확도 출력
print("정확도 : %.4f" % (model.evaluate(X_test, y_test)[1]))
```

```
239/239 [==============================] - 8s 27ms/step - loss: 0.5901 - accuracy: 0.8986
정확도 : 0.8986
```





Confusion matrix

Confusion Matrix

```
[[627   5   4   2   2   1   0   8   7   3]
 [  5 814   8   1   4   3   4   2   1   8]
 [  4  14 586  11   1   3   4   4  11  14]
 [  9  11  13 640   2   6   6  30   7   7]
 [ 20  15   6   2 776   1  10   3   5  31]
 [ 10  15   8   3   0 586   4  13   1  17]
 [  3  19   4   1   7   0 789   3   3  36]
 [ 12   9   1   2   1   5   0 701  12   9]
 [ 11   6   4   3   1   1   1   6 872   6]
 [ 12  50  14   6  12  17  86  11  11 471]]
```

Simple confusion matrix

```python
from sklearn.metrics import confusion_matrix
import matplotlib.pyplot as plt
import itertools
labels = ["DDP", "GLFP", "NP", "NST","THSM",
                "MC", "IHV", "JLT", "HRS", "HBC"]

y_pred=model.predict(X_test)
y_test=np.argmax(y_test, axis=1)
y_pred=np.argmax(y_pred, axis=1)
cm = confusion_matrix(y_test, y_pred)
print(cm)
```

Code for confusion matrix

Confusion matrix

Code for Confusion Matrix by using matplot

```
def plot_confusion_matrix(con_mat, labels, title='Confusion Matrix', cmap=plt.cm.get_cmap('Blues'), normalize=False):
    plt.imshow(con_mat, interpolation='nearest', cmap=cmap)
    plt.title(title)
    plt.colorbar()
    marks = np.arange(len(labels))
    nlabels = []
    for k in range(len(con_mat)):
        n = sum(con_mat[k])
        nlabel = '{0}(n={1})'.format(labels[k],n)
        nlabels.append(nlabel)
    plt.xticks(marks, labels)
    plt.yticks(marks, nlabels)

    thresh = con_mat.max() / 2.
    if normalize:
        for i, j in itertools.product(range(con_mat.shape[0]), range(con_mat.shape[1])):
            plt.text(j, i, '{0}%'.format(con_mat[i, j] * 100 / n), horizontalalignment="center", color="white" if con_mat[i, j] > thresh else "black")
    else:
        for i, j in itertools.product(range(con_mat.shape[0]), range(con_mat.shape[1])):
            plt.text(j, i, con_mat[i, j], horizontalalignment="center", color="white" if con_mat[i, j] > thresh else "black")
    plt.tight_layout()
    plt.ylabel('True label')
    plt.xlabel('Predicted label')
    plt.show()

plot_confusion_matrix(cm, labels=labels)
```

CNN Model build > Week 9

Confusion matrix



- DDP : Dongdaemun Design Plaza
- GLFP : Gyeongui Line Forest Park
- NP : Naksan Park
- NST : Namsan Seoul Tower
- THSM : The Hyundai Seoul Mall
- MC : Myeongdong Cathedral
- IHV : Ikseon Dong Hanok Village
- JLT : Jamsil Lotte Tower
- HRS : Han River Sebitseom
- HBC : Haebangchon

CNN Model build > Week 9

Confusion matrix

All of these are Haebangchon



Hanok village

Gyeongui Line Forest Park

The Hyundai Seoul Mall

➢ Cause of problem

- These place has too much broad regional range
- Especially, Haebangchon has so many different pictures of various location

CNN Model build > Week 9

Confusion matrix

Namsan Seoul Tower

Jamsil lotte tower

➢ Cause of problem

- If we take the picture far from the tower, the features of them is very similar as distance is increasing
- Compare two towers above

CNN Model build > Week 9

Confusion matrix



BEFORE



AFTER

- DDP : Dongdaemun Design Plaza
- GLFP : Gyeongui Line Forest Park
- NP : Naksan Park
- NST : Namsan Seoul Tower
- THSM : The Hyundai Seoul Mall
- MC : Myeongdong Cathedral
- IHV : Ikseon Dong Hanok Village
- JLT : Jamsil Lotte Tower
- HRS : Han River Sebitseom
- HBC : Haebangchon

➢ Improved performance

- We remove ambiguous images
- Then, we can get 91% accuracy as same condition
- Also, we get improved result in confusion matrix

```
#모델 정확도 출력
print("정확도 : %.4f" % (model.evaluate(X_test, y_test)[1]))
```

```
230/230 [==============================] - 7s 31ms/step - loss: 0.4801 - accuracy: 0.9112
정확도 : 0.9112
```

CNN Model build > Week 9

Next week

1. Finally modify the dataset

   HONG SEONG JUN

2. Choose the final model & check the accuracy

   CHE SEUNG YUN

3. Sum up the CNN building process for final report

   CHE SEUNG YUN, UHM JI YONG

Frontend

We are near the end!

- **Last week, we did…**

More on SNS page



"My Page"



Frontend > SNS Page

- Posts by users are shown under the “Top” section
- Posts will consist of an image and some text
- One may keep scrolling to see more posts hypothetically

Frontend > My Page



- Images uploaded by oneself is shown
- Design is similar to hotplace pages
- Needs to be tied with user credential

Frontend > Find Place



- After the AI model predicts, an upload button shows
- The uploaded photo will be shown in My Page

- **Refactoring**

- Writing style is quite different
- Website structure is like a spaghetti code
- For easy maintenance, we need to focus on refactoring

- **Design fix**

- There may still exist still some visual errors and lack of styling
- We have fixed what we discovered before, but some remains


THANK YOU :)