

SANKARA GOMATHI.R.

240701470

Week-12-User-Defined Functions

[Dashboard](#) / [My courses](#) / [GE23131-PUC-2024](#) / [Week-12-User-Defined Functions](#)

A binary number is a combination of 1s and 0s. Its n^{th} least significant digit is the n^{th} digit starting from the right starting with 1. Given a decimal number, convert it to binary and determine the value of the the 4th least significant digit.

Example

number = 23

- Convert the decimal number 23 to binary number: $23^{10} = 2^4 + 2^2 + 2^1 + 2^0 = (10111)_2$.
- The value of the 4th index from the right in the binary representation is 0.

Function Description

Complete the function fourthBit in the editor below.

fourthBit has the following parameter(s):

int number: a decimal integer

Returns:

int: an integer 0 or 1 matching the 4th least significant digit in the binary representation of number.

Constraints

$0 \leq \text{number} < 2^{31}$

Reset answer

```
1  /*
2  * Complete the 'fourthBit' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER number as parameter.
6  */
7
8  int fourthBit(int n)
9  {
10     int b[32];
11     int i=0;
12     while(n>0)
13     {
14         b[i]=n%2;
15         n/=2;
16         i++;
17     }
18     if(i>=4){
19         return b[3];
20     }
21     else
22         return 0;
23
24 }
```

	Test	Expected	Got	
✓	printf("%d", fourthBit(32))	0	0	✓
✓	printf("%d", fourthBit(77))	1	1	✓

Passed all tests! ✓

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the list, sorted ascending. If there is no p^{th} element, return 0.

Example

$n = 20$

$p = 3$

The factors of 20 in ascending order are {1, 2, 4, 5, 10, 20}. Using 1-based indexing, if $p = 3$, then 4 is returned. If $p > 6$, 0 would be returned.

Function Description

Complete the function `pthFactor` in the editor below.

`pthFactor` has the following parameter(s):

`int n`: the integer whose factors are to be found

`int p`: the index of the factor to be returned

`int`: the long integer value of the p^{th} integer factor of n or, if there is no factor at that index, then 0 is returned

Constraints

$1 \leq n \leq 10^{15}$

$1 \leq p \leq 10^9$

Input Format for Custom Testing

Input from `stdin` will be processed as follows and passed to the function.

The first line contains an integer n , the number to factor.

The second line contains an integer p , the 1-based index of the factor to return.

```

1  ▾ /*
2    * Complete the 'pthFactor' function below.
3    *
4    * The function is expected to return a LONG_INTEGER.
5    * The function accepts following parameters:
6    * 1. LONG_INTEGER n
7    * 2. LONG_INTEGER p
8    */
9
10 long pthFactor(long n, long p)
11 {
12     int c=0;
13     for(long i=1;i<=n;i++){
14         if(n%i==0){
15             c++;
16             if(c==p){
17                 return i;
18             }
19         }
20     }
21     return 0;
22 }

```

	Test	Expected	Got	
✓	printf("%ld", pthFactor(10, 3))	5	5	✓
✓	printf("%ld", pthFactor(10, 5))	0	0	✓
✓	printf("%ld", pthFactor(1, 1))	1	1	✓

Passed all tests! ✓