

FEATURES

- Various thread sizes available
- High-quality threaded design
- Head height is equal to shank diameter
- More cost effective than titanium

RS PRO M6 x 16mm Hex Socket Cap Screw Plain Stainless Steel

RS Stock No.: 187-1392



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Brought to you by RS Pro, a range of hex head socket cap screws. Due to their narrow head and lengthy body shape, they are perfect for use in difficult and hard to reach areas. All threaded socket screws are designed to be long lasting and efficient within their applications, especially these A4 stainless steel versions. All models are highly reliable and excellent quality.

General Specifications

Thread Size	M6
Head Shape	Hex Socket Cap
Material	Stainless Steel
Finish	Plain
Thread Type	Metric
Applications	Woodworking, Domestic applications, Fasteners and fixings, Machine tooling and repair, Security guarding, Panel Building

Mechanical Specifications

Length	16mm
Stainless Steel Type	316 A4
Thread Pitch	1mm
Thread Tolerance	6g

Operation Environment Specifications

Maximum Temperature	300°C
----------------------------	-------

Approvals

Compliance/Certifications

RoHS Certificate Of Compliance ,ISO4762, ANSI B18,DIN912




Please view our full range listing below for all A4 316 Stainless Steel Self-Colour Hexagon Socket Cap Head Screws:

Head Shape	Material	Thread Size	Length	RS Part No.
Hex Socket Cap	Stainless Steel	M3	6 mm	1871207
Hex Socket Cap	Stainless Steel	M3	8 mm	1871213
Hex Socket Cap	Stainless Steel	M3	10 mm	6604636
Hex Socket Cap	Stainless Steel	M3	12 mm	1871229
Hex Socket Cap	Stainless Steel	M3	16 mm	1871235
Hex Socket Cap	Stainless Steel	M3	20 mm	3044429
Hex Socket Cap	Stainless Steel	M3	25 mm	3044435
Hex Socket Cap	Stainless Steel	M3	30 mm	3044615
Hex Socket Cap	Stainless Steel	M4	8 mm	1871241
Hex Socket Cap	Stainless Steel	M4	10 mm	6604639
Hex Socket Cap	Stainless Steel	M4	12 mm	1871257
Hex Socket Cap	Stainless Steel	M4	16 mm	1871263
Hex Socket Cap	Stainless Steel	M4	20 mm	1871279
Hex Socket Cap	Stainless Steel	M4	25 mm	1871285
Hex Socket Cap	Stainless Steel	M4	30 mm	1871308
Hex Socket Cap	Stainless Steel	M4	40 mm	3044609
Hex Socket Cap	Stainless Steel	M4	50 mm	3044592
Hex Socket Cap	Stainless Steel	M5	8 mm	6604633
Hex Socket Cap	Stainless Steel	M5	10 mm	3044586
Hex Socket Cap	Stainless Steel	M5	12 mm	1871314
Hex Socket Cap	Stainless Steel	M5	16 mm	1871320
Hex Socket Cap	Stainless Steel	M5	20 mm	1871336
Hex Socket Cap	Stainless Steel	M5	25 mm	1871342
Hex Socket Cap	Stainless Steel	M5	30 mm	1871364
Hex Socket Cap	Stainless Steel	M5	40 mm	1871370
Hex Socket Cap	Stainless Steel	M5	50 mm	3044570
Hex Socket Cap	Stainless Steel	M5	60 mm	3044564

Head Shape	Material	Thread Size	Length	RS Part No.
Hex Socket Cap	Stainless Steel	M6	10 mm	6604642
Hex Socket Cap	Stainless Steel	M6	12 mm	1871386
Hex Socket Cap	Stainless Steel	M6	16 mm	1871392
Hex Socket Cap	Stainless Steel	M6	20 mm	1871409
Hex Socket Cap	Stainless Steel	M6	25 mm	1871421
Hex Socket Cap	Stainless Steel	M6	30 mm	1871437
Hex Socket Cap	Stainless Steel	M6	35 mm	1871443
Hex Socket Cap	Stainless Steel	M6	40 mm	1871459
Hex Socket Cap	Stainless Steel	M6	45 mm	6604645
Hex Socket Cap	Stainless Steel	M6	50 mm	1871465
Hex Socket Cap	Stainless Steel	M6	60 mm	3044558
Hex Socket Cap	Stainless Steel	M8	16 mm	1871471
Hex Socket Cap	Stainless Steel	M8	20 mm	1871487
Hex Socket Cap	Stainless Steel	M8	25 mm	1871493
Hex Socket Cap	Stainless Steel	M8	30 mm	1871500
Hex Socket Cap	Stainless Steel	M8	35 mm	1871516
Hex Socket Cap	Stainless Steel	M8	40 mm	1871522
Hex Socket Cap	Stainless Steel	M8	45 mm	6604649
Hex Socket Cap	Stainless Steel	M8	50 mm	1871538
Hex Socket Cap	Stainless Steel	M8	60 mm	1871544
Hex Socket Cap	Stainless Steel	M8	70 mm	6604658
Hex Socket Cap	Stainless Steel	M8	80 mm	6604651

Hex Socket Cap	Stainless Steel	M10	20 mm	3044542
Hex Socket Cap	Stainless Steel	M10	25 mm	6604655
Hex Socket Cap	Stainless Steel	M10	30 mm	3044520
Hex Socket Cap	Stainless Steel	M10	40 mm	3044514
Hex Socket Cap	Stainless Steel	M10	50 mm	3044508
Hex Socket Cap	Stainless Steel	M10	70 mm	3044485
Hex Socket Cap	Stainless Steel	M12	30 mm	3044463
Hex Socket Cap	Stainless Steel	M12	40 mm	3044457
Hex Socket Cap	Stainless Steel	M12	50 mm	3044441



Head Diameter d2 based on
Knurled Head

Thread Size d1	M36	(M39)	M42	(M45)	M48	M56	M64
Thread Pitch	4	4	4.5	4.5	5	5.5	6
Thread Length b	84	NA	96	NA	108	124	140
Head Dia. d2	min. max.	min. max.	min. max.	min. max.	min. max.	min. max.	min. max.
DIN 912 (1983)	53.54 54.46	57.54 58.46	62.54 63.46	66.54 67.46	71.54 72.46	83.46 84.54	95.46 96.54
ISO 4762 (1997)	53.54 54.46		62.54 63.46		71.54 72.46	83.46 84.54	95.46 96.54
ANSI B 18.3.1 M (1986)	53.37 54.46		62.31 63.46		71.27 72.46		
Head Height k	min. max.	min. max.	min. max.	min. max.	min. max.	min. max.	min. max.
DIN 912 (1983)	35.38 36.00	38.38 39.00	41.38 42.00	44.38 45.00	47.38 48.00	55.26 56.00	63.26 64.00
ISO 4762 (1997)	35.38 36.00		41.38 42.00		47.38 48.00	55.26 56.00	63.26 64.00
ANSI B 18.3.1 M (1986)	35.54 36.00		41.61 42.00		47.58 48.00		
Key Size nominal s	27	27	32	32	36	41	46
min. max.	27.065 27.275	27.065 27.275	32.08 32.33	32.08 32.33	36.08 36.33	41.08 41.33	46.08 46.33
DIN 912 (1983)	27.065 27.275		32.08 32.33		36.08 36.33	41.08 41.33	46.08 46.33
ISO 4762 (1997)	27.065 27.275		32.08 32.33		36.08 36.33	41.08 41.33	46.08 46.33
ANSI B 18.3.1 M (1986)	27.065 27.319		32.080 32.461		36.080 36.461		
Key Engagement t	min.	min.	min.	min.	min.	min.	min.
DIN 912 (1983)	19	22	24	24	28	34	38
ISO 4762 (1997)	19		24		28	34	38
ANSI B 18.3.1 M (1986)	18		21		24		
Thread Size d1	M72	M80	M90	M100			
Thread Pitch	6	6	6	6			
Thread Length b	156	172	192	212			
Head Dia. d2	min. max.	min. max.	min. max.	min. max.			
DIN 912 (1983)	107.46 108.54	119.46 120.54	134.37 135.63	149.37 150.63			
Head Height k	min. max.	min. max.	min. max.	min. max.			
DIN 912 (1983)	71.26 72.00	79.26 80.00	89.13 90.00	99.13 100.00			
Key Size nominal s	55	65	75	85			
min. max.	55.10 55.40	65.10 65.40	75.10 75.40	85.12 85.47			
DIN 912 (1983)	55.10 55.40	65.10 65.40	75.10 75.40	85.12 85.47			
Key Engagement t	min.	min.	min.	min.			
DIN 912 (1983)	43	48	54	60			
Property Class	12.9	8.8 & 16mm	8.8 & 16mm	10.9	A2 / A4-50	A2 / A4-70	A2 / A4-80
Tensile Strength	176900 psi	116000 psi	120350 psi	150800 psi	72500 psi	101500 psi	116000 psi
Yield Strength	159500 psi	92800 psi	95700 psi	136300 psi	30450 psi	65250 psi	87000 psi
Rockwell Hardness (HRC)	min. max.	min. max.	min. max.	min. max.	min. max.	min. max.	min. max.
	39 44	22 32	23 34	32 39	NA NA	NA NA	NA NA

Property Class	Steel	Steel	Stainless Steel
Finish	12.9	8.8 & 10.9	A2 & A4
Thread Tolerance	5g6g	Furnace Black	Plain
		5g	

Diameters & Lengths With () are not recommended for new design.
M1.4, 2.5, 39 and 45 are no longer included in DIN 912.
M1.4, 2.5, 18, 22, 27, 33, 39, and 45 are no longer included in ISO 4762.
The basic difference between DIN 912-12.9 (1983) / ISO 4762-12.9 (1997) and ANSI B 18.3.M (1986) is both DIN and ISO have a thread tolerance of 5g6g, while ANSI has a thread tolerance of 4g6g, which may not be readily available on a worldwide basis.
ANSI B 18.3.1 M is only available in Property Class 12.9.

For More Detailed Information, Please Refer To Complete DIN, ISO, or ANSI Standard, Which Are The Governing Standards.

DIN 912 (1983) / ISO 4762 (1997) / ANSI B 18.3.1M (1982) - LGF 05/01/08

See Next Page For Additional Information