Markdown Parser Test Fixture

A deliberately varied Markdown document for testing common **Markdown conventions** and parser edge cases.

> **Note:** This file is a test fixture, not a specification. Expected rendering can vary by Markdown flavor (CommonMark, GFM, etc.).

1. Headings

Heading level 1

Heading level 2

Heading level 3

Heading level 4

Heading level 5

Heading level 6

2. Paragraphs and line breaks

This is the first paragraph. It contains ordinary text, punctuation, and a URL: https://example.com.

This is a second paragraph, separated by a blank line.

This line ends with two spaces for a Markdown hard line break. This line should appear on the next line in renderers that support it.

This line ends with a backslash for a hard line break.\ This line should also appear on the next line.

3. Emphasis

- *Italic text*
- *Italic text using underscores*
- **Bold text**
- **Bold text using underscores**
- ***Bold and italic***
- ~~Strikethrough (commonly supported by GFM)~~
- `Inline code`

4. Lists

Unordered list

- First item
- Second item
  - Nested item A
  - Nested item B
    - Nested item B.1
- Third item

Ordered list

1. First step
2. Second step
   1. Nested step 2a
   2. Nested step 2b
3. Third step

Ordered list with a non-1 start

3. Third item
4. Fourth item
5. Fifth item

Task list (GFM)

- [x] Completed task
- [ ] Incomplete task
- [ ] Another task

5. Links and images

- Inline link: Example website
- Autolink: https://example.com
- Email link: mailto:hello@example.com
- Reference-style link: [OpenAI][openai]

[openai]: https://openai.com "OpenAI"



6. Blockquotes

> This is a blockquote.
> It has multiple paragraphs.
>
> > This is a nested blockquote.
> > Nested quote continuation.

7. Code

Inline code can contain characters like `*`, `_`, and `#` without formatting them.

Fenced code block:

```
def greet(name: str) -> str:
    """Return a friendly greeting."""
    return f"Hello, {name}!"

print(greet("Markdown"))
```

Fenced code block with a language label:

```
{
  "name": "markdown-parser-fixture",
  "version": 1,
  "enabled": true,
  "tags": ["headings", "lists", "code"]
}
```

Indented code block:

```
line one line two indented line three
```

8. Horizontal rules

Content above the first rule.

Content between rules.

Content below the second rule.

---

9. Tables (GFM)

Feature	Syntax example	Common support
Italic	`*text*`	Yes
Bold	`**text**`	Yes
Tables	`| a | b |`	GFM
Code	`` `code` ``	Yes

10. Escaping Markdown syntax

These characters are escaped so they should display literally:

- *not italic*
- *not italic*
- \# not a heading
- \[not a link\]
- 1\. Not an ordered list item
- Backslash: \\

11. HTML (renderer-dependent)

Inline HTML bold text
A paragraph written in HTML.

12. Footnotes (extension-dependent)

Here is a sentence with a footnote reference.[^note]

[^note]: This is the footnote definition. Support depends on the parser or Markdown flavor.

13. Definition lists (extension-dependent)

Term One : Definition for term one.

Term Two : Definition for term two. : An additional definition for term two.

14. Math (extension-dependent)

Inline math: $E = mc^2$

Display math:

$$ \int_0^1 x^2\,dx = \frac{1}{3} $$

15. Autolinks and plain text edge cases

Bare URL: https://example.org/path?q=markdown&mode=test

Bare email: parser-test@example.org

Text with repeated spaces: alpha beta

Unicode: café, naïve, Ελληνικά, 日本語, 🚀

Entities: & < > " ©

16. Nested mixed content

1. Main ordered item
    - Nested unordered item
    - Another nested item with **bold text** and `inline code`

        > A quote nested inside a list.
        >
        > - A list inside the quote

    - Final nested item
2. Second main item

17. Empty and unusual cases

Empty section

The heading above has no content between it and this paragraph beyond the heading itself.

Punctuation

Em dash — en dash – ellipsis … curly quotes “hello” and ‘world’.

Literal delimiter examples

Asterisks: * ** *** Underscores: _ __ ___ Backticks: ` `` ``` Tildes: ~ ~

18. End marker

If your parser reaches this heading and the paragraph below, it has processed the whole fixture.

End of Markdown parser test fixture.