

Distributed Information Systems: Spring Semester 2018 - Quiz 4

Student Name: _____

Date: April 26 2018

Student ID: _____

Total number of questions: 8

Each question has a single answer!

1. In a FP tree, the leaf nodes are the ones with:
 - a. Lowest confidence
 - b. Lowest support
 - c. Least in the alphabetical order
 - d. None of the above
2. Suppose that an item in a leaf node N exists in every path. Which one is correct?
 - a. N co-occurs with its prefix in every transaction.
 - b. For every node p that is a parent of N in the fp tree, $\text{confidence}(p \rightarrow n) = 1$
 - c. N's minimum possible support is equal to the number of paths.
 - d. The item N exists in every candidate set.

Note: (look at slide 65. E is in every path but it does occur with c in every transaction, c can be in a transaction without e)

3. Fundamentally, why clustering is considered an unsupervised machine learning technique?
 - a. Number of clusters are not known.
 - b. The class labels are not known.
 - c. The features are not known.
 - d. The clusters can be different with different initial parameters.
4. Which of the following is true for a density based cluster C:
 - a. Any two points in C must be density reachable. Each point belongs to one, and only one cluster
 - b. Any two points in C must be density reachable. Border points may belong to more than one cluster
 - c. Any two points in C must be density connected. Border points may belong to more than one cluster
 - d. Any two points in C must be density connected. Each point belongs to one, and only one cluster

5. Suppose that q is density reachable from p . The chain of points that ensure this relationship are $\{t, u, g, r\}$ Which one is FALSE?
- $\{t, u, g, r\}$ have to be all core points.
 - p and q will also be density-connected
 - p has to be a core point
 - q has to be a border point
6. What is a correct pruning strategy for decision tree induction?
- Apply Maximum Description Length principle
 - Stop partitioning a node when either positive or negative samples dominate the samples of the other class
 - Choose the model that maximizes $L(M) + L(M|D)$
 - Remove attributes with lowest information gain
- Solution: b (week 8 classification slide 21)
 c is incorrect: $L(M) + L(D|M)$ (week 8 classification slide 21)
 a is incorrect: minimum description length (week 8 classification slide 22)
7. Given the distribution of positive and negative samples for attributes A1 and A2, which is the best attribute for splitting?

A1	P	N
a	7	0
b	1	4
A2	P	N
x	5	1
y	3	3

- A1
- A2
- They are the same
- There is not enough information to answer the question

You can use this website to compute the binary entropy:

<http://www.wolframalpha.com/widgets/view.jsp?id=4e095a8fa96257fbf9da2529e930ccd3>

Solution:

$$H(A1) = 7/24 * H(7,0) + 5/24 * H(1,4) = 7/24 * 0 + 5/24 * 0.811 = 0.169$$

$$H(A2) = 6/24 * H(5,1) + 6/24 * H(3,3) = 6/24 * 0.65 + 6/24 * 1 = 0.4125$$

$$\rightarrow H(16,8) - H(A1) > H(16,8) - H(A2)$$

\rightarrow A1 is the best attribute for splitting due to better information gain

8. When using bootstrapping in Random Forests, the number of different data items used to construct a single tree is:
- a. smaller than the size of the training data set, with high probability
 - b. of order square root of the size of the training set, with high probability
 - c. the same as the size of the training data set
 - d. subject to the outcome of the sampling process, and can be both smaller or larger than the training set