




Bayesian Statistics and Hierarchical Bayesian Modeling for Psychological Science

Lecture 04

Lei Zhang

Social, Cognitive and Affective Neuroscience Unit (SCAN-Unit)
Department of Basic Psychological Research and Research Methods

https://github.com/lei-zhang/BayesCog_Wien

lei.zhang@univie.ac.at
lei-zhang.net
 @lei_zhang_lz



universität
wien
Fakultät für Psychologie

LINKING DATA AND PARAMETER



$p(\theta | D)$



$p(D | \theta)$

\times



$p(\theta)$

$/$




$p(D)$

Linking Data and Parameter

cognitive model

statistics

computing



The diagram shows two blue arrows originating from the expression $p(A|B)$ in the equation below. One arrow points to the symbol θ , representing the model parameters, and the other points to the symbol D , representing the observed data.

$$p(A|B) = \frac{p(B|A)p(A)}{p(B)}$$

Linking Data and Parameter

cognitive model

statistics

computing

$$p(\theta|D) = \frac{p(D|\theta)p(\theta)}{p(D)}$$

Linking Data and Parameter

cognitive model

statistics

computing

Likelihood

How plausible is the data given our parameter is true?

Prior

How plausible is our parameter before observing the data?

$$p(\theta|D) = \frac{p(D|\theta)p(\theta)}{p(D)}$$

Posterior

How plausible is our parameter given the observed data?

Evidence

How plausible is the data under all possible parameters?

What is $p(\text{Data} | \vartheta)$

cognitive model

statistics

computing

- This is the “Model”
- Data is fixed, ϑ varies
- Not a probability distribution
 - the sum is not “one”

$$Pr(X = 0 | \theta) = Pr(T, T | \theta) = Pr(T | \theta) \times Pr(T | \theta) = (1 - \theta)^2$$

$$Pr(X = 1 | \theta) = Pr(H, T | \theta) + Pr(T, H | \theta) = 2 \times Pr(T | \theta) \times Pr(H | \theta) = 2\theta(1 - \theta)$$

$$Pr(X = 2 | \theta) = Pr(H, H | \theta) = Pr(H | \theta) \times Pr(H | \theta) = \theta^2.$$


Probability of coin landing heads up, θ	Number of heads, X			Total
	0	1	2	
0.0	1.00	0.00	0.00	1.00
0.2	0.64	0.32	0.04	1.00
0.4	0.36	0.48	0.16	1.00
0.6	0.16	0.48	0.36	1.00
0.8	0.04	0.32	0.64	1.00
1.0	0.00	0.00	1.00	1.00
Total	2.20	1.60	2.20	

What is $p(\vartheta)$?

cognitive model

statistics

computing



What is $p(\text{Data})$?

cognitive model

statistics

computing

discrete parameters

$$p(\theta | D) = \frac{p(D | \theta) p(\theta)}{\sum_{\theta^*} p(D | \theta^*) p(\theta^*)}$$

continuous parameters


$$p(\theta | D) = \frac{p(D | \theta) p(\theta)}{\int p(D | \theta^*) p(\theta^*) d\theta^*}$$

Why the Bayes' theorem is important?

cognitive model

statistics

computing





“Probability is orderly opinion and inference from data is nothing other than the revision of such opinion in the light of relevant new information.”

Eliezer S. Yudkowsky

BINOMIAL MODEL



Binomial Model

cognitive model

statistics

computing

- You are curious how much of the surface is covered in water.
- You will toss the globe up in the air.
- You will record whether or not the surface under your right index finger is water (W) or land (L).
- You might observe: W L W W W L W L W
- $\rightarrow 6/9 = 0.666667?$
- Is it right? If not, what to do next?





Steps of (Bayesian) Modeling?

cognitive model

statistics

computing





A Data Story of the Globe

cognitive model

statistics

computing

- The true proportion of water covering the globe is p .
- A single toss of the globe has a probability p of producing a water (W) observation.
- It has a probability $(1 - p)$ of producing a land (L) observation.
- Each toss of the globe is independent of the others.



Components of a Model


cognitive model

statistics

computing

think about the likelihood function (of Binomial):

$$p(\theta | D) = \frac{p(D | \theta) p(\theta)}{\int p(D | \theta^*) p(\theta^*) d\theta^*}$$


$$p(w | N, p) = \binom{N}{w} p^w (1 - p)^{N-w}$$

N : total number of observations
 w : number of water




known (data)

p : proportion of water

unknown (parameter)

Update



cognitive model

statistics

computing

- order doesn't matter
- 2/3 is most likely
- others are not ruled out


Solve it by Grid Approximation

discrete parameters

$$p(\theta | D) = \frac{p(D | \theta) p(\theta)}{\sum_{\theta^*} p(D | \theta^*) p(\theta^*)}$$

continuous parameters

$$p(\theta | D) = \frac{p(D | \theta) p(\theta)}{\int p(D | \theta^*) p(\theta^*) d\theta^*}$$



Binomial Model – Grid Approximation

cognitive model

statistics

computing

```
p_start <- 0; p_end <- 1; n_grid <- 20  
w <- 6; N <- 9  
  
# define grid  
p_grid <- seq( from = p_start ,  
               to = p_end , length.out = n_grid )
```

```
# define prior  
prior <- rep(1 , n_grid)
```


```
# compute likelihood at each value in grid  
likelihood <- dbinom(w , size = N , prob = p_grid )
```

```
# compute product of likelihood and prior  
unstd.posterior <- likelihood * prior
```

```
# standardize the posterior, so it sums to 1  
posterior <- unstd.posterior / sum(unstd.posterior)
```

$$p(\theta | D) = \frac{p(D | \theta)p(\theta)}{\int p(D | \theta^*)p(\theta^*)d\theta^*}$$

$$p(w | N, p) = \binom{N}{w} p^w (1 - p)^{N-w}$$




Binomial Model – Grid Approximation

cognitive model

statistics

computing




Impact of Prior

cognitive model

statistics

computing



Exercise VII

cognitive model

statistics

computing

```
.../BayesCog/02.binomial_globe/_scripts/binomial_globe_grid.R
```

TASK: run a grid approximation with `grid_size = 50`

Components of a Model

cognitive model

statistics

computing

grid approximation for
2 parameters?
5 parameters?
10 parameters?


$$p(\theta | D) = \frac{p(D | \theta) p(\theta)}{\int p(D | \theta^*) p(\theta^*) d\theta^*}$$


$$p(data) = \int_{\text{All } \theta_1} \int_{\text{All } \theta_2} p(data, \theta_1, \theta_2) d\theta_1 d\theta_2$$

$$p(data) = \int_{\mu_1} \int_{\sigma_1} \dots \int_{\mu_{100}} \int_{\sigma_{100}} \underbrace{p(data | \mu_1, \sigma_1, \dots, \mu_{100}, \sigma_{100})}_{\text{likelihood}} \times \underbrace{p(\mu_1, \sigma_1, \dots, \mu_{100}, \sigma_{100})}_{\text{prior}} d\mu_1 d\sigma_1 \dots d\mu_{100} d\sigma_{100}$$

$$p(\theta | D) \propto p(D | \theta) p(\theta)$$

MARKOV CHAIN MONTE CARLO





Solving the Problem by **Approximation**

cognitive model

statistics

computing

$$p(\theta | D) \propto p(D | \theta) p(\theta)$$

Deterministic
Approximation

→ Variational Bayes

Stochastic
Approximation

→ Sampling Methods


An MCMC Robot

cognitive model

statistics

computing

$$p(\theta | D) \propto p(D | \theta)p(\theta)$$




An MCMC Robert in 3D

cognitive model

statistics


computing




Sampling Example

cognitive model
statistics
computing


MCMC summary



MCMC trace



True distribution





Visual Example

cognitive model

statistics

computing




Let's watch a video!

cognitive model

statistics

computing



MCMC Sampling Algorithms

cognitive model

statistics

computing

- Rejection sampling
- Importance sampling
- Metropolis algorithm
- Gibbs sampling → JAGS
- HMC sampling*



Stan!