

NetBrain Integration Deployment Guide

Single Pane of Glass – Solarwinds Device Monitoring

Contents

Overview	3
Use case	3
NetBrain Map with Solarwinds Data Overlay	3
Pre-requisites	4
Application Version	4
Network Connectivity	4
User Account and Privileges	4
Deployment Instructions	4
Deploy the Solarwinds Orion SDK	4
Deploy the NetBrain Solarwinds API Adaptor	4
Create Solarwinds API Server Connection	5
Confirm all steps are followed in section <i>Deploy the Solarwinds Orion SDK</i>	6
Import Solarwinds Data View Template	7
Creating Solarwinds Enabled Device Groups	8
Setup to have clickable URL in NetBrain	9
Visualizing the Solarwinds Data with NetBrain Data View Template	10
On-Demand Data Overlay	10
Schedule Data Import from Solarwinds	10
Troubleshooting	10

Overview

Use case

Using the publicly available Solarwinds Orion SDK, NetBrain has created an integration compatible with NetBrain Integrated Edition release 8.0 (and newer) that enables a NetBrain administrator to overlay the Solarwinds device and interface monitoring data on user created maps.

With this integration, NetBrain can overlay the following extended information as attributes:

Device level:


1. CPU Load% (Map URL to Solarwinds device details)
2. Memory Used %
3. System Uptime
4. SysLog messages

Following data is seen on the interface level:

1. Utilization In %
2. Utilization Out %
3. In Discards This Hour
4. Out Discards This Hour
5. In Errors This Today
6. Out Errors This Today
7. CRC Align Errors Today
8. MTU

NetBrain Map with Solarwinds Data Overlay

Below are two example representations of the Solarwinds data overlay on devices (left) and interfaces (right).



Pre-requisites

Application Version

Please confirm if your application is compatible with the integration.

Application	Version
NetBrain Integrated Edition	IEv8.0 (or newer)
Solarwinds	Orion NMP 12.2 (or newer)

Network Connectivity

It is required that there's **HTTP/HTTPS** connectivity between the **NetBrain Front Server** and the **Solarwinds server**.

User Account and Privileges

Application	User Account	Required Role Assignment(s)
NetBrain Integrated Edition	Required	System Admin
Solarwinds	Required	Guest (or higher)

Deployment Instructions

Deploy the Solarwinds Orion SDK

To support Solarwinds data retrieval, the Orion SDK must be deployed on each Windows based machine where the NetBrain Front Server service is running in the customer environment.

1. Download the Solarwinds Orion SDK, *orion.zip*, from the NetBrain github and stage locally in the *C:\Temp* directory on each NetBrain Windows server where the Front Server service is currently running.
2. Log into the first NetBrain Front Server machine with the *administrator* user.
3. Using Windows Explorer, navigate to the *C:\Temp* directory
4. Unzip the *orion.zip* file locally in the *C:\Temp* directory
5. Copy the resulting directories, *orionsdk* and *orionsdk-0.0.6.dist-info*, to the NetBrain Front Server service python library

C:\Program Files\NetBrain\Front Server\python\Lib\site-packages

Deploy the NetBrain Solarwinds API Adaptor

1. Download the NetBrain Solarwinds API Adapter, *Solarwinds API Adaptor.py*, from the NetBrain github and stage locally on the machine typically used to connect to the NetBrain User Interface.
2. Using a web browser, login to the NetBrain System Management UI using the *System Admin* credentials

http://<NetBrain Web Server IP>/admin

3. In the NetBrain System Management UI, Navigate to *Operations > API Adaptors*.

4. In the *API Adaptors* screen, click “Add”.
5. Complete the *Add Adaptor* dialog screen as follows:

Field / Setting	Value
Adapter Name	<i>Solarwinds API Adaptor</i>
Description	<i>NetBrain Solarwinds API Adaptor</i>
Script	<i><Solarwinds API Adaptor.py></i>

6. Review the adaptor configuration, then click “Save”.
7. Log out of the Netbrain Integrated Edition System Management UI.




Create Solarwinds API Server Connection


Note: If the environment has been deployed with multiple Front Servers, repeat this section for each of the Front Servers.

1. Using a web browser, login to the NetBrain Desktop UI using the *System Admin* credentials
`http://<NetBrain Web Server IP>`
2. Navigate to the NetBrain *API Server Manager*
Domain Management > Operations > API Server Manager
3. In the API Server Manager screen, click “Add”.
4. Complete the Add API Server dialog screen as follows:

Field / Setting	Value
Server Name	<i>Solarwinds API Adaptor</i>
Description	<i>NetBrain Solarwinds API Adaptor</i>
API Source Type	<i><Solarwinds API Adaptor.py></i>
Endpoint	<i>Solarwinds instance endpoint (ex “http://192.168.31.99”)</i>
Username	<i>Solarwinds guest account’s username</i>
Password	<i>Solarwinds password</i>
Front Server/Front Server Group	Select FS/FSG which would have reachability to Solarwinds server

5. Click “Test” to initiate a connectivity test between the NetBrain front server and the Solarwinds instance configured. Pictured below is the result of a successful connectivity test followed by two typical failure scenarios: Incorrect credentials and connectivity between NetBrain and Solarwinds.

<p>Successful Connection</p>	 <p>The screenshot shows a dialog box titled "Test External API Server". It displays the start time as 2019-10-28 16:30:26. The process shows connecting to a front server (WIN-2A8AVLT44E8) and then to endpoints (https://dev85786.service-now.com) via the same front server. A red box highlights the message "Endpoint and credentials are verified!" followed by the word "Successful" in green. The end time is 2019-10-28 16:30:28. An "OK" button is at the bottom right.</p>
<p>Error Scenario: Solarwinds Orion SDK library isn't available to be imported by NetBrain's Plugin</p> <p>Possible Resolution: Confirm all steps are followed in section <i>Deploy the Solarwinds Orion SDK</i>.</p>	 <p>The screenshot shows a dialog box titled "Test External API Server". It displays the start time as 2019-11-13 09:40:16. The process shows connecting to a front server (WIN-2A8AVLT44E8) and then to endpoints (http://192.168.31.99) via the same front server. The status "Failed" is shown in red. The error message is "Failed to import Solarwinds SDK: No module named 'orionsdk1'". The end time is 2019-11-13 09:40:18. An "OK" button is at the bottom right.</p>
<p>Error Scenario: The entered credentials are incorrect.</p> <p>Possible Resolution: Confirm credentials specified in the Solarwinds API Adaptor configuration and retry.</p>	 <p>The screenshot shows a dialog box titled "Test External API Server". It displays the start time as 2019-11-13 09:46:08. The process shows connecting to a front server (WIN-2A8AVLT44E8) and then to endpoints (http://192.168.31.99) via the same front server. The status "Failed" is shown in red. The error message is "Credentials entered are incorrect: 403 Client Error: Forbidden for url: https://192.168.31.99:17778/SolarWinds/InformationService/v3/json/Query". The end time is 2019-11-13 09:46:09. An "OK" button is at the bottom right.</p>

<p>Error Scenario: Solarwinds endpoint is unreachable.</p> <p>Possible Resolution: Confirm that the NetBrain Front Server(s) can reach the Solarwinds platform using 3rd party tools (Ping, Traceroute, Wireshark)</p>	 <p>The screenshot shows a dialog box titled "Test External API Server" with a close button (X) in the top right corner. The content of the dialog box is as follows:</p> <pre> Start Time: 2019-11-05 11:34:23 Connecting to Front Server(WIN-2A8AVLT44E8) ... Successful Connecting to end points (http://192.168.31.66) via Front Server(WIN-2A8AVLT44E8) ... Failed Endpoint is not reachable. End Time:2019-11-05 11:34:26 </pre> <p>An "OK" button is located at the bottom right of the dialog box.</p>
---	--

- Once successful connection with the local Solarwinds instance has been confirmed, click "OK" to finalize Solarwinds server connection.
- Repeat Steps 2-6 for each additional deployed Front Server.

Import Solarwinds Data View Template

- Download the NetBrain Solarwinds Dataview Template, *[Solarwinds] Monitoring Data.xdvt*, from the NetBrain github and stage locally on the machine used to connect to the NetBrain User Interface.
- Using a web browser, login to the NetBrain Desktop UI with the *System Admin* credentials
http://<NetBrain Web Server IP>
- Navigate to the NetBrain *Data View Template Manager*
Start Menu (The Four Dashed Lines) > Dynamic Map > Data View Template Manager
- Right-Click "Shared Templates in Tenant", then click "New Folder".
- Name the folder *Solarwinds Single Pane of Glass*
- Right-Click the "Solarwinds Single Pane of Glass" folder, then click "Import Template"
- In the *Import Data View Template* dialog, click "Add Data View Template ..."
- Select the *[Solarwinds] Monitoring Data.xdvt* file, then click "Open".
- Confirm that the *Import Data View Template* dialog screen reflects the following information:
Name: *[Solarwinds] Device Monitoring Data.xdvt*
Size: *12.32k*
Status: *Ready*
Related Resources: *3 Parsers*
- Click "Import" to initiate the import of the data view template to the NetBrain system.

Note: On successful completion, the status will transition from *Ready* to *Successful*. If any other status is reported, retry the operation, then contact NetBrain support.

11. Navigate to NetBrain *Parser Library*

Start Menu (The Four Dashed Lines) > Automation > Parser Library

12. In the Parser Library, search for “Solarwinds – “. Three Solarwinds parsers should be returned in the search results:

Solarwinds – Device DVT

Solarwinds – Interface DVT

Solarwinds – Syslog DVT

13. Double-click *Solarwinds – Device DVT* to open the custom parser in the *Parser Editor*.
14. In the *Parser Editor*, update the *Parser Type* associated with the *Solarwinds – Device DVT* to the following:

Parser Type: *API, Solarwinds*

15. Click the Save icon in the upper-right corner of the screen, then close the browser tab.
16. Repeat steps 13-15 for the remaining two NetBrain Solarwinds parsers.

Creating Solarwinds Enabled Device Groups

Note: If the environment has been deployed with multiple Front Servers, repeat this section for each of the Front Servers.

1. Navigate to the NetBrain *Device Group Manager*.
Start Menu (The Four Dashed Lines) > Device Group
2. In the *Device Group Manager*, right-click the “Public” folder, then click “New Device Group”.
3. In the *Device Group Properties* dialog, Name the device group as follows:

[Solarwinds] DG <Front Server Hostname>

4. Under *Devices and Interfaces*, click “+Dynamic Search”, then “Dynamic Search Device”.
5. In the *Dynamic Search Device* dialog,

Search Scope: *All Devices (default)*

Device Criteria: *Front Server | Matches | <Front Server>*

where *<Front Server>* is the front server specified in step 3.

6. Click “Search” to populate the device list to front server mapping.
7. Click “OK” button to create a *Dynamic Search* association.
8. In the *Device Group Properties* dialog, click “OK” to complete Device Group creation.
9. In the *Device Group Manager*, right-click the *[Solarwinds] <Front Server Hostname>* object, then click “Open Group Map”.
10. In the resulting NetBrain device group map, right-click any device, then click “Shared Device Settings”.
11. In the *Shared Device Settings...* dialog, click the select the API tab then populate the dropdown fields as follows:

12. Check "Apply above Settings to device group", then select *[Solarwinds] DG <Front Server Hostname>*
13. In the API tab content table, check *Solarwinds API Adaptor*
14. Click "Submit".
15. Repeat steps 1-14 for each additional deployed Front Server.

Setup to have clickable URL in NetBrain

Following setup provides a clickable URL to go to the device's page in Solarwinds.

1. Navigate to the *Single Pane of Glass URL* module
Start Menu (The Four Dashed Lines) > Single Pane of Glass URL
2. Navigate to **Generic Variable** tab
3. Click **Add** button to add a new Generic Variable and fill the following information

Field / Setting	Value
Name	Solarwinds
Value	<URL:port to access Solarwinds> <i>example: http://192.168.31.99:8787</i>

4. Navigate to **Page Link** tab
5. On the left-hand bar of the page, click **Add Vendor**
6. To specify vendor name, enter *Solarwinds*
7. On the right-hand side of the page, click **Add Page Link** to open the *Add Page Link* window and enter the following information

Field / Setting	Value
Page Name	Device page in Solarwinds
Page URL	{{Solarwinds}}/Orion/NetPerfMon/NodeDetails.aspx?NetObject=N:{\$NodeID}

At this step we have configured rules to generate a clickable URL or *SPOG link*. Below we will attach this *SPOG link* with the *Data View Template*.

1. Navigate to the *NetBrain Data View Template Manager*
Start Menu (The Four Dashed Lines) > Dynamic Map > Data View Template Manager
2. Click on the DVT located at
Shared Templates in Tenant > Solarwinds Single Pane of Glass > [Solarwinds] Device Monitoring Data
3. On the left-hand side of the page, look for the device variables listed under *Hostname*. Click on **CPU Load (int)** to toggle the *CPU Load* bar at the bottom of the page
4. Next to the heading *Drill-down Actions:*, click on **+ Add Action**

5. Select **SPOG URL** from the list to open the *select SPOG link* window
6. Click on **Device Page in Solarwinds**
7. Click **Save**

Visualizing the Solarwinds Data with NetBrain Data View Template

On-Demand Data Overlay

1. From the NetBrain Desktop Management UI, open the desired map to overlay Solarwinds data.
2. In *Dynamic Data View* tab, search for “[Solarwinds] Monitoring Data”.
3. In the *Preview – Data View Template* dialog, click “Apply”
4. On the NetBrain map, confirm that the *Cache/Live* data source switch is set to *Live*.
5. Confirm that the objects (devices and interfaces) are properly instrumented with the expected Solarwinds data.

Note: Overlay of the Solarwinds data may take seconds-to-minutes to complete refresh depending on the number of devices on the map.

Schedule Data Import from Solarwinds

1. In the *NetBrain Domain Management* page, navigate to *Schedule Task*.
2. Click on “Schedule Data View Template/Parser”, then click on “Add Task”
3. In the *Add Task* dialog, specify the frequency for which to import device and interface data from Solarwinds.
4. Click on “Device Scope” tab, then click “Device Group” radio button. Add each device group created as part of the integration to limit device scope of the available devices.
5. Click on “Select Data View Template/Parser” tab, click on “Add” and search for *[Solarwinds] Monitoring Data*
6. Click “Submit” to create the scheduled task for Solarwinds data import to NetBrain.

Note: The Solarwinds data will not be available on the map until after the first time that the scheduled task has completed execution.

Troubleshooting

If there are any problems encountered during deployment or integration of NetBrain with Solarwinds, contact NetBrain Support at support@netbraintech.com.