



SHANGHAI BRILLIANT TEXTILE CO.,LTD.

Add.:4 Floor,Building 2,No.6372 Yinggang East Road,Qingpu District,Shanghai,China(201703)

Tel:+86 21-36582868

E-mail:info@brilliant-tex.com

Technical Confirmation

TC No.: TC25010008

Download No.:

Customer: Delta V S.A.

Atten.: Fernando Quinodoz

Date: 2025-01-14

Customer Art.: KR01/JUOO6O

Product Name: Nylon Rockdura 500D Ripstop 4mm*4mm

Finishing: Dyed+C6 W/R+PU clear coating

Mechanical Properties

Care Instructions

TEST ITEMS	UNIT	TEST STANDARD	REQUIRED DATA	CONFIRM DATA
Cutable width	cm	EN 1773		147
Total weight	g/m2	EN 12127		250±5%
Dimensional change in washing-warp	%	ISO 5077;ISO 6330-4N		±3
Dimensional change in washing-weft	%	ISO 5077;ISO 6330-4N		±3
Breaking force-warp	N	EN ISO 13934-1		1600
Breaking force-weft	N	EN ISO 13934-1		1200
Elongation at break-warp	%	EN ISO 13934-1		
Elongation at break-weft	%	EN ISO 13934-1		
Tear force-warp	N	ISO 13937-2		75
Tear force-weft	N	ISO 13937-2		60
Water penetration Hydrostatic head-Original	mm	ISO 811 60cm		
Spray test-Original	Grade	EN 24920, ISO 4920		4
Abrasion resistance, Martindale method 12 kPa (r)	r	EN ISO 12947-2		100000
Colour fastness to laundering, change in shade	Grade	EN ISO 105-C06		4
Staining of multifibre: CA, CO, PA, PES, AC, WO	Grade	EN ISO 105 C06		4
Colour fastness to perspiration, change in shade	Grade	EN ISO 105-E04		4
Staining of multifibre: CA, CO, PA, PES, AC, WO	Grade	EN ISO 105-E04		4
Colour fastness to rubbing, dry	Grade	EN ISO 105-X12		4
Colour fastness to rubbing, wet	Grade	EN ISO 105-X12		3-4
Colour fastness to light- Xenon arc light	Grade	EN ISO 105-B02		4

Remark:BR25010006