Reactionless Compliance: A Human-in-the-Loop Benchmark of Redundancy Resolution and Contact-Safety Limits for Teleoperated Free-Floating Space Manipulators

Annan Gilberto Gonzalez Garnes, Uma Surya Harshith Sourav Gosula, Suhas Suren, Honglin Wang, Zuzanna Maria Kapcia
MA6223 CA3 Group Project, MSc Robotics and Intelligent Systems, Nanyang Technological University, Singapore
P1 Simulation & integration: ANNANGIL001@e.ntu.edu.sg P2 Dynamics: UMASURYA001@e.ntu.edu.sg P3 Control: suhas003@e.ntu.edu.sg
P4 Safety: HONGLIN003@e.ntu.edu.sg P5 Experiment & report: ZUZANNAM001@e.ntu.edu.sg

***Abstract*—A redundant arm on a free-floating servicer turns its own spacecraft whenever it moves, and a 7-joint arm doing a full 6-D task cannot keep the base still: six task rows and three reactionless rows exceed seven joints. We built a teleoperation benchmark to measure this trade-off: a momentum-conserving MuJoCo model of a Kinova Gen3 arm on three servicers (arm-to-base mass ratio 0.30, 0.043, 0.0043), five redundancy-resolution schemes in 3-D and 6-D variants, a PlayStation 4 interface with haptic warnings, and a counterbalanced study protocol. On a scripted two-loop orbital-replacement-unit (ORU) task, the reactionless schemes cut peak base drift by 2.4–2.8× (3-D) and 1.3–1.4× (6-D) on the 150 kg servicer, at the cost of 8–22 mm of hand error. On the 20 kg servicer every scheme that finishes the task breaks the ±5° antenna limit (23–25° in 6-D), and the schemes that respect it cannot finish. For contact safety, where ISO 10218-1 excludes space robots, we apply the ISO/TS 15066 body model. Simulated impacts show that the back-drivable joints, not the spacecraft mass, set the effective mass at contact. A pose-dependent speed limiter built on this keeps all 397 simulated impacts below the ISO force limit (worst 90 %). Human-subject sessions had not been run when this report was written.**

Video presentation: https://entuedu-my.sharepoint.com/REPLACE-WITH-ONEDRIVE-LINK

I. Introduction

On-orbit servicing puts a human operator in charge of an arm whose base is not bolted down. Momentum is conserved, so every hand motion rotates the servicer and moves its antenna off the ground station [1], [2]. A redundant arm can spend its spare joints on cancelling that reaction [3], [4]. But a 7-joint arm doing a 6-D task (position and orientation) has one spare joint, and holding the base still needs three. Exact reactionless motion is then impossible, so every controller trades task accuracy, base drift and posture drift against one another.

Each of the relevant laws exists on paper: damped least squares, gradient projection, null-space impedance, reaction null-space (RNS) control and impedance inside the RNS [5], [6]. They have not been compared under human teleoperation, nor across servicer sizes. Contact safety for such an arm is also unregulated: ISO 10218-1:2025 excludes space robots [7].

Contributions. (i) An open benchmark: three servicers sharing one Kinova Gen3 arm, five schemes in 3-D and 6-D, a scripted closed-loop ORU task, per-tick logging, a fixed tuning rule and a β-sweep that traces the 6-D trade-off. (ii) A characterisation of that trade-off and of where base drift breaks a $\pm 5^\circ$ pointing limit as the arm-to-base mass ratio changes. (iii) A contact-velocity limit from the ISO/TS 15066 body model [8], calibrated and validated by simulated impacts, and enforced at run time. (iv) A teleoperation interface (PS4 gamepad, haptics, head-up display) and a counterbalanced study protocol with an analysis pipeline that runs end to end. Scheme 5 is a known combination [5], [9]; we use it as one condition, not as a claim of novelty.

II. Related Work

Free-floating kinematics. The generalized Jacobian [2] maps joint rates to hand motion with the base free; dynamic singularities and the loss of reach follow from it [1]. **Reactionless control.** The reaction null space [3], [9] gives joint motions that leave base attitude unchanged; it was flight-tested on ETS-VII [4]. Bias-momentum strategies distribute momentum to protect attitude [10], and impedance control has been formulated for free-floating arms [5], [6]. **Redundancy resolution.** The fixed-base classics are gradient projection on a null-space objective [11] such as manipulability [12], damped least squares [13], [14], weighted least norm for joint limits [15], and null-space impedance [16]. **Human factors and safety.** Virtual fixtures guide an operator's commands [17]; predictable motion matters for trust [18]; workload is measured with NASA-TLX [19]. ISO/TS 15066 gives body-region force limits and a two-body energy model for collaborative robots. To our knowledge, no prior work compares these schemes with humans in the loop on a free-floating base, or derives a contact-speed limit for such a base.

III. System

A. Servicers and arm

All three servicers carry the same arm and differ only in the base (Fig. 1, Table I). The arm uses the Kinova




Fig. 1. The three servicers (20, 150, 1500 kg bases) with the same Kinova Gen3 arm, rendered from the simulation. The yellow cylinder is the antenna; its boresight must stay within $\pm 5^\circ$.

TABLE I
SERVICERS AND THE EFFECTIVE MASS AT THE HAND (HOME POSE, TOOL AXIS)

	small	medium	large
Servicer mass [kg]	21.7	151.7	1501.7
Arm / servicer mass ratio	0.30	0.043	0.0043
m_{eff}, rigid joints [kg]	27.5	149.6	1473
m_{eff}, limp joints [kg]	2.56	2.56	2.56
m_{design} (Sec. IV) [kg]	8.9	11.3	37.4
$v_{\max}$ design, free/clamped [m/s]	.38/.17	.34/.15	.21/.08
$v_{\max}$ rigid joints, clamped [m/s]	0.097	0.042	0.013

Gen3 7-DoF geometry and masses (902 mm reach, 6.49 kg moving; MuJoCo Menagerie [20], [21]): roll–pitch–roll–pitch–roll–pitch–roll joints, pitch limits $\pm 128.9/147.8/120.3^\circ$ and roll joints limited to $\pm 170^\circ$. The joints are velocity servos ($k_v = 20$, ± 1 rad/s, torque saturating at ± 5 Nm). The base is a free body with gravity off. Collisions are on, both arm–base and arm–arm. Simulation uses MuJoCo [22] with RK4 at 0.25 ms. Control runs at 100 Hz and holds each command over 40 physics steps.

B. Dynamics

With base twist v_b, joint rates $\dot{q}$ and zero initial momentum,

$$H_b v_b + H_{bm}\dot{q} = 0 \;\Rightarrow\; v_b = V\dot{q}, \quad V = -H_b^{-1}H_{bm}, \quad (1)$$

$$\dot{x} = J_b v_b + J_m \dot{q} = (J_m + J_b V)\dot{q} = J^*\dot{q}. \quad (2)$$

W, the three angular rows of V, maps joint rates to base angular rate. The base attitude is unchanged exactly when $W\dot{q} = 0$, which uses W rather than the angular rows of H_{bm}, because the base frame is not at the system centre of mass. The momentum gate drives random $\dot{q}$ for 10 s on every servicer and checks $\|H_b v_b + H_{bm}\dot{q}\|$ at every physics step. The worst value is 6×10^{-8} against a limit of 10^{-6}, and $J^*\dot{q}$ and $W\dot{q}$ match the simulated hand and base velocities to 10^{-7}. The degree-of-freedom argument holds numerically at 50 random poses: $[J^*; W]$ has rank 7 of 9 rows in 6-D and rank 6 of 6 in 3-D.

C. Five schemes

All schemes output $\dot{q}$ from the operator twist $\dot{x}_c$. They share a pose servo onto the commanded target, $\dot{x} = \dot{x}_c + K_x e$ ($K_x = 2\,\text{s}^{-1}$, e clipped at 5 cm / 0.3 rad), and one joint geofence: a joint within 3° of a limit that is still pushing outward is locked and the rest re-solve.

1) **DLS:** $\dot{q} = J^{*\top}(J^* J^{*\top} + \lambda^2 I)^{-1}\dot{x}$ [13].
2) **Gradient projection:** $\dot{q} = J^{*+}\dot{x} + (I - J^{*+}J^*)\, k_g \nabla w(q)$, with w the manipulability of J^* [11], [12].
3) **Impedance:** the same null-space form with $\dot{q}_0 = -K_p(q - q_{\text{rest}}) - K_d\dot{q}$ [16].
4) **RNS:** in 3-D, solve $[J^*_p; W]\dot{q} = [\dot{x}_p; -k_a\phi]$ exactly, where ϕ is the base attitude error; in 6-D, see (3) with $\dot{q}_0 = 0$.
5) **Impedance+RNS:** as 4, with $\dot{q}_0$ injected only through the remaining freedom.

In 6-D, 6 task rows plus 3 reactionless rows exceed 7 joints, so schemes 4 and 5 become a weighted least-squares problem whose trade-off is set by β:

$$\min_{\dot{q}} \; \|J^*\dot{q} - \dot{x}\|^2 + \beta\,\|W\dot{q} + k_{a6}\phi\|^2 + \gamma\,\|\dot{q} - \dot{q}_0\|^2. \quad (3)$$

Tuning (no strawmen). Each scheme's own gain was swept over four values on the medium servicer, 2 loops, in both modes (40 runs). The selection rule was fixed before the runs: among values that finish both modes, take the lowest summed rms hand error, breaking ties within 10 % by peak base drift. Result: $\lambda = 0.01$ (DLS is insensitive between 0.005 and 0.05), $k_g = 1$, $K_p = 2$ (Impedance), $k_a = 1$ (RNS), $K_p = 1$ (Imp.+RNS). The 6-D weights $\beta = 3$, $k_{a6} = 1$ and $\gamma = 10^{-3}$ are the most reactionless setting with which both schemes 4 and 5 still finish the task on the medium servicer.

D. Teleoperation interface

Fig. 2 shows the operator view: one OpenGL window into which MuJoCo renders. The blue sphere is the commanded target. The green and yellow lines are the antenna boresight at the start and now, and the yellow line turns red past 5°. The head-up display shows the antenna error, the joint nearest its limit, arm contact, and the hand speed against the contact limit. A DualShock 4 is read through SDL2 in a game-style layout: the left stick moves the target relative to the camera, R2/L2 move it up and down, the right stick orbits the camera, holding R1 switches the stick to rotation, and holding L1 gives fine control. A southpaw and a world-axis layout are also available. Haptics use both rumble motors: the heavy motor scales with arm contact force (0.35 at first touch, full at 10 N), the light motor ramps over the last 15° before a joint limit, and a 250 ms pulse fires when the antenna leaves its cone. The scripted task never triggers either motor, so a buzz always means something is wrong. The mapping was checked on a real controller, and missing input reads as a zero command.

E. Task

The task is a closed loop from the hand's home pose, run twice per trial: start, approach, ORU, approach, stow and back to start, with offsets of up to ± 15 cm and 30°. Waypoints are fixed in the world, because the ORU sits on another spacecraft.




Fig. 2. Participant view at the start of a 6-D trial (medium servicer). Orange: current waypoint with its target orientation; grey: the ORU loop. Top right: haptic channels and the live contact-speed limit.

A waypoint counts when the real hand stays within 2 cm (and 10° in 6-D) for 0.3 s. Returning to the start is what makes base drift and joint drift $\|q_f - q_0\|$ measurable. Scripted runs follow a minimum-jerk reference at full-stick speed through the same control loop, logger and safety layer that participants use.

IV. Contact Safety

Body model. For an arm with effective mass $m_{\text{eff}}(q,u) = 1/(u^\top \Lambda_v^{-1} u)$ along contact direction u, the ISO/TS 15066 energy model gives $v_{\max} = F/\sqrt{\mu k}$, with the region's force limit F, spring constant k and effective mass m_H from Annex A. We include every region that allows transient contact. Head and face allow none and are handled procedurally (H3). For *free* contact, where the person can recoil, F is twice the quasi-static limit and μ is the reduced mass of m_{eff} and m_H. For *clamped* contact, e.g. an EVA astronaut in a foot restraint, F is the quasi-static limit and $\mu = m_{\text{eff}}$. The design case is the worst region and restraint, which is the clamped hand.

Which mass hits? With the joints rigid, the whole spacecraft stands behind the hand: 1473 kg on the large servicer, giving a limit of 13 mm/s (Table I). We placed an ISO tissue spring, backed by m_H (free) or the world (clamped), in front of the hand. We then drove the real servos into it at 432 random poses and directions: 3 servicers × 3 body cases × 0 or 5 kg payload × 24. Pushed across the arm, the ±5 Nm servos give way, and the peak force hardly depends on the base mass. The design mass is therefore the limp-joint value plus a calibrated servo share, plus a small rigid share for pushes along the arm, where the joints have no lever arm:

$$m_{\text{design}} = m_{\text{eff}}^{\text{limp}} + 6\,\text{kg} + 0.02\, m_{\text{eff}}^{\text{rigid}} \cos^2 \theta_{u,\text{arm}}. \qquad (4)$$

Limiter and validation. At run time the commanded $\dot{q}$ is scaled so that the predicted hand speed $\|J^* \dot{q}\|$ stays below $0.85\, v_{\max}$ along its own direction. To validate this, every impact was re-run at exactly the limiter's speed and its peak force compared with the ISO limit. All 397 contacts that occurred stayed below it: worst 0.90 of the limit (clamped hand, push along the arm), median 0.32 (Fig. 4, right; Fig. 3). We first converted force into an equivalent mass and extrapolated, but that flagged slow contacts near singularities whose real forces were only 17–33 N. The direct check is the honest test. A Monte Carlo sweep of 2700 samples (pose × direction × payload 0/2.5/5 kg × restraint × size) shows why the limiter is needed. At full joint speed, the arm exceeds the clamped limit in 95–100 % of poses. The teleop's own speed cap (0.15 m/s) exceeds it in every pose once a 5 kg payload is attached.

V. Experimental Method

Scripted benchmark. The Week-7 gate runs 5 schemes × 2 modes × 3 servicers on the 2-loop task, with a timeout of 1.5× the reference duration. The β-sweep runs schemes 4 and 5 in 6-D at $\beta \in \{0.1, \ldots, 100\}$ on all servicers (51 runs). Every tick is logged: commands, full state, hand and target pose, antenna error, haptic channels, limiter scale and camera. Metrics are computed from the logs, so scripted and human trials share one pipeline.

Human-in-the-loop protocol. The design is within-subject, with 5 schemes × 2 task modes on the medium servicer and 2 loops per trial. Modes run as blocks, with odd participants starting in 3-D. Scheme order within a block follows a Williams Latin square [23], and the scheme is hidden from the participant. The plan is 10–12 participants and ≈30 min per session. After each trial, participants rate predictability (1–7) and complete raw NASA-TLX [19]. Analysis uses a Friedman test with Kendall's W, then pairwise Wilcoxon signed-rank tests with Holm correction and effect size r. Below 8 participants, per-participant paired plots replace the inferential tests. One pad layout and the haptics setting are fixed for all participants. The session runner, questionnaire template, statistics and figures were all tested end to end on scripted and synthetic data. *At the time of writing no participant session had been run, so no human results are reported.*

VI. Results

A. Gate and the cost of reactionless motion

Table II and Fig. 6 summarise the gate. All 30 runs were stable, and 26 finished. Medium and large finished 10/10 each; the four failures are schemes 4–5 on the small servicer. In 3-D on the medium servicer, RNS and Imp.+RNS cut peak drift from 1.28° (DLS) to 0.53° and 0.46°. They finish with 0.059° and 0.001° of base error left. The price is hand error: 13 and 22 mm rms against 0.6 mm. Exact reactionless motion is not "zero drift by construction" here, because the ±15 cm loop leaves the arm's reactionless reach. On the earlier generic arm, raising the weight of the reactionless rows cut drift to 0.05°, but the hand then no longer reached the waypoints.

B. The 6-D trade-off

Fig. 5 plots hand error against peak base drift. On the medium servicer, raising β from 0.1 to 100 moves Imp.+RNS from 2.3 mm and 1.66° to 42.8 mm and 0.28°. The task is still completed up to $\beta = 3$; beyond that the hand misses the 2 cm tolerance. Schemes 1–3 sit at the accurate end (0.6 mm,




Fig. 3. Contact-speed limit over shoulder and elbow angle for contact along the tool axis (worst ISO region and restraint; white: arm inside the base; +: home). Top: rigid joints, which vary 2.7–4.0× with pose and fall with servicer mass. Bottom: the real ±5 Nm servos, nearly flat on the small and medium servicers.




Fig. 4. Left: Monte Carlo design limits (blue free, red clamped contact) per servicer and payload, against the teleop speed cap. Right: each simulated impact re-run at the limiter speed; every peak force is below its ISO/TS 15066 limit (worst 0.90).

1.76–2.04°). On the large servicer the trade-off vanishes: every scheme stays under 0.08° with about 1–2 mm of error, so the choice of scheme does not matter there.

C. When does drift matter?

Drift scales roughly with the mass ratio (Fig. 6). Fig. 8 shows the small-servicer case in the demo video. On the 20 kg servicer (ratio 0.30) the schemes split into two groups. Schemes 1–3 finish but peak at 22.9–25.3° in 6-D and 10.4–11.2° in 3-D, which loses the radio link. Schemes 4–5 stay under 1.5° but cannot reach the waypoints. In the β-sweep, holding the base within 5° needs $\beta \geq 1$, and no β then finishes the task. For this arm, a CubeSat-class servicer cannot do the task within the pointing limit with any of the five schemes. The 150 kg servicer can, and the 1500 kg servicer does not need reactionless control at all.

D. Posture drift

Returning the hand does not return the arm (Fig. 7). Without a posture term, joint drift is large: RNS ends 2.92 rad away in 3-D on medium and gradient projection 0.58 rad. With posture impedance, Impedance ends 0.016 rad away and Imp.+RNS




Fig. 5. 6-D trade-off from the β-sweep (curves, schemes 4 and 5) and the single points of schemes 1–3. Black $\times$: task not finished within 1.5$\times$ the reference time. Red dashed line: $\pm 5^\circ$ antenna limit.




Fig. 6. Peak base drift against arm-to-base mass ratio for the 3-D and 6-D tasks ($\times$: task not finished; red: $\pm 5^\circ$ antenna limit).

TABLE II
SCRIPTED GATE, 2 LOOPS (PEAK / FINAL ANTENNA ERROR IN DEGREES, RMS HAND ERROR IN MM)

Scheme	medium 3-D peak/final	rms	medium 6-D peak/final	rms	small 6-D peak (done)
1 DLS	1.28/.040	0.6	2.03/.407	0.6	25.3 (yes)
2 Grad. proj.	1.34/.602	0.7	2.04/.411	0.6	25.0 (yes)
3 Impedance	1.28/.033	0.6	1.76/.230	0.6	22.9 (yes)
4 RNS	0.53/.059	13.1	1.55/.160	8.0	1.42 (no)
5 Imp.+RNS	0.46/.001	22.5	1.44/.154	8.7	1.45 (no)

0.065 rad (6-D). The plain RNS drift also explains its one verification failure (R4 below). Its joints wander through the null space, and the base finishes 0.059° off, while Imp.+RNS finishes 0.001° off. Posture impedance is what makes reactionless control repeatable for an operator.

E. Safety case

The verification matrix is generated from the data (`docs/SAFETY.md`). It covers ten hazards, including antenna loss, an astronaut strike, a head strike, self-collision, joint limits, singularities, a wrong dynamics model, operator confusion, input loss and an infeasible 6-D demand. Table III lists the requirements. The limiter acted in at most 3.9 % of ticks, all on the large servicer during along-arm motion, and the worst hand speed reached 0.84 of $v_{\max}$.

F. Operator aid: the tilt-limit map

In parallel work on an earlier, generic 12.5 kg arm model (repository `v1/`), P2 asked a different question: can the operator *see* which targets the base can afford before commanding them? Probing 98 directions from rest gives three nested cages for 0.5, 1 and 2° of base tilt (Fig. 9). On 300 targets near the edge, the 2° cage was right on 271, with 8 false "go" and 21 false "no-go". A runtime fence held the base at most 2.02° on




Fig. 7. Joint-configuration return error $\|q_f - q_0\|$ after two loops (hatched 3-D, solid 6-D), per scheme and servicer.




Fig. 8. Frame from the demo video: the same scripted 6-D operator input on the 20 kg servicer. DLS (left) follows the loop but tips the antenna past 5° (red line; peak 19° in the one-loop clip); Imp.+RNS (right) holds 0.26° but is still at the first waypoint.




Fig. 9. Tilt-limit cages around the hand (v1 model, 300 kg): blue, 2°; orange, 1°; green, 0.5° of base tilt. The yellow target lies in the caution zone.

TABLE III
VERIFICATION MATRIX (COMPUTED FROM DATA)

Req	Requirement	Result
R1	Antenna within ±5°, 2 loops, 6-D	Pass on medium and large; fail on small
R2	Contact speed $\leq v_{\max}(q)$	Pass: 397/397 impacts under the limit
R3	Momentum residual $< 10^{-6}$	Pass (6×10^{-8})
R4	3-D reactionless: final $< 0.05°$, peak $\leq \frac{1}{2}$ DLS	**Fail**: RNS medium 0.059°
R5	No joint past its limit	Pass (min. margin 2.4°)
R6	No bus contact in task; contact signalled	Pass
R7	$\|\dot{q}\| \leq 1$ rad/s, direction kept	Pass
R8	6-D reactionless infeasible, 3-D exact	Pass (rank 7/9, 6/6)
R9	No head or face contact	Open (procedural)
R10	Missing input ⇒ zero command	Pass (CI)

46 commands that a rehearsal had refused. The cost of such a wrong command was time (median 11–14 s), not attitude. The limit binds only in a band of spacecraft sizes, about 150–600 kg at 2°. This agrees with the benchmark result that drift matters on the small and medium servicers and not on the large one.

VII. Discussion and Limitations

What the trade-off means for mission design. The mass ratio decides which scheme is right. Above about 0.1 no scheme meets a 5° pointing limit for this task, and the operator needs attitude control or a smaller workspace. Near 0.04 the reactionless schemes buy a 1.3–2.8× reduction in peak drift for centimetre-level hand error. Imp.+RNS adds the posture repeatability that plain RNS lacks. Below 0.005 DLS or Impedance is simpler and just as good. Fig. 5 lets a mission choose β from its pointing budget.

Safety. Joint compliance, not the spacecraft, sets the contact limit. With the real servos, $v_{\max}$ varies little over the workspace (0.15–0.18 m/s on medium), whereas rigid joints give 0.04–0.17 m/s. The plan's expectation of a strongly pose-dependent limit holds only for rigid joints, such as an arm with brakes engaged. The clamped case dominates, and a payload of a few kilograms lowers the limit below what the interface can command, so the limiter is not optional.

Limitations. Everything here is simulated. No participant data exists yet, and the benchmark's human half is pending. Other limitations:

- **Model:** one arm, rigid links, no friction, flexible appendages, sensor noise or initial momentum; attitude control is off, though real servicers usually keep it on.
- **Drives:** the real Gen3 joints give about 39/9 Nm, not our ± 5 Nm.
- **Safety assumptions:** the 6 kg servo share is calibrated on our servo model and must be re-measured for real drives. The tissue model is the ISO spring with $e = 0$. The v1 tilt-limit map comes from a different arm model.
- **Tuning:** gains were tuned on scripted input, and a human may prefer different ones.

VIII. Conclusion

A 7-joint arm on a free-floating servicer cannot track a 6-D task, keep its base still and keep its posture at once. The benchmark makes the trade-off concrete. On a 150 kg servicer, reactionless schemes cut drift by 1.3–2.8$\times$ for 8–22 mm of hand error. On a 20 kg servicer no scheme both finishes the task and keeps the antenna within 5°. On a 1500 kg servicer the problem disappears. Posture impedance is what makes reactionless control repeatable. For contact safety, back-drivable joints shield the person from the spacecraft's mass. A limiter calibrated by simulated impacts keeps every tested impact within ISO/TS 15066 force limits. The interface, protocol and analysis are ready for the human study.

References

[1] S. Dubowsky and E. Papadopoulos, "The kinematics, dynamics, and control of free-flying and free-floating space robotic systems," *IEEE Trans. Robot. Autom.*, vol. 9, no. 5, pp. 531–543, 1993.

[2] Y. Umetani and K. Yoshida, "Resolved motion rate control of space manipulators with generalized Jacobian matrix," *IEEE Trans. Robot. Autom.*, vol. 5, no. 3, pp. 303–314, 1989.

[3] D. N. Nenchev, K. Yoshida, P. Vichitkulsawat, and M. Uchiyama, "Reaction null-space control of flexible structure mounted manipulator systems," *IEEE Trans. Robot. Autom.*, vol. 15, no. 6, pp. 1011–1023, 1999.

[4] K. Yoshida, K. Hashizume, and S. Abiko, "Zero reaction maneuver: flight validation with ETS-VII space robot and extension to kinematically redundant arm," in *Proc. IEEE Int. Conf. Robot. Autom. (ICRA)*, 2001, pp. 441–446.

[5] S. Abiko, R. Lampariello, and G. Hirzinger, "Impedance control for a free-floating robot in the grasping of a tumbling target with parameter uncertainty," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst. (IROS)*, 2006, pp. 1020–1025.

[6] H. Nakanishi and K. Yoshida, "Impedance control of free-flying space robot for orbital servicing," *J. Robot. Mechatron.*, vol. 18, no. 5, pp. 608–617, 2006.

[7] ISO, "ISO 10218-1:2025 robotics – safety requirements – part 1: Industrial robots," International Organization for Standardization, Tech. Rep., 2025.

[8] ——, "ISO/TS 15066:2016 robots and robotic devices – collaborative robots," International Organization for Standardization, Tech. Rep., 2016.

[9] D. N. Nenchev and K. Yoshida, "Impact analysis and post-impact motion control issues of a free-floating space robot subject to a force impulse," *IEEE Trans. Robot. Autom.*, vol. 15, no. 3, pp. 548–557, 1999.

[10] D. N. Dimitrov and K. Yoshida, "Utilization of the bias momentum approach for capturing a tumbling satellite," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst. (IROS)*, 2004, pp. 3333–3338.

[11] A. Liégeois, "Automatic supervisory control of the configuration and behavior of multibody mechanisms," *IEEE Trans. Syst. Man Cybern.*, vol. 7, no. 12, pp. 868–871, 1977.

[12] T. Yoshikawa, "Manipulability of robotic mechanisms," *Int. J. Robot. Res.*, vol. 4, no. 2, pp. 3–9, 1985.

[13] C. W. Wampler, "Manipulator inverse kinematic solutions based on vector formulations and damped least-squares methods," *IEEE Trans. Syst. Man Cybern.*, vol. 16, no. 1, pp. 93–101, 1986.

[14] A. S. Deo and I. D. Walker, "Overview of damped least-squares methods for inverse kinematics of robot manipulators," *J. Intell. Robot. Syst.*, vol. 14, pp. 43–68, 1995.

[15] T. F. Chan and R. V. Dubey, "A weighted least-norm solution based scheme for avoiding joint limits for redundant manipulators," in *Proc. IEEE Int. Conf. Robot. Autom. (ICRA)*, 1993, pp. 395–402.

[16] N. Hogan, "Impedance control: an approach to manipulation, parts I–III," *ASME J. Dyn. Syst. Meas. Control*, vol. 107, no. 1, pp. 1–24, 1985.

[17] L. B. Rosenberg, "Virtual fixtures: perceptual tools for telerobotic manipulation," in *Proc. IEEE Virtual Reality Annu. Int. Symp.*, 1993, pp. 76–82.

[18] A. D. Dragan, K. C. T. Lee, and S. S. Srinivasa, "Legibility and predictability of robot motion," in *Proc. ACM/IEEE Int. Conf. Human-Robot Interact. (HRI)*, 2013, pp. 301–308.

[19] S. G. Hart and L. E. Staveland, "Development of NASA-TLX (task load index): results of empirical and theoretical research," in *Human Mental Workload*. North-Holland, 1988, pp. 139–183.

[20] K. Zakka, Y. Tassa, and MuJoCo Menagerie contributors, "MuJoCo Menagerie: a collection of high-quality simulation models for MuJoCo," https://github.com/google-deepmind/mujoco_menagerie, 2022.

[21] Kinova Inc., "Kinova Gen3 ultra lightweight robot: technical specifications," Datasheet, 7-DoF: 902 mm reach, 8.2 kg, 2020.

[22] E. Todorov, T. Erez, and Y. Tassa, "MuJoCo: a physics engine for model-based control," in *Proc. IEEE/RSJ Int. Conf. Intell. Robots Syst. (IROS)*, 2012, pp. 5026–5033.

[23] E. J. Williams, "Experimental designs balanced for the estimation of residual effects of treatments," *Aust. J. Sci. Res. Ser. A*, vol. 2, no. 2, pp. 149–168, 1949.