

Chapter 21 – Transaction Processing Examples

UTD CS-6360 Dr. Chris Irwin Davis

Exercise 21.23 - Consider the three transactions T_1 , T_2 , and T_3 , and the schedules S_1 and S_2 given below. Draw the serializability (precedence) graphs for S_1 and S_2 and state whether each schedule is serializable or not. If a schedule is serializable, write down all of the equivalent serial schedule(s). If a schedule is not serializable, write down all cycles.


T_1 : $r_1(X)$; $r_1(Z)$; $w_1(X)$

T_2 : $r_2(Z)$; $r_2(Y)$; $w_2(Z)$; $w_2(Y)$

T_3 : $r_3(X)$; $r_3(Y)$; $w_3(Y)$


S_1 : $r_1(X)$; $r_2(Z)$; $r_1(Z)$; $r_3(X)$; $r_3(Y)$; $w_1(X)$; $w_3(Y)$; $r_2(Y)$; $w_2(Z)$; $w_2(Y)$

S_2 : $r_1(X)$; $r_2(Z)$; $r_3(X)$; $r_1(Z)$; $r_2(Y)$; $r_3(Y)$; $w_1(X)$; $w_2(Z)$; $w_3(Y)$; $w_2(Y)$



S_1 Serializable:

$T_3 \rightarrow T_1 \rightarrow T_2$



S_2 Non-Serializable:

Cycle: $Z(T_1 \rightarrow T_2)$; $Y(T_2 \rightarrow T_3)$; $X(T_3 \rightarrow T_1)$


Cycle: $Y(T_2 \rightarrow T_3)$; $Y(T_3 \rightarrow T_2)$

Chapter 21 – Transaction Processing Examples


UTD CS-6360 Dr. Chris Irwin Davis

Here are some precedence graphs that have already been drawn. They are simplified in that they do not indicate the database item in conflict for each edge. If a schedule is serializable, write down all of the equivalent serial schedule(s). If a schedule is not serializable, write down all cycles.


(a)




(b)




(c)




(d)




(e)




(f)



(g)



(h)




Chapter 21 – Transaction Processing Examples

UTD CS-6360 Dr. Chris Irwin Davis


Answers:

(a)




$T1 \rightarrow T2 \rightarrow T3 \rightarrow T4$

(b)




$T1 \rightarrow T3 \rightarrow T2 \rightarrow T4$
 $T1 \rightarrow T2 \rightarrow T3 \rightarrow T4$
 $T1 \rightarrow T2 \rightarrow T4 \rightarrow T3$

(c)



$T1 \rightarrow T2 \rightarrow T3 \rightarrow T4$

(d)




$T1 \rightarrow T2 \rightarrow T3 \rightarrow T4$
 $T1 \rightarrow T2 \rightarrow T4 \rightarrow T3$

Chapter 21 – Transaction Processing Examples


UTD CS-6360 Dr. Chris Irwin Davis

(e)




Cycle: (T1→T2), (T2→T3), (T3→T1)

(f)




Cycle: (T2→T3), (T3→T4), (T4→T2)

(g)



T1 → T2 → T3 → T4
T1 → T3 → T2 → T4

(h)



T1 → T3 → T2 → T4 → T5
T1 → T2 → T3 → T4 → T5