

Exam 1 Review Sheet

- 1) Define supervised and unsupervised learning.
- 2) Define reinforcement learning.
- 3) Define regression in the context of machine learning.
- 4) Define classification in the context of machine learning.
- 5) Suppose we train a linear regression model and determine a weight vector $\bar{w}$. What will the prediction $\hat{y}$ be for an instance $\bar{x}$ as a function of $\bar{x}$ and $\bar{w}$?
- 6) Suppose we are doing linear regression using ordinary least squares error. We have a one dimensional problem with $X = \begin{bmatrix} 1 & 2 \\ 1 & 3 \end{bmatrix}$ (the first column is a bias column), and currently $\bar{w} = [\frac{1}{2}, 2]^T$, while $\bar{y} = [\frac{1}{8}, -\frac{1}{10}]^T$.
 - a) What is the current *vector* of predictions $\hat{y}$?
 - b) What is $\nabla J(\bar{w})$?
 - c) What is $\bar{w}$ after one application of gradient descent if $\eta = \frac{1}{10}$?

I am mostly interested to see that you know the formulas rather than computing the exact answers. Everything can be left in a very rough form.

- 7) Describe stochastic gradient descent. Compare it to full gradient descent and mini-batch gradient descent. What are the pros and cons of using the stochastic version?
- 8) Give an example of learning rate scheduling.
- 9) Suppose you currently have a learning algorithm with high error. You want to know whether the error is due more to bias or to variance. To diagnose the problem, you create a learning curve. Draw two “cartoon” representations of what the learning curve might look like in a high bias or high variance scenario, respectively. Also draw a cartoon of the ideal learning curve that balances bias and variance. The x-axis should be the number of data points and the y-axis should be error.
- 10) Define bias and variance in the context of machine learning.
- 11) Draw a diagram with “model complexity” on the x-axis and error on the y-axis. Plot plausible curves for the training error and test error as model complexity changes.
- 12) What might “model complexity” mean in the context of linear regression?
- 13) Explain how the ROC-AUC score is computed. Draw a diagram of a ROC graph showing one curve for each of the following:
 - a) A mediocre model
 - b) A good model
 - c) Random guessing

Be sure to label the axes.

- 14) Suppose we have a confusion matrix given by $\begin{bmatrix} 9 & 1 & 1 \\ 2 & 8 & 3 \\ 1 & 0 & 14 \end{bmatrix}$. Produce a classification report featuring class-wise precision, recall, f1 and support for each class. Also explain how to compute the macro and weighted averages.

- 15) Suppose we have $X = [[18, 2], [11, 1]]$ (there is no bias column – this is a 2d problem with two instances). Show how to apply min-max scaling.
- 16) How would we apply softmax to the vector $[-12, 5, -2]$? What is the purpose of the softmax operation?
- 17) Consider unregularized linear regression on one hand and ridge regression on the other. Are the hypothesis spaces the same? Why or why not?
- 18) Explain ℓ_1 and ℓ_2 regularization.
- 19) How does regularization relate to bias and variance? What is regularization trying to achieve?
- 20) Suppose you have a problem with 120 instances and 240 columns. You decide to apply linear regression. Are you likely to have high bias or high variance? Why?
- 21) Draw a picture of a 2d classification problem that is not linearly separable. You can use “-” for one class and “+” for the other.
- 22) Why is logistic regression called “regression” if it is a classification technique?
- 23) Suppose you have trained a logistic regression model on a binary classification problem. How do you turn an instance $\bar{x}$ and the weight vector $\bar{w}$ into a prediction?
- 24) What is bad about scaling before doing a train/test split?
- 25) What is the difference between the error function J and the loss function?
- 26) Give the expression for cross-entropy loss for a binary classification problem with $y \in \{0, 1\}$. Describe what parts of the expression contribute high error in each of these four scenarios.
a) $y \approx 1$ and $\hat{p} \approx 1$ b) $y \approx 1$ and $\hat{p} \approx 0$ c) $y \approx 0$ and $\hat{p} \approx 1$ d) $y \approx 0$ and $\hat{p} \approx 0$
- 27) Define the meaning of “training epoch”.
- 28) What are the features in the MNIST dataset?
- 29) What is the purpose of cross-validation? Explain how 5x cross validation works.
- 30) What is the purpose of cross-validation? What are the pros and cons of using 1x cross-validation versus 10x cross validation?
- 31) Why don’t we use the test set for hyperparameter tuning?
- 32) What is a hyperparameter? Give three examples of hyperparameters.
- 33) How does grid search work as a method for tuning hyperparameters?
- 34) Give a mathematical description of the true out-of-sample error for a hypothesis $h(x)$ and a target $f(x)$. Why is it “unknowable” in practice? How do we estimate it?
- 35) Give a mathematical expression for cross-entropy loss that includes “class weights”.
- 36) How does SMOTE work? Please include a diagram.
- 37) What is unbalanced data and what problems does it cause? How do we try to mitigate them?
- 38) Suppose you have a problem with 300 columns but you find a feature transformation that compresses down to only 8 columns. What has happened to bias and variance?

- 39) Why is scaling the data essential for applying gradient descent?
- 40) Which usually requires a smaller learning rate: full gradient descent, or stochastic gradient descent? Why?
- 41) Suppose you are trying logistic regression on a problem and the error function does not seem to be converging. What are some things you might try?
- 42) Consider $X = [[2, 3], [-1, 3]]$. Apply a degree 2 polynomial features transformation.