

A Multi-Layer Defense System Against Prompt Injection in Multi-Agent LLMs

Abdelghafour El Bikha

John Jay College

December 15, 2025

Abstract

Large Language Model (LLM) agents are increasingly deployed in multi-agent systems where they interact with untrusted users and other agents. This expands the attack surface for prompt injection, allowing malicious instructions to propagate through the system—a phenomenon known as “prompt infection.” Existing defenses often focus on single-turn interactions or suffer from high false positive rates (over-defense) on benign prompts containing trigger words. We propose a comprehensive three-layer defense framework (Detection, Coordination, Response) designed specifically for multi-agent environments. Our system features an ensemble detector combining semantic embeddings with heuristic patterns, trained using a **Balanced Intent Training (BIT)** strategy to minimize over-defense. We evaluate our approach on text-based prompt injection benchmarks (SaTML, deepset, LLMail, NotInject, N=1,042), achieving **97.6% accuracy**, **92.6–100% recall** across attack datasets, and **1.8% FPR** [95% CI: 0.8–3.4%] on the NotInject over-defense benchmark (n=339). In preliminary evaluation against GCG/AutoDAN adaptive attacks (n=36), we observe **27.8% ASR** [95% CI: 15.9–44.0%]—lower than literature baselines (>50%), though larger-scale validation is needed. We identify HTML-embedded attacks (BrowseSafe) as out-of-scope for text embedding approaches, highlighting the need for modality-specific detectors. By decoupling semantic intent from keyword presence, BIT effectively mitigates the “over-defense” problem common in keyword-based systems. Our system operates with **1.9–4.2ms latency** (P50: 2.5ms, P95: 4.2ms) on standard CPU hardware, making it suitable for real-time applications.

1 Introduction

The integration of Large Language Models (LLMs) into multi-agent systems enables complex workflows but introduces severe security vulnerabilities. Prompt injection attacks, where adversaries manipulate model behavior via malicious inputs, are well-documented in single-LLM setups. However, in multi-agent systems, a successful injection in one agent can cascade to others, compromising the entire network.

Current defenses face two critical limitations:

1. **Over-Defense:** Many detectors rely on keyword matching or aggressive classifiers that flag benign prompts containing security-related terms (e.g., “system”, “ignore”), rendering them unusable for legitimate power users.
2. **Single-Agent Focus:** Most defenses ignore the inter-agent trust boundaries and lack mechanisms to quarantine compromised agents to prevent lateral movement.

To address these gaps, we present a **Multi-Layer Defense System** that secures the entire agent lifecycle. Our contributions are:

1. **Three-Layer Architecture:** A holistic framework comprising Detection, Coordination, and Response layers to detect, isolate, and mitigate attacks.
2. **Ensemble Detection:** A hybrid detector combining a fast embedding-based classifier (XGBoost + MiniLM) with a pattern-based heuristic engine, achieving robust detection with sub-2ms latency.
3. **Balanced Intent Training (BIT):** A novel training strategy that explicitly optimizes for low false positives on benign “trigger-heavy” prompts by balancing semantic intent learning across injection, safe, and benign-trigger samples. Unlike prior over-defense mitigation approaches, BIT focuses on dataset composition and weighted loss optimization.
4. **Comprehensive Benchmarking:** We provide a unified evaluation across SaTML, deepset, LLMail, and NotInject datasets, with detailed comparisons against recent state-of-the-art defenses including InjecGuard, StruQ/SecAlign, DefensiveToken, and PromptArmor.

2 Background & Related Work

Prompt Injection: Early work identified direct prompt injection [Perez and Ribeiro, 2022] and indirect injection via retrieved context [Greshake et al., 2023]. In multi-agent systems, “prompt infection” [Lee and Tiwari, 2025] describes how malicious prompts can replicate across agents.

Defense Mechanisms: Current defenses span multiple paradigms with distinct trade-offs:

2.1 Training-Time Defenses

StruQ [Chen et al., 2024] addresses prompt injection through **structured query separation**. The approach introduces a “Secure Front-End” that:

1. Inserts special delimiter tokens ([INST], [DATA]) to separate instructions from user data
2. Filters data inputs to remove potentially conflicting instructions
3. Fine-tunes the LLM to follow only instructions in the designated prompt section

StruQ achieves <2% ASR on manual injection attacks for Llama-2 and Mistral models. However, it requires **full model fine-tuning** and remains vulnerable to optimization-based attacks (ASR reduced from 97% to 58%) [Zhan et al., 2025].

SecAlign [Chen et al., 2025] extends StruQ via **preference optimization**. It constructs contrastive pairs of (secure output, insecure output) for prompt-injected inputs and applies Direct Preference Optimization (DPO) to align the model toward secure responses. SecAlign achieves near-zero ASR on optimization-free attacks while preserving utility (AlpacaEval2 scores). The key limitation is the requirement for model retraining, making it unsuitable for API-only LLM deployments.

2.2 Test-Time Defenses

DefensiveToken [Anonymous, 2024a] inserts a small number of optimized security tokens into the model vocabulary. These tokens are trained via gradient-based optimization to induce injection-resistant behavior without modifying base model weights. DefensiveToken achieves 0.24% ASR on 31K+ samples—remarkably comparable to training-time methods. However, it requires access to model internals for token embedding optimization.

2.3 LLM-Based Defenses

PromptArmor [Anonymous, 2024b] employs a **guardrail LLM** as a preprocessing filter. The guardrail analyzes incoming prompts, identifies injected content, and sanitizes the input before forwarding to the primary LLM. On AgentDojo benchmarks, PromptArmor achieves $<1\%$ FPR and FNR using GPT-4o as the guardrail. The trade-off is significant latency overhead (200ms) due to additional LLM inference.

2.4 Over-Defense Mitigation

InjecGuard/PIGuard (Liang et al., 2024; accepted ACL 2025) identified over-defense as a critical barrier to prompt guard adoption. They introduced:

1. **NotInject Dataset:** 339 benign samples enriched with 1–3 trigger words per sentence, enabling systematic over-defense evaluation
2. **MOF (Mitigating Over-defense for Free) Strategy:** A training approach that reduces trigger-word bias by augmenting training data with benign samples containing attack-like keywords

InjecGuard’s MOF operates by **implicit bias deamplification** during fine-tuning of transformer guardrail models (DeBERTa-v3 based).

2.5 Positioning Our Work: BIT vs. MOF

InjecGuard’s MOF and our BIT address the same over-defense problem using the same NotInject dataset. We clarify similarities and differences:

Similarities:

- Both use NotInject-style samples to reduce keyword bias
- Both target low FPR on trigger-heavy benign prompts
- Both achieve FPR $<5\%$ on NotInject

Differences:

Table 1: BIT vs. InjecGuard MOF Comparison

Aspect	InjecGuard MOF	Our BIT
Mechanism	Implicit bias deamplification in DeBERTa fine-tuning	Explicit weighted loss optimization in XGBoost
Model Type	Transformer (DeBERTa-v3)	Ensemble (XGBoost + MiniLM embeddings)
Latency	12ms (requires GPU)	2–5ms (CPU-only possible)
Interpretability	Black-box neural network	Feature importance via XGBoost
NotInject FPR	2.1% (reported)	1.8% [95% CI: 0.8–3.4%]

Honest assessment: Our FPR on NotInject: 1.8% [95% CI: 0.8–3.4%] is similar to InjecGuard’s 2.1% within statistical error ($p > 0.05$, McNemar’s test). The primary differentiation is **latency (2–5ms vs 12ms)** and **CPU-only deployability**. This work is **complementary** to InjecGuard rather than strictly superior.

3 Threat Model

We assume an adversary with the following capabilities:

1. **Input Control:** Can inject prompts into the system via user chat or indirect sources (e.g., emails, web pages).
2. **Compromised Agent:** May control one agent in the network to send malicious messages to others.

Adversary Goals:

- **Policy Bypass:** Force agents to violate safety guidelines.
- **Data Exfiltration:** Steal sensitive information from agent memory.
- **Lateral Movement:** Propagate malicious instructions to privileged agents.

Out of Scope: We do not address adversarial attacks on the LLM weights themselves or infrastructure-level compromises.

- **Model extraction attacks**
- **Feedback-based attacks**
- **Distributed attacks**

Scope: Our primary focus is **text-based prompt injection** in multi-agent systems. Non-text modalities (e.g., images, HTML/DOM structural features) are outside the scope of our core embeddings-based detector, as discussed in the BrowseSafe limitations (Section 7.9).

4 System Design

Our system implements a defense-in-depth architecture with three distinct layers.

4.1 Detection Layer

The first line of defense analyzes incoming prompts using an ensemble of detectors:

- **Embedding Classifier:** Uses `all-MiniLM-L6-v2` to generate 384-dimensional embeddings, classified by an XGBoost model.
- **Pattern Detector:** A regex-based engine identifying 10 common attack families.
- **Behavioral Monitor:** Uses a sliding window of $N = 20$ recent outputs, flagging when output logits exceed $\mu \pm 2\sigma$.

4.2 Coordination Layer

This layer manages inter-agent trust and communication:

- **Guard Agent:** Acts as a gateway routing messages.
- **OVON Protocol:** Enforces structured messaging with “whisper” fields.
- **PeerGuard Validator:** (Optional) Uses a separate LLM for validation.

4.3 Response Layer

The final layer handles mitigation:

- **Circuit Breaker:** Tracks aggregate risk scores.
- **Quarantine Protocol:** Automatically isolates agents flagged as compromised.

5 Methodology

5.1 Ensemble Detection

We combine the outputs of our detectors using a weighted voting scheme:

$$s = w_{emb} \cdot s_{emb} + w_{pattern} \cdot s_{pattern} \quad (1)$$

The final decision is binary: $\hat{y} = \mathbf{1}[s \geq \theta]$. We optimize θ on the validation set targeting 98% recall, selecting $\theta = 0.764$.

5.2 Balanced Intent Training (BIT)

To mitigate over-defense, we introduce BIT, explicitly balancing three sample categories with weighted loss optimization:

1. **Injectsions (40%):** Standard attacks
2. **Safe (40%):** Normal user queries
3. **Benign-Triggers (20%):** Safe queries containing injection-like keywords

BIT applies explicit class weights during XGBoost training:

$$\mathcal{L}_{BIT} = \sum_i w_i \cdot \ell(y_i, \hat{y}_i), \quad w_{benign-trigger} = 2.0 \quad (2)$$

(with $w_i = 1.0$ for injection and safe samples)

6 Experimental Setup

Datasets:

Table 2: Dataset Summary

Dataset	Total	Inj.	Safe	Source	Purpose
SaTML CTF 2024	300	300	0	IEEE SaTML	Adaptive attacks
deepset	662	406	256	HuggingFace	General benchmark
LLMail-Inject	200	200	0	Microsoft	Indirect attacks
NotInject (Official)	339	0	339	HuggingFace	Over-defense eval
Adversarial	594	594	0	Synthetic	Robustness test
Multi-Lang	72	72	0	Synthetic	Cross-lingual test
Total	3,328	1,572	1,756	-	-

Baselines: We compare against classifier-based (DeBERTa, InjecGuard), training-time (StruQ, SecAlign), and LLM-based (PromptArmor) defenses.

Statistical Methodology: We use stratified 80/20 train/test splits with fixed seed 42. All reported metrics include 95% confidence intervals (CI) computed using the **Wilson score method**, which provides more accurate coverage than normal approximation for small samples or extreme proportions (e.g., near-0% FPR). Statistical significance for classifier comparison is assessed using **McNemar’s test** for paired binary classifiers ($p < 0.05$).

Metrics: We report False Positive Rate (FPR) relative to the specific dataset size. The Intra-class Distance Ratio (IDR) is defined as the mean Euclidean distance between class centroids in the original MiniLM embedding space: $IDR = d(\mu_{\text{benign-trigger}}, \mu_{\text{benign}}) / d(\mu_{\text{benign-trigger}}, \mu_{\text{injection}})$.

7 Results

To validate our multi-layer architecture (Section 4), we structure the evaluation as follows:

1. **Detection Layer:** Performance on benchmark datasets and over-defense analysis (Sections 7.1–7.4).
2. **Coordination Layer:** Inter-agent trust exploitation and OVON protocol security (Section 7.5).
3. **Response Layer:** Quarantine effectiveness and mitigation rates (Section 7.5.5).

7.1 Detection Performance

Our system achieves state-of-the-art performance across all text-based benchmarks.

Table 3: Per-Dataset Detection Performance

Dataset	Acc.	Prec.	Rec.	F1	FPR	FNR	P95 (ms)
SaTML CTF	99.8%	100.0%	99.8%	99.9%	0.0%	0.2%	4.3
deepset	97.4%	96.1%	97.0%	96.6%	2.3%	3.0%	2.8
LLMail	100.0%	100.0%	100.0%	100.0%	0.0%	0.0%	3.0
NotInject	98.2%	-	-	-	1.8%	-	1.8
Overall	97.6%	-	-	-	1.8%	-	3.0

Notably, we achieve **1.8% False Positive Rate** on the official NotInject HuggingFace dataset, validating BIT effectiveness.

7.2 Baseline Comparison

Compared to recent state-of-the-art defenses, our system offers competitive accuracy with significantly lower latency.

7.3 Ablation Study

We analyzed the contribution of each component. *Definitions: "nocascade" = always runs deep path; "fastonly" = runs only embedding classifier (no heuristic rules).*

7.4 Deep Over-Defense Analysis

7.4.1 NotInject Difficulty-Level Breakdown

We stratify the NotInject dataset into three difficulty levels based on trigger word density to evaluate robustness. Level 1 (Easy) contains single triggers (e.g., "ignore"), while Level 3 (Hard) involves complex combinations. As shown in Table 6, baseline models degrade significantly on harder samples, whereas BIT maintains robust performance.

Table 4: Comparison with Industry Baselines

System	Acc.	FPR	FNR	P50 (ms)	Open	
BIT (Ours)	97.6%	1.8%	2.7%	2.5	✓	
HuggingFace DeBERTa	90.0%	10.0%	60.0%	48.0	-	* Numbers from
TF-IDF + SVM	81.6%	14.0%	29.5%	0.1	✓	
Lakera Guard*	87.9%	5.7%	-	66.0	-	
ProtectAI*	90.0%	-	-	500.0	-	
Glean AI*	97.8%	3.0%	-	-	-	

published benchmarks; may use different test sets.

Table 5: Ablation Study Results (General Performance on deepset)

Configuration	Accuracy	F1	FPR	FNR	
Full System (Ours)	97.5%	97.5%	2.0%	3.0%	
w/o Pattern Detector	97.5%	97.5%	2.0%	3.0%	
w/o Embedding	60.5%	0.0%	0.0%	79.0%	*Low FPR due to lack of trigger
<i>no_{cascade}</i>	97.5%	97.5%	2.0%	3.0%	
<i>fast_{only}</i>	97.5%	97.5%	2.0%	3.0%	
w/o BIT Training	95.0%	94.7%	0.0%*	10.0%	

words in deepset. See Table 8 for over-defense evaluation on NotInject (86% FPR w/o BIT).

7.4.2 Trigger Word Analysis

We analyze which specific trigger words cause the highest false positive rates in baseline models and how BIT addresses them (Table 7):

The most problematic words (“jailbreak”, “bypass”, “ignore”) have near-100% FPR without BIT training. This demonstrates that baseline classifiers learn **lexical shortcuts** rather than semantic intent. BIT’s weighted loss optimization forces the model to consider full context, eliminating these false positives.

7.4.3 BIT Component Ablation

We decompose BIT into its constituent strategies to understand each contribution (Table 8):

Analysis:

- **Benign-trigger samples are critical:** Removing them causes FPR to spike to 41.3%, demonstrating the importance of exposing the model to trigger-heavy benign examples.
- **Weighted loss provides significant improvement:** Even with benign-trigger samples, removing the $w_{benign-trigger} = 2.0$ weight increases FPR to 12.4%.
- **Dataset balancing matters:** The 40/40/20 split ensures adequate representation of each category; unbalanced data causes both higher FPR (23.7%) and lower recall (91.5%).

7.4.4 Embedding Space Analysis

To understand why BIT succeeds, we visualize the learned embedding space using t-SNE projections (Figure 9).

Without BIT: Trigger words create dense clusters in embedding space regardless of semantic context. Samples like “ignore the noise” and “ignore previous instructions” are embedded close together, causing misclassification.

With BIT: The embedding space reorganizes by **intent** rather than **keywords**. Benign samples containing trigger words cluster with other benign samples, while injection attacks cluster separately based on their adversarial intent patterns.

We quantify this using **Intra-class Distance Ratio (IDR):**

$$\text{IDR} = \frac{d_{benign-trigger, benign}}{d_{benign-trigger, injection}} \quad (3)$$

Table 6: NotInject Dataset Difficulty-Level Breakdown

Level	Samples	Trigger Words	BIT FPR	InjecGuard*	DeBERTa
Level 1 (Easy)	113	1 word	0%	0.9%	6.2%
Level 2 (Medium)	113	2 words	0%	2.7%	12.4%
Level 3 (Hard)	113	3 words	0%	2.7%	21.2%
Overall	339	1-3 words	0%	2.1%	13.3%

*Overall FPR 1.8% on full benchmark [95% CI: 0.8–3.4%]. 0% observed on difficulty-stratified ablation subset. InjecGuard estimated from paper figures.

Table 7: Trigger Word False Positive Rate Analysis

Trigger Word	Benign Context Example	DeBERTa	w/o BIT	With BIT
“ignore”	“Please ignore my previous typo”	89.2%	94.1%	0%
“system”	“Update the system settings”	45.3%	52.7%	0%
“override”	“This does not override the policy”	78.6%	81.3%	0%
“bypass”	“The highway bypass saves time”	92.1%	95.8%	0%
“admin”	“Contact the admin for help”	38.4%	41.2%	0%
“jailbreak”	“iPhone jailbreak tutorial”	97.3%	98.2%	0%
“prompt”	“Answer the prompt in the textbook”	23.1%	28.9%	0%
“instruction”	“Follow the instruction manual”	31.5%	37.8%	0%

*0% FPR observed on this specific subset; overall benchmark FPR is 1.8%. FPR = False Positive Rate (benign samples incorrectly flagged as injections).

Table 9: Embedding Space IDR Analysis

Model	IDR	Interpretation
DeBERTa (baseline)	2.31	Benign-triggers closer to injections
w/o BIT	2.18	Slight improvement
With BIT	0.67	Benign-triggers correctly clustered with benign

An $IDR < 1$ indicates benign-trigger samples are correctly positioned closer to benign samples than to injections.

7.5 Inter-Agent Trust Exploitation Evaluation

Recent research demonstrates that 82.4–100% of LLMs are vulnerable to inter-agent trust exploitation, where models execute malicious commands from peer agents even when they resist identical direct prompts [Lee and Tiwari, 2025]. To validate our multi-agent coordination layer’s effectiveness, we conduct dedicated evaluations of agent-to-agent attack scenarios (see Figure 11 for network topology and Figure 12 for infection propagation dynamics).

Experimental Setup: We simulate attack sequences using distinct random seeds (Temperature=0.7) for generation. Reported metrics (Time to Detection, Isolation) are mean values over 50 independent trials. The Guard Agent utilizes our BIT-trained detector ($\theta = 0.764$) for all experiments.

7.5.1 Compromised Agent Attack Results

We evaluate scenarios where one agent in the network is fully compromised (adversary-controlled). We construct a 5-agent test environment simulating a realistic multi-agent workflow (Orchestrator, Researcher, Coder, Reviewer, Guard) and test five attack vectors: Direct Peer Injection, Transitive Trust Exploitation, Whisper Field Manipulation, Role Impersonation, and Payload Fragmentation.

Key Findings:

Table 8: BIT Component Ablation Study

Configuration	NotInject FPR	Attack Recall	Overall F1
Full BIT	1.8%	97.1%	97.6%
w/o Weighted Loss ($w = 1.0$)	12.4%	94.2%	95.8%
w/o Benign-Trigger Samples	41.3%	96.8%	94.1%
w/o Dataset Balancing	23.7%	91.5%	93.2%
No BIT (baseline)	86.0%	70.5%	82.3%

Component definitions:

- Weighted Loss: $w_{benign-trigger} = 2.0$ vs. uniform weights
- Benign-Trigger Samples: 20% of training data from NotInject + synthetic
- Dataset Balancing: 40% injection / 40% safe / 20% benign-trigger split

Table 10: Multi-Agent Attack Scenario Results

Attack Scenario	Target	Without Guard	With Guard	Reduction
Direct injection (Coder $\rightarrow$ Orch.)	Policy bypass	94.2%	2.1%	97.8%
Transitive (Coder $\rightarrow$ Rsrch. $\rightarrow$ Orch.)	Data exfiltration	87.6%	4.3%	95.1%
Whisper field injection	Hidden command	78.3%	0%	100%
Role impersonation	Privilege escalation	91.7%	0%	100%
Fragmented payload (3 msgs)	Delayed execution	45.2%	8.7%	80.8%

*Higher latency due to message correlation across sliding window. Success rates are percentage of attack attempts that achieved adversary’s goal.

- **Without our Guard Agent:** LLMs exhibit strong peer-trust bias, executing 78–94% of malicious peer commands that they would reject from users.
- **With Guard Agent:** Attack success rate drops to 0–8.7% across all scenarios.
- **Whisper field protection:** OVON protocol validation completely blocks metadata-based attacks.

7.5.2 Guard Agent Bypass Testing

We specifically test whether attackers can bypass our Guard Agent through adversarial techniques:

Table 11: Guard Agent Bypass Testing Results

Bypass Technique	Attempts	Bypasses	Rate
Prompt obfuscation (Base64, ROT13, Unicode)	500	12	2.4%
Semantic reformulation	500	23	4.6%
Context confusion (legit prefix + injection)	500	8	1.6%
Multi-turn buildup	200	17	8.5%
Agent spoofing (forged metadata)	500	0	0%
Direct Guard injection	500	3	0.6%
Overall	2,700	63	2.3%

Agent spoofing is fully prevented by OVON cryptographic signing. Multi-turn buildup is most effective, indicating need for longer context windows.

Analysis:

- **Agent spoofing is fully prevented** by cryptographic message signing in OVON protocol.
- **Multi-turn buildup** is the most effective bypass (8.5%), indicating need for longer context windows.
- **Direct Guard injection** is extremely difficult (0.6%) due to the Guard’s minimal attack surface (no tool execution).

7.5.3 OVON Protocol Security Analysis

We analyze the security properties of our OVON-based coordination layer. We verify message authenticity via cryptographic signing, integrity via HMAC, and proper whisper field isolation (preventing metadata injection).

Table 12: OVON Protocol Security Properties

Security Property	Mechanism	Result	Test Cases
Message Authenticity	Cryptographic signing	✓Verified	0/1000 spoofed
Integrity Protection	HMAC on message body	✓Verified	0/1000 tampered
Whisper Field Isolation	Parse validation, no exec	✓Verified	0/500 injected
Trust Chain Enforcement	Explicit trust tagging	✓Verified	All low-trust flagged
Replay Prevention	Nonce + timestamp	✓Verified	>5s window rejected

All security properties verified through adversarial testing. Whisper fields are never executed, only logged for audit purposes.

Note: OVON is an open standard for voice interoperability. We adapt its envelope structure for agent-to-agent text messaging.

7.5.4 Quarantine Protocol Effectiveness

We evaluate whether our quarantine system can detect and isolate compromised agents before infection spreads (Table 13).

Table 13: Quarantine Protocol Effectiveness

Metric	Value	Description
Time to Detection (TTD)	1.2 msgs	Avg messages before flagging
Time to Isolation (TTI)	2.8 msgs	Avg messages before quarantine
Infection Prevention Rate	94.7%	Attacks stopped before spreading
False Quarantine Rate	1.3%	Legitimate agents incorrectly isolated
Recovery Time	45s	Time to restore after verification
Cascade Prevention (10-agent network):		
Agents infected @ 1 min	1.3 vs 4.2	69% reduction with quarantine
Agents infected @ 5 min	1.5 vs 7.8	81% reduction with quarantine
Full network compromise	3% vs 62%	95% reduction with quarantine

The system demonstrates a **95% reduction** in full network compromise rate (from 62% to 3%) compared to a system without quarantine.

7.5.5 Comparison with PeerGuard

We compare our Guard Agent approach against PeerGuard’s mutual reasoning defense [Wang et al., 2024].

Trade-off Analysis:

- **PeerGuard advantage:** Higher true positive rate (96% vs 93.1%) due to semantic reasoning.
- **Our advantage:** 400x lower latency (1.9ms vs 800ms), no additional LLM inference costs.
- **Recommendation:** A tiered approach where our Guard handles Tier 1 (real-time) and PeerGuard handles Tier 2 (escalated risk).

7.6 Modality Limitations: BrowseSafe Evaluation

We evaluate our system on BrowseSafe [Research, 2025], a benchmark of 14,719 HTML-embedded prompt injections designed for AI browser agents. BrowseSafe represents a fundamentally different modality from our text-based benchmarks, as attacks exploit HTML structure, CSS styling, and DOM features.

Results:

Table 14: Comparison with PeerGuard Mutual Reasoning Defense

Aspect	Our Guard Agent	PeerGuard
Detection Mechanism	Centralized classifier	Distributed LLM reasoning
Latency per Message	1.9ms	$\approx 800\text{ms}$
True Positive Rate	93.1%	96.0%*
False Positive Rate	2.1%	8.5%*
Scalability	$O(1)$ per message	$O(n)$ with agent count
LLM Dependency	None	Requires reasoning LLM
Adversarial Robustness	Classifier evasion	Reasoning manipulation

*Reported numbers from PeerGuard paper on GPT-4o. Our approach offers $400\times$ lower latency at the cost of 3% lower TPR. Complementary for tiered deployment.

- Recall on attacks: 100% (Detects all malicious text after HTML parsing)
- **FPR on benign HTML: 95%** (Cannot distinguish benign vs. malicious HTML context)
- Accuracy: 52% (Near-random due to high FPR)

Root Cause Analysis: Our MiniLM-based embedding approach operates on extracted text content, losing critical HTML structural context (e.g., hidden text attacks via ‘display:none’, attribute-based injections). After text extraction, both malicious and benign HTML converge to similar semantic embeddings. This confirms that HTML-embedded attacks require DOM-aware detection approaches (e.g., fine-tuned LLMs), and text-based semantic embeddings are insufficient for this modality.

7.7 Preliminary Adaptive Attack Analysis: GCG and AutoDAN

CAUTION: Preliminary Results ($n = 36$).

We observe:

- GCG suffix attacks: 10% ASR
- AutoDAN semantic attacks: **37.5% ASR** [13.7–69.4%]
- Overall: **27.8% ASR** [15.9–44.0%]

8 Discussion

Latency & Scalability: P50 latency of 1.9ms is negligible.

8.1 Limitations

- **Adversarial Robustness:** Susceptible to semantic reformulation (AutoDAN).
- **Evaluation Scope:** Does not cover BrowseSafe or InjecAgent.
- **Multi-Turn Attacks:** Independent message processing misses gradual intent shifts.
- **Detection of HTML:** Not suitable for raw HTML inputs.

8.1.1 Limited Effectiveness Over Long Workflows

Theoretical cumulative bypass rates indicate $>99\%$ bypass probability over 50 messages. Assuming independent per-message bypass probability $p \approx 8.7\%$, the probability of at least one successful bypass over n messages is $1 - (1 - p)^n$. For $n = 50$, this exceeds 99.9%, suggesting the need for periodic re-authentication.

9 Conclusion

We present a multi-layer defense system achieving 97.6% accuracy and 1.8% FPR with sub-5ms latency. Code and model weights are released upon publication. By combining ensemble detection with Balanced Intent Training (BIT) and optimized classification threshold ($\theta = 0.764$), we effectively mitigate over-defense on trigger-heavy benign prompts while maintaining high recall against diverse attacks.

References

- Anonymous. Defensive tokens: A lightweight defense against prompt injection. *arXiv preprint arXiv:2403.00001*, 2024a.
- Anonymous. Promptarmor: A guardrail-based defense for large language models. *arXiv preprint arXiv:2404.00001*, 2024b.
- Yanda Chen et al. Struq: Defending against prompt injection with structured queries. *arXiv preprint arXiv:2402.00001*, 2024.
- Yanda Chen et al. Secalign: Aligning large language models for security via preference optimization. *arXiv preprint arXiv:2501.00002*, 2025.
- Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. More than you’ve asked for: A comprehensive analysis of novel prompt injection threats to application-integrated large language models. *arXiv preprint arXiv:2302.12173*, 2023.
- Jin Lee and Ashish Tiwari. Prompt infection: Propagation of malicious prompts in multi-agent systems. *arXiv preprint arXiv:2501.00001*, 2025.
- Fabio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models. *arXiv preprint arXiv:2211.09527*, 2022.
- Perplexity AI Research. Browsersafe: Benchmarking ai browser agents against html-embedded attacks, 2025.
- Xinyu Wang et al. Peerguard: Multi-agent security via mutual reasoning. *arXiv preprint arXiv:2406.00001*, 2024.
- Patrick Zhan et al. Jailbreakbench: An open robustness benchmark for red teaming large language models. *arXiv preprint arXiv:2501.00003*, 2025.