FitnessBalance — simplified core ERD

Core collections only • selected identifiers and relationship fields

SHARED CATALOGUE

foods

foodKey [ID]
food_name
nutrition : map

workoutPaths

pathId [ID]
name

contains
1 0..*

lessons

lessonId [ID]
name

contains
1 0..*

workoutExercises

itemId [ID]
exerciseId

exerciseId
0..* 1

exercises

exerciseId [ID]
name

0..*
foodItems[].foodId

1
pathId + lessonId

USER DOCUMENT AND USER-OWNED SUBCOLLECTIONS

All private records shown belong to users/{uid}; ownership lines are omitted.

users

uid [ID]
fullName
totalXp

0..*

foodLogs

date [ID]
foodItems : array(map)
totalCalories

date
0..1 0..1

dailyData

date [ID]
caloriesConsumed
caloriesBurned

exerciseLogs

date [ID]
exercises : array(map)
totalCaloriesBurned

0..*

workoutRecords

sessionId [ID]
pathId
lessonId
localDay
localWeek

0..*

0..1 0..1
same user / date totals
0..1

localDay → date totals

0..*
localWeek
1

exerciseWeeks

week [ID]
completed
target

[ID] = document key. Solid lines show core logical relationships; dotted gold lines show dated summary dependencies, not enforced foreign keys.
foodItems and exercises arrays remain embedded attributes. Food-to-log association is many-to-many through foodItems[].foodId.
Simplification: reusable meals, recipes, weights, wearable receipts, detailed quests/achievements and session-start records are omitted; see the complete ERD.