

Tire

Remove and install a new item

DMC: S1000DBIKE-AAA-DA0-10-20-00AA-921A-A
Language: en/US
Issue No.: 010
Issue date: 2024-06-19
Title: Tire – Remove and install a new item
Security classification: UNCLASSIFIED
Commercial classification: cc51
Caveat: cv51

Table of contents

References 3

Preliminary requirements 4

Procedure 5

Safety conditions 4

Requirements after job completion 5

List of tables

Table 1 - References 3

Table 2 - Required conditions 4

Table 3 - Required persons 4

Table 4 - Support equipment 4

Table 5 - Consumables, materials and expendables 4

Table 6 - Spares 4

Table 7 - Required conditions 5

References

Table 1 References

Data module/Technical publication	Title
DMC-S1000DBIKE-AAA-DA0-00-00--041A-A	(no title provided)
DMC-S1000DBIKE-AAA-DA0-10-20--215A-A	(no title provided)
DMC-S1000DBIKE-AAA-DA1-00-00--341A-A	(no title provided)

Preliminary requirements

Required conditions

Table 2 Required conditions

Action/Condition	Data module/Technical publication
None	

Required persons

Table 3 Required persons

Person	Category	Skill level	Trade/Trade code	Estimated time
A	Basic user		Operator	0,3 hour

Support equipment

Table 4 Support equipment

Name/Alternate name	Identification/Reference	Quantity	Remark
Specialist toolset	MFR: KZ666 /PN: BSK-TLST-001	1 each	
Tire lever	MFR: KZ666 /PN: BSK-TLST-001-04	1 each	
Tire pressure guage	MFR: KZ666 /PN: BSK-TLST-001-01	1 each	

Consumables, materials and expendables

Table 5 Consumables, materials and expendables

Name/Alternate name	Identification/Reference	Quantity	Remark
None			

Spares

Table 6 Spares

Name/Alternate name	Identification/Reference	Quantity	Remark
Tire	MFR: KT666 /PN: TIRES-010101	1 each	

Safety conditions

None

Procedure

- 1 Lift and turn the bicycle and make sure the bicycle is held safely in this position.
- 2 Use a standard wrench from the **Specialist toolset** and loosen the brake caliper.
- 3 Remove the axle bolt.
- 4 Remove the wheel.
- 5 Deflate the tire.
- 6 Use the **Tire lever** from the **Specialist toolset** and remove the old tire from the wheel.
- 7 Use the **Tire lever** from the **Specialist toolset** and attach the new **Tire** to the wheel. Refer to [DMC-S1000DBIKE-AAA-DA0-00-00--041A-A](#)
- 8 Inflate the tire (refer to [DMC-S1000DBIKE-AAA-DA0-10-20--215A-A](#)).
- 9 Install the wheel.
- 10 Tighten the axle bolt.
- 11 Tighten the brake caliper.

Requirements after job completion

Required conditions

Table 7 Required conditions

Action/Condition	Data module/Technical publication
Lift and turn the bicycle to the correct position.	
Do a test of the brakes as given in the brake test procedure.	DMC-S1000DBIKE-AAA-DA1-00-00--341A-A

End of data module