


You're **very close** — you actually have the two flows reversed. 😊 Let's straighten that out, because this distinction is *really* important for everything coming next.

Let's trace them slowly

React + Parcel

In your React app:



So the browser is making the data request.


The important path is:

Browser → Server/API → Browser

And then React renders the data after it arrives.

Next.js Server Component

With a Server Component:



Here **the server makes the data request**.

The browser doesn't need to first render an empty component, run `useEffect`, and then ask for the data.

So your sentence should be flipped:

You said:

"in 1st one server requests from external api and then gives to browser"

That's actually **the Next.js Server Component approach**. 

And:

"in second browser first renders then again req external api and rerenders"

That's actually **React + Parcel + `useEffect`**. 

One subtle but VERY important thing

When we say:

"Browser first renders"

we don't necessarily mean the user sees the **final page** immediately.

It might initially see:

Loading...



Then:

```
useEffect()  
  ↓  
fetch()  
  ↓  
data arrives  
  ↓  
setState()  
  ↓  
render again
```



So you can get:

```
Initial render  
  ↓  
Loading UI  
  ↓  
API request  
  ↓  
Data arrives  
  ↓  
Second render  
  ↓  
Actual UI
```



Whereas server fetching can be conceptually:

```
Server  
  ↓  
Fetch data  
  ↓  
Render with data  
  ↓  
Browser receives useful UI
```



That's the **core reason server-side fetching can be valuable.**

Tiny check before we continue

Imagine your Performance Analyzer has a page showing:

Performance Score: 92



If we use React + `useEffect` to get that score, which of these happens?

A

Server → API → Server → Browser



B

Browser → API → Browser → React updates



And if we use a Server Component to fetch the score?

C

Server → API → Server → Browser



Just answer **A/B/C** (you can explain too). Then we'll move one tiny step further. 🚀



B


Exactly! 🎯 **B is correct.**

React + Parcel + `useEffect`



```
Browser
  |
  | fetch()
  ↓
API / Server
  |
  | response
  ↓
Browser
  |
  | setState()
  ↓
React re-renders
```

And the Server Component version would be:



So you've got the first important Lesson 4 idea. ✅

Lesson 4 — Part 2: What does `await fetch()` actually mean?

Now let's look at this:

❏ TypeScript

```
export default async function Page() {  
  const response = await fetch("https://api.example.com/data");  
  
  const data = await response.json();  
  
  return <h1>{data.name}</h1>;  
}
```

You already know `async/await` from JavaScript/TypeScript, so the syntax itself isn't new.

The **new question** is:

Where is this JavaScript executing?

Because that's what changes everything.

Since `Page` is a **Server Component**, this code runs on the **Next.js server**.

So:


❏ TypeScript

```
const response = await fetch(...)
```

means:

"Next.js server, make this HTTP request and wait for the response before continuing this component's rendering."

The flow is:



Notice what `await` is doing.

The server doesn't say:

"I don't have the data yet, so I'll render the component anyway."

Instead, conceptually:

```
fetch()
  ↓
waiting for data...
  ↓
data arrives
  ↓
continue
  ↓
render
```

Compare that with your React app

In your old React approach:

`</> TypeScript`

```
useEffect(() => {  
  fetch("/api/data")  
    .then(...)  
}, []);
```



The initial render happens **without the data**:

React render

↓

"Loading..."

↓

useEffect

↓

fetch

↓

data

↓

setState

↓

render again



With a Server Component:

`</> TypeScript`

```
const response = await fetch(...)
```



the server can obtain the data **as part of producing the initial result**.

That's the key difference we're building toward.

One important question 🤔

You might now be thinking:

"Wait... if the server has to wait for the API anyway, aren't we just moving the waiting from the browser to the server? How is that actually faster?"



Excellent question.

And that's exactly the next thing we should investigate.

Because **"server fetching = automatically faster"** is NOT a rule.

There are several tradeoffs involving:

- network location
- server → API latency
- browser → server latency
- rendering
- caching
- streaming

We'll tackle **that exact question next**, rather than jumping ahead into caching.





Yes — **you've spotted an important distinction.** 🙌

If the user is already sitting on the page, **time-based revalidation of the server-side cached data does not automatically mean their already-rendered UI changes at 2:15.**

Let's separate two things.

1. The cached server data

Suppose:

```
2:05 → server fetches ₹100
      ↓
      CACHE
      ↓
2:15 → cache becomes stale
```



At 2:15, the **cache** is stale.

2. The user's already-open page

The user already received:

Product price: ₹100



That HTML/React UI is already sitting in their browser.

Nothing inherently tells the browser:

"Hey! The server cache just became stale. Go get the new price."

So yes:

User opens page at 2:05

↓

Sees ₹100

↓

2:15 cache becomes stale

↓

User is still staring at page

↓

Still sees ₹100



until something causes the UI to fetch/render fresh data.

That could be a navigation, refresh, client-side request, polling, server-driven update mechanism, etc., depending on how we design the app.

And this is actually the point of revalidation

Revalidation answers:

"When should the server stop treating this cached data as fresh?"

It does **not** necessarily answer:

"When should every currently-open browser immediately update?"

Those are two different problems.

Think:


SERVER SIDE

↓

CACHE

fresh → stale





The browser needs its **own mechanism** if you want live updates while the user stays on the page.

Example: stock price 📈

If you have:

Stock price: ₹1,250



you probably **don't** want to rely on a 10-minute server revalidation and expect the screen to magically update.

You'd likely need something like:

```
graph TD; A[Browser] --- B[poll every 5 sec]; A --- C[WebSocket]; A --- D[Server-sent events];
```



depending on the requirements.

But for something like:

Blog article
Documentation
Product description



it's perfectly fine if the user continues seeing the version they loaded. They don't necessarily need a live update.



So remember these two separate questions

Cache revalidation:

"Is the server's stored result still fresh?"

UI updating:

"Should an already-open browser get new data?"

They're related, but **not the same thing**.

And this distinction will become really useful when we later talk about **Client Components, Router Cache, polling, and streaming**.

You're asking exactly the right "wait, but what does the user actually see?" questions. That's how you get past the surface-level Next.js tutorials. 🔥



next....also let me know when is the last concept in lesson 4 for lesson 5 i will open new chat

Absolutely 👍 We'll keep this **progressive**, and I'll explicitly tell you when we've reached the **last concept of Lesson 4** so you know when to start a new chat.

Lesson 4 — Part 6: Sequential vs Parallel Data Fetching

This is our next concept.

First: what's the problem?

Imagine your Performance Analyzer needs **two independent pieces of data**:

```
PageSpeed API
  ↓
Performance data

Gemini API
  ↓
AI explanation
```



Let's simplify and say each takes **2 seconds**.

A beginner might write:

```
</> TypeScript
```




```
const performance = await getPerformanceData();  
  
const analysis = await getAIAnalysis();
```

Looks innocent.

But look at what happens:

Time →



Total:

4 seconds 🤔

Why?

Because the second request doesn't even start until the first one finishes.

That's **sequential fetching**.

What if they don't depend on each other?

If API 2 doesn't need the result of API 1, there's no reason to wait.

We can start both:


```
</> TypeScript
```



```
const [performance, analysis] = await Promise.all([  
  getPerformanceData(),  
  getAIAnalysis(),  
]);
```

Now:

Time →



```
API 2
  ↑
both run
together
```

Total $\approx$ 2 seconds, not 4.

🔥 That's the basic idea of **parallel data fetching**.

React + Parcel comparison

You could absolutely do this in normal React too.

For example:

```
</> TypeScript
```

```
Promise.all([
  fetch("/api/performance"),
  fetch("/api/other-data"),
]);
```

So **parallel fetching** isn't a Next.js invention.

Important distinction:

Next.js doesn't magically make JavaScript promises parallel.

The underlying JavaScript behavior is the same.

What Next.js gives us is a server-rendering environment where we can strategically perform these requests **before/during server rendering**, which can make this architecture particularly useful.

Why does this matter so much?

Imagine:

```
Page
├─ User data
├─ Performance data
├─ Recommendations
└─ Configuration
```

If none of these depend on each other:

❌ Sequential

```
graph TD;
  A[User data] --> B[Performance data];
  B --> C[Recommendations];
  C --> D[Configuration];
```



If each takes 1 second:

~4 seconds

✅ Parallel

```
graph LR;
  User[User data] --- P[Performance];
  P --- R[Recommendations];
  R --- C[Configuration];
  Page[Page] --- R;
  R --> Continue[Continue];
```



Roughly:

~1 second

assuming they're independent and network conditions are comparable.

But there's an important exception

Suppose:

```
graph TD;
  A[API 1] --> B[returns user ID];
  B --> C[API 2 needs that user ID];
```



Then:

API 1 → API 2



must be sequential.

You can't start API 2 before you know the ID.

For example:

⌕ TypeScript

```
const user = await getUser();  
  
const orders = await getOrders(user.id);
```

Here there is a genuine dependency:

User
↓
user.id
↓
Orders

So parallelizing them would make no sense.



The rule

Ask:

"Does request B need information produced by request A?"

Yes → Sequential

A → B


No → Parallel

A —┐
 ├→ continue
B —┐

This is a simple rule, but it's a **very useful performance habit**.

Your Performance Analyzer

Suppose later your architecture looks something like:



We should ask:

"Can these requests happen concurrently?"

If yes, we don't want to accidentally create a waterfall:

```
graph TD; A[API 1] --> B[API 2]; B --> C[API 3]; C --> D[API 4];
```

when we could have:

```
graph LR; A[API 1] --> E[Results]; B[API 2] --> E; C[API 3] --> E; D[API 4] --> E;
```

This is especially relevant to the kind of performance-focused application you're building.



Small exercise

Suppose your page needs:

- A = Fetch logged-in user
- B = Fetch product catalog
- C = Fetch user's orders using `user.id`
- D = Fetch site configuration

Which requests can happen **in parallel**, and which have to wait?

Think about the dependency:

A → C



while B and D are independent.

Tell me the groups, e.g.:

A, B, D together → then C

Then we'll continue.

Lesson 4 progress

We're **not at the end yet**.

After this, we still have a few important concepts:

1. Sequential vs parallel fetching ← **we are here**
2. Loading UI
3. Error handling
4. Streaming / Suspense
5. **Final Lesson 4 recap + architecture exercise**

Once we finish **#5**, I'll explicitly say:

 **Lesson 4 COMPLETE — open a new chat for Lesson 5.**

So you won't have to guess. 😊



```
const [performance, analysis] = await Promise.all([
  getPerformanceData(),
  getAIAnalysis(),
]);
```

here promise.all itself awaits and gives both results
why we need await again? and also lets start in new chat
the remaining lessons of 4

Yes — `Promise.all()` **does not itself** `await`. That's the key distinction. Let's clear that up before we move to the new chat. 🙄

`Promise.all()` vs `await`

`Promise.all()` **creates/returns one Promise** that represents all the promises finishing:

</> TypeScript

```
const result = Promise.all([
  getPerformanceData(),
  getAIAnalysis(),
]);
```



At this point, `result` is still a **Promise**.

So:

```
getPerformanceData() ─┐
                       │└─> Promise.all() → Promise
getAIAnalysis() ─────┘
```



Then:

</> TypeScript

```
const [performance, analysis] = await Promise.all([
  getPerformanceData(),
  getAIAnalysis(),
]);
```



`await` says:

"Pause this async function until that combined Promise finishes, then give me the actual results."

So:

```
Promise.all()  
  ↓  
one combined Promise  
  ↓  
await  
  ↓  
actual results  
  ↓  
[performance, analysis]
```



Why is this different from:

```
</> TypeScript  
  
const performance = await getPerformanceData();  
const analysis = await getAIAnalysis();
```



Because here:

```
API 1 starts  
  ↓  
WAIT  
  ↓  
API 1 finishes  
  ↓  
API 2 starts  
  ↓  
WAIT  
  ↓  
API 2 finishes
```



Whereas with `Promise.all()`:

```
API 1 starts ─────────┐  
                        │  
API 2 starts ─────────┘──> both finish → continue
```



So your intuition was **half-right**:

`Promise.all()` gathers the promises, but `await` is what waits for the combined promise and gives you the resolved values.

And yes! 🙌 Let's start a new chat for the remaining Lesson 4 concepts.

When you open it, just say:

Continue Next.js Lesson 4 — remaining concepts

I'll pick up from **Sequential vs Parallel Data Fetching**, then we'll do:

Loading UI → Error Handling → Streaming/Suspense → final Lesson 4 recap + architecture exercise → 🏁 Lesson 4 COMPLETE.



ChatGPT can make mistakes. Check important info.