





Yes — **your intuition is close, but there's one very important correction.** This is actually a fantastic question because it separates **cache revalidation** from **browser UI updating**. 🧠

Let's use your exact scenario.

Your scenario

You're on:

/products



And the data is fetched with:

```
fetch("/api/products", {  
  next: {  
    revalidate: 60  
  }  
})
```

Meaning:

The cached data can be considered stale after 60 seconds.

Now:

12:00 → you open /products
12:01 → 1 minute passes
12:02 → you're STILL sitting on /products



Does the UI automatically change at 12:01?

✗ No.

This is the key correction.

`revalidate: 60` does **not** mean:

"After 60 seconds, push fresh data into whoever is currently looking at this page."

Instead it means:

"After 60 seconds, this cached data is eligible for revalidation when a new request/render needs it."

Think of it like this

At 12:00:

Browser



```
/products
↓
Server
↓
Data Cache
↓
[A, B, C]
```

At 12:01:

```
Data Cache
↓
STALE
```



But the browser is still displaying:

```
[A, B, C]
```



Nothing has caused a new request.

So:

```
CACHE BECAME STALE
≠
UI AUTOMATICALLY UPDATED
```



That's the crucial distinction.

When does the UI get fresh data?

Suppose at 12:02 you navigate away:

```
/products
↓
/profile
```



and then come back:

```
/profile
↓
/products
```



Now a new navigation/request can happen.

Next.js sees:

products cache



STALE



So it can revalidate/fetch fresh data:

Database



fresh products



Data Cache



render



RSC Payload



UI



Now you see the updated data.

What if you manually refresh the browser?

Same idea.

Browser Refresh



new request



stale cache detected



revalidation



fresh data



UI



So your original statement:

"After one minute, even before I refresh, the UI automatically updates."

✗ Not necessarily.

The page being open doesn't itself cause the revalidation to be pushed into the UI.

Now let's bring `updateTag()` into this

This is where your second understanding needs a small correction too.

Suppose you have:

```
updateTag("products");
```

This expires the cached `products` data.

But:

```
updateTag()  
↓  
cache expires
```



doesn't inherently mean:

```
cache expires  
↓  
browser immediately receives new data
```



Those are separate things.

If you're already sitting on:

```
/products
```



and some Server Action does:

```
updateTag("products");
```

you can explicitly request the current route to refresh:

```
updateTag("products");  
refresh();
```

Then:

```
updateTag()  
↓  
old data expires  
↓  
refresh()  
↓  
new RSC request  
↓
```



fresh data



UI updates

But here's the REALLY important part 🔥

Don't think:

"revalidate = UI automatically updates, updateTag = I must call refresh."

That's **not** the correct fundamental model.

Instead:

`revalidate: 60`

means:

"After 60 seconds, this cached data is stale/eligible for revalidation when it is requested again."



It doesn't create a live connection to the browser.

`updateTag()`

means:

"Expire this tagged cached data now."



Again, it doesn't by itself mean:

"Push new data into the browser right now."



`refresh()`

means:

"Refresh the current route and get a new RSC payload."



One beautiful example 🎯

Imagine your database changes because **another user** adds a product.

12:00

You open `/products`



UI:
Laptop
Phone
Tablet

At:

12:01



your 60-second cache lifetime has passed.

Database now has:

Laptop
Phone
Tablet
Monitor



But you're still staring at:

Laptop
Phone
Tablet



Why?

Because **nothing has caused your current UI to request new data.**

Then:

12:03

You navigate to /home

12:04

You navigate back to /products



Now Next.js has a reason to render/fetch the route again.

It discovers the cached data is stale:

STALE

↓

revalidate

↓

fresh data

↓

Monitor appears



And what if you want live updating? 📡

That's a different problem entirely.

If you want:

"I'm sitting on `/products`, and whenever another user adds a product, I want my screen to change immediately."

Then cache revalidation alone isn't enough.

You'd typically need something like:

WebSocket
Server-Sent Events
Polling
Realtime subscription



or some client-side mechanism that periodically causes a refresh/fetch.

Because **Next.js** cache revalidation isn't a real-time push mechanism.

Final mental model 🧠

Keep these three sentences:

Cache expiration does not equal UI update.

A stale cache is discovered/revalidated when something causes a read/render/navigation.

`refresh()` explicitly causes the current route to request fresh RSC/UI state.

So your scenario becomes:

```
revalidate: 60
  ↓
60 seconds pass
  ↓
cache becomes STALE
  ↓
❌ UI does NOT automatically change just because
   you're sitting on the page
  ↓
some new request/navigation/revalidation happens
  ↓
fresh data
```



↓
UI updates

And:

```
updateTag("products")
  ↓
cache expires
  ↓
❌ expiration itself doesn't push UI
  ↓
refresh()
  ↓
fresh RSC
  ↓
UI updates
```



That's the final distinction. Once you understand "*cache freshness ≠ UI freshness*", Next.js caching becomes MUCH less mysterious. 😊



And now that you've got this, the **next logical piece is the most important one**: **Data Cache → Full Route Cache → Router Cache** **dependency chain**—including what happens to each cache when you call each of **these four APIs**. That's where we'll build the final master table. 🚀


Exactly. 🚀 Now let's tie everything together into one **master mental model**: how **Data Cache → Full Route Cache → Router Cache** relate to each other, and where each invalidation API fits.

The goal here isn't to memorize four isolated functions. You should be able to reason from:

What became stale? → what depends on it? → when does fresh data actually get read? → when does the browser UI change?

The three-cache relationship

Start with this:



One caveat: don't imagine this as a mandatory three-step pipeline for every request. These caches have different responsibilities and can depend on one another, but not every route necessarily uses all of them in exactly the same way.

Start with the Data Cache

Suppose your Server Component contains:

`</>` TypeScript

```
const products = await fetch("/api/products", {
  next: {
    tags: ["products"],
  },
});
```

The fetched result can be stored in the Data Cache:

Data Cache



products
[A, B, C]

The Server Component then uses that data to produce its rendered result.

That rendering can produce:

HTML



+
RSC Payload

which can be stored as the route's Full Route Cache entry:

Full Route Cache



/products

HTML
+
RSC Payload

So the relationship is essentially:

Data Cache



[A, B, C]

|
| data used during rendering
▼

Full Route Cache
HTML + RSC Payload
for /products

Then the Router Cache enters

When the browser navigates to `/products`, the RSC payload can be used by the client-side App Router and stored in its Router Cache:

Router Cache



/products
RSC Payload

React then uses that information to maintain the current UI.

So remember the difference:

Full Route Cache — server side

HTML + RSC Payload



Router Cache — client side

RSC Payload



That distinction is worth keeping very clear.

Now introduce a mutation

Suppose everything currently contains:

Database

[A, B, C]



Data Cache

[A, B, C]

Full Route Cache

[A, B, C]

Router Cache

[A, B, C]

UI

[A, B, C]

The user adds **D**.

The database becomes:

Database

[A, B, C, D]



But the caches may still contain:

Data Cache

[A, B, C]




Full Route Cache

[A, B, C]

Router Cache

[A, B, C]

So we now have a mismatch:



This is when invalidation becomes important.

What happens with `revalidateTag()` ?

Suppose the products fetch has:

```

</> TypeScript
next: {
  tags: ["products"]
}
  
```

and after a mutation we call:

```

</> TypeScript
revalidateTag("products");
  
```

The primary thing we're targeting is the **tagged data**.

Conceptually:

```

Data Cache
[A,B,C]
↓
stale
  
```

Because a route may have been rendered using that data, the route's cached rendering can subsequently need to be regenerated as well.

So think:

```

tagged data becomes stale
↓
dependent route needs fresh rendering
  
```

↓
new route output can be generated

If this happens inside a Server Action, Next.js can coordinate the action response with the client's current navigation state. A Route Handler doesn't provide that same automatic coordination with the browser's current UI.

What about `updateTag()` ?

Now use:

`</>` TypeScript



```
updateTag("products");
```

The important difference is the cache semantics.

Conceptually:

`revalidateTag()`



↓
tagged data becomes stale /
revalidation semantics

`updateTag()`

↓
tagged data expires immediately

So `updateTag()` is particularly useful after a mutation where you want the previous cached representation to stop being usable as the valid value.

But don't translate that into:

" `updateTag()` means the UI will never update."

That's not the right model.

It is primarily a **server-side data-cache operation**. Getting that new value onto the currently displayed screen is a separate concern.

Now `revalidatePath()`

Suppose instead you call:

`</>` TypeScript



```
revalidatePath("/products");
```

Here your target is the **route**:

```
/products
↓
route cache invalidated
```



When `/products` subsequently needs to render again, Next.js can perform the necessary data reads and produce a new route result.

Conceptually:

```
revalidatePath("/products")
↓
Full Route Cache
↓
invalidated
↓
/products renders again
↓
Data Cache checked
↓
appropriate data obtained
↓
new HTML + RSC Payload
```



So the clean distinction is:

```
revalidateTag()
↓
DATA-oriented

revalidatePath()
↓
ROUTE-oriented
```



And `refresh()` ?

This one operates at a different level.

```
</> TypeScript
```

```
refresh();
```



is about refreshing the **current client route**.


Conceptually:



But here's an important detail:

`refresh()` does **not** automatically mean "go all the way to the database."

Suppose the Data Cache still contains valid data:



So if you want a mutation followed by a fresh current UI, the combination matters.

For example:

```
<> TypeScript

await db.product.create(...);

updateTag("products");
refresh();
```

The first operation makes the old tagged data expire; the second asks the current route to refresh and therefore consume the now-invalidated data.

Here's the master comparison


API	Main target	Data Cache	Full Route Cache	Current UI / Router Cache
<code>revalidateTag()</code>	Tagged data	Invalidates/revalidates tagged data	Dependent route output can be regenerated	Server Action can coordinate client

API	Main target	Data Cache	Full Route Cache	Current UI / Router Cache
<code>updateTag()</code>	Tagged data	🔴 Expires tagged data immediately	🔄 Dependent rendering can become stale	Server Action can coordinate; <code>refresh()</code> explicitly refreshes current
<code>revalidatePath()</code>	Route/path	🔄 Relevant data may be read again	🔴 Invalidates route	Server Action can coordinate client
<code>refresh()</code>	Current client route	❌ Doesn't itself invalidate data	❌ Doesn't itself invalidate route cache	🔵 Refreshes current route/UI


The arrows are more important than the colors here. Think in terms of **what you're targeting**, not "which function clears which cache."

Let's trace all four individually

`revalidateTag()`



`updateTag()`



revalidatePath()

```

revalidatePath("/products")
    ↓
  /products route
    ↓
  Full Route Cache
    ↓
  invalidated
    ↓
route renders again when needed
    ↓
fresh route output

```

**refresh()**

```

refresh()
  ↓
current route
  ↓
new RSC request
  ↓
server renders using currently
valid/available data
  ↓
new RSC Payload
  ↓
Router Cache / UI

```

**The most important distinction of the whole lesson 🔥**

Don't mix these four concepts:

```

CACHE INVALIDATION
  ≠
DATA FETCHING
  ≠
ROUTE RENDERING
  ≠
UI UPDATE

```



For example:

```
updateTag()
```



doesn't itself mean:

"Go query the database right now."

It means the old tagged cached data has been expired.

Likewise:

```
refresh()
```



doesn't mean:

"Ignore every cache and query the database."


It means:

"Refresh the current route."

The subsequent render decides whether it can use valid cached data or needs fresh data.


Put everything together

Here's the complete chain:



↓
UI

And the APIs conceptually enter at different levels:



So if an interviewer gives you a mutation scenario, ask yourself four questions:

1. What data became invalid?

→ `revalidateTag()` / `updateTag()`

2. What route became invalid?

→ `revalidatePath()`

3. Does the current client route need to refresh?

→ `refresh()`

4. Is this happening through a Server Action or a Route Handler?

→ That determines how closely Next.js can coordinate the server-side change with the current client navigation/UI.

That is the durable mental model. 🚀

One final caveat: **Next.js caching APIs have evolved across versions**, so exact invalidation behavior can differ by API and calling context. For interview preparation, use the current API semantics rather than older blog-post rules; the dependency model above is the part worth internalizing.



Yes — **you're very close**, but there's one wording correction:

`revalidatePath()` invalidates the **Full Route Cache** — not the "Full Router Cache." **Router Cache** is a separate client-side cache.

And the **arrows in my diagram were showing dependency/flow**, not "this API directly clears the next cache." That's what made it confusing. Let me redraw it cleanly. 📌

1. First, the three caches

SERVER

Data Cache



Full Route Cache

CLIENT

Router Cache



React UI

Data Cache

Stores fetched server data:

/products data
/users data

```
/orders data
```

Full Route Cache

Stores the result of rendering a route:

```
/products  
↓  
HTML + RSC Payload
```



Router Cache

Client-side cache:

```
/products  
↓  
RSC Payload
```



2. What each API primarily targets

Now forget the arrows for a second.

```
revalidateTag()
```

```
</> TypeScript  
  
revalidateTag("products");
```



Targets:

```
DATA CACHE  
↑  
revalidateTag()
```




✅ **Data Cache**

```
updateTag()
```

```
</> TypeScript  
  
updateTag("products");
```



Targets:



✔ Data Cache


The difference is **how the tagged data is invalidated**, not that it targets a completely different cache.

```
revalidatePath()
```

</> TypeScript

```
revalidatePath("/products");
```

Targets:




✔ Full Route Cache

```
refresh()
```

</> TypeScript

```
refresh();
```

Targets the **current client route/UI refresh**, involving the Router Cache.



✔ Client-side route state

3. So your understanding should be:

API	Primary target
revalidateTag()	Data Cache

API	Primary target
<code>updateTag()</code>	Data Cache
<code>revalidatePath()</code>	Full Route Cache
<code>refresh()</code>	Current client route / Router Cache

That's the clean version. ✅

4. Then what were my arrows showing?

This diagram:

```
graph TD; A[Data Cache] --> B[Full Route Cache]; B --> C[Router Cache]; C --> D[UI]
```

was showing a **conceptual dependency/flow**:

Data can be used to render a route, and the resulting RSC payload can reach the client.

It did **NOT** mean:


```
graph TD; A[revalidateTag()] --> B[automatically invalidate Full Route Cache]; B --> C[automatically invalidate Router Cache]
```

That would be too simplistic.

5. Think of the arrows as "depends on"

This is the better way to interpret them:

```
graph TD; A[Data Cache] -- "data can be used to render" --> B[Full Route Cache]
```



So:

Full Route Cache



can depend on the data used to render that route.

And:

Router Cache



contains client-side RSC payload information for navigation/rendering.

6. Example

Suppose:


`</> TypeScript`



```

const products = await fetch(..., {
  next: {
    tags: ["products"]
  }
});
  
```

Then conceptually:



|
▼
UI
A B C

Now call:

```
⟨⟩ TypeScript  
revalidateTag("products");
```



The primary thing you're saying is:

DATA CACHE
"A B C"
↓
INVALID / STALE



You're **not directly** saying:

Router Cache → delete



7. What happens when `/products` renders again?

Now suppose something causes `/products` to render again.

Next.js needs the products data.

It sees:

Data Cache
↓
products entry is stale



So it obtains/revalidates the data.

Maybe:

Database
[A,B,C,D]



Then:

fresh data
↓
render `/products`
↓



```

new RSC Payload
  ↓
new UI state

```

That's where the **dependency** matters.

8. `revalidatePath()` is route-oriented

If instead:

```

</> TypeScript

revalidatePath("/products");

```

you're saying:

```

/products
  ↓
Full Route Cache entry
  ↓
INVALID

```

Then when `/products` needs to be rendered again:

```

render /products
  ↓
needs products data
  ↓
Data Cache checked
  ↓
fresh/valid data used
  ↓
new HTML + RSC Payload

```

So:

```

revalidateTag
  ↓
DATA-oriented invalidation

revalidatePath
  ↓
ROUTE-oriented invalidation

```

9. And Router Cache is separate

This is the part I really want you to lock in. 🔒



Full Route Cache ≠ Router Cache

They're two different caches.

So don't say:

"revalidatePath invalidates the Full Router Cache."

Say:


"`revalidatePath()` invalidates the Full Route Cache for the specified path."

And:


"`refresh()` refreshes the current client route, affecting the client-side Router Cache/UI state."

10. Final picture — no confusing arrows

Here's the version I'd put in your notes:




revalidateTag() updateTag()



revalidatePath()

RSC Payload

CLIENT



refresh()

UI

🎯 Memorize this:

revalidateTag() → Data Cache
 updateTag() → Data Cache
 revalidatePath() → Full Route Cache
 refresh() → Current client route / Router Cache



And the arrows between the caches are dependency/data flow arrows, NOT "this API automatically invalidates every cache below it."

That distinction is *exactly* what was missing from the earlier diagram. 👍



so even though revalidate Path invalidates full route cache bcoz data from ful route cache dependes on data cache that also gets invalidated ?

Almost — but **this is the subtle point I want you to get exactly right.** 🔥

❌ Don't think:

`revalidatePath()` invalidates Full Route Cache → therefore Data Cache also gets invalidated because Full Route Cache depends on Data Cache.

That dependency direction isn't quite correct.

✅ Think:

`revalidatePath()` primarily invalidates the **Full Route Cache** for that path.

It does not automatically mean that every Data Cache entry used by that route is invalidated.

Example

Suppose `/products` does:

```
</> TypeScript
const products = await fetch("/api/products", {
  next: {
    tags: ["products"],
  },
});
```



We have:

Data Cache

products → [A, B, C] ✅ valid

Full Route Cache

/products → rendered using [A, B, C]



Now:

```
</> TypeScript
revalidatePath("/products");
```



What happens?

Data Cache

products → [A, B, C]  STILL VALID

Full Route Cache

/products →  INVALIDATED

So when `/products` renders again:

`/products` needs rendering

↓

Full Route Cache MISS

↓

Server renders `/products`

↓

needs products data

↓

Data Cache checked

↓

products is still VALID

↓

[A, B, C] returned from Data Cache

So `revalidatePath()` **did not necessarily force a database fetch.**

That's really important. 🧠

Now compare `revalidateTag()`

If we do:

 TypeScript

```
revalidateTag("products");
```

then:

Data Cache

products → STALE/invalidated

Now when `/products` renders:

Full Route Cache

↓

needs fresh route

```

↓
Data Cache
↓
products is stale
↓
fresh data fetched
↓
new route rendering

```

So the two APIs are targeting different things:

```

revalidatePath("/products")
↓
Full Route Cache
↓
"This route needs rendering again."

revalidateTag("products")
↓
Data Cache
↓
"This data needs revalidation."

```



And THIS is why your question is important

You were thinking:

```

Data Cache
↓
Full Route Cache

```



Therefore:

```

invalidate Full Route Cache
↓
must invalidate Data Cache

```



But **dependencies don't work that way.**

Think:

```

Data Cache
|
| provides data
▼
Rendering of /products
|

```



Full Route Cache

If you throw away the **rendered result**, you haven't necessarily thrown away the **data used to create it**.

It's like:

You delete a finished cake 🍰 .

That doesn't mean you've thrown away the flour in your kitchen.



The reverse is more interesting

If the underlying data becomes invalid:

Data Cache
products
↓
INVALID



then a route that depends on that data **can't safely continue generating its future rendering from that old data**.

So when it renders again, fresh data can produce a new route result.

Conceptually:

Data Cache invalidated
↓
next render gets fresh data
↓
new Full Route Cache result



Final mental model 🗝️

```
revalidatePath()
```

Full Route Cache
↓
❌ invalidate



Doesn't inherently mean Data Cache is invalidated.

revalidateTag()

Data Cache
↓
✗ invalidate



Routes depending on that data may need fresh rendering.

updateTag()

Data Cache
↓
✗ expire now



refresh()

Current client route
↓
🔄 refresh



One sentence to remember

Invalidating a rendered route does not necessarily invalidate the data that was used to render it. But invalidating the underlying data means the next rendering that needs that data must obtain a valid version.

That's the exact distinction. 🎯



okay but when will be the case where route is invalidated but data cache need not invalidate bcoz mostly mutatuions are data changes right

Exactly — in a real CRUD application, you're right that many `revalidatePath()` calls happen after a data mutation, so it can *feel* like the Data Cache should always be invalidated too.

But there are legitimate cases where **the route output needs to be regenerated while the underlying cached data is still perfectly valid.**

Let's use a few concrete examples.

1. The simplest case: route depends on multiple things

Imagine `/products` renders:

Products

Laptop

Phone

Tablet

Current time: 7:30 PM



The products data is cached:

Data Cache

products → [Laptop, Phone, Tablet]



That data hasn't changed.

But maybe the route has some other reason to be regenerated.

For example, you changed something about the route's rendering/configuration.

Full Route Cache

/products

old rendered output



You can invalidate:

❏ TypeScript

```
revalidatePath("/products");
```



Now:

Full Route Cache → ❌

Data Cache → ✅



When `/products` renders again:

/products

↓

fetch products

↓

Data Cache HIT



↓
[Laptop, Phone, Tablet]

No database request is necessary.

So route invalidation $\neq$ data invalidation.

2. A mutation doesn't always modify the data used by the route

This is actually a very common situation.

Imagine:

/products



uses:

products
categories



And both are cached.

Data Cache



products → [A, B, C]
categories → [Phones, Laptops]

Now you mutate something that affects the **route rendering**, but not the products data.

For example, perhaps an admin changes the way the product page is presented:

Product cards
↓
Product table



You might invalidate:

</> TypeScript



```
revalidatePath("/products");
```

But:

products data → still valid
categories → still valid



So the route gets rendered again using the same cached data.

3. A particularly useful example: authentication / personalization

Imagine:

/dashboard



contains:

Welcome, Gopi



Products:

Laptop

Phone

Premium banner

The products might be cached:

Data Cache

products → [Laptop, Phone]



But the route output can depend on the **current user's state**.

For example:

User upgraded to Premium



The product data didn't change.

But the rendered page needs to change:

BEFORE



Products

Laptop

Phone

AFTER

★ Premium Products

Laptop

Phone

The product data remains:

```
Data Cache  
products → [Laptop, Phone] ✓
```



while the route rendering changes.

So:

```
Full Route Cache → needs new rendering  
Data Cache       → still valid
```



4. Another example: CMS / content configuration

Imagine your page fetches:

```
products
```



and also has some rendering configuration:

```
showDiscountBanner = true
```



The products haven't changed.

But an administrator changes:

```
showDiscountBanner  
true → false
```



You might need to invalidate the route:

```
</> TypeScript  
revalidatePath("/products");
```



But there is no reason to invalidate:

```
products
```



because:

```
products → unchanged
```



Again:

Full Route Cache → ❌
Data Cache → ✅



5. And here's an important architectural point

You're absolutely right that **mutations** are usually about data changes.

For example:

Create product
Update product
Delete product



In those situations, you often want something like:

```
</> TypeScript  
  
updateTag("products");
```



or:

```
</> TypeScript  
  
revalidateTag("products");
```



because the underlying data actually changed.

And depending on your desired behavior, you may also invalidate the affected route:

```
</> TypeScript  
  
revalidatePath("/products");
```



So a mutation can legitimately involve **both**:

```
Data Cache  
  ↓  
invalidate  
  
Full Route Cache  
  ↓  
invalidate
```




6. Here's the important relationship

Don't think:

Mutation
↓
always revalidatePath()
↓
therefore Data Cache invalidated



Instead think:



Sometimes:

DATA changed
↓
invalidate Data Cache
↓
route will need fresh rendering



Sometimes:

ROUTE output changed
↓
invalidate Full Route Cache
↓
Data Cache can remain valid



And sometimes:

BOTH changed
↓
invalidate both



7. Your intuition is actually useful for CRUD apps

For your **Web Performance Analyzer** project, imagine you have:

```
/analyze/google.com
```



and cached PageSpeed results:

```
Data Cache
```



```
google.com → performance result
```

Now imagine you change the **presentation of the report**:

```
Before:
```

```
Performance: 92
```



```
After:
```

```
Performance: 92
```

```
Accessibility: 95
```

```
SEO: 98
```

The underlying PageSpeed result hasn't changed.

You may need to regenerate the route, but there's no reason to throw away the cached PageSpeed data.

```
Data Cache
```

```
PageSpeed result →  still valid
```



```
Full Route Cache
```

```
/analyze/google.com →  regenerate
```

That's a very realistic example for the project you're building.

8. The deepest mental model

Here's what I want you to retain:

Data Cache answers:

```
"Can I reuse this fetched data?"
```

Full Route Cache answers:

```
"Can I reuse the rendered result of this route?"
```

Those are **different questions**.

So:

Data Cache

"Is the data reusable?"



versus:

Full Route Cache

"Is the rendered page reusable?"



And therefore:

revalidatePath()



can invalidate the answer to:

"Can I reuse this rendered page?"

without necessarily changing the answer to:

"Can I reuse this fetched data?"

That's why the two caches are separate in the first place. 🧠

One tiny correction to keep in your notes

Don't say:

" `revalidatePath()` invalidates the Full Route Cache, and therefore the Data Cache might also get invalidated."

Say:

" `revalidatePath()` targets the cached rendering for a path. Any Data Cache entries used by that rendering are separate and are not automatically invalidated merely because the route was invalidated."

That's the clean, interview-safe mental model. 🧠



ChatGPT can make mistakes. Check important info.