





Yes! 🔥 You're catching the **exact terminology trap** here. The word **"route"** is being used in two different meanings.

Let's untangle it.

1. "Any route" does NOT mean "any dynamic route"

When I wrote:

Code	Route	Rendering
<code>cookies()</code>	Any route	Traditionally dynamic rendering

I meant:

`cookies()` can appear inside **any kind of route** — `/`, `/products`, `/products/[id]`, etc.

I did **not** mean:

"`cookies()` makes the route a dynamic URL route."

These are two completely different concepts.

2. There are TWO meanings of "dynamic"

This is the big one. 🧠

A. Dynamic Route

This is about the **URL structure**.

Example:

```
app/products/[id]/page.tsx
```



`[id]` means the URL is dynamic.

```
/products/1  
/products/2  
/products/999
```



So:

```
/products/[id]  
  ↑  
Dynamic Route
```



B. Dynamic Rendering

This is about **WHEN** the page is rendered.

A dynamically rendered page means:

```
Request arrives  
  ↓  
Next.js executes page  
  ↓  
fetch data / cookies / headers  
  ↓  
render  
  ↓  
send response
```



That's request-time rendering.

3. So a STATIC URL can have DYNAMIC RENDERING

This is the part you're asking about.

Suppose:

```
app/page.tsx
```



URL:

/



This is a **static route structure**.

There is no:

```
[id]
[slug]
[username]
```



But then we write:

```
export default async function Page() {
  const cookieStore = await cookies()

  const theme = cookieStore.get("theme")?.value

  return (
    <h1>
      Theme: {theme}
    </h1>
  )
}
```

Now look at what happened.

The URL is still:

/



So:

Dynamic Route? ❌



But the **rendering is request-dependent**:

```
User A → theme=dark
User B → theme=light
User C → theme=dark
```



Therefore, in the traditional Layer-1 model:

```
Route structure → Static
Rendering → Dynamic
```



🔥 That's perfectly possible.

4. Your second question is exactly right

You asked:

"Even if route is static rendering, still depends on cookies to be either dynamic or static?"

Yes — **in the traditional Layer-1 model, that's exactly the idea.**

Think of it as two separate decisions.

Step 1 — What does the URL look like?

/products/[id]



or:

/products



This determines **route structure**.

Step 2 — Can the output be generated ahead of time?

Next.js examines the page's dependencies.

For example:

```
cookies()
```

means the result can depend on the incoming request.

Therefore:

Can I generate ONE reusable result ahead of time?



↓
▼
NO

because:

Request A → cookie A → output A



Request B → cookie B → output B

So the route becomes dynamically rendered.

5. Let's use your exact static route example

Start with:

app/products/page.tsx



URL:

/products



There is nothing dynamic in the URL.

And the component:

```
export default function ProductsPage() {  
  return <h1>Products</h1>  
}
```

Next.js can say:

```
/products  
  ↓  
same output for everyone  
  ↓  
STATIC RENDERING
```



Now add:

```
const cookieStore = await cookies()
```

```
export default async function ProductsPage() {  
  const cookieStore = await cookies()
```

```
const user = cookieStore.get("user")

return (
  <h1>
    Hello {user?.value}
  </h1>
)
```

Now:

```
/products
├── URL structure: STATIC
└── Rendering: DYNAMIC
```

Because the output depends on the request's cookies.

6. Why can't Next.js just put it in Full Route Cache?

Suppose Next.js generated this at build time:

```
<h1>Hello Gopi</h1>
```

Then User B visits and has:

```
user=Rahul
```

What should Next.js serve?

If it reused the same Full Route Cache:

```
<h1>Hello Gopi</h1>
```

that's wrong.

The page needs:

```
<h1>Hello Rahul</h1>
```

So there isn't **one universal rendered result** that can safely represent all requests.

That's why, traditionally:

```
cookies()
  ↓
request-specific data
  ↓
can't pre-render one universal route result
  ↓
dynamic rendering
```



7. And this applies to `headers()` too

For example:

```
const headersList = await headers()

const language = headersList.get("accept-language")
```

User A:

```
Accept-Language: en
```



User B:

```
Accept-Language: fr
```



Potentially different output:

```
User A → Hello
User B → Bonjour
```



So again:

```
URL structure → could be completely static
                ↓
Rendering → dynamic
```



8. `searchParams` is another great example

Suppose your route is:

```
app/products/page.tsx
```



That's still a normal/static route structure.

But users request:

```
/products?category=shoes  
/products?category=laptops  
/products?category=phones
```



Now the output can depend on the request URL.

Conceptually:

```
/products?category=shoes  
  ↓  
Shoes  
  
/products?category=laptops  
  ↓  
Laptops
```



So again:

```
Route structure → static  
Rendering dependency → request-specific
```



9. This is the mental model I want you to use

Don't ask:

"Is this route static or dynamic?"

as your **first** question.

Break it into two questions:

Question A — Is the URL structurally dynamic?

```
/products
```



VS.

`/products/[id]`

That's about **Dynamic Routes**.

Question B — Is the rendering dependent on request-time information?

Look for things such as:

```
cookies()
headers()
request-time APIs
uncached data
```



That's about **Dynamic Rendering** in the traditional model.

Put them into a 2×2 matrix

This is SUPER useful:

	Static Rendering	Dynamic Rendering
Static URL <code>/products</code>	✅ possible	✅ possible
Dynamic URL <code>/products/[id]</code>	✅ possible	✅ possible

So all four combinations are possible in the traditional mental model.

Example 1

```
/products
+
no request-specific dependencies
=
Static URL + Static Rendering
```



Example 2

```
/products
+
cookies()
=
Static URL + Dynamic Rendering
```



Example 3

```
/products/[id]
+
generateStaticParams()
=
Dynamic URL + Static Rendering
```



Example 4

```
/products/[id]
+
cookies()
+
no-store fetch
=
Dynamic URL + Dynamic Rendering
```



🔥 This is the distinction you were missing.

And one final connection

You asked:

"Even if route is static rendering still depends on cookies to be either dynamic or static?"

I'd phrase it slightly differently:

The route doesn't start as "static rendering" and then cookies somehow modify it. Next.js determines the rendering behavior from the route's code/dependencies.

So:

```
app/products/page.tsx
|
▼
Analyze dependencies
|
├── no request-time dependency
|   ↓
|   STATIC
|
└── cookies()/headers()/etc.
```



↓
DYNAMIC

And **this is exactly the decision tree we're about to study.**

One caveat: all of the above is deliberately the **traditional Layer-1 model** we're learning first. With modern **Cache Components**, request-time APIs can be isolated to dynamic portions rather than necessarily making the entire route dynamic. That's the Layer-2 architecture we'll tackle afterward. 🔥



ok

Perfect 😎 Let's now build the **actual Layer-1 Static vs Dynamic decision tree.**

🧠 Lesson 6 — How Next.js decides Static vs Dynamic

Forget SSG/SSR/ISR for a moment.

Start with just this question:

Can Next.js produce one reusable rendered result for this route?

If yes → traditionally **static rendering**.

If no → traditionally **dynamic rendering**.

1 Start with the simplest route

</> TypeScript


// app/products/page.tsx

```
export default function ProductsPage() {  
  return <h1>Products</h1>  
}
```

Next.js looks at it:

Does output depend on request?

|



So conceptually:

```
build
  ↓
render
  ↓
HTML + RSC
  ↓
Full Route Cache
```



2 Add a normal calculation

```
</> TypeScript

export default function ProductsPage() {
  const price = 100
  const tax = 18

  const total = price + tax

  return <h1>₹{total}</h1>
}
```



Still static.

Why?

Because:

```
price = 100
tax = 18
```



are known during rendering and aren't dependent on the request.

So:

```
JavaScript logic
  ↓
known result
```



↓
STATIC

Important:

Having **logic** does NOT make a route dynamic.

You can have:

```
if  
map  
filter  
reduce  
calculations  
loops  
functions
```



and still be completely static.

3 Add a cacheable API fetch

</> TypeScript



```
const products = await fetch(  
  "https://api.example.com/products"  
)
```

Assuming the fetch is cacheable under our traditional model:

```
API data  
  ↓  
can be cached  
  ↓  
render can be reused  
  ↓  
STATIC
```



So:

```
fetch()  
≠  
dynamic rendering
```



This is one of the biggest misconceptions people have.

4 Add revalidate

</> TypeScript

```
const products = await fetch(url, {  
  next: {  
    revalidate: 60  
  }  
})
```



Still potentially static.

But now:

STATIC



revalidate after 60s



regenerate



update Full Route Cache



That's our ISR-style model.

5 Now add cache: "no-store"

</> TypeScript

```
const products = await fetch(url, {  
  cache: "no-store"  
})
```



Now the question becomes:

Can I safely reuse the rendered result?

Suppose API data changes:

Request A → products A

Request B → products B



The page needs fresh data.

Traditional model:

```
no-store
  ↓
request-time data
  ↓
request-time rendering
  ↓
DYNAMIC
```



6 Now the BIG one: `cookies()`

Suppose:

```
</> TypeScript

export default async function Page() {
  const cookieStore = await cookies()

  const user = cookieStore.get("user")

  return <h1>Hello {user?.value}</h1>
}
```



Think about two requests:

```
Request A
cookie: user=Gopi
  ↓
Hello Gopi

Request B
cookie: user=Rahul
  ↓
Hello Rahul
```



Can Next.js create **one universal HTML result at build time?**

✗ No



Traditional model:

```
cookies()
  ↓
request-specific data
```



↓
DYNAMIC rendering

7 Same thing with `headers()`

`</>` TypeScript

```
const headersList = await headers()
```



Headers belong to the incoming request.

For example:

User A
Accept-Language: en

User B
Accept-Language: fr



Potentially different output.

So traditionally:

```
headers()  
  ↓  
request-specific  
  ↓  
DYNAMIC
```



8 What about `searchParams` ?

Suppose:

`</>` TypeScript

```
export default async function Page({ searchParams }) {  
  const { category } = await searchParams  
  
  return <h1>{category}</h1>  
}
```



Requests:

/products?category=shoes



and:

/products?category=laptops



can produce different results.

So:

```
searchParams
  ↓
request-specific URL information
  ↓
DYNAMIC rendering
```



But notice:

The **route itself** is still:

/products




It's not:

/products/[category]




That's the distinction we just established.

9 So our Layer-1 decision tree looks like this



▼ SSG ▼ ISR ▼ SSR

What influences that decision?



And:

revalidate
↓
STATIC + periodic revalidation

🔥 But there's an important subtlety

Don't turn this into:


cookies() → page always dynamic

without qualification.

That is the **traditional Layer-1 mental model** we're deliberately learning.

Modern Next.js with **Cache Components** changes the picture.

For example, modern architecture can conceptually do:



```
Product list      User info
                  |
                  cookies()
```

instead of forcing:

```
cookies()
  ↓
ENTIRE PAGE = dynamic
```



That's why we're keeping Layer 2 separate for now.

One more VERY important concept: "dynamic function"

You'll hear Next.js documentation/interviews use terminology like:

Dynamic APIs

Historically, APIs such as:

```
</> TypeScript
```



```
cookies()
headers()
```

were called **Dynamic APIs** because their values cannot be known ahead of time.

They're request-dependent.

Think:

```
Build time
  |
  |— Can I know cookies?
  |
  |— ❌ No
```



Whereas:

```
Request time
  |
  |— Incoming Cookie header
  |
  |— ✅ available
```



That's why they affect rendering.

Let's test your understanding

Consider these four pages:

A

 TypeScript 

```
export default function Page() {  
  return <h1>Hello</h1>  
}
```

B

 TypeScript 

```
export default async function Page() {  
  const data = await fetch(url)  
  return <List data={data} />  
}
```

C

 TypeScript 

```
export default async function Page() {  
  const data = await fetch(url, {  
    cache: "no-store"  
  })  
  
  return <List data={data} />  
}
```

D

 TypeScript 

```
export default async function Page() {  
  const cookieStore = await cookies()  
  return <h1>{cookieStore.get("name")?.value}</h1>  
}
```

Under our **Layer-1/traditional model**:

A → STATIC 

B → STATIC (assuming cacheable fetch)

C → DYNAMIC

D → DYNAMIC

And that gives us:

STATIC

- └─ plain page
- └─ cacheable fetch
- └─ revalidated fetch

↓

SSG / ISR

DYNAMIC

- └─ no-store
- └─ cookies()
- └─ headers()
- └─ request-specific dependencies

↓

SSR

🔥 Next piece: `searchParams` deserves its own lesson

There's a subtle point here because:

`/products/[id]`

and:

`/products?id=123`

look similar but behave very differently in Next.js routing.

We'll connect:

params
searchParams
dynamic segments
generateStaticParams()
static rendering
dynamic rendering

and you'll finally have a clean mental model for:

`/products/123`

VS.

/products?id=123



That's the next piece.





Ahhh, yes — I see the exact confusion now. 😊 You're asking:

"If `/products` is cached and doesn't depend on the cookie, and I change a cookie in the browser, how does the server ever learn that the cookie changed?"

The answer is: **it learns it on the next request that actually reaches the server.** And if that request is satisfied entirely by a CDN cache, the origin server may **not need to know at all.**

Let's separate these cases.

1. Cookie changes in the browser

Suppose:

Browser

`theme = light`



Server Action changes it:

```
cookies().set("theme", "dark")
```



Response:

```
</> http
```

```
Set-Cookie: theme=dark
```



Browser now has:

Browser

theme = dark



At this point:

Server: ❌ hasn't received "theme=dark" as a new request

Browser: ✅ knows theme=dark



2. Then user requests `/products`

Browser makes:

```
</> http
```

```
GET /products
```

```
Cookie: theme=dark
```



Now there are two possibilities.

Case A — CDN handles it

Browser

| GET /products

| Cookie: theme=dark



CDN

| Cache HIT



Cached /products response



The request **doesn't reach Next.js origin**.

Therefore:

Next.js server

❌ doesn't learn about this request

❌ doesn't need to



The CDN has already answered the request.

And that's perfectly fine if `/products` doesn't care about `theme`.

3. So when does Next.js actually learn the new cookie?

When there is a request that reaches Next.js.

For example:

```
graph TD; Browser -- "Cookie: theme=dark" --> CDN; CDN -- "Cache MISS" --> Nextjs[Next.js]; Nextjs --> cookies[cookies()];
```

Now Next.js can see:

theme=dark

So:

```
graph TD; A[Cookie changed] --> B[Browser stores new cookie]; B --> C[Future HTTP request]; C --> D[Cookie automatically attached]; D --> E[If request reaches server]; E --> F[Server can read new cookie];
```

4. But here's the important realization 💡

You don't actually need to "tell the server that the cookie changed" as a separate operation.

The cookie itself is the state.

The browser effectively says:

"From now on, whenever I make an applicable request, I'll send `theme=dark`."

So imagine:

10:00

Browser:
theme=light



Server Action:

Set-Cookie: theme=dark



Browser:

theme=dark



Then:

10:05
GET /profile
Cookie: theme=dark



Server sees it.

There was no separate:

UPDATE_COOKIE /api/notify-server



required.

5. What if `/products` is completely cached?

Suppose:

`/products`



doesn't care about cookies.

CDN has:

`/products` → Product HTML



User requests it:

```
Browser
Cookie: theme=dark
  |
  ▼
CDN
  |
  ▼
Cached Product HTML
```



Next.js doesn't learn about the cookie.

And that's okay.

Because the page doesn't use it.

It's exactly like sending someone a letter that says:

```
"Here is my favorite color: dark"
```



but the person only needs to answer:

```
"What products are available?"
```



They don't need to process your favorite color. 😊

6. Now compare with `/profile`

Suppose `/profile` says:

```
</> TypeScript

const cookieStore = await cookies()
const theme = cookieStore.get("theme")?.value
```



Now the cookie matters.

Browser:

```
</> http

GET /profile
Cookie: theme=dark
```



If CDN cannot safely serve a generic cached response:

```
Browser
  ↓
CDN
  ↓
Next.js
  ↓
cookies()
  ↓
theme = dark
  ↓
render
```



Now Next.js **does** learn about it.

7. There's one more scenario: you WANT the server to know immediately

Suppose you have some client-side cookie that you change using JavaScript:

```
</> JavaScript
```

```
document.cookie = "theme=dark"
```



The server isn't immediately notified.

If you specifically need the server to know immediately, you make a request:

```
</> JavaScript
```

```
document.cookie = "theme=dark"
```

```
await fetch("/api/theme", {
  method: "POST"
})
```



Now:

```
Browser
|
| Cookie already changed
| Cookie: theme=dark
▼
POST /api/theme
▼
```



Next.js



Server knows theme=dark

But normally you don't need this extra request unless your application has a reason to synchronize server-side state.



This is the BIG distinction

There are actually **three events**:

Event 1 — Cookie changes

Server → Set-Cookie → Browser



or JavaScript changes it.

Event 2 — Browser makes a request

Browser → HTTP Request + Cookie → network



Event 3 — Somebody processes that request

Could be:

Browser



CDN



response



or

Browser



CDN



Next.js



If CDN answers it:

Next.js doesn't see it.



If CDN forwards it:


Next.js sees the cookie.



🔥 The sentence that should make this click

A cookie is not a live connection between the browser and server. It's client-side state that gets included in applicable HTTP requests.

So:



In **Request A**, Next.js never knows the cookie existed.

In **Request B**, Next.js sees the cookie.

And that's completely normal. 👍

The next thing that will make this whole topic click is understanding **what exactly a CDN cache key is and whether cookies are part of that key**—because that determines whether two users with different cookies can receive the same cached response.



ok

Perfect 😊 Let's lock this piece in.


🧠 Next: CDN Cache Key + Cookies

The question we'll answer is:


If two users request `/products` but have different cookies, how does the CDN know whether it can give them the same cached response?

We'll trace:

User A
Cookie: theme=dark



User B
Cookie: theme=light



Then we'll understand:

1. What a cache key actually is
2. Why `/products` normally maps to one cached response
3. How `Vary` works
4. Whether cookies can be part of cache variation
5. Why personalized pages generally shouldn't be blindly CDN-cached
6. How this differs from **Next.js Data Cache / Full Route Cache / Router Cache**
7. Finally, we'll return to our **Layer 1 static vs dynamic exercise**. 🚀



ok

Alright 😊 let's do it. This is one of those concepts that makes **CDN caching + cookies** suddenly click.

🌐 **CDN Cache Key — What actually identifies a cached response?**

Imagine the CDN receives:

```
</> http
GET /products
```



The CDN needs to answer:

"Do I already have a response for this request?"

It uses something called a **cache key**.

A simplified cache key might be:

```
https://example.com/products
```



So:

```
Request
GET /products
  ↓
Cache Key
example.com/products
  ↓
CDN Cache
  ↓
Cached Response
```



1. Two users request the same URL

Suppose:

User A

```
GET /products
Cookie: theme=dark
```



User B

GET /products
Cookie: theme=light




If the CDN's cache key is simply:

example.com/products



then both requests map to:



So the CDN could potentially return the **same cached response** to both.

That's perfectly fine **if the response doesn't depend on the cookie.**

2. Example where this is perfectly safe

Your `/products` page:

`</>` TypeScript



```
export default async function ProductsPage() {  
  const products = await getProducts()  
  
  return (  
    <ul>  
      {products.map(product => (  
        <li key={product.id}>{product.name}</li>  
      ))}  
    </ul>  
  )  
}
```

The page doesn't care about:

theme
session
language
user ID



So:

```
User A
Cookie: theme=dark
  |
  ▼
/products
  |
  ▼
  CDN
  |
  ▼
Cached products response
```



User B:

```
User B
Cookie: theme=light
  |
  ▼
/products
  |
  ▼
  CDN
  |
  ▼
SAME cached products response
```



That's fine.

Because:

```
Cookie —X—> Products HTML
```



The cookie doesn't influence the response.

3. Now let's make the cookie matter

Suppose:

```
</> TypeScript

export default async function ProductsPage() {
  const cookieStore = await cookies()

  const theme = cookieStore.get("theme")?.value
```



```
return (  
  <div className={theme}>  
    Products  
  </div>  
)  
}
```

Now:

Cookie
↓
theme
↓
HTML



User A:

theme=dark
↓
<div class="dark">



User B:

theme=light
↓
<div class="light">



So one cached response cannot represent both.

4. Here's the problem with a naive CDN

Suppose CDN already has:

Cache:

/products
↓
<div class="dark">



User B arrives:

```
</> http  
  
GET /products  
Cookie: theme=light
```



If CDN says:

"Oh, `/products` is cached! I'll return it."

then:

```
User B
theme=light

↓

CDN

↓

<div class="dark">
```

🔥 Wrong response.

That's a **cache correctness problem**.

5. So how does a CDN handle this?

There are several mechanisms in real systems.

One important HTTP mechanism is:

```
</> http
Vary
```

For example:

```
</> http
Vary: Accept-Language
```

This tells caches:

"The response varies based on this request header."

So conceptually:

```
/products + language=en
/products + language=fr
```

can be treated as different variants.

6. What about cookies?

Here's where things get more nuanced.

You *can* design caching behavior around cookies, but you generally don't want to casually make:

```
Cache Key =  
URL + entire Cookie header
```



because imagine:

```
Cookie:  
session=abc123;  
theme=dark;  
cart=92837;  
...
```



Now every user's session could produce a completely different cache entry.

You'd destroy much of the benefit of shared caching.

You could theoretically get:

```
/products + userA cookie  
/products + userB cookie  
/products + userC cookie  
/products + userD cookie  
...
```



That's basically **personalized caching**.

7. This is why personalized pages are tricky

Imagine:

```
<> TypeScript  
  
const session = cookies().get("session")  
  
return <h1>Welcome, {sessionUser.name}</h1>
```



User A:

Welcome Gopi



User B:

Welcome Rahul



You absolutely cannot have:

/products



Welcome Gopi



as one generic shared CDN response.

Otherwise:

User B



CDN



"Welcome Gopi"



😞 That's obviously terrible.

So systems generally avoid treating such personalized responses as ordinary shared public cache entries, or explicitly vary/cache them according to an appropriate strategy.

8. Now connect this to Next.js

This is why our earlier statement was:

cookies()



request-dependent



dynamic rendering



Under the **traditional Layer 1 model**, Next.js doesn't say:

"I'll just put this personalized page in the generic Full Route Cache."

Instead, the route is treated as request-dependent.

Conceptually:

```
Request
  ↓
Next.js
  ↓
cookies()
  ↓
render THIS request
  ↓
response
```



9. But here's a very important distinction 🚨

Don't think:

"If a request contains a cookie, CDN can never cache it."

That's too simplistic.

The correct idea is:

The presence of a cookie doesn't automatically make every response uncacheable. What matters is whether the response is safe to reuse for another request.

For example:

Cookie: theme=dark



but `/products` doesn't use theme.

The response could still potentially be shared.

Whereas:

Cookie: userId=123



and the response says:

Welcome Gopi



That's personalized.


Different situation.

10. Now our three cache layers become clearer

Let's put them side-by-side.

Layer	What it caches	Where
Data Cache	Fetches data	Next.js/server infrastructure
Full Route Cache	Rendered route result	Next.js/server infrastructure
CDN/HTTP cache	HTTP responses	CDN/edge/intermediary
Router Cache	RSC payload	Browser/client

So:



And importantly, **these aren't duplicate copies of exactly the same thing for the same purpose.**

11. One killer example 🔥

Imagine your page:

</> TypeScript



```
export default async function Page() {
  const cookieStore = await cookies()
  const theme = cookieStore.get("theme")?.value

  const response = await fetch(
    "https://api.example.com/products",
    {
      next: { revalidate: 60 }
    }
  )

  const products = await response.json()

  return (
    <div className={theme}>
      ...
    </div>
  )
}
```

Now there are **two different kinds of information**:

Cookie

theme=dark



Request-specific.

Products API data


iPhone
MacBook
AirPods




Potentially cacheable/reusable.

So conceptually:

Cookie





This is a really important insight:

One route can have request-specific information AND separately cacheable data dependencies.

And this becomes **hugely important when we get to Layer 2 / Cache Components**, because modern Next.js gives you more precise control over which parts are cached and which parts remain request-dependent.



Your mental model now

Don't think:

```

graph TD
    A[Cookie changed] --> B[Update CDN cache]
  
```



Instead:

```

graph TD
    A[Cookie changed] --> B[Browser stores new cookie]
    B --> C[Future request]
    C --> D[Cookie automatically attached]
    D --> E[CDN receives request]
    E --> F{Can cached response safely represent this request?}
    F -- YES --> G[CDN can serve it]
    F -- NO --> H[request may need origin/server]
    H --> I[Next.js]
    I --> J[cookies()]
  
```



That's the whole game. 🎯

And now we're ready for the **Layer 1 debugging exercise**. I'll give you a route and code, and you tell me what happens. I'll deliberately mix **dynamic URL segments**, **cookies**, `searchParams`, `fetch`, `no-store`, **and** `revalidate` so you have to distinguish all of them.



ChatGPT can make mistakes. Check important info.