

6.11.5 — RSC Payload + Router Cache + Navigation Caching

Alright 😊 This is where the pieces we've learned finally **lock together**.

We want to answer one question:

When I navigate with `<Link>`, where does the RSC Payload go, and when does Next.js actually need to ask the server again?

1. Start with the basic pipeline

Suppose we're here:

`/products`



and click:

```
<Link href="/products/123">  
  Product 123  
</Link>
```

The basic flow is:

```
graph TD; A[User click] --> B[Next.js Client Router]; B --> C[Router Cache?]; C -- HIT --> D[use cached RSC data]; C -- MISS --> E[request server]; E --> F[React Server Components]; F --> G[React Flight]; G --> H[RSC Payload]; H --> I[Browser]; I --> J[Router Cache]; J --> K[React]; K --> L[DOM update];
```

Diagram illustrating the basic flow:

- User click
- ↓
- Next.js Client Router
- ↓
- Router Cache?
 - HIT → use cached RSC data
 - MISS
- ↓
- request server
- ↓
- React Server Components
- ↓
- React Flight
- ↓
- RSC Payload
- ↓
- Browser
- ↓
- Router Cache
- ↓
- React
- ↓
- DOM update

That's the core.

But there are some important nuances. 📌

2. What exactly is Router Cache caching?

Remember:

Router Cache is a **client-side** cache maintained by the Next.js App Router.

Conceptually, think of it as:

Router Cache

/	→ RSC tree information
/products	→ RSC tree information
/products/123	→ RSC tree information
/about	→ RSC tree information

It's not:

- ✗ HTML cache
- ✗ database cache
- ✗ browser HTTP cache
- ✗ client JS bundle cache



It's specifically related to the App Router's **RSC/route-segment data**.

3. Why does Router Cache exist?

Imagine you visit:

/products



Then:

/products/123



Then:

/products/456



Then go back:

/products/123



Without any client-side route caching, you might need to repeatedly ask the server for the same RSC result.

Router Cache allows the client router to reuse previously received RSC information where applicable.

So:

/products/123
↓
RSC payload received
↓



```
Router Cache
  ↓
later navigation
  ↓
reuse if still valid
```

4. Cache HIT

Let's say you've already visited:

/products/123



and its RSC information is available in Router Cache.

You navigate there again.

Conceptually:

```
Click /products/123
  ↓
Router Cache lookup
  ↓
HIT ✓
  ↓
Use cached RSC information
  ↓
React
  ↓
DOM
```



No new server request is necessary for the cached portion.

This is one reason client-side navigation can be fast.

5. Cache MISS

Now suppose:

/products/999



hasn't been fetched or prefetched.

You click:

/products/999



Router Cache:

/products/999



↓
not found
↓
MISS ❌

Then:

Browser



↓
RSC request
↓
Server
↓
Server Components execute
↓
Flight
↓
RSC Payload
↓
Browser

The newly received information can then be placed into Router Cache.

6. Where does prefetching fit?

This is really important.

Suppose you have:

```
<Link href="/products/123">  
  Product 123  
</Link>
```

Next.js can prefetch routes in applicable circumstances.

So **before you click**, the client router may request information for:

/products/123



Conceptually:

```
User sees Link
  ↓
Next.js prefetch
  ↓
RSC request
  ↓
Server
  ↓
RSC Payload
  ↓
Router Cache
```



Then you click:

```
click
  ↓
Router Cache HIT
  ↓
navigation can use prefetched data
```



So the network request may happen **before the navigation itself**.

7. This explains why `<Link>` and `<a>` aren't equivalent

We've talked about this before, but now you can see *why*.

`<a>`

```
<a href="/products/123">
```

is a normal browser link.

It can cause:

```
new document navigation
```



`<Link>`

```
<Link href="/products/123">
```

integrates with Next.js's client router.

That enables things like:

```
client-side navigation
+
prefetching
+
Router Cache
+
RSC navigation
```



So:

```
<a>
  ↓
browser navigation

<Link>
  ↓
Next.js navigation system
```



8. But wait — what about the Data Cache?


🔥 This is where people often mix up the layers.


Imagine `/products/123` needs:

```
const product = await fetch(
  `https://api.example.com/products/123`
);
```

There can be **multiple caching layers** involved.

Conceptually:





These caches have **different jobs**.

9. Data Cache vs Router Cache

Data Cache

Lives on the server side.

It can cache results of data fetching.



```
graph TD; A[Server] --> B[fetch(...)] --> C[Data Cache];
```

Its question is:

"Can I reuse this data without fetching it again?"

Router Cache

Lives on the client side.

Its question is:

"Can I reuse the RSC route/segment information I've already received?"

So:



```
graph TD; A[Data Cache] --> B[→ caches data];
```

Router Cache

→ caches client-side RSC route information

Very different things.

10. Example: Router Cache HIT + Data Cache HIT

Imagine:

/products/123



is already in Router Cache.

You navigate there.

Browser

↓

Router Cache HIT

↓

RSC information reused

↓

React

↓

DOM



The server may not even be contacted.

Therefore the Data Cache isn't involved in that particular navigation.

11. Router Cache MISS + Data Cache HIT

Now imagine:

/products/456



isn't in Router Cache.

So:

Browser

↓

Router Cache MISS

↓

RSC request



↓
Server

The server renders the route.

During rendering:

fetch(product/456)
↓
Data Cache
↓
HIT



So the server doesn't necessarily have to hit the external API.

Then:

Data
↓
Server Component render
↓
Flight
↓
RSC Payload
↓
Browser
↓
Router Cache



This is a really useful distinction.

12. Router Cache MISS + Data Cache MISS

Worst case:

Browser
↓
Router Cache MISS
↓
Server request
↓
Data Cache MISS
↓
API/database
↓
data
↓



```
RSC render
↓
Flight
↓
RSC Payload
↓
Browser
↓
Router Cache
```

So potentially:

```
Router Cache
↓
MISS

Data Cache
↓
MISS
```




Both layers miss.

13. What about Full Route Cache?

And now we have **three caching concepts** you've already been studying:

CACHE LAYERS



Their jobs differ.

Data Cache

"What data can I reuse?"



Full Route Cache

"What rendered route output can I reuse?"



Router Cache

"What RSC route/segment information can the client reuse?"



14. The BIG picture


Let's say:


/products/123



is requested.

Potential flow:





Now you're seeing how all the caching concepts fit together. 🔥

15. One important nuance about Full Route Cache

Don't think:

Router Cache MISS



Full Route Cache MUST be checked



as an absolute mechanical rule.

The actual path depends on whether the route/rendering is cacheable and how the current Next.js version's caching model applies.

For example, a dynamically rendered route may not have reusable Full Route Cache output, while its underlying data may still be cached.

So think in terms of **independent caching opportunities**, not one giant mandatory cache pipeline.

16. Navigation isn't always "fetch RSC every time"

This is the key takeaway.

A naive mental model is:

```
<Link>  
↓  
always fetch RSC
```



Better:

```
<Link>  
↓  
client router  
↓  
Can existing/prefetched RSC information be reused?  
  |  
  ├── YES → use Router Cache  
  |  
  └── NO → request server
```



That's why we care about Router Cache.

17. What happens when data changes?

Now imagine you're on:

```
/products/123
```



and something changes on the server.

Your Router Cache could still contain the previous RSC result.

That's why **cache invalidation / refresh** becomes important.

And this leads directly into our next topics:

```
mutation  
↓  
server data changes  
↓  
cached RSC result may be stale  
↓  
revalidation / refresh  
↓  
new RSC payload  
↓  
Router Cache updated
```



Which is exactly why `router.refresh()` deserves its own section.

18. One thing I DON'T want you to memorize

Don't memorize:

Router Cache = X seconds



as a universal rule.

Router Cache behavior depends on the type of navigation, prefetched/visited segments, route behavior, and current Next.js caching semantics.

Likewise, don't assume:

"cache" = one single cache.



Next.js has several layers with different lifetimes and invalidation behavior.

Interview answer

If asked:


"What is Router Cache and how does it relate to RSC?"


You can say:

"Router Cache is a client-side cache used by the Next.js App Router to store RSC route/segment information. During client-side navigation, Next.js can reuse that cached RSC information instead of requesting the server again. If the required information isn't available, the client requests a new RSC payload, which can then be stored in the Router Cache. This is separate from server-side Data Cache and Full Route Cache, which cache data and rendered route output respectively."

That's a strong answer. 

One diagram to remember





✅ 6.11.5 complete.

We have **two pieces left in the 6.11.x series**:

- **6.11.6 — RSC + Streaming + Suspense + partial rendering**
- **6.11.7 — Complete 6.11 recap + interview questions**

Then 🎉 **6.11.x is DONE**, and per our plan, **6.12 starts in a brand-new chat**.



so in interview do i have to explain modern caching system or data cache and full route cache system when asked

Yes — **for a modern Next.js interview, you should explain the current caching model**, but you **should also know the older Data Cache + Full Route Cache model** because interviewers may still use that terminology.

The trick is **don't dump the entire caching architecture unless they ask for it.** 😊

🎯 What I'd recommend for your interviews

Since you're targeting a **mid-level Frontend / Next.js role**, structure your answer in layers.

If they simply ask:

"Explain caching in Next.js."

Start with the **modern model**:

Next.js caching



- |
- ├ Request/Data caching
- ├ Client Router Cache
- ├ rendered output / route caching
- └ cache invalidation & revalidation

Then explain the relevant layers and how they interact.

If they specifically ask about Data Cache / Full Route Cache

Then absolutely explain the **Data Cache + Full Route Cache terminology**.

For example:

"Historically, Next.js documentation commonly described caching using Data Cache, Full Route Cache, and Router Cache. In newer Next.js versions, the caching model has evolved, particularly with the newer Cache Components model, so I distinguish the current model from the older terminology."

Then explain whichever model the interviewer is asking about.



Why you should know BOTH

Because interviews are messy. 😂

You might get:

Interviewer A

"What is Data Cache?"

You need to know it.

Interviewer B

"How does caching work in the latest Next.js?"


You need the **modern model**.

Interviewer C

"What's the difference between Full Route Cache and Router Cache?"

You need the old terminology and how it relates to current behavior.

So your preparation should be:



★ For YOUR preparation specifically

I would **not throw away** what we learned about Data Cache and Full Route Cache.

You've already built an important mental model:

Data Cache
→ cached data

Full Route Cache
→ cached rendered route output

Router Cache
→ client-side RSC route/segment information

That is useful historical/current terminology and is still extremely relevant for understanding Next.js.

But we should now add:

Modern Next.js

↓

Cache Components / newer caching semantics

↓

more granular caching

↓

"use cache"

↓

cache components

↓

PPR-style behavior



rather than treating the old three-cache diagram as **the complete modern architecture**.

What I'd say in an interview

If asked:

"How does caching work in Next.js?"

A concise answer could be:

"Next.js has caching at multiple levels. The important distinction is between cached data or component results on the server and the client-side Router Cache, which stores RSC information used for navigation. The exact server-side caching model depends on the Next.js version and whether you're using the newer Cache Components model. I also understand the older Data Cache and Full Route Cache terminology because it's still common in existing applications and interview discussions."

Then if they say:

"Explain the Data Cache and Full Route Cache."

You go deeper.

If they say:

"Explain the latest caching architecture."

You switch to the modern model.



One thing I DON'T want you to do

Don't answer every caching question with a giant:

Data Cache

↓

Full Route Cache

↓

Router Cache

↓

CDN

↓

Request Memoization

↓

Cache Components

↓

PPR

↓

RSC

↓

Flight

↓

Suspense

↓

...



You'll lose the interviewer before reaching the interesting part.

Instead:

Answer the question first → then expand if they probe.

And this is exactly why our roadmap is useful

We're doing:

6.11 RSC / Flight

6.12 Serialization / References

6.13 Boundaries

6.14 refresh vs navigation vs reload

6.15 Router Cache + RSC + navigation

6.16 DevTools

6.17 Complete mental model + interview questions



At **6.17**, I'll explicitly give you:

"What to say in an interview" vs "what you should understand internally."

Those are **not the same amount of information.** 😊

For example:

INTERNAL UNDERSTANDING

↓

10 concepts

↓

INTERVIEW ANSWER

↓

2–5 concepts



That's the goal — **deep understanding without sounding like you're reading the Next.js source code aloud.** 🚀



😊 Perfect. Next we'll do **6.11.7 — the complete RSC + React Flight recap and interview questions.**

After that, **6.11.x is officially done 🏁**, and we'll start **6.12 in a new chat.**




sure go ahead


🏁 6.11.7 — Complete RSC Payload + React Flight Recap

Alright 😊 this is the **final 6.11.x lesson**. After this, we're done with RSC/Flight fundamentals and **6.12 will start in a fresh chat**, as planned.

Let's consolidate everything into one mental model first.

1. The entire RSC story in one picture





The biggest thing to remember:

Server Components don't need to be shipped to the browser as JavaScript. Their rendered result is represented in the RSC payload.

Client Components are different because their JavaScript needs to be available in the browser for interactivity.

2. Flight vs RSC Payload

This was one of your original questions.

React Flight

Think:

The protocol/mechanism used by React to transport Server Component information.

RSC Payload

Think:

The actual serialized data produced using that mechanism for a particular render/navigation.

So:

```
Flight
↓
protocol / mechanism

RSC Payload
↓
actual Flight data
```



Don't say:

"Flight is the payload."



Say:

"The RSC payload is transmitted using React Flight."



3. What does "serialized representation" mean?

Suppose the server has:

```
</> TypeScript

<Product
  name="Dosa"
  price={80}
/>
```



React has an internal representation of this component tree.

That internal representation can't simply be sent directly over HTTP.

So React converts the relevant information into a **transferable Flight representation**.

```
React tree
↓
serialization
↓
Flight representation
↓
network
```



↓
client React

So:

Serialized representation = a network-transferable representation of the Server Component tree, supported values, and relevant references.

And importantly:

Flight serialization
≠
JSON.stringify()



Flight has React-specific semantics.

4. Client References

Suppose:

```
</> TypeScript
'use client';

export default function AddButton() {
  return <button>Add</button>;
}
```



The Server Component tree can contain:

```
</> TypeScript
<AddButton />
```



The server doesn't need to send the component's source code inside the RSC payload.

Instead, Flight can represent a **Client Reference**.

Conceptually:

```
Server
|
| "Client Component X goes here"
↓
Client Reference
|
↓
```



```
Browser
|
↓
client JS module
|
↓
AddButton
```

So:

```
Client Reference
  ≠
Client Component source code
```




It's a reference to the client-side module/export.

5. Client JS vs RSC Payload

Don't mix these up.

BROWSER



The two work together.

RSC Payload

Answers roughly:

"What Server Component result/tree should React use?"

Client JS

Provides:

"Here is the executable code for Client Components."

6. Server Functions / Server References

Now reverse the direction.

```
</> TypeScript


'use server';

export async function addToCart(productId) {
  await db.cart.add(productId);
}
```

The browser doesn't receive the implementation.

Instead, it can receive/use a **Server Reference**.

Conceptually:



And remember the important distinction:

```
function that happens to execute on server
    ≠
Server Function
```

A Server Function has explicit Server Function semantics, typically via:

```
</> TypeScript

'use server';
```

7. Ordinary function vs Server Function

Ordinary server-side function

</> TypeScript



```
function getProducts() {  
  return db.products.findMany();  
}
```

It may execute on the server.

But it isn't automatically remotely invocable.

server-side function

↓

runs on server

↓

ordinary function



Server Function

</> TypeScript



```
'use server';  
  
export async function addToCart() {  
  ...  
}
```

Server Function

↓

Server Reference

↓

can be invoked through supported server-action mechanisms



8. Serialization boundary

Suppose:

</> TypeScript



```
export default function Page() {  
  const product = {  
    id: 1,  
  }  
}
```

```

    name: "Dosa"
  };

  return <ProductCard product={product} />;
}

```

and:

```

</> TypeScript

'use client';

function ProductCard({ product }) {
  ...
}

```

The `product` data crosses:

```

Server
  |
  | serializable value
  ↓
Client boundary
  |
  ↓
Client Component

```

But an ordinary server function cannot simply be passed the same way:

```

</> TypeScript

<ProductCard
  onSave={someServerFunction}
/>

```

unless that function has the appropriate **Server Function/reference semantics**.

9. 'use client' vs 'use server'

Keep this distinction very clear.

'use client'

```

'use client'
  ↓
Client Component boundary
  ↓

```

```
client module graph
```

```
↓
```

```
browser JS
```

```
'use server'
```

```
'use server'
```

```
↓
```

```
Server Function semantics
```

```
↓
```

```
Server Reference
```

```
↓
```

```
remote invocation
```



And:

`'use client'` does **not** simply mean "this component only renders in the browser."

That's a common oversimplification.

10. RSC navigation

Now suppose:

```
/products
```



and:

```
</> TypeScript
```

```
<Link href="/products/123">
```



is clicked.

The important flow is:

```
<Link>
```

```
↓
```

```
Next.js Client Router
```

```
↓
```

```
RSC request
```

```
↓
```

```
Server Components execute/render
```

```
↓
```

```
React Flight
```

```
↓
```



```
RSC Payload
↓
Browser
↓
React reconciliation
↓
DOM update
```

Notice:

No full HTML document replacement is required for this client-side navigation.

11. DOM can change without replacing the document

This was another question you asked earlier.

Suppose:

Before

```
<main>
  <h1>Products</h1>
  <ProductList />
</main>
```



After navigation

```
<main>
  <h1>Product 123</h1>
  <ProductDetails />
</main>
```



The DOM can change substantially.

But:

```
DOM changed
  ≠
whole HTML document replaced
```




React can update the existing DOM based on the new RSC result.

That's a **very important App Router concept**.

12. Router Cache

The RSC payload received during navigation can be used by the App Router and stored in its client-side Router Cache.

Conceptually:



```
graph TD; Server --> RSC_Payload[RSC Payload]; RSC_Payload --> Router_Cache[Router Cache]; Router_Cache --> React; React --> DOM
```


Server
↓
RSC Payload
↓
Router Cache
↓
React
↓
DOM



Router Cache is:

Client-side cached RSC route/segment information used by the App Router.

Don't confuse it with:




Data Cache
Full Route Cache
browser HTTP cache
JS bundle cache



They're different things.

13. Cache HIT vs MISS

HIT



```
graph TD; Navigation --> Router_Cache[Router Cache]; Router_Cache --> HIT[HIT]; HIT --> Reuse[reuse cached RSC information]; Reuse --> React; React --> DOM
```

Navigation
↓
Router Cache
↓
HIT 
↓
reuse cached RSC information
↓
React
↓
DOM



MISS



```
graph TD; A[Navigation] --> B[Router Cache]; B --> C[MISS ❌]; C --> D[RSC request]; D --> E[Server]; E --> F[Flight]; F --> G[RSC Payload]; G --> H[Router Cache]; H --> I[React];
```

Navigation
↓
Router Cache
↓
MISS ❌
↓
RSC request
↓
Server
↓
Flight
↓
RSC Payload
↓
Router Cache
↓
React




This is the core navigation-caching model.

14. Prefetching

A `<Link>` can also be prefetched in applicable situations.

Conceptually:




```
graph TD; A["<Link href='/products/123'>"] --> B[prefetch]; B --> C[RSC Payload]; C --> D[Router Cache];
```

`<Link href="/products/123">`
↓
prefetch
↓
RSC Payload
↓
Router Cache



Then:



```
graph TD; A[User clicks] --> B[cached RSC information]; B --> C[React];
```

User clicks
↓
cached RSC information
↓
React



↓
UI

So a request can happen **before the user actually navigates**.

15. Streaming + Suspense

Now connect the last part.

Suppose:

Header → fast
Products → fast
Reviews → slow



With:

```
</> TypeScript  
  
<Suspense fallback={<ReviewsSkeleton />}>  
  <Reviews />  
</Suspense>
```



React can conceptually produce:

Header
↓
Products
↓
ReviewsSkeleton



then later:

Reviews
↓
replace fallback



Flight allows the RSC result to be **streamed progressively**.

So:

Suspense
↓
defines boundary

Streaming




↓
delivers results progressively

Flight
↓
transports RSC representation

These aren't interchangeable concepts.


16. The complete architecture 🔥

Here's your final 6.11 mental model:



↓
DOM

For server mutations:



🎯 17. Interview Questions

Now let's test whether you've actually got it rather than just nodding along. 😂

Q1. What is React Flight?

Answer:

React Flight is the protocol/mechanism React uses to communicate the Server Component tree between server and client.

Q2. What is the RSC Payload?

The RSC Payload is the serialized Flight data representing the Server Component result/tree, supported values, and relevant references for a particular render or navigation.

Q3. Is RSC Payload HTML?

No.

HTML

→ document/UI representation



RSC Payload

→ React Server Component representation

Q4. Is RSC Payload JSON?

Not simply.

Flight has its own serialization format and semantics beyond ordinary JSON serialization.

Q5. Does the browser receive Server Component source code?

No.

The Server Component executes on the server, and its result is represented in the RSC payload.

Q6. Does the browser receive Client Component JavaScript?

Yes.

Client Components need client-side JavaScript for their interactivity.

Q7. What is a Client Reference?

A reference in the RSC system to a Client Component/module that the browser can resolve to its client-side code.

Q8. What is a Server Reference?

A reference to a Server Function that allows the client to request its invocation without receiving the function implementation.

Q9. Can any function become a Server Function just because it runs on the server?

No.

```
runs on server
  ≠
Server Function
```



Server Function semantics are explicitly established, typically with `'use server'`.

Q10. During `<Link>` navigation, does Next.js normally download a complete new HTML document?

No.

For client-side App Router navigation, Next.js can request the RSC payload and use it to update the existing React tree and DOM.

Q11. Can the DOM structure change during client navigation?

Absolutely.

```
existing DOM
  ↓
React receives new RSC result
  ↓
reconciliation
  ↓
new DOM structure
```



But the entire browser document doesn't have to be replaced.

Q12. What does Router Cache store?

Client-side RSC route/segment information used by the App Router for navigation and reuse.

18. Your 30-second interview answer

If they ask:

"Explain React Server Components and RSC Payload in Next.js."

You can say:

"Next.js uses React Server Components to execute server-side component logic. React's Flight protocol provides the mechanism for representing and transporting the Server Component result to the client as an RSC payload. The payload contains serialized component-tree information, supported values, and references to Client Components. The client combines that information with the Client Component JavaScript and React uses it to construct or reconcile the UI. During App Router navigation, the RSC payload can be fetched and stored in the client Router Cache, allowing the existing application tree to be updated without a full document reload."

That's a **very solid mid-level answer**. 🎯

🏁 6.11.x — COMPLETE

You now have:

6.11 RSC Payload + React Flight



- |
- |— Flight
- |— RSC Payload
- |— serialization
- |— Client References
- |— Server References
- |— Server Functions
- |— RSC navigation
- |— Router Cache relationship
- |— prefetching
- |— streaming
- |— Suspense

🏁 DONE

And now we **STOP** this chat. 🙅

As planned, **don't start 6.12 here**.

Open a **new chat** and say:

"Continue Next.js 6.12"

Then we'll begin the next major piece:

6.12 — Serialization, Client References & Server References

We'll go deeper there, without mixing it back into 6.11. 😊



server function vs server side function invocation and diff

Yes — this distinction is **super important**, because "server-side function" and "Server Function" sound almost identical. 😊

1. Server-side function

A **server-side function** simply means:

A normal function whose code executes on the server.

Example:

`</> TypeScript`

```
async function getProducts() {  
  const products = await db.products.findMany();  
  return products;  
}  
  
export default async function Page() {  
  const products = await getProducts();  
  
  return <ProductList products={products} />;  
}
```

Here:

```
Page()  
  ↓  
getProducts()  
  ↓  
Database
```

`getProducts()` runs on the server.

But it's just a **normal function call**:

```
Page()  
  |  
  | normal JS call  
  ↓  
getProducts()
```



There is **no network request** between **Page** and **getProducts**.

The function isn't remotely callable by the browser.

2. Server Function

A **Server Function** is different.

It is explicitly given Server Function semantics, typically with:

```
</> TypeScript  
  
'use server';  
  
export async function addToCart(productId) {  
  await db.cart.add(productId);  
}
```



Now the function can be exposed through a **Server Reference**.

Conceptually:

```
Browser  
  |  
  | invoke Server Reference  
  ↓  
NETWORK REQUEST  
  ↓  
Server  
  ↓  
addToCart(123)
```



So there's a fundamental difference:

	Server-side function	Server Function
Runs on server	✓	✓

	Server-side function	Server Function
Normal JS function	✓	Also a function, but special semantics
'use server'	✗	✓
Callable remotely from client	✗	✓ through supported mechanisms
Server Reference	✗	✓
Network involved when called from server code	✗	Not necessarily
Designed for client → server invocation	✗	✓

3. "Server-side function invocation" means something different

Suppose:

```
</> TypeScript

async function getUser() {
  return db.user.find();
}

async function Page() {
  const user = await getUser();
}
```

The invocation is:

```
Page()
|
| function call
↓
getUser()
```

Everything is happening inside the **same server execution environment**.


There's no:



```
graph TD; browser --> network; network --> server;
```

browser
↓
network
↓
server

It's simply:



```
graph TD; Server --> Page; Server --> DB; Page --> getUser;
```

Server
|
├── Page()
| └── getUser()
└── DB

4. Server Function invocation is different

Now:



```
</> TypeScript

'use server';

export async function addToCart(productId) {
  await db.cart.add(productId);
}
```

And the browser wants to invoke it.

The browser doesn't have:




```
</> JavaScript

addToCart() // implementation
```

Instead it has a reference.

Conceptually:



```
graph TD; Client -- "Server Reference: XYZ  
arguments: 123" --> Network;
```

Client
|
| Server Reference: XYZ
| arguments: 123
↓
Network

```
↓  
↓  
Server  
|  
| resolve XYZ  
↓  
addToCart(123)
```

That's a **remote invocation**.

5. Here's the easiest way to remember it 🧠

Ask:

"Who is calling the function?"

If it's:

```
Server code  
↓  
Server function
```



that's just a normal function invocation, even if the function is a Server Function.

No special network trip is needed.

But if:

```
Browser  
↓  
Server Function
```



then the browser can't directly execute it.

It invokes the **Server Reference**, which causes communication with the server.

6. This is the subtle point

A Server Function doesn't mean:

"Every time this function is called, a network request happens."



It means:

The function has semantics that allow it to be referenced and invoked from the client.

So:

```
</> TypeScript

'use server';

export async function addToCart(id) {
  ...
}
```

If server code does:

```
</> TypeScript

await addToCart(123);
```

that's simply:

```
Server
  ↓
normal function invocation
  ↓
addToCart()
```

But when the **client** invokes it through its **Server Reference**, then:

```
Client
  ↓
Server Reference
  ↓
network
  ↓
Server Function
```

7. One more example

Normal server-side helper

```
</> TypeScript

async function calculatePrice(productId) {
  const product = await db.products.find(productId);
```

```
    return product.price * 1.18;
  }
```

Used by:

```
</> TypeScript   
  
export default async function Page() {  
  const price = await calculatePrice(123);  
  
  return <div>{price}</div>;  
}
```

Flow:

```
Page()  
  ↓  
calculatePrice()  
  ↓  
DB 
```

No client involvement.

Server Function

```
</> TypeScript   
  
'use server';  
  
export async function purchase(productId) {  
  await db.orders.create({ productId });  
}
```

Client:

```
</> TypeScript   
  
'use client';  
  
import { purchase } from './actions';  
  
export function BuyButton({ productId }) {  
  return (  
    <button onClick={() => purchase(productId)}>  
      Buy  
    </button>  
  )  
}
```

```
);  
}
```

Conceptually:

```
CLICK  
↓  
purchase(123)  
↓  
Server Reference  
↓  
NETWORK  
↓  
Server  
↓  
actual purchase(123)  
↓  
DB
```



The interview distinction

If they ask:

"What's the difference between a server-side function and a Server Function?"

Say:

"A server-side function is simply a normal function that executes in the server environment. It can be called by other server code through an ordinary JavaScript function call. A Server Function has explicit Server Function semantics, typically through `'use server'`, which allows it to be represented by a Server Reference and invoked from client code through the server-action mechanism. The function implementation remains on the server."

And the one-liner:

```
Server-side function  
= where it executes
```

```
Server Function  
= special semantics for server invocation from the client
```



 That distinction is exactly what I want you to carry into 6.12.



ChatGPT can make mistakes. Check important info.