

# 2024mt12082-gopinath M .

## 2024mt12082

 Final

 S2-25 DISSERTATION - Pilani 3

 Birla Institute of Technology and Science Pilani WILP Division

### Document Details

Submission ID

trn:oid::1:3567453218

Submission Date

May 12, 2026, 11:00 AM GMT+5:30

Download Date

May 12, 2026, 11:05 AM GMT+5:30

File Name

Final\_Report\_Predictive\_ABS.pdf

File Size

1.8 MB

21 Pages

2,441 Words

21,968 Characters

# 6% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

## Filtered from the Report

- Bibliography
- Quoted Text

## Match Groups

-  **12 Not Cited or Quoted 6%**  
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**  
Matches that are still very similar to source material
-  **0 Missing Citation 0%**  
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**  
Matches with in-text citation present, but no quotation marks

## Top Sources

- 4%  Internet sources
- 4%  Publications
- 4%  Submitted works (Student Papers)

## Match Groups

- 12 Not Cited or Quoted 6%**  
Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%**  
Matches that are still very similar to source material
- 0 Missing Citation 0%**  
Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%**  
Matches with in-text citation present, but no quotation marks

## Top Sources

- 4% Internet sources
- 4% Publications
- 4% Submitted works (Student Papers)

## Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

|    |                                                                                    |  |     |
|----|------------------------------------------------------------------------------------|--|-----|
| 1  | Student papers                                                                     |  |     |
|    | University of Hertfordshire                                                        |  | 1%  |
| 2  | Publication                                                                        |  |     |
|    | Augusto César de Camargo Neto. "Evaluating the robustness of AI-based vocal bi...  |  | <1% |
| 3  | Publication                                                                        |  |     |
|    | Ioan Bondrea, Lucian Eugen Rosca. "Statisticaly Analysis For In-Depth Understan... |  | <1% |
| 4  | Student papers                                                                     |  |     |
|    | University of Wales, Lampeter                                                      |  | <1% |
| 5  | Publication                                                                        |  |     |
|    | Venus Dimri, Rajeev Chandra Ramola, Shrey Dandriyal, Prateeksha, Gunjan Panw...    |  | <1% |
| 6  | Student papers                                                                     |  |     |
|    | Southampton Solent University                                                      |  | <1% |
| 7  | Internet                                                                           |  |     |
|    | vijayshinva.github.io                                                              |  | <1% |
| 8  | Internet                                                                           |  |     |
|    | commercialvehicle.in                                                               |  | <1% |
| 9  | Internet                                                                           |  |     |
|    | ia801407.us.archive.org                                                            |  | <1% |
| 10 | Internet                                                                           |  |     |
|    | www.see.asso.fr                                                                    |  | <1% |

11

Publication

Raminder Kaur, Saif Eqbal. "Adventure Comics and Youth Cultures in India", Routl...

&lt;1%

**A REPORT  
ON  
PREDICTIVE ABS THROUGH PREDICTIVE WHEEL LOCK AND PRESSURE MODULATION**

**BY**

**GOPINATH MADHESWARAN**

**ID.No.:2024MT12082**

**AT**



**BIRLA INSTITUTE OF TECHNOLOGY & SCIENCE PILANI (RAJASTHAN)**

**AUMOVIO INDIA PVT LTD, Bangalore**

11

7



**BIRLA INSTITUTE OF TECHNOLOGY & SCIENCE, PILANI**

**(May, 2026)**

**A REPORT**

**ON**

**PREDICTIVE ABS THROUGH PREDICTIVE WHEEL LOCK AND PRESSURE MODULATION**

**S2-25\_SSZG628T: Dissertation**

**BY**

**GOPINATH MADHESWARAN**

**ID.No. : 2024MT12082**

**M.TECH**

**Prepared in fulfilment of the**

**WILP Dissertation**

**AT**

**AUMOVIO INDIA PVT LTD, Bangalore**



## ACKNOWLEDGEMENTS

I would like to express my sincere gratitude to my supervisor and mentors at AUMOVIO India Pvt Ltd for their continuous guidance, technical support, and encouragement throughout this dissertation work.

I would also like to thank Professor Eht E Sham and the faculty members of BITS Pilani WILP Division for providing academic direction and valuable suggestions during the course of this project.

I extend my appreciation to my colleagues and Test team members who supported me during discussions related to braking systems, signal processing, and automotive software implementation.



Finally, I would like to thank my family for their motivation and support throughout the completion of this degree.

**BIRLA INSTITUTE OF TECHNOLOGY & SCIENCE, PILANI**  
(May, 2026)

**BIRLA INSTITUTE OF TECHNOLOGY AND SCIENCE PILANI**  
(RAJASTHAN)  
WILP Division

Organization: AV MOVIO India Pvt Ltd Location: BENGALURU  
Duration: 5 MONTHS Date of Start: 20TH DECEMBER 2025  
Date of Submission: 11-05-2026

**Title of the Project:** PREDICTIVE ABS THROUGH PREDICTIVE WHEEL LOCK AND PRESSURE MODULATION

**ID No./Name of the student:** 2024MT12082, GOPINATH MADHESWARAN


**Name (s) and Designation (s) of your supervisor:** VAIDYANATHAN AG, CHIEF MANAGER  
**and Additional Examiner:** BALAKUMAR VENGUDUSAMY, CHIEF ARCHITECT

**Name of the Faculty mentor:** - Eht E SHAM

**Key Words:** Predictive ABS, Wheel Slip, Approximate Entropy, Kurtosis, Signal Processing, Brake Pressure Modulation, Automotive Safety

**Project Areas:** Automotive Embedded Systems, Vehicle Dynamics, Signal Processing

**Abstract:** This dissertation presents a predictive Anti-lock Braking System (ABS) using wheel speed signal analysis for early wheel lock detection. The proposed method utilizes entropy, kurtosis, and frequency-based features to predict unstable wheel behaviour before conventional ABS activation. The system is validated using braking data analysis and demonstrates smoother brake pressure modulation and improved slip regulation.

  
Signature of Student

Date :- 11-05-2026

Thank You Team EVM

BITS Pilani WILP

  
Signature of your Supervisor

Date :- 11-05-2026



2

## Table of Contents

|                                                |          |
|------------------------------------------------|----------|
| <b>1. INTRODUCTION</b>                         | <b>1</b> |
| 1.1. Background                                | 1        |
| 1.2. Problem Statement                         | 1        |
| 1.3. Objectives                                | 1        |
| 1.4. Scope of Work                             | 2        |
| <b>2. SYSTEM OVERVIEW AND ARCHITECTURE</b>     | <b>2</b> |
| 2.1. System Overview                           | 2        |
| 2.2. Functional Architecture                   | 2        |
| 2.3. Wheel Speed Data Acquisition              | 4        |
| 2.4. Signal Conditioning                       | 4        |
| <b>3. MATHEMATICAL BACKGROUND</b>              | <b>4</b> |
| 3.1. Slip Ratio Calculation                    | 4        |
| 3.2. Tire-Road Friction Characteristics        | 5        |
| 3.3. Approximate Entropy                       | 5        |
| 3.4. Statistical Kurtosis                      | 5        |
| 3.5. Dominant Frequency Estimation             | 6        |
| <b>4. METHODOLOGY AND ALGORITHM DESIGN</b>     | <b>6</b> |
| 4.1. Overall Methodology                       | 6        |
| 4.2. Sliding Window Analysis                   | 7        |
| 4.3. Feature Extraction                        | 7        |
| 4.3.1. Entropy Analysis                        | 7        |
| 4.3.2. Kurtosis Analysis                       | 7        |
| 4.3.3. Frequency Analysis                      | 7        |
| 4.3.4. Slip Dynamics                           | 7        |
| 4.4. Weighted Lockup Probability               | 7        |
| 4.5. Predictive Warning Logic                  | 8        |
| <b>5. PREDICTIVE LOCKUP DETECTION STRATEGY</b> | <b>8</b> |
| 5.1. Traditional ABS Behavior                  | 8        |
| 5.2. Predictive ABS Behavior                   | 8        |
| 5.3. Lockup Probability Estimation             | 9        |
| 5.4. State-Based Control Strategy              | 9        |

9

|              |                                                          |           |
|--------------|----------------------------------------------------------|-----------|
| <b>6.</b>    | <b>VALIDATION RESULTS.....</b>                           | <b>9</b>  |
| <b>6.1.</b>  | <b>Simulation Overview .....</b>                         | <b>9</b>  |
| <b>6.2.</b>  | <b>Slip Regulation Performance.....</b>                  | <b>9</b>  |
| <b>6.3.</b>  | <b>Early Detection Capability .....</b>                  | <b>9</b>  |
| <b>6.4.</b>  | <b>Brake Pressure Modulation.....</b>                    | <b>9</b>  |
| <b>6.5.</b>  | <b>Stopping Distance Improvement .....</b>               | <b>10</b> |
| <b>6.6.</b>  | <b>Performance Metrics.....</b>                          | <b>10</b> |
| <b>6.7.</b>  | <b>Validation Scenarios.....</b>                         | <b>11</b> |
| <b>6.8.</b>  | <b>Result – Traditional vs Predictive ABS .....</b>      | <b>11</b> |
| <b>7.</b>    | <b>COMPUTATIONAL ANALYSIS AND ECU FEASIBILITY.....</b>   | <b>12</b> |
| <b>7.1.</b>  | <b>Real-Time Constraints .....</b>                       | <b>12</b> |
| <b>7.2.</b>  | <b>Computational Requirements.....</b>                   | <b>12</b> |
| <b>7.3.</b>  | <b>Memory Usage .....</b>                                | <b>12</b> |
| <b>7.4.</b>  | <b>ECU Feasibility .....</b>                             | <b>12</b> |
| <b>8.</b>    | <b>ADVANTAGES AND LIMITATIONS .....</b>                  | <b>12</b> |
| <b>8.1.</b>  | <b>Advantages .....</b>                                  | <b>12</b> |
| <b>8.2.</b>  | <b>Limitations .....</b>                                 | <b>13</b> |
| <b>9.</b>    | <b>FUTURE SCOPE.....</b>                                 | <b>13</b> |
| <b>10.</b>   | <b>CONCLUSION .....</b>                                  | <b>13</b> |
| <b>11.</b>   | <b>REFERENCES.....</b>                                   | <b>14</b> |
| <b>12.</b>   | <b>GLOSSARY .....</b>                                    | <b>14</b> |
| <b>13.</b>   | <b>APPENDICES.....</b>                                   | <b>15</b> |
| <b>13.1.</b> | <b>Appendix A – Major Technical Specifications .....</b> | <b>15</b> |
| <b>13.2.</b> | <b>Appendix B – Validation Parameters.....</b>           | <b>15</b> |
| <b>13.3.</b> | <b>Appendix C – Software Modules .....</b>               | <b>15</b> |

5

6

# 1. INTRODUCTION

## 1.1. Background

Road safety systems have evolved significantly in modern vehicles to improve braking efficiency and vehicle stability. Among these systems, the Anti-lock Braking System (ABS) plays a major role in preventing wheel lockup during sudden braking conditions.

Conventional ABS systems operate using reactive logic. The brake controller continuously monitors wheel slip and reduces hydraulic pressure when excessive slip is detected. Although this method is reliable and widely used in the automotive industry, it reacts only after unstable wheel behavior has already started.

This reactive behavior introduces certain limitations:

- Delayed brake pressure response
- Oscillatory pressure modulation
- Reduced braking smoothness
- Less time spent in optimal slip region
- Reduced braking efficiency under rapidly changing road conditions

To overcome these limitations, predictive braking approaches are gaining importance in modern automotive research.

## 1.2. Problem Statement

Traditional ABS controllers depend mainly on wheel slip thresholds for intervention. However, wheel speed signals often contain predictive characteristics before actual wheel lockup occurs.

The objective of this work is to identify these early indicators using signal processing methods and generate predictive braking intervention before severe wheel instability develops.

## 1.3. Objectives

The major objectives of this dissertation are:

- To study wheel speed behavior during braking events
- To analyze predictive indicators before wheel lockup
- To design a predictive lockup detection algorithm
- To implement multi-feature signal analysis methods
- To compare predictive ABS behavior with conventional ABS logic
- To evaluate feasibility for embedded automotive ECUs

## 1.4. Scope of Work

The scope of this dissertation includes:

- Wheel speed signal analysis
- Slip ratio computation
- Approximate entropy analysis
- Statistical kurtosis analysis
- Dominant frequency estimation
- Weighted lockup probability computation
- Simulation-based validation
- Computational feasibility assessment

The following activities are outside the scope of this work:

- Real vehicle validation
- Hardware-in-loop testing
- Production ECU integration
- ISO 26262 certification activities
- Machine learning based optimization

## 2. SYSTEM OVERVIEW AND ARCHITECTURE

### 2.1. System Overview

The proposed predictive ABS system continuously monitors wheel speed signals and computes multiple signal features in real time. These features are combined to estimate the probability of wheel lockup.

The system architecture consists of the following major modules:

- Wheel speed acquisition module
- Signal conditioning module
- Slip ratio computation module
- Feature extraction module
- Lockup probability estimation module
- Predictive warning generation module
- Performance evaluation module

### 2.2. Functional Architecture

The wheel speed signals from all four wheels are sampled at 1000 Hz. The incoming data is stored in a sliding window buffer for short-term signal analysis.

The feature extraction block computes:

- Approximate entropy
- Statistical kurtosis
- Dominant frequency

The outputs are combined using weighted feature fusion to compute a lockup probability value.




Figure 1. Functional Overview

## 2.3. Wheel Speed Data Acquisition

The braking dataset contains:

- Front left wheel speed
- Front right wheel speed
- Rear left wheel speed
- Rear right wheel speed
- Brake pressure values
- Vehicle reference speed
- Surface condition information

The sampling frequency used in this work is 1000 Hz.

## 2.4. Signal Conditioning

Signal conditioning improves the stability of feature computation.

The following operations are performed:

- Sliding window buffering
- Noise reduction
- Signal normalization
- Buffer synchronization

A window size of 20 samples is selected to balance prediction accuracy and computational latency.

# 3. MATHEMATICAL BACKGROUND

## 3.1. Slip Ratio Calculation

Wheel slip ratio represents the difference between vehicle speed and wheel rotational speed.

The slip ratio is calculated using:

### Wheel Slip Definition

The normalized longitudinal slip ratio is defined as:

$$\lambda = \frac{v_{vehicle} - v_{wheel}}{v_{vehicle}}$$

where  $v_{vehicle}$  is the vehicle reference velocity (typically from speedometer or GPS) and  $v_{wheel}$  is the wheel rotational velocity converted to linear units. This dimensionless metric captures the relative motion between the tire and road:

- $\lambda = 0$ : Free rolling (no braking)
- $\lambda \in [0.10, 0.20]$ : Optimal operating region for most tire-road interfaces
- $\lambda = 1.0$ : Fully locked wheel (zero rotation)

Typical optimal slip values lie between **10% and 20%**, which corresponds to maximum tire-road friction conditions.

### 3.2. Tire-Road Friction Characteristics

Maximum tire-road friction occurs in the slip range of approximately 10% to 20% for most road conditions.

Conventional ABS attempts to maintain operation within this region through pressure modulation.

### 3.3. Approximate Entropy

Approximate entropy measures signal irregularity and complexity.

During normal braking, wheel speed signals remain relatively stable. As the wheel approaches lockup, signal irregularities increase.

Lower entropy values indicate increased predictability and possible transition toward wheel lock conditions.

Approximate entropy is computed using pattern comparison within a tolerance range.

#### Approximate Entropy (ApEn)

Approximate entropy is a regularity statistic that quantifies the unpredictability of fluctuations in a time series. For a discrete signal  $\{u_i\}_{i=1}^N$ , ApEn is defined as:

$$\text{ApEn}(m, r, N) = \phi(m) - \phi(m + 1)$$

where:

$$\phi(m) = \frac{1}{N - m + 1} \sum_{i=1}^{N-m+1} \log C_i^m(r)$$

and  $C_i^m(r)$  is the relative frequency of template matches. Intuitively, a complex or irregular signal has high ApEn, while a regular or predictable signal has low ApEn.

### 3.4. Statistical Kurtosis

Kurtosis measures the peakedness of signal distribution.

The excess kurtosis is the fourth standardized moment of a distribution:

$$\kappa = E \left[ \left( \frac{X - \mu}{\sigma} \right)^4 \right] - 3$$

where  $\mu$  is the mean and  $\sigma$  is the standard deviation. Kurtosis characterizes the "peakedness" and tail behavior:

- $\kappa < 0$ : Platykurtic (flatter than normal distribution)
  - $\kappa = 0$ : Mesokurtic (normal distribution)
  - $\kappa > 0$ : Leptokurtic (more peaked, heavier tails)
- Kurtosis  $> 0 \rightarrow$  Sharp impulsive behavior
  - Kurtosis  $= 0 \rightarrow$  Gaussian distribution
  - Kurtosis  $< 0 \rightarrow$  Flat distribution

Near lockup conditions, wheel speed signals show impulsive characteristics that increase kurtosis.

### 3.5. Dominant Frequency Estimation

Dominant frequency estimation identifies oscillatory behavior in wheel speed signals.

Frequency reduction often indicates reduced tire-road oscillation and possible transition toward unstable braking conditions.

A zero-crossing based frequency estimation method is used in this work due to its computational simplicity.

The dominant frequency provides information about the characteristic oscillation timescale:

$$f_{\text{dominant}} = \frac{N_{\text{zero crossings}}}{2T_{\text{window}}} \cdot f_{\text{sample}}$$

where  $N_{\text{zero crossings}}$  is the number of times the signal crosses its mean value. This zero-crossing method is computationally efficient (suitable for embedded systems) and captures the main frequency content without requiring FFT computation.

## 4. METHODOLOGY AND ALGORITHM DESIGN

### 4.1. Overall Methodology

The proposed methodology consists of:

- Acquiring wheel speed data
- Computing slip ratio
- Extracting predictive signal features
- Estimating lockup probability



- Generating predictive warnings
- Comparing results with conventional ABS behavior

## 4.2. Sliding Window Analysis

A sliding window approach is used for feature extraction.

Window size: 20 samples

Sampling rate: 1000 Hz

Analysis duration: 20 ms

This approach enables continuous real-time monitoring of wheel dynamics.

## 4.3. Feature Extraction

### 4.3.1. Entropy Analysis

Entropy is computed from wheel speed fluctuations within the sliding window.

Entropy contribution weight: 35%

### 4.3.2. Kurtosis Analysis

Kurtosis detects impulsive signal characteristics associated with unstable braking.

Kurtosis contribution weight: 25%

### 4.3.3. Frequency Analysis

Dominant frequency is estimated using zero-crossing methods.

Frequency contribution weight: 15%

### 4.3.4. Slip Dynamics

Slip acceleration and slip magnitude are also included as predictive indicators.

Combined contribution weight: 25%

## 4.4. Weighted Lockup Probability

The overall lockup probability is calculated using weighted multi-feature fusion.

Table1. The feature weights used are:

| Feature             | Weight |
|---------------------|--------|
| Approximate Entropy | 35%    |
| Kurtosis            | 25%    |
| Frequency Analysis  | 15%    |
| Slip Rate           | 15%    |
| Slip Magnitude      | 10%    |

The weighted fusion approach improves robustness by avoiding dependency on a single signal indicator.

#### 4.5. Predictive Warning Logic

Predictive intervention is generated when:

- Multiple wheels exceed risk threshold
- Lockup probability exceeds 60%
- Slip dynamics indicate unstable braking

## 5. PREDICTIVE LOCKUP DETECTION STRATEGY

### 5.1. Traditional ABS Behavior

Traditional ABS activates after excessive wheel slip is detected.

This leads to:

- Reactive pressure modulation
- Pressure oscillation
- Delayed intervention

### 5.2. Predictive ABS Behavior

The predictive ABS system identifies unstable wheel behavior before severe slip saturation occurs.

This enables:

- Earlier intervention
- Smooth brake pressure reduction
- Improved slip regulation
- Better vehicle stability

### 5.3. Lockup Probability Estimation

The weighted lockup probability is continuously monitored.

A probability threshold of 60% is used for predictive warning generation.

### 5.4. State-Based Control Strategy

The controller operates in multiple states:

- Normal braking
- Predictive warning
- Pressure reduction
- Pressure hold
- Pressure reapply

This state-based approach supports smooth pressure modulation.

## 6. VALIDATION RESULTS

### 6.1. Simulation Overview

The predictive ABS algorithm was validated using braking datasets and simulation-based analysis.

Performance comparison was carried out against traditional ABS behavior.

### 6.2. Slip Regulation Performance

The predictive ABS approach maintains wheel slip closer to the optimal 10%–20% range compared to conventional ABS logic.

This improves tire-road friction utilization.

### 6.3. Early Detection Capability

The predictive method demonstrates earlier detection of unstable wheel conditions using entropy and multi-feature analysis.

The system provides advance warning before severe wheel lockup develops.

### 6.4. Brake Pressure Modulation

Predictive ABS demonstrates smoother brake pressure transitions compared to abrupt pressure cycling observed in conventional ABS.

This reduces braking oscillation.

## 6.5. Stopping Distance Improvement

Simulation results indicate improvement in braking efficiency and reduction in stopping distance under emergency braking conditions.




Figure 2. Predictive ABS vs Traditional ABS

## 6.6. Performance Metrics

Table 2. The following parameters were evaluated:

| Parameter                | Traditional ABS | Predictive ABS |
|--------------------------|-----------------|----------------|
| Detection Method         | Reactive        | Predictive     |
| Pressure Behavior        | Oscillatory     | Smooth         |
| Slip Regulation          | Moderate        | Improved       |
| Detection Timing         | Delayed         | Earlier        |
| ECU Feasibility          | High            | High           |
| Computational Complexity | Low             | Moderate       |

## 6.7. Validation Scenarios

The system was evaluated under:

- Dry road condition
- Wet road condition
- Low friction surface
- Split friction condition
- Repeated braking events

## 6.8. Result – Traditional vs Predictive ABS




Figure 3. Result of Traditional vs Predictive ABS

## 7. COMPUTATIONAL ANALYSIS AND ECU FEASIBILITY

### 7.1. Real-Time Constraints

Automotive braking systems require deterministic execution with strict timing constraints.

The proposed algorithm was designed considering embedded ECU limitations.

### 7.2. Computational Requirements

Table 3. The major computational blocks include:

| Function            | Relative Complexity |
|---------------------|---------------------|
| Signal Conditioning | Low                 |
| Entropy Computation | Medium              |
| Kurtosis Analysis   | Low                 |
| Frequency Analysis  | Low                 |
| Weighted Fusion     | Low                 |

### 7.3. Memory Usage

The implementation uses fixed-size buffers and deterministic memory allocation.

Dynamic memory allocation is avoided to improve real-time reliability.

### 7.4. ECU Feasibility

The algorithm is suitable for implementation on automotive microcontrollers such as Cortex-M4 class processors.

The computational overhead remains within acceptable limits for real-time braking applications.

## 8. ADVANTAGES AND LIMITATIONS

### 8.1. Advantages

The proposed predictive ABS system offers the following advantages:

- Earlier lockup detection
- Improved braking smoothness
- Better slip regulation

- Reduced pressure oscillation
- Deterministic implementation
- Compatibility with existing ABS systems
- Low computational overhead

## 8.2. Limitations

The present work also has certain limitations:

- Validation performed mainly on simulation datasets
- Limited real-world vehicle testing
- Threshold tuning required for production systems
- Environmental variations not fully covered
- No hardware-in-loop validation

## 9. FUTURE SCOPE

Future improvements for this work include:

- Real vehicle testing
- Hardware-in-loop validation
- Adaptive threshold optimization
- Integration with Electronic Stability Control
- Machine learning assisted prediction
- Sensor fusion techniques
- Production ECU implementation
- ISO 26262 safety analysis

Further research can also explore integration with autonomous driving systems and predictive vehicle control architectures.

## 10. CONCLUSION

This dissertation presented a predictive anti-lock braking system based on wheel speed signal analysis and predictive lockup detection.

Unlike conventional ABS systems that react after excessive slip occurs, the proposed approach attempts to identify unstable wheel behavior earlier using signal processing methods.

Approximate entropy, kurtosis, frequency analysis, and slip dynamics were successfully combined using weighted multi-feature fusion to estimate lockup probability.

Simulation and dataset-based validation demonstrate that predictive braking intervention can improve braking smoothness and support earlier lockup detection compared to traditional ABS logic.

The computational analysis also indicates that the proposed algorithm is suitable for real-time embedded automotive systems.

The work demonstrates the potential of predictive signal-processing-based braking control for future automotive safety systems.

## 11. REFERENCES

1. Rajamani, R., "Vehicle Dynamics and Control," Springer, 2nd Edition, 2012.
2. Gillespie, T. D., "Fundamentals of Vehicle Dynamics," SAE International, 1992.
3. Pincus, S. M., "Approximate Entropy as a Measure of System Complexity," Proceedings of the National Academy of Sciences, Vol. 88, No. 6, 1991.
4. Bosch Automotive Handbook, 10th Edition, Robert Bosch GmbH.
5. Pacejka, H., "Tire and Vehicle Dynamics," Elsevier, 3rd Edition, 2012.
6. ISO 26262 Road Vehicles – Functional Safety Standard.
7. SAE International Papers on Brake Control and Wheel Slip Regulation.

## 12. GLOSSARY

| Term               | Description                                      |
|--------------------|--------------------------------------------------|
| ABS                | Anti-lock Braking System                         |
| ECU                | Electronic Control Unit                          |
| Slip Ratio         | Difference between wheel speed and vehicle speed |
| Entropy            | Signal irregularity measurement                  |
| Kurtosis           | Statistical measure of signal impulsiveness      |
| Frequency Analysis | Oscillation behavior analysis                    |
| HIL                | Hardware-in-loop                                 |
| ASIL               | Automotive Safety Integrity Level                |
| RPM                | Revolutions Per Minute                           |



## 13. APPENDICES

### 13.1. Appendix A – Major Technical Specifications

| Parameter           | Specification                 |
|---------------------|-------------------------------|
| Application         | Predictive ABS                |
| Sampling Rate       | 1000 Hz                       |
| Number of Wheels    | Four                          |
| Buffer Size         | 20 Samples                    |
| Feature Extraction  | Entropy, Kurtosis, Frequency  |
| Processing Platform | Python                        |
| Prediction Method   | Weighted Multi-feature Fusion |
| Output              | Predictive Warning Signal     |

### 13.2. Appendix B – Validation Parameters

| Validation Item   | Description                 |
|-------------------|-----------------------------|
| Slip Threshold    | 10%–20% Optimal Range       |
| Warning Threshold | 60% Lockup Probability      |
| Window Size       | 20 ms                       |
| Surface Types     | Dry, Wet, Ice, Split- $\mu$ |

### 13.3. Appendix C – Software Modules

The implementation includes the following software modules:

- Wheel speed acquisition
- Slip ratio computation
- Entropy computation
- Kurtosis computation
- Frequency estimation
- Lockup probability computation
- Predictive warning generation
- Validation and visualization