

# TABLE OF CONTENTS

GE23131-Programming Using C-2024	1
Question 1	1
Question 2	2
Question 3	5
Quiz navigation	1

# GE23131-Programming Using C-2024

Quiz navigation



[Show one page at a time](#)

[Finish review](#)

<b>Status</b>	Finished
<b>Started</b>	Monday, 23 December 2024, 5:33 PM
<b>Completed</b>	Saturday, 26 October 2024, 12:58 PM
<b>Duration</b>	58 days 4 hours

Question **1**

Correct

Marked out of  
3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false  
Sample Input 2 27 77 Sample Output 2 true

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main(){
3     int a,b;
4     scanf("%d%d", &a,&b);
5     if(a%10==b%10) {
6         printf("true");
7     }
8     else {
9         printf("false");
10    }
11    return 0;
12 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of  
5.00

🚩 [Flag question](#)

## Objective

In this challenge, we're getting started with conditional statements. //

## Task

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print **Weird**
- If ***n*** is even and in the inclusive range of **2** to **5**, print ***Not Weird***
- If ***n*** is even and in the inclusive range of **6** to **20**, print ***Weird***
- If ***n*** is even and greater than **20**, print ***Not Weird***

Complete the stub code provided in your editor to print whether or not ***n*** is weird.

### Input Format

A single line containing a positive integer, ***n***.

### Constraints

$$1 \leq n \leq 100$$

### Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

### Sample Input 0

3

### Sample Output 0

Weird

### Sample Input 1

24

### Sample Output 1

Not Weird

### Explanation

*Sample Case 0:  $n = 3$*

$n$  is odd and odd numbers are weird, so we print **Weird**.

*Sample Case 1:  $n = 24$*

$n > 20$  and  $n$  is even, so it isn't weird. Thus, we print **Not Weird**.

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main() {
3     int n;
4     scanf("%d", &n);
5     if(n%2==1) {
6         printf("Weird");
7     }
8     else if(n/2==0&& n<=6&& n>=20) {
9         printf("Not Weird");
10    }
11    else if(n/2==0&& n<=6&& n>=20) {
12        printf("Weird");
13    }
14    else
15    {
16        printf("Not Weird");
17    }
18    return 0;
19
20 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of  
7.00

🚩 [Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since  $3^2 + 4^2 = 25 = 5^2$ . You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main() {
3      int a,b,c;
4      scanf("%d\n%d\n%d\n", &a,&b,&c);
5      if(a*a+b*b==c*c || a*a+c*c==b*b || b*b+c*c==a*a) {
6          printf("yes");
7      }
8      else{
9          printf("no");
10     }
11     return 0;
12 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review