

Loops and iteration

Loops offer a quick and easy way to do something repeatedly. You can think of a loop as a computerized version of the game where you tell someone to take X steps in one direction, then Y steps in another.

There are many different kinds of loops, but they all essentially do the same thing: they repeat an action some number of times.

The statements for loops provided in JavaScript are:

1. for statement
2. do...while statement
3. while statement
4. labeled statement
5. break statement
6. continue statement
7. for...in statement
8. for...of statement

for statement

A for loop repeats until a specified condition evaluates to false. The JavaScript for loop is similar to the Java and C for loop.

A for statement looks as follows:

```
for (initialization; condition; afterthought)
  statement
```

When a for loop executes, the following occurs:

1. The initializing expression `initialization`, if any, is executed. This expression usually initializes one or more loop counters, but the syntax allows an expression of any degree of complexity. This expression can also declare variables.

2. The condition expression is evaluated. If the value of the condition is true, the loop statements execute. Otherwise, the for loop terminates. (If the condition expression is omitted entirely, the condition is assumed to be true.)
3. The statement executes. To execute multiple statements, use a block statement ({ }) to group those statements.
4. If present, the update expression afterthought is executed.
5. Control returns to Step 2.

Here, the for statement declares the variable `i` and initializes it to 0. It checks that `i` is less than the number of options in the `<select>` element, performs the succeeding if statement, and increments `i` by 1 after each pass through the loop.

```
function countSelected(selectObject) {
  let numberSelected = 0;
  for (let i = 0; i < selectObject.options.length; i++) {
    if (selectObject.options[i].selected) {
      numberSelected++;
    }
  }
  return numberSelected;
}

const btn = document.getElementById("btn");

btn.addEventListener("click", () => {
  const musicTypes = document.selectForm.musicTypes;
  console.log(`You have selected ${countSelected(musicTypes)} option(s).`);
});
```

do...while statement

The `do...while` statement repeats **until a specified condition evaluates to false**.

```
do
  statement
while (condition);
```

statement is always executed once before the condition is checked. (To execute multiple statements, use a block statement ({ }) to group those statements.)

If condition is true, the statement executes again. At the end of every execution, the condition is checked. When the condition is false, execution stops, and control passes to the statement following do...while.

Example

In the following example, the do loop iterates at least once and reiterates until i is no longer less than 5.

```
let i = 0;
do {
  i += 1;
  console.log(i);
} while (i < 5);
```

while statement

A while statement executes its statements **as long as a specified condition evaluates to true**. A while statement looks as follows:

```
while (condition)
  statement
```

If the condition becomes false, statement within the loop stops executing and control passes to the statement following the loop.

The condition test occurs before statement in the loop is executed. If the condition returns true, statement is executed and the condition is tested again. If the condition returns false, execution stops, and control is passed to the statement following while.

To execute multiple statements, use a block statement ({ }) to group those statements.

Example 1

The following while loop iterates as long as n is less than 3:

```
let n = 0;
let x = 0;
while (n < 3) {
  n++;
  x += n;
}
```

With each iteration, the loop increments `n` and adds that value to `x`. Therefore, `x` and `n` take on the following values:

- After the first pass: `n = 1` and `x = 1`
- After the second pass: `n = 2` and `x = 3`
- After the third pass: `n = 3` and `x = 6`

After completing the third pass, the condition `n < 3` is no longer true, so the loop terminates.

Example 2

Avoid infinite loops. Make sure the condition in a loop eventually becomes `false`—otherwise, the loop will never terminate! The statements in the following `while` loop execute forever because the condition never becomes `false`:

```
// Infinite loops are bad!
while (true) {
  console.log("Hello, world!");
}
```

labeled statement

A `label` provides a statement with an identifier that lets you refer to it elsewhere in your program. For example, you can use a label to identify a loop, and then use the `break` or `continue` statements to indicate whether a program should interrupt the loop or continue its execution.

The syntax of the labeled statement looks like the following:

```
label:
  statement
```

The value of `label` may be any JavaScript identifier that is not a reserved word. The statement that you identify with a label may be any statement.

Example

In this example, the label `markLoop` identifies a `while` loop.

```
markLoop: while (theMark) {  
    doSomething();  
}
```

break statement

Use the `break` statement to terminate a loop, `switch`, or in conjunction with a labeled statement.

- When you use `break` without a label, it terminates the innermost enclosing `while`, `do-while`, `for`, or `switch` immediately and transfers control to the following statement.
- When you use `break` with a label, it terminates the specified labeled statement.

The syntax of the `break` statement looks like this:

```
break;  
break label;
```

1. The first form of the syntax terminates the innermost enclosing loop or `switch`.
2. The second form of the syntax terminates the specified enclosing labeled statement.

Example 1

The following example iterates through the elements in an array until it finds the index of an element whose value is `theValue`:

```
for (let i = 0; i < a.length; i++) {  
    if (a[i] === theValue) {  
        break;  
    }  
}
```

Example 2: Breaking to a label

```
let x = 0;
let z = 0;
labelCancelLoops: while (true) {
  console.log("Outer loops: ", x);
  x += 1;
  z = 1;
  while (true) {
    console.log("Inner loops: ", z);
    z += 1;
    if (z === 10 && x === 10) {
      break labelCancelLoops;
    } else if (z === 10) {
      break;
    }
  }
}
```

continue statement

The continue statement can be used to restart a while, do-while, for, or label statement.

- When you use continue without a label, it terminates the current iteration of the innermost enclosing while, do-while, or for statement and continues execution of the loop with the next iteration. In contrast to the break statement, continue does not terminate the execution of the loop entirely. In a while loop, it jumps back to the condition. In a for loop, it jumps to the increment-expression.
- When you use continue with a label, it applies to the looping statement identified with that label.

The syntax of the continue statement looks like the following:

```
continue;
continue label;
```

Example 1

The following example shows a while loop with a continue statement that executes when the value of i is 3. Thus, n takes on the values 1, 3, 7, and 12.

```
let i = 0;
```

```

let n = 0;
while (i < 5) {
  i++;
  if (i === 3) {
    continue;
  }
  n += i;
  console.log(n);
}
//1,3,7,12

```

If you comment out the `continue;`, the loop would run till the end and you would see 1,3,6,10,15.

Example 2

A statement labeled `checkiandj` contains a statement labeled `checkj`. If `continue` is encountered, the program terminates the current iteration of `checkj` and begins the next iteration. Each time `continue` is encountered, `checkj` reiterates until its condition returns false. When false is returned, the remainder of the `checkiandj` statement is completed, and `checkiandj` reiterates until its condition returns false. When false is returned, the program continues at the statement following `checkiandj`.

If `continue` had a label of `checkiandj`, the program would continue at the top of the `checkiandj` statement.

```

let i = 0;
let j = 10;
checkiandj: while (i < 4) {
  console.log(i);
  i += 1;
  checkj: while (j > 4) {
    console.log(j);
    j -= 1;
    if (j % 2 === 0) {
      continue checkj;
    }
    console.log(j, " is odd.");
  }
  console.log("i = ", i);
  console.log("j = ", j);
}

```

for...in statement

The `for...in` statement iterates a specified variable over all the enumerable properties of an object. For each distinct property, JavaScript executes the specified statements. A `for...in` statement looks as follows:

```
for (variable in object)
  statement
```

Example

The following function takes as its argument an object and the object's name. It then iterates over all the object's properties and returns a string that lists the property names and their values.

```
function dumpProps(obj, objName) {
  let result = "";
  for (const i in obj) {
    result += `${objName}.${i} = ${obj[i]}<br>`;
  }
  result += "<hr>";
  return result;
}
```

For an object `car` with properties `make` and `model`, `result` would be:

```
car.make = Ford
car.model = Mustang
```

Arrays

Although it may be tempting to use this as a way to iterate over `Array` elements, the `for...in` statement will return the name of your user-defined properties in addition to the numeric indexes.

Therefore, it is better to use a traditional `for` loop with a numeric index when iterating over arrays, because the `for...in` statement iterates over user-defined properties in addition to the array elements, if you modify the `Array` object (such as adding custom properties or methods).

for...of statement

The `for...of` statement creates a loop iterating over iterable objects (including `Array`, `Map`, `Set`, arguments object, and so on), invoking a custom iteration hook with statements to be executed for the value of each distinct property.

```
for (variable of object)
  statement
```

The following example shows the difference between a `for...of` loop and a `for...in` loop. While `for...in` iterates over property names, `for...of` iterates over property values:

```
const arr = [3, 5, 7];
arr.foo = "hello";

for (const i in arr) {
  console.log(i);
}
// "0" "1" "2" "foo"

for (const i of arr) {
  console.log(i);
}
// Logs: 3 5 7
```

The `for...of` and `for...in` statements can also be used with **destructuring**. For example, you can simultaneously loop over the keys and values of an object using `Object.entries()`.

```
const obj = { foo: 1, bar: 2 };

for (const [key, val] of Object.entries(obj)) {
  console.log(key, val);
}
// "foo" 1
// "bar" 2
```