


PresentationRequest

Experimental: This is an **experimental technology**.
Check the [Browser compatibility table](#) carefully before using this in production.

Secure context: This feature is available only in [secure contexts](#) (HTTPS), in some or all [supporting browsers](#).

A `PresentationRequest` object is used to initiate or reconnect to a presentation made by a [controlling browsing context](#). The `PresentationRequest` object *MUST* be implemented in a [controlling browsing context](#) provided by a [controlling user agent](#).

When a `PresentationRequest` is constructed, the given `uris` *MUST* be used as the list of *presentation request URLs* which are each a possible [presentation URL](#) for the `PresentationRequest` instance.



Constructor

`PresentationRequest()`
Creates a `PresentationRequest`.

Instance properties

None

Instance methods

`PresentationRequest.start()`
Returns a [Promise](#) that resolves with a [PresentationConnection](#) after the user agent prompts the user to select a display and grant permission to use that display.

`PresentationRequest.reconnect()`
When the `reconnect(presentationId)` method is called on a `PresentationRequest` *presentationRequest*, the [user agent](#) *MUST* run the following steps to *reconnect to a presentation*.

`PresentationRequest.getAvailability()`
When the `getAvailability()` method is called, the user agent *MUST* run the steps as the link.

Specifications

Specification
Presentation API
interface-presentationrequest

Browser compatibility

[Report problems with this compatibility data on GitHub](#)

	Desktop					Mobile				
	Chrome	Edge	Firefox	Opera	Safari	Chrome Android	Firefox for Android	Opera Android	Safari on iOS	Samsung Internet
<code>PresentationRequest</code>	✓ Chrome 47	✓ Edge 79	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Chrome 47 Android	✗ Firefox No for Android	✓ Opera 34 Android	✗ Safari No on iOS	✓ Samsung 5.0 Internet

PresentationRequest() constructor	✓ Chrome 47	✓ Edge 79	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Chrome 47	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Samsung 5.0	
						Android	for Android	Android	on iOS	Internet	
<code>connectionavailable</code> event	✓ Chrome 47	✓ Edge 79	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Chrome 47	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Samsung 5.0	
	Chrome	Edge	Firefox	Opera	Safari	Chrome	Firefox for Android	Opera	Safari on iOS	Samsung Internet	
getAvailability	✓ Chrome 47	✓ Edge 79	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Chrome 47	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Samsung 5.0	
						Android	for Android	Android	on iOS	Internet	
reconnect	✓ Chrome 47	✓ Edge 79	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Chrome 47	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Samsung 5.0	
						Android	for Android	Android	on iOS	Internet	
Secure context required	✓ Chrome 61	✓ Edge 79	✗ Firefox 51–60	✓ Opera 48	✗ Safari No	✓ Chrome 61	✗ Firefox 51–68	✓ Opera 45	✗ Safari No	✓ Samsung 8.0	
						Android	for Android	Android	on iOS	Internet	
start	✓ Chrome 47	✓ Edge 79	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Chrome 47	✗ Firefox No	✓ Opera 34	✗ Safari No	✓ Samsung 5.0	
						Android	for Android	Android	on iOS	Internet	

Tip: you can click/tap on a cell for more information.

✓ Full support ✗ No support Experimental. Expect behavior to change in the future.

This page was last modified on Aug 4, 2023 by [MDN contributors](#).