

Machine Learning

Lecture 7 Linear Regression

Chen-Kuo Chiang (江振國)
ckchiang@cs.ccu.edu.tw

中正大學 資訊工程學系


The Storyline

How Can Machines Learn?

Linear Regression

- Linear Regression Problem
- Linear Regression Algorithm
- Linear Regression for Binary Classification

Credit Limit Problem



$\mathcal{Y} = \mathbb{R}$: regression

Linear Regression Hypothesis

age	23 years
annual salary	NTD 1,000,000
year in job	0.5 year
current debt	200,000

門閥值

- For $\mathbf{x} = (\boxed{x_0}, x_1, x_2, \dots, x_d)$ 'features of customer', approximate the **desired credit limit** with a **weighted sum**


$$y \approx \sum_{i=0}^d w_i x_i$$

- linear regression hypothesis: $h(\mathbf{x}) = \mathbf{w}^T \mathbf{x}$


$h(\mathbf{x})$: like **perceptron**, but **without the sign**

Illustration of Linear Regression

$$\mathbf{x} = (x) \in \mathbb{R}$$



$$\mathbf{x} = (x_1, x_2) \in \mathbb{R}^2$$



linear regression:
find lines/hyperplanes with small residuals

The Error Measure

popular/historical error measure:

把err function求出後，再使用optimize function

越小越好

$$\text{squared error } \text{err}(\hat{y}, y) = (\hat{y} - y)^2$$

in-sample

$$E_{\text{in}}(\mathbf{w}) = \frac{1}{N} \sum_{n=1}^N \underbrace{(h(\mathbf{x}_n) - y_n)^2}_{\mathbf{w}^T \mathbf{x}_n}$$

out-of-sample

$$E_{\text{out}}(\mathbf{w}) = \mathcal{E}_{(\mathbf{x}, y) \sim P} (\mathbf{w}^T \mathbf{x} - y)^2$$

next: how to minimize $E_{\text{in}}(\mathbf{w})$?

Fun Time


Consider using linear regression hypothesis $h(\mathbf{x}) = \mathbf{w}^T \mathbf{x}$ to predict the credit limit of customers \mathbf{x} . Which feature below shall have a positive weight in a **good hypothesis** for the task?

- 1 birth month
- 2 monthly income
- 3 current debt
- 4 number of credit cards owned

Matrix Form of $E_{\text{in}}(\mathbf{w})$

$$\begin{aligned}
 E_{\text{in}}(\mathbf{w}) &= \frac{1}{N} \sum_{n=1}^N (\mathbf{w}^T \mathbf{x}_n - y_n)^2 = \frac{1}{N} \sum_{n=1}^N (\mathbf{x}_n^T \mathbf{w} - y_n)^2 \\
 &= \frac{1}{N} \left\| \begin{array}{c} \text{預測} \quad \text{標準} \\ \mathbf{x}_1^T \mathbf{w} - y_1 \\ \mathbf{x}_2^T \mathbf{w} - y_2 \\ \vdots \\ \mathbf{x}_N^T \mathbf{w} - y_N \end{array} \right\|^2 \\
 &= \frac{1}{N} \left\| \begin{bmatrix} - & - & \mathbf{x}_1^T & - & - \\ - & - & \mathbf{x}_2^T & - & - \\ & & \vdots & & \\ - & - & \mathbf{x}_N^T & - & - \end{bmatrix} \mathbf{w} - \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_N \end{bmatrix} \right\|^2 \\
 &= \frac{1}{N} \left\| \underbrace{\mathbf{X}}_{\text{多了0 } N \times d+1} \underbrace{\mathbf{w}}_{d+1 \times 1} - \underbrace{\mathbf{y}}_{N \times 1} \right\|^2
 \end{aligned}$$

$$\min_{\mathbf{w}} E_{\text{in}}(\mathbf{w}) = \frac{1}{N} \|\mathbf{X}\mathbf{w} - \mathbf{y}\|^2$$



- $E_{\text{in}}(\mathbf{w})$: continuous, differentiable, convex
- necessary condition of 'best' \mathbf{w}

$$\nabla E_{\text{in}}(\mathbf{w}) \equiv \begin{bmatrix} \frac{\partial E_{\text{in}}}{\partial w_0}(\mathbf{w}) \\ \frac{\partial E_{\text{in}}}{\partial w_1}(\mathbf{w}) \\ \vdots \\ \frac{\partial E_{\text{in}}}{\partial w_d}(\mathbf{w}) \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \end{bmatrix}$$

—not possible to 'roll down'

task: find \mathbf{w}_{LIN} such that $\nabla E_{\text{in}}(\mathbf{w}_{\text{LIN}}) = \mathbf{0}$

The Gradient $\nabla E_{\text{in}}(\mathbf{w})$

$$E_{\text{in}}(\mathbf{w}) = \frac{1}{N} \|\mathbf{X}\mathbf{w} - \mathbf{y}\|^2 = \frac{1}{N} \left(\underbrace{\mathbf{w}^T \mathbf{X}^T \mathbf{X} \mathbf{w}}_{\text{A}} - 2 \underbrace{\mathbf{w}^T \mathbf{X}^T \mathbf{y}}_{\text{b}} + \underbrace{\mathbf{y}^T \mathbf{y}}_{\text{c}} \right)$$

轉至
轉至才可以相乘

one w only

$$E_{\text{in}}(w) = \frac{1}{N} (aw^2 - 2bw + c)$$

$$\nabla E_{\text{in}}(w) = \frac{1}{N} (2aw - 2b) \quad \text{微分}$$

simple! :-)

vector \mathbf{w}

$$E_{\text{in}}(\mathbf{w}) = \frac{1}{N} (\mathbf{w}^T \mathbf{A} \mathbf{w} - 2\mathbf{w}^T \mathbf{b} + c)$$

$$\nabla E_{\text{in}}(\mathbf{w}) = \frac{1}{N} (2\mathbf{A} \mathbf{w} - 2\mathbf{b})$$

similar (**derived by definition**)

$$\nabla E_{\text{in}}(\mathbf{w}) = \frac{2}{N} (\underbrace{\mathbf{X}^T \mathbf{X}}_{\text{A}} \mathbf{w} - \underbrace{\mathbf{X}^T \mathbf{y}}_{\text{b}})$$

Optimal Linear Regression Weights

task: find \mathbf{w}_{LIN} such that $\frac{2}{N} (\mathbf{X}^T \mathbf{X} \mathbf{w} - \mathbf{X}^T \mathbf{y}) = \nabla E_{\text{in}}(\mathbf{w}) = \mathbf{0}$

$\mathbf{X}^T \mathbf{X} \mathbf{w} = \mathbf{X}^T \mathbf{y} \Rightarrow \mathbf{X}^T \mathbf{X} (\mathbf{X}^T \mathbf{X})^{-1} \mathbf{w} = (\mathbf{X}^T \mathbf{X})^{-1} \mathbf{X}^T \mathbf{y}$ 反向

考

invertible $\mathbf{X}^T \mathbf{X}$

- **easy!** unique solution

$$\mathbf{w}_{\text{LIN}} = \underbrace{\left(\overset{\text{存在}}{\mathbf{X}^T \mathbf{X}} \right)^{-1} \mathbf{X}^T}_{\text{pseudo-inverse } \mathbf{X}^\dagger} \mathbf{y}$$

- often the case because $N \gg d + 1$

singular $\mathbf{X}^T \mathbf{X}$

- **many** optimal solutions
- one of the solutions

$$\mathbf{w}_{\text{LIN}} = \boxed{\mathbf{X}^\dagger \mathbf{y}}$$

Linear regression

by defining \mathbf{X}^\dagger in other ways

practical suggestion:

use **well-implemented \dagger routine**

instead of $\boxed{(\mathbf{X}^T \mathbf{X})^{-1} \mathbf{X}^T}$

for numerical stability when **almost-singular**

Linear Regression Algorithm

- 1 from \mathcal{D} , construct **input matrix X** and **output vector y** by

$$X = \underbrace{\begin{bmatrix} - & - & \mathbf{x}_1^T & - & - \\ - & - & \mathbf{x}_2^T & - & - \\ & & \dots & & \\ - & - & \mathbf{x}_N^T & - & - \end{bmatrix}}_{N \times (d+1)} \quad y = \underbrace{\begin{bmatrix} y_1 \\ y_2 \\ \dots \\ y_N \end{bmatrix}}_{N \times 1}$$

- 2 calculate pseudo-inverse $\underbrace{X^\dagger}_{(d+1) \times N}$

- 3 return $\underbrace{\mathbf{w}_{\text{LIN}}}_{(d+1) \times 1} = \underline{X^\dagger y}$

simple and efficient
with **good \dagger routine**

Fun Time

預測
結果

After getting \mathbf{w}_{LIN} , we can calculate the predictions $\hat{y}_n = \mathbf{w}_{\text{LIN}}^T \mathbf{x}_n$. If all \hat{y}_n are collected in a vector $\hat{\mathbf{y}}$ similar to how we form \mathbf{y} , what is the matrix formula of $\hat{\mathbf{y}}$? 收集成一個向量

- 1 \mathbf{y}
- 2 $\mathbf{X}\mathbf{X}^T \mathbf{y}$
- 3 $\mathbf{X}\mathbf{X}^\dagger \mathbf{y}$
- 4 $\mathbf{X}\mathbf{X}^\dagger \mathbf{X}\mathbf{X}^T \mathbf{y}$

Linear Classification vs. Linear Regression

Linear Classification

相同

$$\mathcal{Y} = \{-1, +1\}$$

$$h(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x})$$

$$\text{err}(\hat{y}, y) = \mathbb{I}[\hat{y} \neq y]$$

NP-hard to solve in general

Linear Regression

$$\mathcal{Y} = \mathbb{R}$$

$$h(\mathbf{x}) = \mathbf{w}^T \mathbf{x}$$

$$\text{err}(\hat{y}, y) = (\hat{y} - y)^2$$

efficient analytic solution

$\{-1, +1\} \subset \mathbb{R}$: linear regression for classification?


- 1 run LinReg on binary classification data \mathcal{D} (**efficient**) 先求linear regression
- 2 return $g(\mathbf{x}) = \text{sign}(\mathbf{w}_{\text{LIN}}^T \mathbf{x})$ 再取sign

but explanation of this **heuristic**?


Relation of Two Errors

$$\text{err}_{0/1} = \llbracket \text{sign}(\mathbf{w}^T \mathbf{x}) \neq y \rrbracket \quad \text{err}_{\text{sqr}} = (\mathbf{w}^T \mathbf{x} - y)^2$$

desired $y = 1$



desired $y = -1$



$$\text{err}_{0/1} \leq \text{err}_{\text{sqr}}$$

初始化條件 Upper bound

Linear Regression for Binary Classification

$$\text{err}_{0/1} \leq \text{err}_{\text{sqr}}$$

$$\begin{aligned} \text{classification } E_{\text{out}}(\mathbf{w}) &\stackrel{\text{VC}}{\leq} \text{classification } E_{\text{in}}(\mathbf{w}) + \sqrt{\dots\dots\dots} \\ &\leq \text{regression } E_{\text{in}}(\mathbf{w}) + \sqrt{\dots\dots\dots} \end{aligned}$$

- (loose) upper bound err_{sqr} as $\widehat{\text{err}}$ to approximate $\text{err}_{0/1}$
- trade **bound tightness** for **efficiency**

\mathbf{w}_{LIN} : useful baseline classifier,
or as **initial PLA/pocket vector**

Fun Time

Which of the following functions are upper bounds of the pointwise 0/1 error $[\text{sign}(\mathbf{w}^T \mathbf{x}) \neq y]$ for $y \in \{-1, +1\}$?

- ① $\exp(-y\mathbf{w}^T \mathbf{x})$
- ② $\max(0, 1 - y\mathbf{w}^T \mathbf{x})$
- ③ $\log_2(1 + \exp(-y\mathbf{w}^T \mathbf{x}))$
- ④ ☒ all of the above

Summary

How Can Machines Learn?

Linear Regression

- Linear Regression Problem
use hyperplanes to approximate real values
- Linear Regression Algorithm
可以寫出一個公式 **analytic solution** with pseudo-inverse
- Linear Regression for Binary Classification
0/1 error \leq squared error