


Polyglot and Poly-paradigm Programming

Dean Wampler
dean@deanwampler.com
@deanwampler

Co-author,
*Programming
Scala*

programmingscala.com



Guest Editor,
IEEE Software
Special Issue on
Multi-paradigm Programming

Sept/Oct 2010

computer.org/software

[Find a Meetup Group](#)
[Start a Meetup Group](#)

[Dean Wampler](#)
[Profile](#)
[Account](#)
[New Features \(42\)](#)
[Help](#)
[Log out](#)

The Chicago-Area Scala Enthusiasts (CASE) Meetup Group

[Home](#)
[About](#)
[Meetups](#)
[Ideas](#)
[Members](#)
[Photos](#)
[Discussions](#)
[More](#)
[Group Tools](#)

[Change photo](#)

Chicago, IL

(6 comments)

181 Scala Software Developers

Meetups

14 so far

Founded

February 24, 2009

Organizer:

[Dean Wampler](#)

Co-Organizers:

[Michael Norton](#)

[View The Leadership Team](#)

About The Chicago-Area Scala Enthusiasts (CASE) Meetup Group

[Edit this page](#)
[Past edits](#)
[Table of contents](#)
[Add a page](#)

Come to the **Chicago-Area Scala Enthusiasts** to learn about the **Scala** programming language, a hybrid object-functional JVM language that is a logical "upgrade" path from Java.


We welcome new and experienced Scala users. We also welcome suggestions for meeting topics and volunteer speakers.

Recently updated pages

Page title	Most recent update	Last edited by
About this Meetup Group	June 14, 2010 8:42 PM	Dean Wampler


Today's applications:

- Are *networked*,
- Have graphical and “service” *interfaces*,




Today's applications:

- *Persist* data,
- Must be *resilient* and *secure*,
- Must *scale*,



Today's applications:

- ... and must do all that by *Friday*.



Polyglot or
Multilingual:
many languages

*Poly-paradigm or
Multiparadigm:*
many modularity
paradigms

Thesis:
modern problems
are poorly served by
“Monocultures”



*Mono-
paradigm:*

*Object-Oriented
Programming:*

right for all
requirements?

[flickr.com/photos/deanwampler](https://www.flickr.com/photos/deanwampler/)



Monolingual

Is one *language*
best for all *domains*?

twitter.com/photos/watchsmart

Symptoms of Monocultures

- *Why is there so much XML in my Java?*
- *Why do I have similar code for persistence, transactions, security, etc. scattered all over my code base?*

Symptoms of Monocultures

- *How can I **scale** my application to internet scales?*
- *Why is my application so hard to **extend**?*
- *Why can't I **respond** quickly when **requirements change**?*


```
switch (elementItem)
```

```
{
```

```
case "header1:SearchBox" :
```

```
{
```

```
    __doPostBack("header1:doSearch");
```

```
    break;
```

```
}
```

```
case "Text1":
```

```
{
```

```
    window.event.returnValue=false;
```

```
    window.event.cancel = true;
```

```
    document.forms[0].elements[1].focus();
```

```
    break;
```

```
} ...
```

Pervasive Symptom:

Too much code!

Let's examine some
common problems
with *PPP solutions*:

Change
is *slow*
and *painful.*

Problem #1




[flickr.com/photos/arrrika](https://www.flickr.com/photos/arrrika)

Symptoms

- *Features* take *too long* to implement.
- We can't *react* fast enough to *change*.
- Users want to *customize* the system *themselves*.

Solution



(C Components) + (Lisp scripts) = Emacs

Components + Scripts
=
Applications

see John Ousterhout, IEEE Computer, March '98

Kernel Components

- *Statically-typed language:*
 - C, C++, Java, C#, ...
- *Compiled* for speed, efficiency.
- Access *OS services*, 3rd-party *libraries*.
- Lower developer *productivity*.

Scripts

- *Dynamically-typed language:*
 - Ruby, Lisp, JavaScript, Lua, ...
- *Interpreted* for agility.
- *Performance* less important.
- *Glue* together components.
- Raise developer *productivity*.

To be clear about typing,

- *Static typing*

- *compile time* checking.

- *Dynamic typing*

- *run time* checking.

In practice,
the *boundaries* between
components and scripts
are not so *distinct*...

Ola Bini's *Three Layers*

- *Stable* layer
 - JVM + generic libraries
- *Dynamic* layer
 - e.g., JRuby, application libs.
- *Domain* layer
 - *Internal* and *External* DSLs.

Other Examples:

- *UNIX/Linux* + *shells*.
- Also *find*, *make*, *grep*, ...
- Have their own *DSLs*.

C++/Lua Examples:

- *Adobe Lightroom*
 - 40-50% written in Lua.
- *Game Engines*

Embedded Systems:

- *Tektronix Oscilloscopes*: C + Smalltalk.
- *NRAO Telescopes*: C + Python.
- *Google Android*: Linux + libraries (C) + Java.


```
<view-state id="displayResults" view="/searchResults.jsp">
  <render-actions>
    <bean-action bean="phonebook" method="search">
      <method-arguments>
        <argument expression="searchCriteria"/>
      </method-arguments>
      <method-result name="results" scope="flash"/>
    </bean-action>
  </render-actions>
  <transition on="select" to="browseDetails"/>
  <transition on="newSearch" to="enterCriteria"/>
</view-state>
</flow>
```

**SpringSource just
acquired G2One
(Groovy and Grails).
Will they switch to
Groovy for configuration?**

x

Hopefully, SpringSource will de-emphasize XML and emphasize Groovy for configuration “wiring”.

Property-based Programming

```
/* Prototype JavaScript framework, version 1.6.0.
 * (c) 2005-2007 Sam Stephenson
 *
 * Prototype is freely distributable under the terms of an MIT-style license.
 * For details, see the Prototype web site: http://www.prototypejs.org
 *
 * -----*/
```

```
var Prototype = {
  Version: '1.6.0',
```

- Excellent for *malleable* objects.

```
  Browser: {
```

- See Steve Yegge's blog

- <http://steve-yegge.blogspot.com/2008/10/universal-design-pattern.html>

universal-design-pattern.html

- JavaScript, Lua, Self, ...

```
  BrowserFeatures: {
```

```
    XPath: !!document.evaluate,
```

```
    ElementExtensions: !!window.HTMLElement,
```

```
    SpecificElementExtensions:
```

```
      document.createElement('div').__proto__ &&
```

```
      document.createElement('div').__proto__ !== x
```

“Malleable” objects are those whose properties and behaviors may not be so clear cut. They may need to change over the life of the object.

Other Examples: Multilingual VM's

- On the *JVM*:
- JRuby, Groovy, Jython, Scala.
- Ruby on Rails on JRuby.

Other Examples: Multilingual VM's

- *Dynamic Language Runtime (DLR).*
- Ruby, Python, ... on the *.NET CLR.*

XML in Java


Why not *replace* XML
with *JavaScript*, *Groovy*
or *JRuby??*

De facto “scripting language” in Java.

Not an optimal choice:


- All data.
- No behavior (to speak of...).
- Verbose.

Benefits




- Optimize *performance* where it matters.
- Optimize *productivity*, *extensibility*, *agility* and *end-user customization* everywhere else.

Disadvantages



- More *complexity* with 2+ languages.
- *Interface* between the layers.
- *Splitting behavior* between layers.



An *underutilized*
architecture!


Parting Thought...

Why don't *Eclipse, IntelliJ*, etc.
have built-in *scripting engines*?

Parting Thought...

Cell phone makers ~~are~~ ^{were}
drowning in C++.

(One reason the *iPhone*
and *Android* are interesting.)



I don't
know what
my *code* is
doing.

Problem #2

[flickr.com/photos/dominic99/](https://www.flickr.com/photos/dominic99/)

The *intent*
of our *code*
is *lost*
in the *noise*.

Symptoms

- New team members have a long *learning curve*.
- The system *breaks* when we *change* it.
- Translating *requirements* to *code* is *error prone*.

Solution #1

Write
less code!

You're welcome.

Less Code

- Means *problems* are *smaller*:
 - Maintenance
 - Duplication
 - Testing
 - Performance
 - *etc.*

How to Write Less Code

- Root out *duplication*.
- Use *economical* designs.
 - *Functional* vs. *Object-Oriented*?
- Use *economical* languages.

Solution #2

Separate

implementation details
from *business logic*.

Domain Specific Languages

*Make the code read like
“structured” domain prose.*

Example DSL

```
internal {  
  case extension  
    when 100...200  
      callee = User.find_by_extension extension  
      unless callee.busy? then dial callee  
      else  
        voicemail extension  
      end  
    when 111 then join 111  
    when 888  
      play weather_report( 'Dallas, Texas' )  
    when 999  
      play %w(a-connect-charge-of 22  
        cents-per-minute will-apply)  
      sleep 2.seconds  
      play 'just-kidding-not-upset'  
      check_voicemail  
    end  
  }  
}
```

Adhearsion
=
Ruby DSL
+
Asterisk
+
Jabber/XMPP
+
...

DSL Advantages

- Code *looks* like domain prose:
- Is easier to understand by *everyone*,
- Is easier to *align* with the *requirements*,
- Is more *succinct*.


DSL Disadvantages

Many people are
poor API designers.

DSLs are *harder* to *design*.

DSL Disadvantages

DSLs can be **hard** to
implement, test, and debug.



ADSL *Tower of Babel?*

47

Brueghel the Elder

Not too many of this examples yet, but one comes to mind: mocking (for testing) frameworks in Ruby, BDD tools in several languages.

Parting Thought...

*Perfection is achieved,
not when there is nothing left to add,
but when there is nothing left to remove.*

-- Antoine de Saint-Exupery

Parting Thought #2...

*Everything should be made as **simple**
as possible, but not **simpler**.*

-- Albert Einstein

Corollary:

*Entia non sunt multiplicanda
praeter necessitatem.*

-- Occam's Razor


Corollary:

*All other things being equal,
the simplest solution is the best.*

-- Occam's Razor

We have
code duplication
everywhere.

Problem #3



deanwampler

Symptoms

- *Persistence logic* is embedded in *every* “domain” class.
- Error handling and logging is *inconsistent*.

Cross-Cutting Concerns.

Solution

*Aspect-Oriented
Programming*

Removing Duplication

- In order, use:
 - *Object* or *functional* decomposition.
 - *DSLs*.
 - *Aspects*.

An Example...


```
class BankAccount
  attr_reader :balance

  def credit(amount)
    @balance += amount
  end

  def debit(amount)
    @balance -= amount
  end

  ...
end
```

Clean Code

But, real applications need:

```
def BankAccount
  attr_reader :balance
  def credit(amount)
    ...
  end
  def debit(amount)
    ...
  end
end
```

Transactions

Persistence

Security

So credit becomes...

```
def credit(amount)
  raise “...” if unauthorized()
  save_balance = @balance
  begin
    begin_transaction()
    @balance += amount
    persist_balance(@balance)
```

...

...

```
rescue => error
```

```
  log(error)
```

```
  @balance = saved_balance
```


```
ensure
```

```
  end_transaction()
```

```
end
```

```
end
```



We're mixing *multiple domains*, with fine-grained *intersections*.



Objects alone *don't*
prevent *tangling*.

Aspect-Oriented
Programming:
restore *modularity* for
cross-cutting concerns.

Aspects restore *modularity* by encapsulating the *intersections*.




See “extra” slides

If you have used the
Spring Framework,
you have
used *aspects*.

Parting Thought...

Metaprogramming can be used for some *aspect-like* functionality.

DSLs can solve some *cross-cutting concerns*, by localizing behaviors expressed by the DSL.



Our service
must be
available 24x7
and highly
scalable.

Problem #4

Symptoms

- Only *one* of our developers *really knows* how to write *thread-safe* code.
- The system *freezes* every few *weeks* or so.

Solution

*Functional
Programming*

Functional Programming

Modeled after *mathematics*.

$$y = \sin(x)$$

Functional Programming

Values are *immutable*.
Variables are assigned *once*.

```
y = sin(x)
```

Functional Programming

Functions are *side-effect free*.

Functions don't alter *state*.

The *result* depends *solely*
on the *arguments*.

```
y = sin(x)
```


Functional Programming: *Concurrency* Is *Easier*

No *writes*, so no *synchronization*.
Hence, *no* locks, semaphores, mutexes...


$$y = \sin(x)$$

Functional Programming: *Reasoning* is *Easier*

Without *side effects*,
functions are *easier to test, understand, ...*
and *reuse!*


```
y = sin(x)
```

Which fits your needs?



Object Oriented

Which fits your needs?



Functional

What if you're doing *cloud computing*?

E.g., is map-reduce
object-oriented
or functional?



FP Code:
more *declarative*
than *imperative*.

$F(n) = F(n-1) + F(n-2)$
where: $F(0) = 0$ and $F(1) = 1$

0, 1, 1, 2, 3, 5, 8, 13, ...

... and so are DSLs.

```
class Customer < ActiveRecord::Base
  has_many :accounts
  validates_uniqueness_of :name,
    :on => :create,
    :message => 'Evil twin!'
end
```

A Few *Functional* Languages

Haskell

```
module Main where
```

```
-- Function f returns the n'th Fibonacci number.
```

```
-- It uses binary recursion.
```

```
f n | n <= 2 = 1
```

```
    | n > 2 = f (n-1) + f (n-2)
```

```
-- Print the Fibonacci number F(8)
```

```
main = print(show (f 8))
```

x

Note how closely the definition reads compared to the mathematical definition I presented earlier.

Erlang

- Ericsson Functional Language.
- For distributed, reliable, *soft* real-time, *highly* concurrent systems.
- Used in telecom switches.
 - *9-9's reliability* for AXD301 switch.

Erlang

- No *mutable variables* and *side effects*.
- Uses the *actor model* of concurrency.
 - All IPC is optimized *message passing*.
- *Let it fail* philosophy.
- *Very* lightweight and fast *processes*.
 - Lighter than most OS threads.

Scala

- Hybrid: *object* and *functional*.
- Targets the *JVM* and *.NET*.
- “*Endorsed*” by *James Gosling* at JavaOne.
- Could be the most popular *replacement* for Java.

Times Change...

InfoQ
439,108 Mar unique visitors

Tracking change and innovation in the enterprise software development community

News

Contribute

Register

Login

About us

Personal feed

The End of an Era: Scala Community Arrives, Java Deprecated

Posted by [Ryan Slobojan](#) on Apr 01, 2010

Community [Architecture](#), [Ruby](#), [Java](#)

Topics [Leadership](#), [Language](#), [InfoQ Announcements](#), [Change](#), [Careers](#)

Tags [migration](#), [Legacy Code](#)

Share  |        

...

Dean Wampler, Ph.D., the co-author of O'Reilly's "Programming Scala", offered this comment on the sudden industry switch to Scala vs. the less appealing alternatives:

We all know that object-oriented programming is dead and buried. Scala gives you a 'grace period'; you can use its deprecated support for objects until you've ported your code to use [Monads](#).

Note that date on this InfoQ post...

Clojure

- *Functional*, with *principled* support for mutability.
- Targets the *JVM* and *.NET*.
- Best *buzz*?
- Too many *good ideas* to name here...

Functional Languages in Industry

- *Erlang*
 - *CouchDB, Basho Riak, and Amazon's Simple DB.*
 - *GitHub*
 - *Jabber/XMPP server ejabberd.*

Functional Languages in Industry

- *OCaml*
 - Jane Street Capital
- *Scala*
 - Twitter
 - LinkedIn
- *Clojure*
 - Flightcaster

Parting Thought...

Which is better:

A *hybrid object-functional* language
for everything?

An *object* language for some code and
a *functional* language for other code?

e.g., *Scala* vs. *Java* + *Erlang*??

Recap:

Polyglot and *Poly-paradigm*
Programming (PPP)

Disadvantages of PPP

- *N* tool chains, languages, libraries, “ecosystems”, idioms, ...
- *Impedance mismatch* between tools.
- Different *meta-models*.
- *Overhead* of calls between languages.

Advantages of PPP

- Can use the *best tool* for a *particular job*.
- Can *minimize* the *amount* of code required.
- Can keep code *closer* to the domain using DSLs.
- Encourages *thinking* about *architecture*.

Is This *New*?


- *Functional Programming Comes of Age.*
- Dr. Dobbs, *1994*
- *Scripting: Higher Level Programming for the 21st Century.*
- *IEEE Computer, 1998*
- *In Praise of Scripting: Real Programming Pragmatism.*
- *IEEE Computer, 2008*

Why go *mainstream* now?

- *Rapidly increasing* pace of development,
 - Scripting (dynamic languages), DSLs.
- *Pervasive concurrency* (e.g., *Multicore CPUs*)
 - Functional programming.
- *Cross-cutting concerns*
 - Aspect-oriented programming.


Thank You!

- dean@deanwampler.com
- [@deanwampler](#)
- polyglotprogramming.com
- thinkbiganalytics.com



Extra Slides

Aspect-Oriented Tools

- Java
 - **AspectJ**
 - Spring AOP
 - JBoss AOP
 - Ruby
 - **Aquarium**
 - Facets
 - AspectR
- shameless plug* 

I would like to write...

Before returning the *balance*, *read* the current *value* from the database.

After setting the *balance*, *write* the current *value* to the database.

Before accessing the *BankAccount*, *authenticate* and *authorize* the *user*.

I would like to write...

Before returning the *balance*, read the current *value* from the database.

After setting the *balance*, write the current *value* to the database.

Before accessing the *BankAccount*, authenticate and authorize the user.

Aquarium

```
require 'aquarium'
class BankAccount
  ...
  after :writing => :balance \
    do |context, account, *args|
      persist_balance account
    end
  ...
end
```

use aquarium lib.

reopen class

“event” to trigger on

new behavior

Back to *clean code*

```
def credit(amount)
  @balance += amount
end
```


Common Themes

- *Less* code is *more*.
- Keep the code *close* to the *domain*: DSLs.
- Be *declarative* rather than *imperative*.
- *Minimize* side effects and mutable data.