Danfoss (no H Bridge needed)



acc. ISO13850

H Bridge



Power Input Connector



TITLE: Motor Driver, Power Input		REV: 1.0
EasyEDA	Company: agopengps.discourse.group	Sheet: 1/1
	Date: 2020-12-11 Drawn By: GoRoNb	

RS485 / ModbusRTU





e.g.: http://www.amazon.de/dp/B08JV9J36T/







QWIIC

CAN











Main connector





P1: Weidmuller 1289550000 + 1372870000
S2C-SMT 3.50/24/90LF 3.2SN BK BX + B2CF 3.50/24/180LH SN BK BX

TITLE: Serial Communication, PushIn Connector		REV: 1.0
EasyEDA	Company: agopengps.discourse.group	Sheet: 1/1
	Date: 2020-12-11 Drawn By: GoRoNb	

Ardusimple Onboard Module(s)





Wheel Angle Sensor



Option: Bynav-C1



Use Teensy Ethernet picktail to connect to Bynav Ethernet for configuration



IMU



TITLE: Sensors (RTK, ADC, IMU)		REV: 1.0
EasyEDA	Company: agopengps.discourse.group	Sheet: 1/1
	Date: 2020-12-11 Drawn By: GoRoNb	

USB Loops









Socket for all 59 contacts:
e. g. combination Fischerelektronik
MK 05 30 Z + MK 01 30 Z (2 pieces each)

GPIOs



GPIO, e. g. SPI



GPIO, e. g. IBT-2



GPIO, e. g. Serial
e.g.: https://de.aliexpress.com/item/2054995985.html



Ethernet



Protected General Propose Inputs











LED colors:
white: power
green/blue: serial data RxD/TxD
yellow/orange: I/O
red: error

TITLE: Teensy 4.1, USB, Inputs		REV: 1.0
EasyEDA	Company: agopengps.discourse.group	Sheet: 1/1
	Date: 2020-12-11 Drawn By: GoRoNb	

USB-C Power Delivery Role Swap



DC/DC 5V/9V/12/19.5V 3A



Switch Mode Power Supply 5V



TITLE: DCDC_USB-PD		REV: 1.0
EasyEDA	Company: Your Company	Sheet: 1/1
	Date: 2021-05-02 Drawn By: GoRoNb	