Advanced Data Management: Every Method with Practice, Solution and Gotcha

20 methods in the exam's order: compute (Part B), read a plan (Part C), buffer pool, argue a ticket (Part D). Each: the method, a practice question stated in full, its solution worked right underneath, the trap that costs points

Advanced Data Management, chapters 1–6

2026-11-01

How to use it in three hours. For each method: read the method box, cover the green *Solution* box, do the practice on paper, uncover and compare line by line, then read the red *Gotcha*. Every number was recomputed by a script from the data as stated. Formulas that the exam's formula sheet provides are marked [formula sheet] and used, not re-derived.

Order if short on time: §5 (index or scan), §8 (joins), §11–§13 (the plan: estimate, time, fix), §15 and §17 (EAT, flooding), §19 (tickets). Then §4, §7, §9, §10, §16, and §20 last as a self-test.

Concept: The database used in every practice: `bookly`, PostgreSQL 16, 8 KB pages

Table	Rows	Pages	Rows/page	Notes
`orders`	3,000,000	28,038	107	48 B of column data per row; columns `id, customer_id, product_id, order_ts, amount, status, country`; inserted in `id` and time order
`customers`	300,000	2,500	120	`customers_pkey` on `id`, fanout 250
`products`	50,000	500	100	

Indexes on `orders`: `orders_pkey` on `id` (fanout 250, 250 entries per leaf), `orders_cust_idx` on `customer_id` (3 levels, 350 entries per leaf), `orders_ts_idx` on `order_ts` (3 levels, 350 per leaf, correlation 0.98). `pg_stats`: `status` MCV `shipped` 0.80, `pending` 0.15, `returned` 0.05; `country` MCV `MA` 0.60, `FR` 0.20; `product_id` 50,000 distinct, no MCV list; `customer_id` 300,000 distinct (10 orders per customer); `order_ts` uniform over 730 days; `amount` uniform 5–205, histogram of 10 equi-depth buckets with bounds $5, 25, 45, \ldots, 205$. Prices: `seq_page_cost` 1, `random_page_cost` 4, `cpu_tuple_cost` 0.01, `cpu_index_tuple_cost` 0.005, `cpu_operator_cost` 0.0025. Devices: RAM 0.1 μs, SSD 100 μs, HDD 10 ms per random page; sequential 500 MB/s. `work_mem` 4 MB (512 pages) unless stated.

Contents

1 Which component owns the symptom 3

2 Storage estimate and what VACUUM does 4

3 B^+ tree height, lookup, latency **5**

4 Selectivity and estimated rows **6**

5 Index or scan: pages touched, with the correlation **7**

6 Which index form **9**

7 External sort and "what changes with M" **10**

8 Join cost comparison **11**

9 The tree: blocking or streaming, and why LIMIT does not help **12**

10 Node-line arithmetic: loops, rows, time, Buffers **14**

11 Where an estimate comes from, the failure, the command **15**

12 Where the time goes **16**

13 Choosing the fix: what each proposal changes in the plan **17**

14 Reconstruct the query from the plan **19**

15 Effective access time and hit ratio **20**

16 Replacement trace: LRU, FIFO, clock **20**

17 Sequential flooding, rings, sizing the pool **22**

18 Steal, no-force, WAL: what the log must hold **23**

19 The ticket method, with three worked tickets **24**

20 Quick checks: the letter and the one line **25**

A Computing: the Part B situations

1 Which component owns the symptom

Method

The idea. A query passes through five stages, each with one job: **parser** (grammar only) → **binder** (every name, type and permission against the catalog) → **rewriter** (algebra: views, pushdown) → **planner** (access path, join algorithm and order, by cost from statistics) → **executor** (runs the plan through the buffer pool). Beside them: the transaction manager (locks, log) and the catalog (schema and statistics).

1. Ask "what information was needed to notice the problem?" Grammar → parser. Existence of a name, a type, a right → binder. A cost or a row count → planner, and if the count is wrong, statistics. A page that was not in memory → buffer pool. Two transactions → transaction manager.
2. Name the component *and* the object it consulted (grammar, catalog, statistics, page table, lock table).

Practice

Given. Six symptoms on `bookly`: (a) `SELCT * FROM orders;` fails. (b) `WHERE custmer_id = 5` fails. (c) `SUM(status)` fails. (d) A query reads all 28,038 pages of `orders` although `orders_ts_idx` would touch 1,200. (e) The same query's `rows=` is 100 times below `actual rows`. (f) Two payroll jobs wait on each other forever.

Your task. For each: the component, what it consulted, and one phrase of why.

Solution

(a) **Parser**, the grammar: `SELCT` is not a keyword, the statement does not parse. (b) **Binder**, the catalog (`pg_attribute`): the statement is grammatical, but no column of that name exists. (c) **Binder**, the catalog types: `status` is text, `SUM` needs a number; a type error is a binding error. (d) **Planner**, the cost model: it chose the Seq Scan because its costing said so; if the choice is wrong with correct statistics, the cost constants are off (`random_page_cost` 4 on an SSD). (e) **Statistics**, `pg_stats`: a 100× estimate error is stale or correlated statistics, fixed by `ANALYZE` or `CREATE STATISTICS`, not by the planner. (f) **Transaction manager**, the lock table: a deadlock, detected by the waits-for cycle, one job is aborted.

Gotcha

"The parser rejects a misspelled column": the parser knows no columns. "The executor chose the scan": it only runs what the planner chose. A wrong estimate is a statistics problem even when the symptom is a bad plan.

2 Storage estimate and what VACUUM does

Method

1. record = column bytes +24 (tuple header), rounded *up* to a multiple of 8.
2. rows per page $r = \lfloor (8192 - 24)/(\text{record} + 4) \rfloor$: 24 B page header, 4 B slot per row, floor because rows never straddle pages.
3. pages $B = \lceil N/r \rceil$; size = $8B$ KB. Compare with `pg_relation_size`: a larger file means dead tuples or TOAST.
4. time of a sequential scan = $8B$ KB / 500 MB/s; of p random pages = $p\times$ device latency.
5. **VACUUM** marks dead tuples' space reusable inside each page and truncates only empty *trailing* pages: after a scattered delete the file keeps its size. **VACUUM FULL** and **CLUSTER** rewrite the file to $\lceil \text{live rows}/r \rceil$ pages.

Practice

Given. `orders`: 3,000,000 rows, 48 B of column data per row.

Your task. (a) Rows per page, pages, size in MB. (b) Time of one sequential scan, and of 1,000 random page reads on SSD and on HDD. (c) 40 % of the rows are deleted at random and a normal `VACUUM` runs: pages in the file? Then `VACUUM FULL`: pages?

Solution

(a) record = $48 + 24 = 72$ B (a multiple of 8 already); per row on the page $72 + 4 = 76$ B; $r = \lfloor 8168/76 \rfloor = \lfloor 107.5 \rfloor = 107$; $B = \lceil 3{,}000{,}000/107 \rceil = 28{,}038$ pages; size = $28{,}038 \times 8$ KB = 219 MB.

(b) Sequential: 219 MB /500 MB/s = 0.44 s. Random: $1{,}000 \times 100\,\mu$s = 0.1 s on SSD; $1{,}000 \times 10$ ms = 10 s on HDD. One thousand random pages on an HDD cost 23 times more than reading the whole table sequentially: that is why "pages touched, and in what order" is the whole cost question.

(c) After `VACUUM`: still 28,038 pages. The dead rows are scattered over every page, so no trailing page is empty and nothing is truncated; the freed space inside pages is reused by future inserts. After `VACUUM FULL`: live rows = 1,800,000, $\lceil 1{,}800{,}000/107 \rceil = 16{,}823$ pages (131 MB), a rewrite under an exclusive lock.

Gotcha

Dividing by the column bytes alone (gives 170 rows per page). Forgetting the floor. "VACUUM shrinks the file". Counting rows where the question is pages.

3 B$^+$ tree height, lookup, latency

Method

1. Height h: the smallest h with $F^h \geq N$, bracket N between powers of the fanout [formula sheet]. Typical 3–4; never $\log_2 N$.
2. Point lookup $= h$ index pages $+1$ heap page. Absent key: h. Index-only: h.
3. Range of k matches $= h + (\lceil k/L \rceil - 1)$ leaf pages + heap pages [formula sheet]: $\lceil k/r \rceil$ if the heap is in key order, k if scattered, 0 if index-only.
4. Time = reads $\times$ device latency; levels that are cached cost the RAM price. Say which target is met and what to buy.

Practice

Given. `orders_pkey`: 3,000,000 entries, fanout 250, 250 entries per leaf. `GET /orders/{id}` must answer in 1 ms.

Your task. (a) Height and page reads per lookup. (b) Latency cold on SSD and on HDD. (c) Root and second level always cached: latency on SSD. (d) A range of 10,000 consecutive ids: page reads, knowing that `orders` is stored in `id` order; and if it were not.

Solution

(a) $250^2 = 62{,}500 < 3{,}000{,}000 \leq 250^3 = 15{,}625{,}000$, so $h = 3$. Lookup $= 3 + 1 = 4$ page reads.

(b) SSD: $4 \times 100\,\mu\text{s} = 0.4$ ms, the target is met. HDD: 4×10 ms $= 40$ ms, missed by $40\times$.

(c) Two hits at $0.1\,\mu$s and two reads (leaf, heap) at $100\,\mu$s: ≈ 0.2 ms. On an HDD it would still be 20 ms: the device, not the cache, decides.

(d) Index pages $= 3 + \lceil 10{,}000/250 \rceil - 1 = 3 + 40 - 1 = 42$. Heap in key order: $\lceil 10{,}000/107 \rceil = 94$ contiguous pages: total 136 reads. Scattered heap: 10,000 random pages: total 10,042, 74 times more. The heap order, not the index, decides a range's cost.

Gotcha

$\log_2 3{,}000{,}000 \approx 22$ levels: that is a binary tree. Forgetting the heap page. Charging cached levels at the device price. Counting matching rows when the heap is in key order (it is pages).

4 Selectivity and estimated rows

Method

The rules are on the formula sheet [formula sheet]; the method is *where to read each number*.

1. Equality: is the value in `most_common_vals`? Yes: its frequency. No: $(1 - \text{null_frac} - \sum \text{MCV freqs})/(n_{\text{distinct}} - \#\text{MCV})$; no MCV list at all: $1/n_{\text{distinct}}$.
2. Range: count whole histogram buckets on the right side of the bound, add the linear share of the bucket that contains it, divide by the number of buckets.
3. Combine under independence: AND multiplies, OR adds minus the product, NOT complements.
4. rows $= sN$. Join: $|R||S|/\max(d_R, d_S)$; a key–foreign-key join returns the foreign-key side after its filters.
5. Then say whether independence is believable (correlated columns make the AND an underestimate).

Practice

Given. The `bookly` statistics.

Your task. Estimated rows for: (a) `status = 'returned' AND country = 'FR'`; (b) `amount > 165`; (c) `status = 'returned' OR country = 'FR'`; (d) `product_id = 777`; (e) `orders JOIN customers ON customer_id = id`; (f) `order_ts >= now() - interval '30 days'`. (g) Which of (a)–(f) would you distrust, and why?

Solution

(a) Both in the MCV lists: $0.05 \times 0.20 = 0.01$; $0.01 \times 3{,}000{,}000 = 30{,}000$ rows.
(b) Bounds $5, 25, \ldots, 205$: bucket boundaries every 20; 165 is the boundary between buckets 8 and 9, so two whole buckets lie above it: $2/10 = 0.2$; 600,000 rows.
(c) $0.05 + 0.20 - 0.05 \times 0.20 = 0.24$; 720,000 rows.
(d) No MCV list: 1/50,000; $3{,}000{,}000/50{,}000 = 60$ rows.
(e) $|R||S|/\max(d) = 3{,}000{,}000 \times 300{,}000/300{,}000 = 3{,}000{,}000$: every order has one customer, the join returns the foreign-key side.
(f) Uniform over 730 days: $s = 30/730 = 0.0411$; 123,288 rows.
(g) (a): returns and country are plausibly correlated (a country with a different returns policy); the product is then an under-estimate, and the fix is `CREATE STATISTICS (dependencies) ON status, country`. (d) is also fragile: a uniform guess on a column that surely has best-sellers; a longer MCV list (`SET STATISTICS 1000`) fixes it.

Gotcha

Adding for AND (0.25). Using $1/d$ for a value that is in the MCV list. Counting the bucket that contains the bound as whole. $\min(d)$ or $d_R + d_S$ in the join size.

5 Index or scan: pages touched, with the correlation

Method

The idea. An index scan costs what it touches in the *heap*, and that depends on where the matching rows sit, not on how many there are.

1. s and $k = sN$ from §4.
2. Read `pg_stats.correlation` for the column. Near ± 1 (append-only, after CLUSTER): the k rows are contiguous, heap pages $= \lceil k/r \rceil \approx sB$. Near 0: scattered, expected heap pages $= B\,(1-(1-s)^r)$; compute $(1-s)^r = e^{r\ln(1-s)}$; when $sr \geq 3$ it is practically every page.
3. Index cost = descent (h random pages) + leaf pages ($\lceil k/L \rceil$, sequential) + heap pages (sequential price if contiguous, random price 4 if scattered) + per-row CPU ($0.015\,k$). Seq Scan $= B + 0.01N + 0.0025N$ per predicate [formula sheet].
4. Between the plain-index threshold and a few percent, a **bitmap scan** reads the same scattered pages once, in physical order: cheaper than a plain index scan, rarely much cheaper than a Seq Scan in I/O.
5. Add the write price (one random page per index per INSERT) and decide in one sentence that quotes both costs.

Practice

Given. The dashboard runs `SELECT country, count(*) FROM orders WHERE order_ts >= now() - interval '30 days' GROUP BY country` every minute. A colleague says "a 4 % filter can never use an index, drop `orders_ts_idx`". Separately, the returns team wants `CREATE INDEX ON orders (status)` for `WHERE status = 'returned'` (5 %).

Your task. (a) For the 30-day filter: k, heap pages, Seq Scan cost, Index Scan cost, winner and factor. (b) For `status = 'returned'` with the proposed index: heap pages touched, Index Scan cost, bitmap scan cost in pages, decision. (c) What index *would* make the returns report cheap, and how many pages would it read?

Solution

(a) $s = 30/730 = 0.0411$, $k = 123{,}288$. Correlation 0.98: contiguous, heap pages $= \lceil 123{,}288/107 \rceil = 1{,}153$. Seq Scan $= 28{,}038 + 30{,}000 + 7{,}500 = 65{,}538$. Index Scan = descent $3 \times 4 = 12$ + leaves $\lceil 123{,}288/350 \rceil = 353$ + heap 1,153 (sequential) + CPU $123{,}288 \times 0.015 = 1{,}849$: total 3,367. The index wins by $65{,}538/3{,}367 \approx 19\times$. Decision: keep it; the "4 % never" rule assumes scattered rows, and these are the last 1,153 pages of the file. A BRIN index on `order_ts` would do the same job in a few pages.

(b) $s = 0.05$, $k = 150{,}000$; `status` has no physical order, correlation ≈ 0. $(1 - 0.05)^{107} = e^{107 \times \ln 0.95} = e^{-5.49} = 0.0041$, so heap pages $= 28{,}038 \times (1 - 0.0041) = 27{,}922$: 99.6 % of the table, about 5 returns per page. Index Scan $= 12 + \lceil 150{,}000/350 \rceil (= 429) + 4 \times 27{,}922 + 150{,}000 \times 0.015 = 12 + 429 + 111{,}688 + 2{,}250 = 114{,}379$, almost double the Seq Scan. Bitmap scan: the same 27,922 pages once, in order, plus 429 leaf pages: $\approx 28{,}351$ pages against 28,038 for the Seq Scan, a draw in I/O (the planner may still prefer it in cost units because it skips the per-row CPU of non-matching rows, but it reads the whole table). Decision: the index on `status` buys nothing and costs a random write per insert; do not create it.

(c) A **covering** index, `CREATE INDEX ON orders (status) INCLUDE (customer_id, amount)` (or a partial one, `WHERE status = 'returned'`, if the report always filters on returns): an index-only scan reads $\lceil 150{,}000/350 \rceil = 429$ leaf pages and *no* heap page (`Heap Fetches: 0` once VACUUM has set the visibility map), 65 times fewer pages than the Seq Scan. The heap pages were the cost; remove the need to visit them.

Gotcha

Deciding from s alone ("5 % is small, index"). Using the scattered formula on an append-ordered column, or the contiguous one on a random column. Counting k random reads when $k > B$ (the formula caps at B). Forgetting that a bitmap scan still reads the pages.

6 Which index form

Method

Match the predicate to the index that can *descend* on it:

- B-tree on one column: $=$, $<$, BETWEEN, ORDER BY, LIKE `'abc%'` on that column.
- Composite (a, b): sorted by a then b; serves a, a AND b, $a =$ AND $b >$; not b alone. Equality columns first, the range column last.
- Expression (`lower(email)`): serves exactly `WHERE lower(email) = ...`
- Partial `WHERE status = 'pending'`: small; used only when the query repeats the predicate.
- Covering `INCLUDE (cols)`: index-only scan when every needed column is in the index.
- BRIN: min/max per block range; only a physically ordered column (append-only time stamps), tiny.
- Hash: $=$ only. No index: a predicate keeping tens of percent, or a column written far more than read.

Practice

Given. Seven queries on `orders`: (1) `WHERE customer_id = ? AND order_ts > ?`; (2) `WHERE lower(email) = ?` on `customers`; (3) the pending-orders screen `WHERE status = 'pending' ORDER BY order_ts` (15 % of rows, read every second); (4) `SELECT customer_id, amount WHERE order_ts BETWEEN ? AND ?`; (5) `ORDER BY order_ts DESC LIMIT 10`; (6) `WHERE country = 'MA'` (60 %); (7) a 2 TB append-only log table queried by month once a week.

Your task. The index to create (or none), and why, one line each.

Solution

(1) Composite `(customer_id, order_ts)`: equality first, range last; one descent lands on the customer's rows in time order. (2) Expression index `ON customers (lower(email))`; an index on `email` cannot be searched for `lower(email)`. (3) Partial `ON orders (order_ts) WHERE status = 'pending'`: 15 % of a 3 M table is 450,000 entries, sorted by time, and the index shrinks as orders ship; a plain index on `status` would be read 99 % of the table (see §5). (4) Covering `ON orders (order_ts) INCLUDE (customer_id, amount)`: index-only range, `Heap Fetches: 0`; or `orders_ts_idx` as it is, since correlation 0.98 already makes the heap pages contiguous. (5) B-tree on `order_ts`: the planner walks the leaves backwards and stops after 10 rows, no sort. (6) None: 60 % of the rows touch every page; a Seq Scan is the right plan. (7) BRIN on the time stamp: a few hundred KB for 2 TB, prunes whole block ranges; a B-tree would be tens of GB for a weekly query.

Gotcha

Composite in the wrong order (range first). An index on `email` "for" `lower(email)`. Indexing a 60 % value. BRIN on a column with no physical order.

7 External sort and "what changes with M"

Method

1. runs $= \lceil B/M \rceil$ (pass 0 sorts M pages at a time). Fan-in $= M - 1$ (one buffer for the output).
2. merge passes: divide the run count by $M - 1$ with a ceiling, repeat until 1, count the divisions [formula sheet].
3. total I/O $= 2B \times (1 +$ merge passes): every pass reads and writes all B pages.
4. "What changes with M'": recompute; a doubling removes at most one merge pass. One merge pass needs $\lceil B/M \rceil \leq M - 1$; no merge pass at all needs $M \geq B$.
5. PostgreSQL: `Sort Method: external merge Disk: x kB` means spilled; `work_mem` $\geq x$ makes it `quicksort Memory`. Set it with `SET LOCAL` inside the transaction.

Practice

Given. Nightly `ORDER BY amount` on `orders` (28,038 pages), $M = 100$. The DBA says "double `work_mem` and the sort will take half the time".

Your task. (a) Runs, merge passes, total I/O at $M = 100$. (b) At $M = 200$. (c) Is the DBA right? The smallest M that gives one merge pass, and the M that gives no merge pass at all, in pages and MB.

Solution

(a) Runs $= \lceil 28{,}038/100 \rceil = 281$. Fan-in 99: $281 \to \lceil 281/99 \rceil = 3 \to 1$: two merge passes. I/O $= 2 \times 28{,}038 \times (1 + 2) = 168{,}228$.

(b) Runs $= \lceil 28{,}038/200 \rceil = 141 \leq 199$: one merge pass. I/O $= 2 \times 28{,}038 \times 2 = 112{,}152$.

(c) From 168,228 to 112,152 is one third less, not half: passes are a ceiling of a logarithm, and the doubling removed exactly one merge pass. One merge pass needs $\lceil 28{,}038/M \rceil \leq M - 1$, i.e. $M(M-1) \geq 28{,}038$: $M = 168$ ($168 \times 167 = 28{,}056$), so 200 was already past the useful point and 400 would change nothing. No merge pass needs the whole input in memory, $M \geq 28{,}038$ pages $= 219$ MB of `work_mem`; then the sort reads once and writes nothing.

Gotcha

Fan-in M instead of $M - 1$. Forgetting pass 0 in the total. Counting reads only. "Doubling memory halves the time".

8 Join cost comparison

Method

1. Write the data: $B_R, B_S, |R|, |S|, M$, distinct values, indexes, existing order. The smaller input is the outer (nested loop) or the build (hash).
2. For each algorithm settle the "fits" case first, then its formula [formula sheet]: block NL chunks $= \lceil B_R/(M-2) \rceil$; hash in memory iff $B_{\text{build}} \leq M$, else Grace $3(B_R + B_S)$; sort-merge pays the *full* external sort (§7) of each unsorted input, then $B_R + B_S$; index NL $= B_R + |R| \times (h +$ matching heap pages).
3. Pick the minimum. Name the trap answers (rows where pages belong; M for $M-2$).
4. Say when the loser wins: more memory (both read each input once), an index with a tiny outer, sorted output wanted.
5. ORDER BY on the result: aggregate first, then sort the groups, never the big input.

Practice

Given. Payroll joins `customers` (R: 2,500 pages, 300,000 rows) with `orders` (S: 28,038 pages) on `customer_id`, sums `amount` per customer, ordered by `customer_id`. `orders_cust_idx` exists (3 levels); each customer has 10 orders, scattered. $M = 50$, then $M = 3{,}000$.

Your task. (a) Block nested loop. (b) Hash join. (c) Sort-merge join. (d) Index nested loop with `customers` outer. (e) Redo (a)–(c) at $M = 3{,}000$, decide, and say how to get the sorted output.

Solution

(a) $M = 50$, block NL. Chunks $= \lceil 2{,}500/48 \rceil = 53$; cost $= 2{,}500 + 53 \times 28{,}038 = 1{,}488{,}514$ page I/Os: `orders` read 53 times.

(b) Hash. Build $=$ `customers`, $2{,}500 > 50$: Grace, $3 \times (2{,}500 + 28{,}038) = 91{,}614$. Sixteen times cheaper than the block NL.

(c) Sort-merge. `orders`: runs $\lceil 28{,}038/50 \rceil = 561$, fan-in 49: $561 \to 12 \to 1$, two merge passes, $2 \times 28{,}038 \times 3 = 168{,}228$. `customers`: runs 50, $50 \to 2 \to 1$, two merge passes, $2 \times 2{,}500 \times 3 = 15{,}000$. Merge 30,538. Total 213,766.

(d) Index NL. $2{,}500 + 300{,}000 \times (3 + 10) = 3{,}902{,}500$: every customer costs a descent plus 10 random heap pages; the worst of all, because the outer is not tiny.

(e) $M = 3{,}000$. Block NL: $\lceil 2{,}500/2{,}998 \rceil = 1$ chunk, 30,538. Hash: build fits, 30,538. Sort-merge: `orders` runs $\lceil 28{,}038/3{,}000 \rceil = 10$, one merge pass, 112,152; `customers` fits in memory, 2,500; merge 30,538; total 145,190. Decision: the hash join with `customers` as build (2,500 pages $= 20$ MB of `work_mem`); block NL ties in I/O but does $300{,}000 \times 3{,}000{,}000$ comparisons in memory. Sorted output: HashAggregate the join (300,000 groups, a few tens of MB) and sort the 300,000 result rows, not the 28,038-page input; or, if memory is tight, the sort-merge join delivers the result already in `customer_id` order, which is the one case where its 145,190 buys something.

Gotcha

$|R| = 300{,}000$ in the block NL formula (that is the simple nested loop, 8×10^9). M instead of $M - 2$. A sort-merge without the sort cost. Sorting the big input for ORDER BY.

B Reading a real plan: the Part C questions

The plan used in §9–§13 is the real `EXPLAIN (ANALYZE, BUFFERS)` of the returns dashboard of `bookly`, `work_mem` 4 MB, parallelism off:

```
SELECT c.name, count(*) AS n, sum(o.amount) AS refunded
FROM orders o JOIN customers c ON c.id = o.customer_id
WHERE o.status = 'returned' AND o.country = 'FR'
GROUP BY c.name ORDER BY refunded DESC LIMIT 20;
```

```
Limit  (cost=115982.1..115982.2 rows=20)
       (actual time=3480.2..3480.3 rows=20 loops=1)
  Buffers: shared hit=458038 read=50000
  ->  Sort  (cost=115982.1..116057.1 rows=30000)
            (actual time=3480.1..3480.2 rows=20 loops=1)
        Sort Key: (sum(o.amount)) DESC
        Sort Method: top-N heapsort  Memory: 27kB
        ->  HashAggregate  (cost=114632.1..114932.1 rows=30000)
                  (actual time=3440.6..3462.3 rows=98210 loops=1)
              Group Key: c.name
              ->  Nested Loop  (cost=0.42..114482.1 rows=30000)
                        (actual time=0.3..3390.8 rows=120000 loops=1)
                    ->  Seq Scan on orders o
                          (cost=0.00..65538.0 rows=30000)
                          (actual time=0.1..410.5 rows=120000 loops=1)
                          Filter: ((status = 'returned') AND (country = 'FR'))
                          Rows Removed by Filter: 2880000
                          Buffers: shared hit=28038
                    ->  Index Scan using customers_pkey on customers c
                          (cost=0.42..1.63 rows=1)
                          (actual time=0.020..0.024 rows=1 loops=120000)
                          Index Cond: (id = o.customer_id)
                          Buffers: shared hit=430000 read=50000
Planning Time: 0.3 ms
Execution Time: 3482.0 ms
```

9 The tree: blocking or streaming, and why LIMIT does not help

Method

1. Indentation gives the children. The first child of a join is the outer (or probe) side, the second the inner (or build) side. Draw it top-down, arrows from child to parent.
2. Tag each node. **Blocking** (all input before the first output): Sort, Hash build, HashAggregate, Materialize, Bitmap Index Scan. **Streaming**: Seq/Index/Bitmap Heap Scan, Filter, Limit, Nested Loop, Merge Join, hash probe, GroupAggregate on sorted input. One phrase of why per node.
3. Consequence: nothing above a breaker starts before it finishes; a LIMIT above a breaker saves only the breaker's output phase. Execution starts at the leftmost leaf of the deepest breaker.

Practice

Given. The plan above.

Your task. Draw the tree (six nodes); tag each blocking or streaming with a phrase; say why `LIMIT 20` leaves the query at 3.5 s, reading it off the `actual time` values.

Solution

Limit ← Sort ← HashAggregate ← Nested Loop {outer: Seq Scan `orders`; inner: Index Scan `customers`, once per outer row}.

Node	Blocking?	Why
Seq Scan orders	no	tests the filter row by row and passes survivors on
Index Scan customers	no	one lookup per outer row, the match is emitted at once
Nested Loop	no	emits each (order, customer) pair as the inner returns it
HashAggregate	**yes**	a customer's sum is final only after its last order
Sort	**yes**	the largest sum is known only when every group is in
Limit	no	forwards the first 20 rows it receives, then stops

The join ends at 3,390.8 ms; the HashAggregate's first output is at 3,440.6 ms (it waited for the whole join); the Sort's first row is at 3,480.1 ms; the Limit gets its 20 rows at 3,480.3 ms. The LIMIT saved only the sort's output (hence `top-N heapsort` in 27 kB); the 3.4 s were spent below two breakers that cannot stop early.

Gotcha

Calling the Nested Loop blocking (it streams; its *inner lookups* are what is slow). Calling the Limit the slow node because it is on top. A Bitmap Heap Scan streams; a Bitmap Index Scan blocks.

10 Node-line arithmetic: loops, rows, time, Buffers

Method

1. `cost=start..total rows=est`: the planner's belief. `actual time=first..last rows=act loops=n`: measured, *per loop*. Totals: rows = act × loops, time = last × loops.
2. q-error of a node = max(est/act, act/est) on the *total* rows.
3. `Buffers: shared hit=h read=r`: pages requested, children included; hit ratio = $h/(h+r)$; `read` means not in `shared_buffers` (OS cache or disk). `temp read/written` means a sort or hash spilled.
4. Pages per inner lookup = $h_{\text{tree}} + 1$; expected total = loops × that; compare with hit + read.

Practice

Given. The inner Index Scan of the plan: `rows=1 loops=120000`, `actual time=0.020..0.024`, `Buffers: shared hit=430000 read=50000`; `customers_pkey` has 3 levels.

Your task. (a) Rows and time the inner side produced in total. (b) q-error of the Seq Scan and of the Nested Loop. (c) Expected pages for the inner side, and whether `hit + read` agrees. (d) Hit ratio of the inner side and of the whole query; is either number useful?

Solution

(a) Rows = 1 × 120,000 = 120,000; time = 0.024 ms ×120,000 = 2,880 ms: the inner lookups are 2.9 of the 3.5 seconds.

(b) Seq Scan: est 30,000, act 120,000, q-error = 4, an under-estimate. Nested Loop: est 30,000, act 120,000, q-error 4: inherited unchanged from its outer child (one match per order).

(c) 120,000 × (3 + 1) = 480,000 pages; `hit` + `read` = 430,000 + 50,000 = 480,000. Exactly: three index pages and one heap page per lookup. The index pages are hot (hit); 50,000 of the heap page fetches missed.

(d) Inner: 430,000/480,000 = 89.6 %. Whole query: 458,038/508,038 = 90.2 %. Neither tells the story: the cost is the 50,000 random `read`s on one node. Read `Buffers` per node and look at `read`, not at a ratio.

Gotcha

Reading `rows=1` on the inner side as "one row" (it is per loop). Reading `actual time=a..b` as a duration (first row, last row). "`read` means disk". Judging by the global hit ratio.

11 Where an estimate comes from, the failure, the command

Method

1. Rebuild the planner's arithmetic: scan `rows=` = (MCV frequency, or $1/d$, or histogram share) $\times N$; each extra predicate multiplies by its own selectivity (independence); join `rows=` by the join formula.
2. Compare with `actual rows`: q-error. Find the *lowest* node where it is large: that is the cause; everything above inherits it.
3. Name the failure and its fix: **stale statistics** (`n_live_tup` $\neq$ `reltuples`, old `last_analyze`) $\rightarrow$ `ANALYZE t`; **correlated columns** (single frequencies right, product wrong; ANALYZE changes nothing) $\rightarrow$ `CREATE STATISTICS s (dependencies) ON a, b FROM t; ANALYZE t`; **skew** (a rare value estimated at $1/d$) $\rightarrow$ `ALTER TABLE t ALTER COLUMN c SET STATISTICS 1000; ANALYZE t`.
4. Say what estimate the fix produces and what the planner will do with it.

Practice

Given. The Seq Scan line: `rows=30000`, actual 120,000; `pg_stats`: `returned` 0.05, `FR` 0.20, both fresh (`last_analyze` ten minutes ago).

Your task. (a) Where does 30,000 come from? (b) q-error and direction, and why that direction is dangerous here. (c) The failure, whether `ANALYZE orders` helps, the command, the new estimate.

Solution

(a) $0.05 \times 0.20 = 0.01$; $0.01 \times 3{,}000{,}000 = 30{,}000$: two MCV frequencies multiplied under independence.

(b) $120{,}000/30{,}000 = 4$, an *under*-estimate. With 30,000 outer rows the planner priced the inner lookups at $30{,}000 \times 1.63 \approx 49{,}000$ units and chose the nested loop; with the true 120,000 rows they cost four times more, and the random heap reads behind them are the 2.9 s. Under-estimates buy per-row plans for inputs that are not small.

(c) Correlated columns: French orders are returned four times more often than average, so `status` and `country` are not independent. `ANALYZE` does not help: both single-column frequencies are already right; the product is the error. Fix:

```
CREATE STATISTICS s_ret (dependencies) ON status, country FROM orders;
ANALYZE orders;
```

The planner then scales the product by the measured dependency and estimates about 120,000, and at 120,000 it switches to a hash join (§13).

Gotcha

"Run ANALYZE" for a correlation error. Fixing the top node. Adding an index for an estimate error (symptom, not cause). Forgetting the `ANALYZE` after `CREATE STATISTICS` (the object exists, the numbers do not).

12 Where the time goes

Method

1. Per node, compute the span: `last` × `loops`; subtract the children to get the node's own time. The node with the biggest own time owns the seconds.
2. Convert that node's work into pages: scan = pages of the table (or `Heap Blocks` for a bitmap scan, from the scattered-pages formula); inner side = loops $\times(h+1)$, split into `hit` and `read`.
3. seconds $\approx$ `read` × random price (50–100 μs SSD, 10 ms HDD) + `hit` $\times 0.1\,\mu$s + CPU per row. Check against the measured time.
4. Say in one sentence what the fix must change: the number of random reads, the number of loops, or the number of pages scanned.

Practice

Given. The plan. `customers` is 2,500 pages (20 MB); `shared_buffers` is 128 MB but busy with `orders`; a random SSD read costs 60 μs here.

Your task. (a) Own time of the Seq Scan, the inner lookups, the HashAggregate and the Sort. (b) Explain `hit=430000 read=50000` and estimate the seconds from the reads. (c) If the planner had used a bitmap scan on an index on `status`, how many `Heap Blocks` would it have shown, and would it have saved time? (d) The one sentence: what must the fix change?

Solution

(a) Seq Scan: 410.5 ms. Inner lookups: $0.024 \times 120{,}000 = 2{,}880$ ms. Nested Loop's own overhead: $3{,}390.8 - 410.5 - 2{,}880 \approx 100$ ms. HashAggregate: $3{,}462.3 - 3{,}390.8 = 72$ ms. Sort: 18 ms. The inner lookups own 83 % of the time.

(b) 120,000 lookups × 4 pages = 480,000. The three index pages per lookup are the same hot pages every time: hits. The heap page differs per customer: 98,210 distinct customers spread over 2,500 pages, but `customers`' pages keep getting evicted by `orders` traffic, so 50,000 of the fetches missed. $50{,}000 \times 60\,\mu\text{s} = 3.0$ s, which matches the 2.9 s measured: the time is the random heap reads of `customers`.

(c) `status = 'returned'` is 5 % of rows with no physical order: $28{,}038 \times (1 - 0.95^{107}) = 27{,}922$ heap blocks, 99.6 % of the table. The bitmap scan would read what the Seq Scan reads, in the same order: no time saved, and the 2.9 s of the join untouched.

(d) The fix must remove the 120,000 random lookups, not speed up the scan: get the estimate right so that the planner joins by hashing (§13), or make `customers` resident.

Gotcha

Fixing the scan (indexes, CLUSTER) when the join owns the time. Summing `actual time` of nested nodes twice (children are included in the parent's span). Costing a `read` as a disk seek when it was the OS cache (hence 60, not 100, μs).

13 Choosing the fix: what each proposal changes in the plan

Method

For every proposal, say what changes in four places: the **plan lines**, the **pages** (`Heap Blocks`, `Buffers`), the **estimate**, the **time**. Then order the proposals by what they cost to apply.

Proposal	What it changes
extended statistics	estimate right → join algorithm and order change; nothing else; two commands, no lock
`ANALYZE`	only stale counts
composite index on the filter columns	`Filter` moves into `Index Cond`; pages unchanged if the rows are scattered; estimate unchanged; a slower insert
CLUSTER on an index	correlation → 1: `Heap Blocks` → $\lceil k/r \rceil$, the scan collapses; the join is untouched; a one-off rewrite under lock, decays with new rows
covering / partial index	index-only scan, `Heap Fetches: 0`: no heap pages at all for that predicate
`work_mem`	`Disk`, `Batches` disappear; nothing about the plan shape
hash join alternative	build on the smaller *filtered* input (check it fits: rows × width vs `work_mem`), probe with a Seq Scan: sequential pages instead of loops of random ones

Practice

Given. Four proposals for the 3.5 s dashboard: (i) `CREATE INDEX ON orders (status, country)`; (ii) `CLUSTER orders USING` that index; (iii) the extended statistics of §11; (iv) `CREATE INDEX ON orders (status, country) INCLUDE (customer_id, amount)`.

Your task. For each: plan lines, pages, estimate, time. Then: with (iii), what plan does the planner choose, does its build side fit in 4 MB, what does it cost in units and seconds against the 3.5 s? Which proposal first?

Solution

(i) The Seq Scan becomes a Bitmap Heap Scan with `Recheck Cond` on both columns; `Heap Blocks` $= 28{,}038 \times (1 - 0.99^{107}) \approx 28{,}038 \times 0.66 = 18{,}400$ (1 % of rows, scattered): two thirds of the table, read in order; estimate still 30,000 (same independence rule inside the index condition); the 120,000 lookups remain: 3.5 s becomes about 3.3 s. Plus a random write per insert.

(ii) Rewrites 219 MB under an exclusive lock; the 120,000 matching rows become $\lceil 120{,}000/107 \rceil = 1{,}122$ contiguous pages, the scan drops to milliseconds; estimate unchanged; the join unchanged: about 3.0 s. New orders append out of order.

(iii) Estimate 120,000; the planner abandons the nested loop. Nothing else changes in the plan lines of the scan.

(iv) Index-only scan of $\lceil 120{,}000/350 \rceil = 343$ leaf pages, `Heap Fetches: 0`; the scan drops from 410 ms to a few ms; the estimate and the join unchanged: about 3.0 s.

With (iii). Hash join. Build side = the smaller input after filtering = the 120,000 `orders` rows × about 80 B = 9.6 MB > 4 MB: `Batches: 4`, so either accept the batches or `SET LOCAL work_mem = '16MB'` for `Batches: 1`. Probe = Seq Scan of `customers`: $2{,}500 + 300{,}000 \times 0.01 = 5{,}500$ units. Total $\approx 65{,}538$ (scan of `orders`) $+5{,}500 + 0.0025 \times 420{,}000 \approx 72{,}000$ units against the nested loop's $65{,}538 + 120{,}000 \times 1.63 \approx 261{,}000$ at the true row count. Time: 0.41 s for the scan + 2,500 sequential pages (20 MB, 40 ms) + hashing ≈ 0.5 s instead of 3.5 s.

Order. (iii) first: two commands, no rewrite, fixes the node that owns the time. Then (iv) if the 0.4 s scan matters, since it also makes the index the whole access path. (i) and (ii) spend effort on the 12 % of the time that the scan owns.

Gotcha

Building the hash on `customers` "because it is the smaller table": after the filter, `orders` is the smaller input. Forgetting to check the build against `work_mem`. Proposing CLUSTER for a join problem.

14 Reconstruct the query from the plan

Method

`Seq Scan on t a` = `FROM t a`. `Hash Cond` / `Merge Cond` / `Join Filter` = `ON`. `Filter`, `Index Cond`, `Recheck Cond` = `WHERE` (on that table). `Group Key` = `GROUP BY`; an `Aggregate` with no key = a single `count(*)` or `sum`. `Sort Key` = `ORDER BY`, an aggregate in parentheses is a computed column. `Limit` = `LIMIT`. The outer child of a Hash Join is the probe side, the `Hash` child the build side.

Practice

Given.

```
Sort
  Sort Key: c.country, (count(*)) DESC
  ->  HashAggregate
        Group Key: c.country
        ->  Hash Join
              Hash Cond: (o.customer_id = c.id)
              ->  Bitmap Heap Scan on orders o
                    Recheck Cond: (order_ts >= '2026-10-01')
                    Filter: (amount > 100)
                    ->  Bitmap Index Scan on orders_ts_idx
                          Index Cond: (order_ts >= '2026-10-01')
              ->  Hash
                    ->  Seq Scan on customers c
                          Filter: (country <> 'MA')
```

Your task. Write the SQL. Which table is the build side, and why did the planner pick it?

Solution

```
SELECT c.country, count(*)
FROM orders o JOIN customers c ON o.customer_id = c.id
WHERE o.order_ts >= '2026-10-01' AND o.amount > 100 AND c.country <> 'MA'
GROUP BY c.country
ORDER BY c.country, count(*) DESC;
```

Build side: `customers` (under `Hash`), filtered to 40 % = 120,000 rows, a few MB; the filtered `orders` side is probed. The planner builds on the smaller *filtered* input.

Gotcha

Putting a `Filter` of one table into the `ON` clause. Missing the second `Sort Key`. Reading the `Hash` child as the probe.

C The buffer pool: Part B numbers and Part D arguments

15 Effective access time and hit ratio

Method

$\mathrm{EAT} = h\,T_{\mathrm{hit}} + (1-h)\,T_{\mathrm{miss}}$. Then two ratios: $\mathrm{EAT}/T_{\mathrm{hit}}$ ("× RAM") and $\mathrm{EAT}_1/\mathrm{EAT}_2$ ("× the other scenario"). $h = \mathrm{hit}/(\mathrm{hit}+\mathrm{read})$ from `Buffers` or `pg_statio_user_tables`. The miss term dominates until h is very close to 1: OLTP wants 99.9 %+.

Practice

Given. $T_{\mathrm{hit}} = 0.1\,\mu$s, $T_{\mathrm{miss}} = 100\,\mu$s (SSD). The monitoring page says "hit ratio 98 %, the pool is fine".

Your task. (a) EAT at 98 %; how many times RAM? (b) EAT at 99.9 %, and the factor between the two. (c) The dashboard's `Buffers: shared hit=458038 read=50000`: its hit ratio, and the sentence that explains why 90 % hides a 3-second problem.

Solution

(a) $0.98 \times 0.1 + 0.02 \times 100 = 0.098 + 2 = 2.1\,\mu$s: 21 times RAM. The 2 % of misses cost twenty times more than all the hits.

(b) $0.999 \times 0.1 + 0.001 \times 100 = 0.0999 + 0.1 = 0.2\,\mu$s: twice RAM, and 10.5 times faster than at 98 %. From 98 to 99.9 is "a bit more cache"; in time it is a factor of ten.

(c) 458,038/508,038 = 90.2 %. The ratio averages 458,038 cheap hits with 50,000 random reads that cost $50{,}000 \times 60\,\mu\mathrm{s} = 3$ s; the reads are concentrated on one node and that node is the query. A hit ratio is a global average; the cost is a per-node count of `read`.

Gotcha

"98 % is good" without the EAT. Using the hit ratio of the query to judge one node. Forgetting that a miss on HDD is 10 ms, making 98 % a 200μs EAT, 2,000 times RAM.

16 Replacement trace: LRU, FIFO, clock

Method

Draw the frames; process the reference string one request at a time; count misses (and writes if dirty).

- **LRU**: hit moves the page to the most-recent end; miss evicts the least-recent end.
- **FIFO**: hit changes nothing; miss evicts the oldest *loaded* page.
- **Clock**: one reference bit per frame, a hand. Hit: set the bit. Miss: advance the hand, clearing bits that are 1, until a frame with bit 0: evict it, load the new page (bit 0), move the hand on.
- **PostgreSQL clock-sweep**: the bit is a `usage_count` 0–5, +1 per hit, −1 per hand pass, evict at 0; pinned frames are skipped.

Practice

Given. 3 frames, all empty; reference string 1 2 3 1 4 1 2 5 1 2 3 4.

Your task. Misses under LRU, FIFO and clock, with the frame contents after each request for LRU and FIFO.

Solution

request	1	2	3	1	4	1	2	5	1	2	3	4
LRU (old → new)	1	12	123	231	314	341	412	125	251	512	123	234
hit / miss	M	M	M	H	M	H	M	M	H	H	M	M
FIFO (old → new)	1	12	123	123	234	341	412	125	125	125	253	534
hit / miss	M	M	M	H	M	M	M	M	H	H	M	M

LRU: 8 misses. FIFO: 9 misses (page 1 is evicted at the fifth request although it was just used; LRU kept it). Clock: 8 misses, same as LRU here: after 1 2 3 the hit on 1 sets its bit; request 4 finds the hand on frame 1 (page 1, bit 1): clears it and moves on, evicts page 2; and so on. Clock behaves like LRU at a fraction of the bookkeeping, which is the point.

Gotcha

Moving a page on a hit under FIFO. Evicting the least-recently *loaded* under LRU. Forgetting that a clock miss first clears bits that are set, and that the hand moves past the frame it just filled.

17 Sequential flooding, rings, sizing the pool

Method

1. A scan larger than the pool is use-once: under LRU, clock or FIFO it streams through every frame and evicts the whole working set W; the scan itself gains nothing from caching. Reload cost $= W \times T_{\text{miss}}$.
2. PostgreSQL: frames = `shared_buffers`/8 KB; a Seq Scan of a table larger than frames/4 runs through a 32-frame ring (256 KB); W survives iff $W \leq$ frames $- 32$. Below the threshold the table simply becomes resident after one scan. COPY uses a 16 MB ring, VACUUM 256 KB; index scans never ring.
3. Sizing: `shared_buffers` $\approx 25\,\%$ of RAM; size for W (measure it with `pg_buffercache`), not for the database; a streaming workload has $h \approx 0$ at any size; more pool starves the OS cache and `work_mem`.

Practice

Given. `shared_buffers = 256MB`. Working set 12,000 pages, hit ratio 99.5 % by day. Every night a job scans `orders` (28,038 pages); every morning the first minutes are slow. A second job scans `customers` (2,500 pages).

Your task. (a) Under plain LRU: pages of W that survive the `orders` scan and the morning reload cost on SSD. (b) PostgreSQL: frames, threshold, is the `orders` scan ringed, does W survive, what does the ring cost the scan? (c) Same for the `customers` scan. (d) The DBA wants `shared_buffers = 2GB` "so the scan fits": two sentences.

Solution

(a) Frames = 256 MB/8 KB = 32,768. The scan is 28,038 pages, less than the pool, so under LRU it evicts 28,038 of the 32,768 least recent pages: at most $32{,}768 - 28{,}038 = 4{,}730$ of the 12,000 hot pages survive, and only if they were the most recently used; the typical morning reloads about 7,300–12,000 pages at 100 μs: 0.7–1.2 s of misses, spread over the first transactions.

(b) Threshold $= 32{,}768/4 = 8{,}192$ pages; $28{,}038 > 8{,}192$: ringed. The scan recycles 32 frames; $12{,}000 \leq 32{,}736$: W survives intact. The ring costs the scan nothing: every scan page is a compulsory miss that would not be reused. So on PostgreSQL the slow morning comes from somewhere else (the OS cache, which the ring does not protect; a COPY ring; a checkpoint): check `pg_buffercache` after the job.

(c) $2{,}500 \leq 8{,}192$: not ringed; `customers` goes through the pool and stays resident, which is exactly what the dashboard of §12 needed.

(d) The scan gains nothing from 2 GB: a use-once read has hit ratio 0 at any size and is ringed anyway. Measure W first: 12,000 pages = 94 MB already fit in 256 MB; the morning problem is not pool size, and 2 GB would starve the OS cache that serves the `reads`.

Gotcha

"LRU always beats FIFO" (not on a scan). Comparing the table with `shared_buffers` instead of a quarter of it. Thinking the ring slows the scan. "More cache is always better".

18 Steal, no-force, WAL: what the log must hold

Method

Steal: a dirty page of an uncommitted transaction may be written to disk (the pool needs the frame) ⇒ the log needs *before-images* to **undo**. **No-force**: commit does not write the data pages ⇒ the log needs *after-images* to **redo**. **WAL rule**: a log record reaches disk before the data page it describes; at commit the log is forced (one sequential append); data pages go later. Recovery: redo every committed change, undo every uncommitted one. Committed data is safe in the log, not necessarily in the data file.

Practice

Given. T_1 updates page P and commits; T_2 updates page Q, which the pool writes to disk to free a frame; the server crashes before P is written and before T_2 commits.

Your task. (a) State of P and Q on disk at the crash. (b) What the log must contain, and why the policy pair is steal + no-force. (c) What recovery does to P and Q.

Solution

(a) P on disk is *old* (the commit did not write it: no-force). Q on disk is *new*, holding an uncommitted change (steal).

(b) For P: T_1's after-image, written and forced before the commit record, so the commit is durable without writing P. For Q: T_2's before-image, written before Q was flushed (write-ahead), so the premature write can be reversed. Steal keeps the pool free to evict anything; no-force makes commit a single sequential log write instead of random page writes.

(c) Redo T_1: apply its after-image to P. Undo T_2: restore Q from its before-image, then write an abort record. The user who got "committed" for T_1 loses nothing; T_2 vanishes as if never run.

Gotcha

"No-force loses committed data" (the log has it). "Commit writes the pages" (it writes the log). Confusing which image (before/after) serves undo and redo.

D Tickets and quick checks

19 The ticket method, with three worked tickets

Method

Half a page, four moves, in this order: **claim** (right, wrong, or "both") → **mechanism** (which subsystem, which rule) → **one number** with units, from this course's formulas → **consequence**: what to do instead, and the tempting wrong answer. A ticket answered without a number scores half.

Practice

Given. Three tickets. (1) "The returns report is slow, add an index on `status`." (2) "Set `work_mem = 2GB` in `postgresql.conf`, the nightly sort spills." (3) "Our hit ratio is 98 %, the buffer pool is not the problem."

Your task. Answer each in the four moves.

Solution

(1) Index on status. **Claim**: wrong as stated, right with a different index. **Mechanism**: an index costs the heap pages it touches; `status = 'returned'` keeps 5 % of rows with no physical order. **Number**: $28{,}038 \times (1 - 0.95^{107}) = 27{,}922$ pages, 99.6 % of the table, so a plain index scan costs 114,379 units against 65,538 for the Seq Scan, and a bitmap scan reads the same pages. **Consequence**: do not create it; create the covering index `(status) INCLUDE (customer_id, amount)` (429 leaf pages, no heap) or the partial one if the report is only about returns; and check first whether the report's time is in the scan at all (in the dashboard it was 12 %; the join owned the rest). Tempting answer: "5 % is selective".

(2) work_mem = 2GB. **Claim**: wrong place, right idea. **Mechanism**: `work_mem` is granted *per sort or hash node, per connection*; a server-wide 2 GB lets one report with three sorts take 6 GB and 100 connections exhaust RAM, and the OS cache (which serves the `reads`) is what shrinks. **Number**: the nightly sort of 28,038 pages needs $M \geq 168$ pages = 1.3 MB for one merge pass and 219 MB to avoid merging altogether; the `Disk:` figure of its `Sort Method` line is the exact amount. **Consequence**: `BEGIN; SET LOCAL work_mem = '256MB'; <the sort>; COMMIT;` in the job, default unchanged elsewhere. Tempting answer: "more memory is harmless".

(3) 98 % hit ratio. **Claim**: wrong. **Mechanism**: EAT $= hT_{\text{hit}} + (1-h)T_{\text{miss}}$, the miss term dominates. **Number**: $0.98 \times 0.1 + 0.02 \times 100 = 2.1\,\mu$s, 21 times RAM; at 99.9 % it is $0.2\,\mu$s. And the ratio is a global average: the dashboard's 90 % hid 50,000 random reads on one node, 3 s. **Consequence**: measure the working set with `pg_buffercache` and the `reads` per node with `EXPLAIN (ANALYZE, BUFFERS)`; size `shared_buffers` for W (here 94 MB), make `customers` resident, and aim at 99.9 %. Tempting answer: "98 is an A".

Gotcha

Agreeing or refusing without the mechanism. No number. Not saying what to do instead. Numbers without units.

20 Quick checks: the letter and the one line

Method

One point for the letter, two for the reason: a number, a formula or one mechanism sentence. Write the reason as "because ⟨rule⟩, so ⟨number⟩". The reason also rules out the neighbouring options.

Practice

Given. (a) Which node cannot emit before reading all its input: Seq Scan with Filter / Nested Loop / Sort / Merge Join? (b) `WHERE lower(email) = ?`: B-tree on `email` / B-tree on `lower(email)` / hash on `email` / BRIN on `email`? (c) Rows for `status = 'returned' AND country = 'FR'`: 30,000 / 150,000 / 600,000 / 750,000? (d) Clock-sweep hand reaches an unpinned frame with `usage_count` 2: evicted / becomes 1 and the hand moves on / becomes 3 / pinned? (e) After deleting 40 % of `orders` at random and `VACUUM`: 28,038 / 16,823 / 11,215 / 0 pages? (f) Sort of 28,038 pages with $M = 200$, total I/O: 28,038 / 56,076 / 112,152 / 168,228?

Your task. Letter and one line each.

Solution

(a) **Sort**: the smallest key is known only after the last input row; the others emit as they go (Merge Join needs sorted *inputs*, the sorting is a separate node). (b) **B-tree on `lower(email)`**: an index serves its own key expression; the others index a different key, BRIN also needs physical order. (c) **30,000**: $0.05 \times 0.20 \times 3{,}000{,}000$; 150,000 and 600,000 are the single predicates, 750,000 their sum. (d) **Becomes 1, hand moves on**: the hand decrements and evicts only at 0; hits increment. (e) **28,038**: VACUUM reuses space inside pages and truncates only trailing empty pages; 16,823 is VACUUM FULL. (f) **112,152**: 141 runs ≤ 199, one merge pass, $2 \times 28{,}038 \times 2$; 168,228 is two merge passes, 56,076 one pass counted once.

Gotcha

A letter alone. A reason that does not contain the rule or the number. Picking the option that matches the *trap* computation (sum instead of product, reads only, M instead of $M - 1$).